



E980

Sinotech R&D Group Limited

Note

- Before using the product, please read the Quick Guide to fully benefit from it.
- This product involves constant upgrading and/or improvement, our company reserves the right to change the specifications of software and/or hardware are mentioned in this operating guide without any prior notice. The product specifications and information mentioned in the operating guide are for reference only.

Check list

- Please check the following accessories before you discard the packing material. Please contact your local dealer immediately if there is any missing or damage parts.

Accessories	Quantity
E980	1
Battery	1
USB Data Cable	1
Charging Plug	1
Quick Start Guide	1

1. Overview of E980




LED indicator light

Operating state	Indication
Charging	Red (Steady)
Message Prompt	Blue (Steady)
More than 90% charge capacity	Green (Steady)


2. Installation of SIM card

- Anticlockwise the with of battery cover 45°, open it and reach the battery.
- Insert the SIM card as shown in the picture.
- Insert the SD card into the slot as shown in the picture.
- Place the battery in the correct direction in the battery slot, and then close the battery cover by turning the battery cover clockwise 45° to lock the battery cover.



3. Charging the Battery

- Using USB Data Cable



- Connect the IP smart terminal and power adapter using the USB Data Cable.
- Red light on the IP smart terminal indicates battery charging in progress.
- Green light indicates fully charged.

Important:

- Use only the designated charger.
- Battery must be fully charged before first use.
- Do not expose the battery to high temperature.
- Do not dismantle the battery.

4. Basic operations

- Startup**
Press the power on button for 3 seconds. Once the screen goes light up. You will see the "E980", it indicates successful Startup.
- Shut Down**
Press the power off button for 3 seconds. Propo window showing shutdown and restart, click on shutdown. Once the screen goes blank, the smart terminal is fully shut down.
- Unlock**
Press Home or Power to light the screen.
Slide lock icon on the screen to unlock.

Group Call

- Press and hold the PTT button until you hear the Permit Tone.
- You are now connected to the Group.
- You may begin to talk.
- Release PTT button to end the call and the device will be in the receiving mode.

Emergency Call

- Press and hold the Emergency button for 3 seconds can start.

Backlight

- Press "Power" button to on and off backlight. You can select the time duration of the backlight.

Low Batt

- When the battery power fall below 15%, a "warning" tone will be heard.

Document Manager

- Select document manager, you will see all folder including pictures and videos.

E980 Series Operating

5. Troubleshooting

No	Problem	Solution
1	Silent, no response	- Battery might be drained, please replace the battery or charge it. - Battery might not be installed correctly, please replace it with the correct battery or change the battery. - Check if the device has been power on. - Check if the external audio accessory is connected.
2	Unable to make/receive calls	- Check if you are in the same group. - Check whether the network is connected.
3	Battery drained rapidly	Shut down the Wi-Fi and GPS if not in use.
4	Cannot Charge	Check USB cable, replace if faulty.

FCC Statement

15.19 Labeling requirements.

This device complies with part 15 of the FCC Rules. Operation is subject to the following conditions:
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

15.21 Information to user.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.105 Information to user.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio

IC STATEMENT

This device complies with Industry Canada's licence-exempt RSS. Operation is subject to the following two conditions:
(1) This device must not cause interference, and
(2) This device must accept any interference, including interference that may cause undesired operation of the device.
Le présent appareil est conforme aux CNR d'Industrie Canada relatives aux appareils radio exempts de licence. L'exploitation de l'appareil ne doit pas produire de brouillage, et l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Specific Absorption Rate (SAR) information: This product meets the government's requirements for exposure to radio waves. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough testing of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons regardless of age or health.

IC RF Exposure Information and Statement

The SAR limit of USA (IC) is 1.6 W/kg averaged over one gram of tissue. This device was tested for typical body-worn operations and found to be in compliance with the body worn. To maintain compliance with IC RF exposure requirements, use accessories that maintain a 10mm from back of the product, 10mm from the belt.

The use of the following accessories and similar accessories that do not satisfy these requirements may not comply with IC RF exposure requirements, and should be avoided.
This transmitter may operate with the antenna(s) documented in this filing in body-worn configurations. RF exposure compliance is limited to the specific belt-clip and accessory configurations as documented in this filing. The device must be at least 10 mm.

RED Statement

- 1. Risk of explosion if battery is replaced by an incorrect type. Dispose of used batteries according to the instructions.
- 2. This product is not to be connected to a USB interface of version USB 2.0 or higher.
- 3. Adapter shall be installed near the equipment and shall be easily accessible.
- 4. The operating temperature of the EUT can't exceed 40°C and shouldn't be lower than -20°C.
- 5. The plug considered as disconnect device of product, 10mm from the belt.
- 6. The device complies with RF specifications when the device used at 5mm from back of the product, 10mm from the belt.

Hereby, SINOTECH R&D GROUP LIMITED declares that this Mobile phone product is in compliance with the requirements and other relevant provisions of Directive 2014/53/EU. This product is allowed to be used in all EU member states.

尺寸: 260*110mm
颜色: 双面四色印刷
材质: 105g铜版纸