



MPE REPORT

FCC ID: 2AUTE-MT800

Date of issue: Oct. 22, 2019

Report number: MTi19091603-9E3

Sample description: A4 Mobile Printer

Model(s): MT800, MT808, MT818, MT866, MT888, MPT8C, M81C, MTU81C, MTU82C, MTU83C, MTU84C, MTU85C, MTX81C, MTX82C, MTX83C, MTX84C, MTX85C

Applicant: Xiamen Hanin Electronic Technology Co., Ltd.

Address: Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen

Date of test: Oct. 10, 2019 to Oct. 22, 2019

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.



TEST RESULT CERTIFICATION	
Applicant's name:	Xiamen Hanin Electronic Technology Co., Ltd.
Address:	Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen
Manufacture's name:	Xiamen Hanin Electronic Technology Co., Ltd.
Address:	Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen
Product name:	A4 Mobile Printer
Trademark:	HPRT
Model and/or type reference ..:	MT800
Serial model.....:	MT808, MT818, MT866, MT888, MPT8C, M81C, MTU81C, MTU82C, MTU83C, MTU84C, MTU85C, MTX81C, MTX82C, MTX83C, MTX84C, MTX85C
RF exposure procedures.....:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Demi Mu

Oct. 22, 2019

Reviewed by:

Blue Zheng

Oct. 22, 2019

Approved by:

Smith Chen

Oct. 22, 2019



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1415926

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

BT/BLE:

Operation Frequency: BT GFSK, $\pi/4$ -DQPSK, 8DPSK: 2402-2480MHz,

BLE GFSK: 2402-2480MHz,

Antenna Type: BT/BLE Antenna: PCB Antenna;
antenna gain: 1dBi

R=20cm

$mW = 10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)} = 10^{(1/10)} = 1.26$

BT:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)		
				tune-up power		Gain					
				(dBm)	(mW)	(dBi)	Numeric				
2402	GFSK	3.380	4±1	5	3.162	1.00	1.26	0.0008	1		
2441		4.153	4±1	5	3.162	1.00	1.26	0.0008	1		
2480		4.162	4±1	5	3.162	1.00	1.26	0.0008	1		
2402	$\pi/4$ -DQPSK	4.657	5±1	6	3.981	1.00	1.26	0.0010	1		
2441		5.010	5±1	6	3.981	1.00	1.26	0.0010	1		
2480		5.224	5±1	6	3.981	1.00	1.26	0.0010	1		
2402	8DPSK	4.860	5±1	6	3.981	1.00	1.26	0.0010	1		
2441		5.545	5±1	6	3.981	1.00	1.26	0.0010	1		
2480		5.799	5±1	6	3.981	1.00	1.26	0.0010	1		

BLE:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)		
				tune-up power		Gain					
				(dBm)	(mW)	(dBi)	Numeric				
2402	GFSK	-3.220	-4±1	-3	0.501	1.00	1.26	0.0001	1		
2440		-4.130	-4±1	-3	0.501	1.00	1.26	0.0001	1		
2480		-4.240	-4±1	-3	0.501	1.00	1.26	0.0001	1		

Conclusion:

For the max result: $0.0010 \leq 1.0$ for 1g SAR, No SAR is required.

----END OF REPORT----