






















5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6)
FCC 47 CFR Part 15 Subpart C Section 15.209/205

Test Method: KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

1. Limits of Radiated Emission and Band edge Measurement

Radiated emissions that fall in the restricted bands must comply with the general emissions limits in 15.209(a) as below table. Other emissions shall be at least 20 dB below the highest level of the desired power.

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dB μ V/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

2. Limits of Unwanted Emission Out of the Restricted Bands

Applicable To	Limit	
789033 D02 General U-NII Test Procedures New Rules v01r04	Field Strength at 3 m	
	PK: 74 (dBμV/m)	AV: 54 (dBμV/m)
Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
FCC Part 15.407 (b)(1)	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
FCC Part 15.407 (b)(2)	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
FCC Part 15.407 (b)(3)	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)
FCC Part 15.407 (b)(4)	27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;	PK: 68.2 (dBμV/m)
	15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;	
	10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges;	
	-27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.	

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

- The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Remark:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for RMS Average (Duty cycle < 98 %) for Average detection (AV) at frequency above 1 GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle ≥ 98 %) or ≥ 1/T(duty cycle is < 98%) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):
Worst-Case Configuration
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	47.703	38.14	-15.35	22.79	40.00	-17.21	QP
2	69.230	35.93	-13.54	22.39	40.00	-17.61	QP
3	123.181	43.51	-11.70	31.81	43.50	-11.69	QP
4	259.443	32.33	-7.54	24.79	46.00	-21.21	QP
5	327.155	29.24	-6.00	23.24	46.00	-22.76	QP
6	713.692	26.87	1.79	28.66	46.00	-17.34	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

Radiated Emission Test Data (Above 1GHz):
SISO_Chain 0_IEEE 802.11a_Channel 36

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10360.00	39.94	11.11	51.05	74.00	-22.95	Peak	Horizontal
2	10360.00	28.13	11.11	39.24	54.00	-14.76	Average	Horizontal
3	15540.00	30.50	10.76	41.26	74.00	-32.74	Peak	Horizontal
4	15540.00	18.68	10.76	29.44	54.00	-24.56	Average	Horizontal
5	10360.00	37.42	9.39	46.81	74.00	-27.19	Peak	Vertical
6	10360.00	25.89	9.39	35.28	54.00	-18.72	Average	Vertical
7	15540.00	36.33	11.59	47.92	74.00	-26.08	Peak	Vertical
8	15540.00	24.38	11.59	35.97	54.00	-18.03	Average	Vertical

SISO_Chain 0_IEEE 802.11a_Channel 44

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10440.00	38.31	11.31	49.62	74.00	-24.38	Peak	Horizontal
2	10440.00	27.11	11.31	38.42	54.00	-15.58	Average	Horizontal
3	15660.00	34.18	11.00	45.18	74.00	-28.82	Peak	Horizontal
4	15660.00	21.94	11.00	32.94	54.00	-21.06	Average	Horizontal
5	10440.00	37.52	9.43	46.95	74.00	-27.05	Peak	Vertical
6	10440.00	26.09	9.43	35.52	54.00	-18.48	Average	Vertical
7	15660.00	36.74	11.93	48.67	74.00	-25.33	Peak	Vertical
8	15660.00	24.94	11.93	36.87	54.00	-17.13	Average	Vertical

SISO_Chain 0_IEEE 802.11a_Channel 48

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10480.00	38.17	11.41	49.58	74.00	-24.42	Peak	Horizontal
2	10480.00	26.34	11.41	37.75	54.00	-16.25	Average	Horizontal
3	15720.00	33.21	11.08	44.29	74.00	-29.71	Peak	Horizontal
4	15720.00	21.00	11.08	32.08	54.00	-21.92	Average	Horizontal
5	10480.00	35.87	9.45	45.32	74.00	-28.68	Peak	Vertical
6	10480.00	24.69	9.45	34.14	54.00	-19.86	Average	Vertical
7	15720.00	30.88	12.05	42.93	74.00	-31.07	Peak	Vertical
8	15720.00	19.00	12.05	31.05	54.00	-22.95	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 52

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10520.00	38.41	11.42	49.83	74.00	-24.17	Peak	Horizontal
2	10520.00	26.33	11.42	37.75	54.00	-16.25	Average	Horizontal
3	15780.00	33.41	11.16	44.57	74.00	-29.43	Peak	Horizontal
4	15780.00	21.18	11.16	32.34	54.00	-21.66	Average	Horizontal
5	10520.00	36.10	9.43	45.53	74.00	-28.47	Peak	Vertical
6	10520.00	24.79	9.43	34.22	54.00	-19.78	Average	Vertical
7	15780.00	30.82	12.19	43.01	74.00	-30.99	Peak	Vertical
8	15780.00	18.70	12.19	30.89	54.00	-23.11	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 60

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10600.00	39.35	11.33	50.68	74.00	-23.32	Peak	Horizontal
2	10600.00	27.39	11.33	38.72	54.00	-15.28	Average	Horizontal
3	15900.00	32.35	11.33	43.68	74.00	-30.32	Peak	Horizontal
4	15900.00	20.38	11.33	31.71	54.00	-22.29	Average	Horizontal
5	10600.00	39.21	9.37	48.58	74.00	-25.42	Peak	Vertical
6	10600.00	26.96	9.37	36.33	54.00	-17.67	Average	Vertical
7	15900.00	31.17	12.45	43.62	74.00	-30.38	Peak	Vertical
8	15900.00	18.89	12.45	31.34	54.00	-22.66	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 64

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10640.00	39.77	11.29	51.06	74.00	-22.94	Peak	Horizontal
2	10640.00	27.73	11.29	39.02	54.00	-14.98	Average	Horizontal
3	15960.00	32.09	11.49	43.58	74.00	-30.42	Peak	Horizontal
4	15960.00	20.22	11.49	31.71	54.00	-22.29	Average	Horizontal
5	10640.00	39.17	9.34	48.51	74.00	-25.49	Peak	Vertical
6	10640.00	26.99	9.34	36.33	54.00	-17.67	Average	Vertical
7	15960.00	31.55	12.66	44.21	74.00	-29.79	Peak	Vertical
8	15960.00	18.84	12.66	31.50	54.00	-22.50	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 100

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11000.00	39.67	10.30	49.97	74.00	-24.03	Peak	Horizontal
2	11000.00	27.16	10.30	37.46	54.00	-16.54	Average	Horizontal
3	16500.00	33.09	13.35	46.44	74.00	-27.56	Peak	Horizontal
4	16500.00	19.85	13.35	33.20	54.00	-20.80	Average	Horizontal
5	11000.00	38.50	8.50	47.00	74.00	-27.00	Peak	Vertical
6	11000.00	26.64	8.50	35.14	54.00	-18.86	Average	Vertical
7	16500.00	36.49	13.45	49.94	74.00	-24.06	Peak	Vertical
8	16500.00	23.71	13.45	37.16	54.00	-16.84	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 120

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11200.00	38.66	9.97	48.63	74.00	-25.37	Peak	Horizontal
2	11200.00	26.32	9.97	36.29	54.00	-17.71	Average	Horizontal
3	16800.00	37.74	13.24	50.98	74.00	-23.02	Peak	Horizontal
4	16800.00	25.37	13.24	38.61	54.00	-15.39	Average	Horizontal
5	11200.00	37.89	8.27	46.16	74.00	-27.84	Peak	Vertical
6	11200.00	25.80	8.27	34.07	54.00	-19.93	Average	Vertical
7	16800.00	39.65	13.01	52.66	74.00	-21.34	Peak	Vertical
8	16800.00	27.44	13.01	40.45	54.00	-13.55	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 140

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11400.00	39.89	9.86	49.75	74.00	-24.25	Peak	Horizontal
2	11400.00	27.91	9.86	37.77	54.00	-16.23	Average	Horizontal
3	17100.00	36.61	13.42	50.03	74.00	-23.97	Peak	Horizontal
4	17100.00	24.39	13.42	37.81	54.00	-16.19	Average	Horizontal
5	11400.00	40.63	8.30	48.93	74.00	-25.07	Peak	Vertical
6	11400.00	28.24	8.30	36.54	54.00	-17.46	Average	Vertical
7	17100.00	38.38	12.76	51.14	74.00	-22.86	Peak	Vertical
8	17100.00	26.27	12.76	39.03	54.00	-14.97	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 149

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11490.00	39.24	9.78	49.02	74.00	-24.98	Peak	Horizontal
2	11490.00	27.31	9.78	37.09	54.00	-16.91	Average	Horizontal
3	17235.00	41.30	13.98	55.28	74.00	-18.72	Peak	Horizontal
4	17235.00	27.79	13.98	41.98	54.00	-12.02	Average	Horizontal
5	11490.00	39.63	8.27	47.90	74.00	-26.10	Peak	Vertical
6	11490.00	27.30	8.27	35.57	54.00	-18.43	Average	Vertical
7	17235.00	40.98	13.24	54.22	74.00	-19.78	Peak	Vertical
8	17235.00	27.91	13.24	41.15	54.00	-12.85	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 157

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11570.00	38.48	9.86	48.34	74.00	-25.66	Peak	Horizontal
2	11570.00	25.74	9.86	35.60	54.00	-18.40	Average	Horizontal
3	17355.00	39.96	14.49	54.45	74.00	-19.55	Peak	Horizontal
4	17355.00	27.61	14.49	42.10	54.00	-11.90	Average	Horizontal
5	11570.00	36.93	8.47	45.40	74.00	-28.60	Peak	Vertical
6	11570.00	25.47	8.47	33.94	54.00	-20.06	Average	Vertical
7	17355.00	39.16	13.68	52.84	74.00	-21.16	Peak	Vertical
8	17355.00	27.89	13.68	41.57	54.00	-12.43	Average	Vertical

SISO_Chain 0_IIEEE 802.11a_Channel 165

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11650.00	38.27	9.95	48.22	74.00	-25.78	Peak	Horizontal
2	11650.00	26.99	9.95	36.94	54.00	-17.06	Average	Horizontal
3	17475.00	37.83	14.89	52.72	74.00	-21.28	Peak	Horizontal
4	17475.00	26.04	14.89	40.93	54.00	-13.07	Average	Horizontal
5	11650.00	38.59	8.69	47.28	74.00	-26.72	Peak	Vertical
6	11650.00	26.11	8.69	34.80	54.00	-19.20	Average	Vertical
7	17475.00	38.76	14.00	52.76	74.00	-21.24	Peak	Vertical
8	17475.00	26.54	14.00	40.54	54.00	-13.46	Average	Vertical

SISO_Chain 1_IIEEE 802.11a_Channel 36

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10360.00	39.08	11.11	50.19	74.00	-23.81	Peak	Horizontal
2	10360.00	27.96	11.11	39.07	54.00	-14.93	Average	Horizontal
3	15540.00	36.05	10.76	46.81	74.00	-27.19	Peak	Horizontal
4	15540.00	23.32	10.76	34.08	54.00	-19.92	Average	Horizontal
5	10360.00	30.68	9.39	40.07	74.00	-33.93	Peak	Vertical
6	10360.00	19.10	9.39	28.49	54.00	-25.51	Average	Vertical
7	15540.00	32.85	11.59	44.44	74.00	-29.56	Peak	Vertical
8	15540.00	20.26	11.59	31.85	54.00	-22.15	Average	Vertical

SISO_Chain 1_IIEEE 802.11a_Channel 44

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10440.00	39.47	10.76	50.23	74.00	-23.77	Peak	Horizontal
2	10440.00	27.84	10.76	39.15	54.00	-14.85	Average	Horizontal
3	15660.00	39.53	5.85	45.38	74.00	-28.62	Peak	Horizontal
4	15660.00	22.50	5.85	33.50	54.00	-20.50	Average	Horizontal
5	10440.00	33.03	9.43	42.46	74.00	-31.54	Peak	Vertical
6	10440.00	21.33	9.43	30.76	54.00	-23.24	Average	Vertical
7	15660.00	31.48	11.93	43.41	74.00	-30.59	Peak	Vertical
8	15660.00	19.86	11.93	31.79	54.00	-22.21	Average	Vertical

SISO_Chain 1_IIEEE 802.11a_Channel 48

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10480.00	39.09	11.41	50.50	74.00	-23.50	Peak	Horizontal
2	10480.00	27.14	11.41	38.55	54.00	-15.45	Average	Horizontal
3	15720.00	33.40	11.08	44.48	74.00	-29.52	Peak	Horizontal
4	15720.00	21.51	11.08	32.59	54.00	-21.41	Average	Horizontal
5	10480.00	31.74	9.45	41.19	74.00	-32.81	Peak	Vertical
6	10480.00	19.08	9.45	28.53	54.00	-25.47	Average	Vertical
7	15720.00	31.17	12.05	43.22	74.00	-30.78	Peak	Vertical
8	15720.00	18.50	12.05	30.55	54.00	-23.45	Average	Vertical

SISO_ Chain 1_ IEEE 802.11a_ Channel 52

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10520.00	38.34	11.42	49.76	74.00	-24.24	Peak	Horizontal
2	10520.00	26.74	11.42	38.16	54.00	-15.84	Average	Horizontal
3	15780.00	34.42	11.16	45.58	74.00	-28.42	Peak	Horizontal
4	15780.00	21.55	11.16	32.71	54.00	-21.29	Average	Horizontal
5	10520.00	30.60	9.43	40.03	74.00	-33.97	Peak	Vertical
6	10520.00	19.10	9.43	28.53	54.00	-25.47	Average	Vertical
7	15780.00	30.70	12.19	42.89	74.00	-31.11	Peak	Vertical
8	15780.00	18.70	12.19	30.89	54.00	-23.11	Average	Vertical

SISO_ Chain 1_ IEEE 802.11a_ Channel 60

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10600.00	39.90	11.33	51.23	74.00	-22.77	Peak	Horizontal
2	10600.00	27.99	11.33	39.32	54.00	-14.68	Average	Horizontal
3	15900.00	32.70	11.33	44.03	74.00	-29.97	Peak	Horizontal
4	15900.00	20.66	11.33	31.99	54.00	-22.01	Average	Horizontal
5	10600.00	34.76	9.37	44.13	74.00	-29.87	Peak	Vertical
6	10600.00	22.69	9.37	32.06	54.00	-21.94	Average	Vertical
7	15900.00	31.09	12.45	43.54	74.00	-30.46	Peak	Vertical
8	15900.00	19.37	12.45	31.82	54.00	-22.18	Average	Vertical

SISO_ Chain 1_ IEEE 802.11a_ Channel 64

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10640.00	39.14	11.29	50.43	74.00	-23.57	Peak	Horizontal
2	10640.00	27.91	11.29	39.20	54.00	-14.80	Average	Horizontal
3	15960.00	32.57	11.49	44.06	74.00	-29.94	Peak	Horizontal
4	15960.00	20.22	11.49	31.71	54.00	-22.29	Average	Horizontal
5	10640.00	35.90	9.34	45.24	74.00	-28.76	Peak	Vertical
6	10640.00	25.81	9.34	35.15	54.00	-18.85	Average	Vertical
7	15960.00	30.33	12.66	42.99	74.00	-31.01	Peak	Vertical
8	15960.00	18.84	12.66	31.50	54.00	-22.50	Average	Vertical

SISO_Chain 1_ IEEE 802.11a_Channel 100

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11000.00	41.04	10.30	51.34	74.00	-22.66	Peak	Horizontal
2	11000.00	28.18	10.30	38.48	54.00	-15.52	Average	Horizontal
3	16500.00	32.63	13.35	45.98	74.00	-28.02	Peak	Horizontal
4	16500.00	20.00	13.35	33.35	54.00	-20.65	Average	Horizontal
5	11000.00	36.18	8.50	44.68	74.00	-29.32	Peak	Vertical
6	11000.00	24.34	8.50	32.84	54.00	-21.16	Average	Vertical
7	16500.00	36.32	13.45	49.77	74.00	-24.23	Peak	Vertical
8	16500.00	24.26	13.45	37.71	54.00	-16.29	Average	Vertical

SISO_Chain 1_ IEEE 802.11a_Channel 120

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11200.00	38.57	9.97	48.54	74.00	-25.46	Peak	Horizontal
2	11200.00	26.11	9.97	36.08	54.00	-17.92	Average	Horizontal
3	16800.00	38.28	13.24	51.52	74.00	-22.48	Peak	Horizontal
4	16800.00	26.33	13.24	39.57	54.00	-14.43	Average	Horizontal
5	11200.00	35.09	8.27	43.36	74.00	-30.64	Peak	Vertical
6	11200.00	23.52	8.27	31.79	54.00	-22.21	Average	Vertical
7	16800.00	39.68	13.01	52.69	74.00	-21.31	Peak	Vertical
8	16800.00	27.75	13.01	40.76	54.00	-13.24	Average	Vertical

SISO_Chain 1_ IEEE 802.11a_Channel 140

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11400.00	41.28	9.86	51.14	74.00	-22.86	Peak	Horizontal
2	11400.00	29.25	9.86	39.11	54.00	-14.89	Average	Horizontal
3	17100.00	36.69	13.42	50.11	74.00	-23.89	Peak	Horizontal
4	17100.00	24.73	13.42	38.15	54.00	-15.85	Average	Horizontal
5	11400.00	39.85	8.30	48.15	74.00	-25.85	Peak	Vertical
6	11400.00	28.24	8.30	36.54	54.00	-17.46	Average	Vertical
7	17100.00	38.43	12.76	51.19	74.00	-22.81	Peak	Vertical
8	17100.00	26.34	12.76	39.10	54.00	-14.90	Average	Vertical

SISO_ Chain 1_ IEEE 802.11a_ Channel 149

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11490.00	39.73	9.78	49.51	74.00	-24.49	Peak	Horizontal
2	11490.00	27.37	9.78	37.15	54.00	-16.85	Average	Horizontal
3	17235.00	39.77	14.49	54.26	74.00	-19.74	Peak	Horizontal
4	17235.00	28.62	14.49	42.60	54.00	-11.40	Average	Horizontal
5	11490.00	35.30	8.27	43.57	74.00	-30.43	Peak	Vertical
6	11490.00	23.77	8.27	32.04	54.00	-21.96	Average	Vertical
7	17235.00	41.06	13.24	54.30	74.00	-19.70	Peak	Vertical
8	17235.00	28.65	13.24	41.89	54.00	-12.11	Average	Vertical

SISO_ Chain 1_ IEEE 802.11a_ Channel 157

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11570.00	39.29	9.86	49.15	74.00	-24.85	Peak	Horizontal
2	11570.00	27.06	9.86	36.92	54.00	-17.08	Average	Horizontal
3	17355.00	40.53	14.89	55.42	74.00	-18.58	Peak	Horizontal
4	17355.00	27.27	14.89	42.16	54.00	-11.84	Average	Horizontal
5	11570.00	36.93	8.47	45.40	74.00	-28.60	Peak	Vertical
6	11570.00	25.85	8.47	34.32	54.00	-19.68	Average	Vertical
7	17355.00	41.04	13.68	54.72	74.00	-19.28	Peak	Vertical
8	17355.00	28.06	13.68	41.74	54.00	-12.26	Average	Vertical

SISO_ Chain 1_ IEEE 802.11a_ Channel 165

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11650.00	37.80	9.95	47.75	74.00	-26.25	Peak	Horizontal
2	11650.00	26.45	9.95	36.40	54.00	-17.60	Average	Horizontal
3	17475.00	38.23	14.89	53.12	74.00	-20.88	Peak	Horizontal
4	17475.00	26.04	14.89	40.93	54.00	-13.07	Average	Horizontal
5	11650.00	35.04	8.69	43.73	74.00	-30.27	Peak	Vertical
6	11650.00	26.11	8.69	34.80	54.00	-19.20	Average	Vertical
7	17475.00	37.85	14.00	51.85	74.00	-22.15	Peak	Vertical
8	17475.00	26.74	14.00	40.74	54.00	-13.26	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 36

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10360.00	39.24	11.11	50.35	74.00	-23.65	Peak	Horizontal
2	10360.00	27.66	11.11	38.77	54.00	-15.23	Average	Horizontal
3	15540.00	35.31	10.76	46.07	74.00	-27.93	Peak	Horizontal
4	15540.00	23.32	10.76	34.08	54.00	-19.92	Average	Horizontal
5	10360.00	29.93	9.39	39.32	74.00	-34.68	Peak	Vertical
6	10360.00	18.77	9.39	28.16	54.00	-25.84	Average	Vertical
7	15540.00	33.28	11.59	44.87	74.00	-29.13	Peak	Vertical
8	15540.00	20.81	11.59	32.40	54.00	-21.60	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 44

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10440.00	38.92	11.31	50.23	74.00	-23.77	Peak	Horizontal
2	10440.00	27.67	11.31	38.98	54.00	-15.02	Average	Horizontal
3	15660.00	34.07	11.00	45.07	74.00	-28.93	Peak	Horizontal
4	15660.00	22.61	11.00	33.61	54.00	-20.39	Average	Horizontal
5	10440.00	32.90	9.43	42.33	74.00	-31.67	Peak	Vertical
6	10440.00	21.33	9.43	30.76	54.00	-23.24	Average	Vertical
7	15660.00	31.05	11.93	42.98	74.00	-31.02	Peak	Vertical
8	15660.00	19.25	11.93	31.18	54.00	-22.82	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 48

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10480.00	39.82	11.41	51.23	74.00	-22.77	Peak	Horizontal
2	10480.00	26.82	11.41	38.23	54.00	-15.77	Average	Horizontal
3	15720.00	33.33	11.08	44.41	74.00	-29.59	Peak	Horizontal
4	15720.00	21.63	11.08	32.71	54.00	-21.29	Average	Horizontal
5	10480.00	32.96	9.45	42.41	74.00	-31.59	Peak	Vertical
6	10480.00	19.55	9.45	29.00	54.00	-25.00	Average	Vertical
7	15720.00	31.98	12.05	44.03	74.00	-29.97	Peak	Vertical
8	15720.00	20.08	12.05	32.13	54.00	-21.87	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 52

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10520.00	39.46	11.42	50.88	74.00	-23.12	Peak	Horizontal
2	10520.00	27.20	11.42	38.62	54.00	-15.38	Average	Horizontal
3	15780.00	33.95	11.16	45.11	74.00	-28.89	Peak	Horizontal
4	15780.00	21.67	11.16	32.83	54.00	-21.17	Average	Horizontal
5	10520.00	31.02	9.43	40.45	74.00	-33.55	Peak	Vertical
6	10520.00	19.72	9.43	29.15	54.00	-24.85	Average	Vertical
7	15780.00	30.22	12.19	42.41	74.00	-31.59	Peak	Vertical
8	15780.00	18.53	12.19	30.72	54.00	-23.28	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 60

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10600.00	40.38	11.33	51.71	74.00	-22.29	Peak	Horizontal
2	10600.00	27.87	11.33	39.20	54.00	-14.80	Average	Horizontal
3	15900.00	32.80	11.33	44.13	74.00	-29.87	Peak	Horizontal
4	15900.00	20.79	11.33	32.12	54.00	-21.88	Average	Horizontal
5	10600.00	31.42	9.37	40.79	74.00	-33.21	Peak	Vertical
6	10600.00	20.54	9.37	29.91	54.00	-24.09	Average	Vertical
7	15900.00	30.89	12.45	43.34	74.00	-30.66	Peak	Vertical
8	15900.00	19.21	12.45	31.66	54.00	-22.34	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 64

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10640.00	39.22	11.29	50.51	74.00	-23.49	Peak	Horizontal
2	10640.00	28.31	11.29	39.60	54.00	-14.40	Average	Horizontal
3	15960.00	33.59	11.49	45.08	74.00	-28.92	Peak	Horizontal
4	15960.00	20.50	11.49	31.99	54.00	-22.01	Average	Horizontal
5	10640.00	32.68	9.34	42.02	74.00	-31.98	Peak	Vertical
6	10640.00	20.97	9.34	30.31	54.00	-23.69	Average	Vertical
7	15960.00	31.01	12.66	43.67	74.00	-30.33	Peak	Vertical
8	15960.00	19.16	12.66	31.82	54.00	-22.18	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 100

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11000.00	38.78	10.30	49.08	74.00	-24.92	Peak	Horizontal
2	11000.00	27.29	10.30	37.59	54.00	-16.41	Average	Horizontal
3	16500.00	31.78	13.35	45.13	74.00	-28.87	Peak	Horizontal
4	16500.00	19.85	13.35	33.20	54.00	-20.80	Average	Horizontal
5	11000.00	36.90	8.50	45.40	74.00	-28.60	Peak	Vertical
6	11000.00	25.26	8.50	33.76	54.00	-20.24	Average	Vertical
7	16500.00	36.34	13.45	49.79	74.00	-24.21	Peak	Vertical
8	16500.00	24.43	13.45	37.88	54.00	-16.12	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 120

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11200.00	39.20	9.97	49.17	74.00	-24.83	Peak	Horizontal
2	11200.00	26.80	9.97	36.77	54.00	-17.23	Average	Horizontal
3	16800.00	38.92	13.24	52.16	74.00	-21.84	Peak	Horizontal
4	16800.00	25.75	13.24	38.99	54.00	-15.01	Average	Horizontal
5	11200.00	36.14	8.27	44.41	74.00	-29.59	Peak	Vertical
6	11200.00	24.94	8.27	33.21	54.00	-20.79	Average	Vertical
7	16800.00	39.42	13.01	52.43	74.00	-21.57	Peak	Vertical
8	16800.00	27.98	13.01	40.99	54.00	-13.01	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 140

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11400.00	40.28	9.86	50.14	74.00	-23.86	Peak	Horizontal
2	11400.00	28.84	9.86	38.70	54.00	-15.30	Average	Horizontal
3	17100.00	37.65	13.42	51.07	74.00	-22.93	Peak	Horizontal
4	17100.00	24.48	13.42	37.90	54.00	-16.10	Average	Horizontal
5	11400.00	38.74	8.30	47.04	74.00	-26.96	Peak	Vertical
6	11400.00	27.84	8.30	36.14	54.00	-17.86	Average	Vertical
7	17100.00	38.43	12.76	51.19	74.00	-22.81	Peak	Vertical
8	17100.00	26.41	12.76	39.17	54.00	-14.83	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 149

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11490.00	40.00	9.78	49.78	74.00	-24.22	Peak	Horizontal
2	11490.00	27.56	9.78	37.34	54.00	-16.66	Average	Horizontal
3	17235.00	41.55	13.98	55.53	74.00	-18.47	Peak	Horizontal
4	17235.00	28.23	13.98	42.21	54.00	-11.79	Average	Horizontal
5	11490.00	38.27	8.27	46.54	74.00	-27.46	Peak	Vertical
6	11490.00	25.94	8.27	34.21	54.00	-19.79	Average	Vertical
7	17235.00	40.04	13.24	53.28	74.00	-20.72	Peak	Vertical
8	17235.00	28.43	13.24	41.67	54.00	-12.33	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 157

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11570.00	38.54	9.86	48.40	74.00	-25.60	Peak	Horizontal
2	11570.00	26.39	9.86	36.25	54.00	-17.75	Average	Horizontal
3	17355.00	44.46	14.49	58.95	74.00	-15.05	Peak	Horizontal
4	17355.00	29.00	14.49	43.49	54.00	-10.51	Average	Horizontal
5	11570.00	35.69	8.47	44.16	74.00	-29.84	Peak	Vertical
6	11570.00	24.22	8.47	32.69	54.00	-21.31	Average	Vertical
7	17355.00	40.30	13.68	53.98	74.00	-20.02	Peak	Vertical
8	17355.00	28.18	13.68	41.86	54.00	-12.14	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT20_Channel 165

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11650.00	37.87	9.95	47.82	74.00	-26.18	Peak	Horizontal
2	11650.00	26.45	9.95	36.40	54.00	-17.60	Average	Horizontal
3	17475.00	38.05	15.69	53.74	74.00	-20.26	Peak	Horizontal
4	17475.00	25.02	15.69	40.71	54.00	-13.29	Average	Horizontal
5	11650.00	37.29	8.69	45.98	74.00	-28.02	Peak	Vertical
6	11650.00	25.13	8.69	33.82	54.00	-20.18	Average	Vertical
7	17475.00	38.80	14.00	52.80	74.00	-21.20	Peak	Vertical
8	17475.00	26.74	14.00	40.74	54.00	-13.26	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 38

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10380.00	38.98	11.17	50.15	74.00	-23.85	Peak	Horizontal
2	10380.00	27.42	11.17	38.59	54.00	-15.41	Average	Horizontal
3	15570.00	34.89	10.84	45.73	74.00	-28.27	Peak	Horizontal
4	15570.00	23.34	10.84	34.18	54.00	-19.82	Average	Horizontal
5	10380.00	35.91	9.41	45.32	74.00	-28.68	Peak	Vertical
6	10380.00	22.49	9.41	31.90	54.00	-22.10	Average	Vertical
7	15570.00	31.91	11.69	43.60	74.00	-30.40	Peak	Vertical
8	15570.00	20.58	11.69	32.27	54.00	-21.73	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 46

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10460.00	40.44	11.35	51.79	74.00	-22.21	Peak	Horizontal
2	10460.00	27.69	11.35	39.04	54.00	-14.96	Average	Horizontal
3	15690.00	35.01	11.03	46.04	74.00	-27.96	Peak	Horizontal
4	15690.00	22.68	11.03	33.71	54.00	-20.29	Average	Horizontal
5	10460.00	35.82	9.43	45.25	74.00	-28.75	Peak	Vertical
6	10460.00	23.71	9.43	33.14	54.00	-20.86	Average	Vertical
7	15690.00	31.08	11.98	43.06	74.00	-30.94	Peak	Vertical
8	15690.00	18.87	11.98	30.85	54.00	-23.15	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 54

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10540.00	41.10	11.41	52.51	74.00	-21.49	Peak	Horizontal
2	10540.00	27.51	11.41	38.92	54.00	-15.08	Average	Horizontal
3	15810.00	33.64	11.21	44.85	74.00	-29.15	Peak	Horizontal
4	15810.00	21.00	11.21	32.21	54.00	-21.79	Average	Horizontal
5	10540.00	33.54	9.42	42.96	74.00	-31.04	Peak	Vertical
6	10540.00	21.19	9.42	30.61	54.00	-23.39	Average	Vertical
7	15810.00	30.48	12.26	42.74	74.00	-31.26	Peak	Vertical
8	15810.00	18.49	12.26	30.75	54.00	-23.25	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 62

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10620.00	39.23	11.30	50.53	74.00	-23.47	Peak	Horizontal
2	10620.00	27.96	11.30	39.26	54.00	-14.74	Average	Horizontal
3	15930.00	32.72	11.41	44.13	74.00	-29.87	Peak	Horizontal
4	15930.00	20.71	11.41	32.12	54.00	-21.88	Average	Horizontal
5	10620.00	31.59	9.35	40.94	74.00	-33.06	Peak	Vertical
6	10620.00	19.40	9.35	28.75	54.00	-25.25	Average	Vertical
7	15930.00	31.77	12.56	44.33	74.00	-29.67	Peak	Vertical
8	15930.00	19.57	12.56	32.13	54.00	-21.87	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 102

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11020.00	38.82	11.30	50.12	74.00	-23.88	Peak	Horizontal
2	11020.00	27.00	11.30	38.30	54.00	-15.70	Average	Horizontal
3	16530.00	32.10	11.41	43.51	74.00	-30.49	Peak	Horizontal
4	16530.00	20.71	11.41	32.12	54.00	-21.88	Average	Horizontal
5	11020.00	33.36	8.45	41.81	74.00	-32.19	Peak	Vertical
6	11020.00	21.87	8.45	30.32	54.00	-23.68	Average	Vertical
7	16530.00	35.21	13.40	48.61	74.00	-25.39	Peak	Vertical
8	16530.00	23.76	13.40	37.16	54.00	-16.84	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 110

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11100.00	38.44	10.00	48.44	74.00	-25.56	Peak	Horizontal
2	11100.00	26.97	10.00	36.97	54.00	-17.03	Average	Horizontal
3	16650.00	37.36	13.29	50.65	74.00	-23.35	Peak	Horizontal
4	16650.00	24.58	13.29	37.87	54.00	-16.13	Average	Horizontal
5	11100.00	34.94	8.26	43.20	74.00	-30.80	Peak	Vertical
6	11100.00	22.93	8.26	31.19	54.00	-22.81	Average	Vertical
7	16650.00	39.44	13.18	52.62	74.00	-21.38	Peak	Vertical
8	16650.00	27.46	13.18	40.64	54.00	-13.36	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 134

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11340.00	39.86	9.89	49.75	74.00	-24.25	Peak	Horizontal
2	11340.00	28.36	9.89	38.25	54.00	-15.75	Average	Horizontal
3	17010.00	34.68	13.18	47.86	74.00	-26.14	Peak	Horizontal
4	17010.00	22.90	13.18	36.08	54.00	-17.92	Average	Horizontal
5	11340.00	38.40	8.29	46.69	74.00	-27.31	Peak	Vertical
6	11340.00	26.02	8.29	34.31	54.00	-19.69	Average	Vertical
7	17010.00	37.52	12.67	50.19	74.00	-23.81	Peak	Vertical
8	17010.00	25.40	12.67	38.07	54.00	-15.93	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 151

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11510.00	39.93	9.79	49.72	74.00	-24.28	Peak	Horizontal
2	11510.00	27.17	9.79	36.96	54.00	-17.04	Average	Horizontal
3	17265.00	40.49	14.11	54.60	74.00	-19.40	Peak	Horizontal
4	17265.00	28.27	14.11	42.38	54.00	-11.62	Average	Horizontal
5	11510.00	36.20	8.30	44.50	74.00	-29.50	Peak	Vertical
6	11510.00	25.14	8.30	33.44	54.00	-20.56	Average	Vertical
7	17265.00	39.67	13.35	53.02	74.00	-20.98	Peak	Vertical
8	17265.00	28.09	13.35	41.44	54.00	-12.56	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11n-HT40_Channel 159

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11590.00	37.47	9.87	47.34	74.00	-26.66	Peak	Horizontal
2	11590.00	25.73	9.87	35.60	54.00	-18.40	Average	Horizontal
3	17385.00	39.18	14.62	53.80	74.00	-20.20	Peak	Horizontal
4	17385.00	27.35	14.62	41.97	54.00	-12.03	Average	Horizontal
5	11590.00	33.72	8.52	42.24	74.00	-31.76	Peak	Vertical
6	11590.00	23.33	8.52	31.85	54.00	-22.15	Average	Vertical
7	17385.00	38.07	13.79	51.86	74.00	-22.14	Peak	Vertical
8	17385.00	27.78	13.79	41.57	54.00	-12.43	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11ac-VHT80_Channel 42

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10460.00	36.50	11.35	47.85	74.00	-26.15	Peak	Horizontal
2	10460.00	25.38	11.35	36.73	54.00	-17.27	Average	Horizontal
3	15690.00	36.77	11.03	47.80	74.00	-26.20	Peak	Horizontal
4	15690.00	26.13	11.03	37.16	54.00	-16.84	Average	Horizontal
5	10460.00	36.90	9.43	46.33	74.00	-27.67	Peak	Vertical
6	10460.00	26.02	9.43	35.45	54.00	-18.55	Average	Vertical
7	15690.00	36.83	11.98	48.81	74.00	-25.19	Peak	Vertical
8	15690.00	25.37	11.98	37.35	54.00	-16.65	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11ac-VHT80_Channel 58

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10580.00	38.36	11.36	49.72	74.00	-24.28	Peak	Horizontal
2	10580.00	26.93	11.36	38.29	54.00	-15.71	Average	Horizontal
3	15870.00	36.09	11.29	47.38	74.00	-26.62	Peak	Horizontal
4	15870.00	24.66	11.29	35.95	54.00	-18.05	Average	Horizontal
5	10580.00	38.02	9.39	47.41	74.00	-26.59	Peak	Vertical
6	10580.00	26.17	9.39	35.56	54.00	-18.44	Average	Vertical
7	15870.00	36.93	12.38	49.31	74.00	-24.69	Peak	Vertical
8	15870.00	24.47	12.38	36.85	54.00	-17.15	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11ac-VHT80_Channel 106

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11060.00	37.86	10.12	47.98	74.00	-26.02	Peak	Horizontal
2	11060.00	27.28	10.12	37.40	54.00	-16.60	Average	Horizontal
3	16590.00	35.21	13.31	48.52	74.00	-25.48	Peak	Horizontal
4	16590.00	22.92	13.31	36.23	54.00	-17.77	Average	Horizontal
5	11060.00	35.25	8.36	43.61	74.00	-30.39	Peak	Vertical
6	11060.00	23.50	8.36	31.86	54.00	-22.14	Average	Vertical
7	16590.00	34.46	13.29	47.75	74.00	-26.25	Peak	Vertical
8	16590.00	21.80	13.29	35.09	54.00	-18.91	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11ac-VHT80_Channel 122

No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11220.00	41.28	9.94	51.22	74.00	-22.78	Peak	Horizontal
2	11220.00	27.92	9.94	37.86	54.00	-16.14	Average	Horizontal
3	16830.00	38.41	13.21	51.62	74.00	-22.38	Peak	Horizontal
4	16830.00	25.74	13.21	38.95	54.00	-15.05	Average	Horizontal
5	11220.00	36.80	8.27	45.07	74.00	-28.93	Peak	Vertical
6	11220.00	23.62	8.27	31.89	54.00	-22.11	Average	Vertical
7	16830.00	36.21	12.85	49.06	74.00	-24.94	Peak	Vertical
8	16830.00	22.99	12.85	35.84	54.00	-18.16	Average	Vertical

MIMO_Chain 0+1_ IEEE 802.11ac-VHT80_Channel 155



No.	Frequency (MHz)	Reading (dBuV/m)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11550.00	39.23	9.93	49.16	74.00	-24.84	Peak	Horizontal
2	11550.00	27.47	9.93	37.40	54.00	-16.60	Average	Horizontal
3	17325.00	30.80	14.36	45.16	74.00	-28.84	Peak	Horizontal
4	17325.00	19.08	14.36	33.44	54.00	-20.56	Average	Horizontal
5	11550.00	35.14	8.41	43.55	74.00	-30.45	Peak	Vertical
6	11550.00	23.05	8.41	31.46	54.00	-22.54	Average	Vertical
7	17325.00	32.00	13.57	45.57	74.00	-28.43	Peak	Vertical
8	17325.00	18.44	13.57	32.01	54.00	-21.99	Average	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

Band Edge Measurements (Radiated)

SISO_Chain 0_IEEE 802.11a



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886



E-mail: info@uttlab.com



<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0









Shenzhen UnionTrust Quality and Technology Co., Ltd.



Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888



Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0



SISO_Chain 1_ IEEE 802.11a



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886



E-mail: info@uttlab.com



<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0









Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888



Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

MIMO_Chain 0+1_ IEEE 802.11n-HT20


Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886



E-mail: info@uttlab.com



<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0









Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

