



TEST REPORT

Report Reference No. : CHTEW19100170 Report verification: 

Project No. : SHT1910023301EW

FCC ID : 2AUWY-LD1

Applicant's name : LiveCare Corp

Address : 252 W 37th Street, 17th Floor, New York, NY 10018, USA

Manufacturer : Soyas Science Technology Limited

Address : Unit 1402A 14/f The Belgian Bank Bldg Nos 721-725 Nathan Rd, Mongkok, KL, Hongkong

Test item description : Mini smart phone

Trade Mark : Link+

Model/Type reference : LD1

Listed Model(s) : -

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample : Oct 17, 2019

Date of testing : Oct 18, 2019- Oct 30, 2019

Date of issue : Oct 31, 2019

Result : PASS

Compiled by
(position+printedname+signature).... : File administrators Silvia Li

Supervised by
(position+printedname+signature).... : Project Engineer Aaron Fang

Approved by
(position+printedname+signature).... : RF Manager Hans Hu

Silvia Li

Aaron Fang

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>10</u>
5.1.	Antenna requirement	10
5.2.	Conducted Emissions (AC Main)	11
5.3.	Conducted Peak Output Power	14
5.4.	Power Spectral Density	15
5.5.	6dB bandwidth	21
5.6.	Restricted band	27
5.7.	Band edge and Spurious Emissions (conducted)	32
5.8.	Spurious Emissions (radiated)	49
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>58</u>
<u>7.</u>	<u>EXTERANAL AND INTERNAL PHOTOS</u>	<u>59</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-10-31	Original

2. TEST DESCRIPTION

Test Item	FCC Rule	Result	Test Engineer
Antenna requirement	15.203/15.247(c)	PASS	Kang Yang
Line Conducted Emissions (AC Main)	15.207	PASS	Kang Yang
Conducted Peak Output Power	15.247(b)(3)	PASS	Ximing Huang
Power Spectral Density	15.247(e)	PASS	Ximing Huang
6dB Bandwidth	15.247(a)(2)	PASS	Ximing Huang
Restricted band	15.247(d)/15.205	PASS	Barry Chang
Spurious Emissions	15.247(d)/15.209	PASS	Barry Chang

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	LiveCare Corp
Address:	252 W 37 th Street, 17 th Floor, New York, NY 10018, USA
Manufacturer:	Soyes Science Technology Limited
Address:	Unit 1402A 14/f The Belgian Bank Bldg Nos 721-725 Nathan Rd, Mongkok, KL, Hongkong

3.2. Product Description

Name of EUT:	Mini smart phone
Trade Mark:	Link+
Model No.:	LD1
Listed Model(s):	-
IMEI:	Conducted: 86805040001043 Radiated: 86805040001050
Power supply:	DC 3.8V
Adapter information:	Model:PA-US5V1A-019 Input: 100-240Va.c., 50/60Hz, 0.2A Output: 5.0Vd.c.,1.0A
Hardware version:	R3705-MB-V1.1
Software version:	R3705-V1.0.0
WIFI	
Supported type:	802.11b/802.11g/802.11n(HT20)/802.11n(HT40)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)/802.11n(HT40)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20) 2422MHz~2452MHz for 802.11n(HT40)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Channel separation:	5MHz
Antenna type:	PIFA Antenna
Antenna gain:	2.0dBi

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below gray bottom.

802.11b/g/n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	01	-
02	2417	02	-
03	2422	03	2422
04	2427	04	2427
05	2432	05	2432
06	2437	06	2437
07	2442	07	2442
08	2447	08	2447
09	2452	09	2452
10	2457	10	-
11	2462	11	-

➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	/	Manufacturer:	/
		Model No.:	/
○	/	Manufacturer:	/
		Model No.:	/

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377A

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377A.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.51 dB	(1)
Conducted spurious emissions 9kHz~40GHz	0.51 dB	(1)
Conducted Disturbance 150kHz~30MHz	3.02 dB	(1)
Radiated Emissions below 1GHz	4.90 dB	(1)
Radiated Emissions above 1GHz	4.96 dB	(1)
Occupied Bandwidth	70 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX_142	EF-NM-BNCM-2M	2019/10/23	2020/10/22
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated Emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2019/10/26	2020/10/25
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2018/11/14	2019/11/13
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2019/8/21	2020/8/20
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX104	501184/4	2019/5/27	2020/5/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/30	2021/09/29
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2017/04/01	2020/03/31
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2019/05/23	2020/05/22
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	25841	2017/03/27	2020/03/26
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	RE-7-FH	N/A	2018/11/15	2019/11/14
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2019/10/26	2020/10/25
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2019/10/26	2020/10/25
●	Test software	Tonscend	JS1120-2(WIFI)	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna requirement

REQUIREMENT:

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd=Cable lose+ Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit -Level

Test Line:

L

**MEASUREMENT RESULT: "GM1910225027_fin"**

10/22/2019 1:40PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.168000	44.40	10.1	65	20.7	QP	L1	GND
0.568500	30.40	10.1	56	25.6	QP	L1	GND
0.870000	26.60	10.1	56	29.4	QP	L1	GND
16.507500	26.10	10.2	60	33.9	QP	L1	GND
22.609500	28.10	10.2	60	31.9	QP	L1	GND
23.464500	28.40	10.2	60	31.6	QP	L1	GND


MEASUREMENT RESULT: "GM1910225027_fin2"

10/22/2019 1:40PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.168000	28.90	10.1	55	26.2	AV	L1	GND
0.564000	25.60	10.1	46	20.4	AV	L1	GND
0.991500	17.50	10.1	46	28.5	AV	L1	GND
4.947000	16.20	10.1	46	29.8	AV	L1	GND
9.802500	17.70	10.2	50	32.3	AV	L1	GND
23.707500	19.80	10.2	50	30.2	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1910225028_fin"**

10/22/2019 1:43PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	42.40	10.1	65	22.9	QP	N	GND
0.564000	26.20	10.1	56	29.8	QP	N	GND
0.928500	22.00	10.1	56	34.0	QP	N	GND
3.885000	19.00	10.1	56	37.0	QP	N	GND
11.931000	22.30	10.2	60	37.7	QP	N	GND
23.190000	27.20	10.2	60	32.8	QP	N	GND

MEASUREMENT RESULT: "GM1910225028_fin2"

10/22/2019 1:43PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.262500	15.30	10.1	51	36.1	AV	N	GND
0.829500	15.90	10.1	46	30.1	AV	N	GND
0.987000	9.60	10.1	46	36.4	AV	N	GND
3.952500	12.40	10.1	46	33.6	AV	N	GND
11.850000	14.40	10.2	50	35.6	AV	N	GND
22.965000	18.90	10.2	50	31.1	AV	N	GND

5.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable


Type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
802.11b	01	19.46	17.42	≤30.00	Pass
	06	19.69	17.51		
	11	19.81	17.63		
802.11g	01	22.32	18.56	≤30.00	Pass
	06	22.24	18.46		
	11	22.04	18.05		
802.11n(HT20)	01	22.28	18.58	≤30.00	Pass
	06	22.30	18.61		
	11	22.14	18.46		
802.11n(HT40)	03	22.19	18.48	≤30.00	Pass
	06	21.98	18.35		
	09	21.87	17.97		

5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:


Please refer to the clause 3.3


TEST RESULTS


☒ Passed ☐ Not Applicable


Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	0.57	≤8.00	Pass
	06	0.57		
	11	0.61		
802.11g	01	-1.71	≤8.00	Pass
	06	-2.01		
	11	-2.07		
802.11n(HT20)	01	-1.20	≤8.00	Pass
	06	-1.10		
	11	-1.55		
802.11n(HT40)	03	-5.83	≤8.00	Pass
	06	-6.09		
	09	-5.58		

Test plot as follows:










5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW $\geq$ 3 x RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:


Please refer to the clause 3.3


TEST RESULTS


☒ Passed ☐ Not Applicable


Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	9.18	≥500	Pass
	06	9.18		
	11	9.18		
802.11g	01	16.38	≥500	Pass
	06	16.41		
	11	16.41		
802.11n(HT20)	01	17.64	≥500	Pass
	06	17.64		
	11	17.64		
802.11n(HT40)	03	36.48	≥500	Pass
	06	36.48		
	09	36.48		

Test plot as follows:










5.6. Restricted band

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:
RBW=1MHz, VBW=3MHz PEAK detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final level= Read level + Factor

802.11b				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	11.90	35.78	47.68	54.00	6.32	Horizontal	AV
2390.036	11.29	35.50	46.79	54.00	7.21	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	21.63	35.78	57.41	74.00	16.59	Horizontal	PK
2390.036	21.91	35.50	57.41	74.00	16.59	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	12.06	35.78	47.84	54.00	6.16	Vertical	AV
2390.036	11.32	35.50	46.82	54.00	7.18	Vertical	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	22.37	35.78	58.15	74.00	15.85	Vertical	PK
2390.036	21.73	35.50	57.23	74.00	16.77	Vertical	PK

802.11b				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	11.38	35.31	46.69	54.00	7.31	Horizontal	AV
2500.000	11.29	35.28	46.57	54.00	7.43	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	22.66	35.31	57.97	74.00	16.03	Horizontal	PK
2500.000	21.36	35.28	56.64	74.00	17.36	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	11.41	35.31	46.72	54.00	7.28	Vertical	AV
2500.000	11.38	35.28	46.66	54.00	7.34	Vertical	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	21.72	35.31	57.03	74.00	16.97	Vertical	PK
2500.000	21.53	35.28	56.81	74.00	17.19	Vertical	PK

802.11g				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	22.97	35.78	58.75	74.00	15.25	Horizontal	PK
2390.036	21.77	35.50	57.27	74.00	16.73	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	11.78	35.78	47.56	54.00	6.44	Horizontal	AV
2390.036	11.71	35.50	47.21	54.00	6.79	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	21.94	35.78	57.72	74.00	16.28	Vertical	PK
2390.036	22.23	35.50	57.73	74.00	16.27	Vertical	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	11.71	35.78	47.49	54.00	6.51	Vertical	AV
2390.036	11.53	35.50	47.03	54.00	6.97	Vertical	AV
802.11g				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	22.16	35.31	57.47	74.00	16.53	Horizontal	PK
2500.000	22.07	35.28	57.35	74.00	16.65	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	11.39	35.31	46.70	54.00	7.30	Horizontal	AV
2500.000	11.38	35.28	46.66	54.00	7.34	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	21.71	35.31	57.02	74.00	16.98	Vertical	PK
2500.000	22.73	35.28	58.01	74.00	15.99	Vertical	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	11.79	35.31	47.10	54.00	6.90	Vertical	AV
2500.000	11.27	35.28	46.55	54.00	7.45	Vertical	AV

802.11n(HT20)				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	11.90	35.78	47.68	54.00	6.32	Horizontal	AV
2390.036	11.92	35.50	47.42	54.00	6.58	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	21.60	35.78	57.38	74.00	16.62	Horizontal	PK
2390.036	22.63	35.50	58.13	74.00	15.87	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	22.03	35.78	57.81	74.00	16.19	Vertical	PK
2390.036	22.03	35.50	57.53	74.00	16.47	Vertical	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	11.86	35.78	47.64	54.00	6.36	Vertical	AV
2390.036	11.75	35.50	47.25	54.00	6.75	Vertical	AV

802.11n(HT20)				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	11.45	35.31	46.76	54.00	7.24	Horizontal	AV
2500.000	11.41	35.28	46.69	54.00	7.31	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	21.55	35.31	56.86	74.00	17.14	Horizontal	PK
2500.000	21.16	35.28	56.44	74.00	17.56	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	22.53	35.31	57.84	74.00	16.16	Vertical	PK
2500.000	22.17	35.28	57.45	74.00	16.55	Vertical	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.531	11.71	35.31	47.02	54.00	6.98	Vertical	AV
2500.000	11.52	35.28	46.80	54.00	7.20	Vertical	AV

802.11n(HT40)				CH03			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	11.87	35.78	47.65	54.00	6.35	Horizontal	AV
2390.028	12.01	35.50	47.51	54.00	6.49	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	22.13	35.78	57.91	74.00	16.09	Horizontal	PK
2390.028	22.62	35.50	58.12	74.00	15.88	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	11.95	35.78	47.73	54.00	6.27	Vertical	AV
2390.028	12.16	35.50	47.66	54.00	6.34	Vertical	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	21.34	35.78	57.12	74.00	16.88	Vertical	PK
2390.028	22.46	35.50	57.96	74.00	16.04	Vertical	PK

802.11n(HT40)				CH09			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.517	11.63	35.31	46.94	54.00	7.06	Horizontal	AV
2500.000	11.39	35.28	46.67	54.00	7.33	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.517	21.97	35.31	57.28	74.00	16.72	Horizontal	PK
2500.000	21.78	35.28	57.06	74.00	16.94	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.517	11.73	35.31	47.04	54.00	6.96	Vertical	AV
2500.000	11.56	35.28	46.84	54.00	7.16	Vertical	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.517	22.33	35.31	57.64	74.00	16.36	Vertical	PK
2500.000	22.02	35.28	57.30	74.00	16.70	Vertical	PK


5.7. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level

Note: the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.


TEST MODE:



Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Test Item:	Bandedge	Type:	802.11b																																										
CH01	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 246.5 μs VBW 300 kHz Mode Auto FFT Count 300/300 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] 6.09 dBm M2[1] 2.412520 GHz M3 -53.07 dBm M4 -58.83 dBm M5 -35.11 dBm D1 -13.910 dBm Start 2.31 GHz 691 pts Stop 2.422 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.41252 GHz</td><td>6.09 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-40.53 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-51.66 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-58.83 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.3996 GHz</td><td>-35.11 dBm</td><td></td><td></td></tr></tbody></table> Date: 25 OCT 2019 11:04:04			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.41252 GHz	6.09 dBm			M2	1		2.4 GHz	-40.53 dBm			M3	1		2.39 GHz	-51.66 dBm			M4	1		2.31 GHz	-58.83 dBm			M5	1		2.3996 GHz	-35.11 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.41252 GHz	6.09 dBm																																									
M2	1		2.4 GHz	-40.53 dBm																																									
M3	1		2.39 GHz	-51.66 dBm																																									
M4	1		2.31 GHz	-58.83 dBm																																									
M5	1		2.3996 GHz	-35.11 dBm																																									
CH11	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 113.8 μs VBW 300 kHz Mode Auto FFT Count 300/300 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] 6.19 dBm M2[1] 2.4614920 GHz M3 -53.07 dBm M4 -50.24 dBm D1 -13.810 dBm Start 2.452 GHz 691 pts Stop 2.5 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.461492 GHz</td><td>6.19 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-53.07 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-55.17 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.4869913 GHz</td><td>-50.24 dBm</td><td></td><td></td></tr></tbody></table> Date: 25 OCT 2019 11:07:24			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.461492 GHz	6.19 dBm			M2	1		2.4835 GHz	-53.07 dBm			M3	1		2.5 GHz	-55.17 dBm			M4	1		2.4869913 GHz	-50.24 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.461492 GHz	6.19 dBm																																									
M2	1		2.4835 GHz	-53.07 dBm																																									
M3	1		2.5 GHz	-55.17 dBm																																									
M4	1		2.4869913 GHz	-50.24 dBm																																									




Test Item:	Bandedge	Type:	802.11n(HT20)																																																
CH01	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 246.5 μs VBW 300 kHz Mode Auto FFT Count 300/300 1Pk Max  Start 2.31 GHz 691 pts Stop 2.422 GHz <table><thead><tr><th>Marker</th><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td></td><td>2.41138 GHz</td><td>0.97 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td></td><td>2.4 GHz</td><td>-31.07 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td></td><td>2.39 GHz</td><td>-41.08 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td></td><td>2.31 GHz</td><td>-56.80 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td></td><td>2.3996 GHz</td><td>-31.05 dBm</td><td></td><td></td></tr></tbody></table> Date: 25 OCT 2019 11:16:23			Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			2.41138 GHz	0.97 dBm			M2	1			2.4 GHz	-31.07 dBm			M3	1			2.39 GHz	-41.08 dBm			M4	1			2.31 GHz	-56.80 dBm			M5	1			2.3996 GHz	-31.05 dBm		
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																												
M1	1			2.41138 GHz	0.97 dBm																																														
M2	1			2.4 GHz	-31.07 dBm																																														
M3	1			2.39 GHz	-41.08 dBm																																														
M4	1			2.31 GHz	-56.80 dBm																																														
M5	1			2.3996 GHz	-31.05 dBm																																														
CH11	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 113.8 μs VBW 300 kHz Mode Auto FFT Count 300/300 1Pk Max  Start 2.452 GHz 691 pts Stop 2.5 GHz <table><thead><tr><th>Marker</th><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td></td><td>2.461343 GHz</td><td>0.62 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td></td><td>2.4835 GHz</td><td>-42.24 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td></td><td>2.5 GHz</td><td>-52.20 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td></td><td>2.483513 GHz</td><td>-42.24 dBm</td><td></td><td></td></tr></tbody></table> Date: 25 OCT 2019 11:19:11			Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			2.461343 GHz	0.62 dBm			M2	1			2.4835 GHz	-42.24 dBm			M3	1			2.5 GHz	-52.20 dBm			M4	1			2.483513 GHz	-42.24 dBm										
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																												
M1	1			2.461343 GHz	0.62 dBm																																														
M2	1			2.4835 GHz	-42.24 dBm																																														
M3	1			2.5 GHz	-52.20 dBm																																														
M4	1			2.483513 GHz	-42.24 dBm																																														


Test Item:	Bandedge	Type:	802.11n(HT40)																																										
CH03	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 303.4 μs VBW 300 kHz Mode Auto FFT Count 296/300 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] M3 M4 M5 M6 -2.85 dBm 2.424140 GHz -33.03 dBm 2.394174 GHz -31.62 dBm -22.850 dBm Start 2.31 GHz 691 pts Stop 2.442 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.42414 GHz</td><td>-2.85 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-33.03 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-37.97 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-58.40 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.394174 GHz</td><td>-31.62 dBm</td><td></td><td></td></tr></tbody></table> Date: 25 OCT 2019 11:20:53			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.42414 GHz	-2.85 dBm			M2	1		2.4 GHz	-33.03 dBm			M3	1		2.39 GHz	-37.97 dBm			M4	1		2.31 GHz	-58.40 dBm			M5	1		2.394174 GHz	-31.62 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.42414 GHz	-2.85 dBm																																									
M2	1		2.4 GHz	-33.03 dBm																																									
M3	1		2.39 GHz	-37.97 dBm																																									
M4	1		2.31 GHz	-58.40 dBm																																									
M5	1		2.394174 GHz	-31.62 dBm																																									
CH09	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 300/300 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1 M2[1] M3 M4 -3.11 dBm 2.4505500 GHz -39.65 dBm 2.4835000 GHz Start 2.432 GHz 691 pts Stop 2.5 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.45055 GHz</td><td>-3.11 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-39.65 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-47.64 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.4836406 GHz</td><td>-39.41 dBm</td><td></td><td></td></tr></tbody></table> Date: 25 OCT 2019 11:23:32			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.45055 GHz	-3.11 dBm			M2	1		2.4835 GHz	-39.65 dBm			M3	1		2.5 GHz	-47.64 dBm			M4	1		2.4836406 GHz	-39.41 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.45055 GHz	-3.11 dBm																																									
M2	1		2.4835 GHz	-39.65 dBm																																									
M3	1		2.5 GHz	-47.64 dBm																																									
M4	1		2.4836406 GHz	-39.41 dBm																																									

Test Item:	SE	Type:	802.11b
CH01 Reference level	Spectrum Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100 1Pk Max		


CH06
Reference level





CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference levelCH11
30MHz~1000MHzCH11
1GHz~26GHz

Test Item:	SE	Type:	802.11g
CH01 Reference level	Spectrum Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100 IPk Max		


CH06
Reference level






CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference levelCH11
30MHz~1000MHzCH11
1GHz~26GHz

Test Item:	SE	Type:	802.11n(HT20)
CH01 Reference level	Spectrum Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100 1Pk Max M1[1] 1.01 dBm 2.4113490 GHz M1 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm CF 2.412 GHz 691 pts Span 30.0 MHz Date: 25 OCT.2019 11:16:30		
CH01 30MHz~1000MHz	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 1Pk Max M1[1] -52.66 dBm 878.4470 MHz D1 -18.990 dBm M1 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm Start 30.0 MHz 30001 pts Stop 1.0 GHz Date: 25 OCT.2019 11:16:46		
CH01 1GHz~26GHz	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 1Pk Max M1[1] -44.83 dBm 16.780000 GHz D1 -18.990 dBm M1 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm Start 1.0 GHz 30001 pts Stop 26.0 GHz Date: 25 OCT.2019 11:17:02		


CH06
Reference level









CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference levelCH11
30MHz~1000MHzCH11
1GHz~26GHz

Test Item:	SE	Type:	802.11n(HT40)
CH03 Reference level		 Spectrum Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 132.7 μs VBW 300 kHz Mode Auto FFT Count 100/100 IPk Max M1[1] -2.82 dBm 2.4240840 GHz CF 2.422 GHz 691 pts Span 60.0 MHz Date: 25 OCT.2019 11:21:00	
CH03 30MHz~1000MHz		 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPk Max M1[1] -51.73 dBm 897.0290 MHz D1 -22.820 dBm Start 30.0 MHz 30001 pts Stop 1.0 GHz Date: 25 OCT.2019 11:21:15	
CH03 1GHz~26GHz		 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPk Max M1[1] -44.14 dBm 16.720000 GHz D1 -22.820 dBm Start 1.0 GHz 30001 pts Stop 26.0 GHz Date: 25 OCT.2019 11:21:31	


CH06
Reference level




CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH09
Reference level



CH09
30MHz~1000MHz



CH09
1GHz~26GHz



5.8. Spurious Emissions (radiated)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9kHz ~30MHz



➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) Final Level =Receiver Read level + Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

➤ **9kHz ~ 30MHz**

The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.


➤ **30MHz ~1000MHz**

Have pre-scan all modulation mode, found the 802.11b mode CH01 which it was worst case, so only the worst case's data on the test report.

➤ 30MHz ~ 1GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1910236150_red"**

10/24/2019 12:49AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	30.40	-8.1	40.0	9.6	QP	100.0	196.00	VERTICAL
57.160000	23.30	-4.7	40.0	16.7	QP	100.0	91.00	VERTICAL
148.340000	25.40	-9.4	43.5	18.1	QP	100.0	196.00	VERTICAL
307.420000	25.60	-2.3	46.0	20.4	QP	100.0	91.00	VERTICAL
546.040000	31.60	4.1	46.0	14.4	QP	100.0	161.00	VERTICAL
959.260000	39.00	12.4	46.0	7.0	QP	100.0	150.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1910236149_red"**

10/24/2019 12:47AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	24.10	-4.4	40.0	15.9	QP	300.0	83.00	HORIZONTAL
55.220000	24.20	-4.4	40.0	15.8	QP	300.0	12.00	HORIZONTAL
156.100000	23.90	-9.0	43.5	19.6	QP	100.0	195.00	HORIZONTAL
289.960000	25.50	-2.6	46.0	20.5	QP	300.0	315.00	HORIZONTAL
546.040000	31.70	4.1	46.0	14.3	QP	300.0	335.00	HORIZONTAL
928.220000	39.90	11.8	46.0	6.1	QP	300.0	12.00	HORIZONTAL

➤ 1 GHz ~ 25 GHz

802.11b CH01

Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3181.093	33.98	0.74	34.72	74.00	39.28	Horizontal	PK
4823.156	45.52	7.08	52.60	74.00	21.40	Horizontal	PK
7234.843	35.24	15.01	50.25	74.00	23.75	Horizontal	PK
9905.031	30.50	17.27	47.77	74.00	26.23	Horizontal	PK

Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3019.531	33.40	-0.03	33.37	74.00	40.63	Vertical	PK
4823.156	41.45	7.08	48.53	74.00	25.47	Vertical	PK
7237.781	35.87	15.01	50.88	74.00	23.12	Vertical	PK
9821.312	32.03	17.24	49.27	74.00	24.73	Vertical	PK

802.11b CH06

Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3175.218	32.61	0.71	33.32	74.00	40.68	Horizontal	PK
4874.562	44.89	7.15	52.04	74.00	21.96	Horizontal	PK
7309.750	32.48	15.08	47.56	74.00	26.44	Horizontal	PK
9841.875	31.88	17.25	49.13	74.00	24.87	Horizontal	PK

Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
4068.218	32.44	3.18	35.62	74.00	38.38	Vertical	PK
4873.093	42.14	7.15	49.29	74.00	24.71	Vertical	PK
7309.750	33.54	15.08	48.62	74.00	25.38	Vertical	PK
9890.343	31.60	17.27	48.87	74.00	25.13	Vertical	PK

802.11b				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3705.437	32.89	1.61	34.50	74.00	39.50	Horizontal	PK
4924.500	42.73	7.34	50.07	74.00	23.93	Horizontal	PK
7387.593	31.24	15.33	46.57	74.00	27.43	Horizontal	PK
10326.56	31.27	17.48	48.75	74.00	25.25	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3571.781	32.31	1.34	33.65	74.00	40.35	Vertical	PK
4924.500	38.95	7.34	46.29	74.00	27.71	Vertical	PK
7384.656	31.90	15.32	47.22	74.00	26.78	Vertical	PK
9865.375	31.14	17.26	48.40	74.00	25.60	Vertical	PK

802.11g				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3176.687	32.84	0.72	33.56	74.00	40.44	Horizontal	PK
4820.218	38.06	7.08	45.14	74.00	28.86	Horizontal	PK
7325.906	31.09	15.13	46.22	74.00	27.78	Horizontal	PK
10380.90	30.76	17.51	48.27	74.00	25.73	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3179.625	33.61	0.73	34.34	74.00	39.66	Vertical	PK
4821.687	33.86	7.08	40.94	74.00	33.06	Vertical	PK
6553.343	30.77	12.86	43.63	74.00	30.37	Vertical	PK
7980.968	30.64	16.21	46.85	74.00	27.15	Vertical	PK

802.11g				CH06			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3110.593	33.57	0.38	33.95	74.00	40.05	Horizontal	PK
4868.687	40.23	7.14	47.37	74.00	26.63	Horizontal	PK
7355.281	31.08	15.23	46.31	74.00	27.69	Horizontal	PK
10407.34	31.24	17.52	48.76	74.00	25.24	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3649.625	33.33	1.52	34.85	74.00	39.15	Vertical	PK
4880.437	35.47	7.15	42.62	74.00	31.38	Vertical	PK
7306.812	33.32	15.07	48.39	74.00	25.61	Vertical	PK
10799.50	31.02	17.71	48.73	74.00	25.27	Vertical	PK

802.11g				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3110.593	33.09	0.38	33.47	74.00	40.53	Horizontal	PK
4923.031	37.80	7.33	45.13	74.00	28.87	Horizontal	PK
7322.968	29.71	15.12	44.83	74.00	29.17	Horizontal	PK
9327.812	31.24	17.76	49.00	74.00	25.00	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3197.250	33.00	0.83	33.83	74.00	40.17	Vertical	PK
4924.500	35.22	7.34	42.56	74.00	31.44	Vertical	PK
7468.375	30.80	15.40	46.20	74.00	27.80	Vertical	PK
9194.156	32.07	16.69	48.76	74.00	25.24	Vertical	PK

802.11n(HT20)				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3123.812	33.45	0.44	33.89	74.00	40.11	Horizontal	PK
4823.156	35.98	7.08	43.06	74.00	30.94	Horizontal	PK
8017.687	30.64	16.22	46.86	74.00	27.14	Horizontal	PK
10104.78	31.85	17.37	49.22	74.00	24.78	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3037.156	33.76	0.04	33.80	74.00	40.20	Vertical	PK
5185.937	31.30	8.95	40.25	74.00	33.75	Vertical	PK
8101.406	30.49	16.34	46.83	74.00	27.17	Vertical	PK
10326.56	31.49	17.48	48.97	74.00	25.03	Vertical	PK

802.11n(HT20)				CH06			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3186.968	32.95	0.77	33.72	74.00	40.28	Horizontal	PK
4874.562	38.17	7.15	45.32	74.00	28.68	Horizontal	PK
6628.250	30.85	13.24	44.09	74.00	29.91	Horizontal	PK
9081.062	32.26	16.69	48.95	74.00	25.05	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3654.031	32.74	1.53	34.27	74.00	39.73	Vertical	PK
4877.500	35.43	7.15	42.58	74.00	31.42	Vertical	PK
7299.468	31.92	15.05	46.97	74.00	27.03	Vertical	PK
9803.687	31.52	17.23	48.75	74.00	25.25	Vertical	PK

802.11n(HT20)				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3120.875	33.83	0.43	34.26	74.00	39.74	Horizontal	PK
4927.437	37.48	7.36	44.84	74.00	29.16	Horizontal	PK
7895.781	30.21	16.27	46.48	74.00	27.52	Horizontal	PK
9909.437	31.55	17.27	48.82	74.00	25.18	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3163.468	33.13	0.65	33.78	74.00	40.22	Vertical	PK
4925.968	32.40	7.35	39.75	74.00	34.25	Vertical	PK
7364.093	31.43	15.26	46.69	74.00	27.31	Vertical	PK
9272.000	30.76	17.58	48.34	74.00	25.66	Vertical	PK

802.11n(HT40)				CH03			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3194.312	33.31	0.81	34.12	74.00	39.88	Horizontal	PK
4830.500	37.02	7.09	44.11	74.00	29.89	Horizontal	PK
7571.187	29.95	15.74	45.69	74.00	28.31	Horizontal	PK
9319.000	30.64	17.81	48.45	74.00	25.55	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3134.093	33.63	0.50	34.13	74.00	39.87	Vertical	PK
4846.656	33.72	7.11	40.83	74.00	33.17	Vertical	PK
7622.593	30.80	15.78	46.58	74.00	27.42	Vertical	PK
10330.96	31.00	17.48	48.48	74.00	25.52	Vertical	PK

802.11n(HT40)				CH06			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3651.093	33.35	1.52	34.87	74.00	39.13	Horizontal	PK
4877.500	36.95	7.15	44.10	74.00	29.90	Horizontal	PK
7043.906	30.42	14.28	44.70	74.00	29.30	Horizontal	PK
9317.531	31.65	17.82	49.47	74.00	24.53	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3157.593	32.56	0.62	33.18	74.00	40.82	Vertical	PK
5053.750	31.24	8.36	39.60	74.00	34.40	Vertical	PK
7427.250	30.46	15.38	45.84	74.00	28.16	Vertical	PK
9584.843	31.25	17.24	48.49	74.00	25.51	Vertical	PK


802.11n(HT40)				CH09			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
3147.312	33.00	0.57	33.57	74.00	40.43	Horizontal	PK
4898.062	34.16	7.18	41.34	74.00	32.66	Horizontal	PK
7859.062	30.31	15.89	46.20	74.00	27.80	Horizontal	PK
10789.21	31.23	17.71	48.94	74.00	25.06	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
4066.750	31.50	3.17	34.67	74.00	39.33	Vertical	PK
4901.000	32.69	7.19	39.88	74.00	34.12	Vertical	PK
6892.625	30.40	14.03	44.43	74.00	29.57	Vertical	PK
9222.062	31.59	16.96	48.55	74.00	25.45	Vertical	PK

Remark:

1. Final Level = Receiver Read level + Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.



6. TEST SETUP PHOTOS

Conducted Emissions



Radiated Emissions





7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No.: CHTEW19100165

-----End of Report-----