



**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 ISSUE 2**

**TEST REPORT**

*For*

**CHAMPe Bingo Handset**

**MODEL NUMBER: VK10**

**FCC ID: 2AUX7-VK10**

**IC: 25598-VK10**

**REPORT NUMBER: 4789182259-9**

**ISSUE DATE: November 08, 2019**

*Prepared for*

**Estone Technology LTD  
2F, Building No.1, Jia'an Industrial Park, No.2 Long Chang Road, Bao'an, Shenzhen,  
China.**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake  
Hi-Tech Development Zone Dongguan, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



## Revision History

Rev.	Issue Date	Revisions	Revised By
V0	11/08/2019	Initial Issue	

Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (d)	Pass
3	Power Spectral Density	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d) RSS-247 Clause 5.5	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
6	Conducted Emission Test For AC Power Port	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
7	Antenna Requirement	FCC Part 15.203 RSS-GEN Clause 6.8	Pass

Note: This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>6</b>
<b>2. TEST METHODOLOGY .....</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	8
4.2. <i>MEASUREMENT UNCERTAINTY .....</i>	8
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>9</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	9
5.2. <i>MAXIMUM OUTPUT POWER .....</i>	9
5.3. <i>CHANNEL LIST .....</i>	9
5.4. <i>TEST CHANNEL CONFIGURATION .....</i>	9
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER .....</i>	10
5.6. <i>THE WORSE CASE CONFIGURATIONS .....</i>	10
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	10
5.8. <i>DESCRIPTION OF TEST SETUP .....</i>	11
5.9. <i>MEASURING INSTRUMENT AND SOFTWARE USED .....</i>	12
<b>6. MEASUREMENT METHODS .....</b>	<b>13</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>14</b>
7.1. <i>ON TIME AND DUTY CYCLE .....</i>	14
7.2. <i>6 dB DTS BANDWIDTH AND 99% OCCUPIED BANDWIDTH .....</i>	17
7.2.1. 802.11b MODE .....	18
7.2.2. 802.11g MODE .....	22
7.2.3. 802.11n HT20 MODE .....	26
7.3. <i>PEAK CONDUCTED OUTPUT POWER .....</i>	30
7.3.1. 802.11b MODE .....	31
7.3.2. 802.11g MODE .....	31
7.3.3. 802.11n HT20 MODE .....	31
7.4. <i>POWER SPECTRAL DENSITY .....</i>	32
7.4.1. 802.11b MODE .....	33
7.4.2. 802.11g MODE .....	35
7.4.3. 802.11n HT20 MODE .....	37
7.5. <i>CONDUCTED BANDEdge AND SPURIOUS EMISSIONS .....</i>	39
7.5.1. 802.11b MODE .....	41
7.5.2. 802.11g MODE .....	44
7.5.3. 802.11n HT20 MODE .....	47



<b>8. RADIATED TEST RESULTS.....</b>	<b>50</b>
8.1. <i>RESTRICTED BANDEdge</i> .....	56
8.1.1. 802.11b MODE .....	56
8.1.2. 802.11g MODE .....	63
8.1.3. 802.11n HT20 MODE .....	71
8.2. <i>SPURIOUS EMISSIONS (3~18GHz)</i> .....	79
8.2.1. 802.11b MODE .....	79
8.2.2. 802.11g MODE .....	85
8.2.3. 802.11n HT20 MODE .....	91
8.3. <i>SPURIOUS EMISSIONS (1~3GHz)</i> .....	97
8.3.1. 802.11b MODE .....	97
8.3.2. 802.11g MODE .....	103
8.3.3. 802.11n HT20 MODE .....	109
8.4. <i>WORST-CASE CO-LOCATION</i> .....	115
8.4.1. BT GFSK AND 802.11n HT20 MIMO MODE .....	115
8.6. <i>SPURIOUS EMISSIONS (18~26GHz)</i> .....	123
8.6.1. 802.11g MODE .....	123
8.7. <i>SPURIOUS EMISSIONS (0.03 ~ 1 GHz)</i> .....	125
8.7.1. 802.11g MODE .....	125
8.8. <i>SPURIOUS EMISSIONS BELOW 30M</i> .....	127
8.8.1. 802.11g MODE .....	127
<b>9. AC POWER LINE CONDUCTED EMISSIONS.....</b>	<b>130</b>
9.1. 802.11g MODE .....	131
<b>10. ANTENNA REQUIREMENTS .....</b>	<b>133</b>

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Estone Technology LTD  
Address: 2F, Building No.1, Jia'an Industrial Park, No.2 Long Chang Road, Bao'an, Shenzhen, China.

### Manufacturer Information

Company Name: Estone Technology LTD  
Address: 2F, Building No.1, Jia'an Industrial Park, No.2 Long Chang Road, Bao'an, Shenzhen, China.

### EUT Description

EUT Name: CHAMPe Bingo Handset  
Model: VK10  
Sample Status: Normal  
Sample ID: 2609387  
Sample Received Date: October 10, 2019  
Date of Tested: October 15~November 07, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:



Kebo Zhang  
Engineer Project Associate

Checked By:



Shawn Wen  
Laboratory Leader

Approved By:



Stephen Guo  
Laboratory Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules</p> <p><b>ISED(Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.</p> <p>Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9kHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)( include Fundamental emission)	5.78dB (1GHz-18Gz) 5.23dB (18GHz-26Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	CHAMPe Bingo Handset
Model	VK10
Radio Technology	IEEE802.11b/g/n HT20
Operation frequency	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz
Modulation	IEEE 802.11b: DSSS(CCK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Power Supply	DC 3.7V

### 5.2. MAXIMUM OUTPUT POWER

Number of Transmit Chains (NTX)	IEE Std. 802.11	Frequency (MHz)	Channel Number	Max AVG Conducted Power (dBm)
1	IEEE 802.11b	2412-2462	1-11[11]	15.94
1	IEEE 802.11g	2412-2462	1-11[11]	14.94
1	IEEE 802.11nHT20	2412-2462	1-11[11]	13.55

### 5.3. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

### 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
WiFi TX(802.11b)	CH1,CH6,CH11/ Low, Middle, High	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11g)	CH1,CH6,CH11/ Low, Middle, High	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT20)	CH1,CH6,CH11/ Low, Middle, High	2412MHz, 2437MHz, 2462MHz

## 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		Ampak RFTestTool		
Modulation Mode	Transmit Antenna Number	Test Channel Power Setting		
		NCB: 20MHz		
		CH 1	CH 6	CH 11
802.11b	1	63	63	59
802.11g	1	62	61	56
802.11n HT20	1	56	56	51

## 5.6. THE WORSE CASE CONFIGURATIONS

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps  
802.11g mode: 6 Mbps  
802.11n HT20 mode: MCS0

## 5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	PCB Antenna	-0.83

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
Note: 1. BT&WLAN 2.4G and BT&WLAN 5G can transmit simultaneously, WLAN 2.4G and WLAN 5G can't transmit simultaneously. (declared by client)		

## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	DC power supply	ZHAOXIN	PS-305D	Input: AC 110/220V ±10% Output: DC 0-30V
2	Headphone	Sony	N/A	N/A

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	AUX	/	/	1	/


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

### TEST SETUP

The EUT can work in engineering mode with a software.

### SETUP DIAGRAM FOR TESTS





## 5.9. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions										
Instrument										
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.				
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	101961	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	101983	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Dec.10,2018	Dec.10,2019				
Software										
Used	Description		Manufacturer	Name	Version					
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance		Farad	EZ-EMC	Ver. UL-3A1					
Radiated Emissions										
Instrument										
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.				
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400 036	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17, 2018	Sep.17, 2021				
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A090 99	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Sep.17, 2018	Sep.17, 2021				
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11, 2018	Aug.11, 2021				
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Jan.07,2019	Jan.07, 2022				
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.10,2018	Dec.10,2019				
<input checked="" type="checkbox"/>	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.10,2018	Dec.10,2019				
Software										
Used	Description		Manufacturer	Name	Version					
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance		Farad	EZ-EMC	Ver. UL-3A1					

Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Power Meter	Keysight	N1911A	MY55416024	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Power Sensor	Keysight	U2021XA	MY5100022	Dec.10,2018	Dec.10,2019

## 6. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6dB Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Peak Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.1.3/8.3.2.3
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test For AC Power Port	ANSI C63.10-2013	6.2
8	99% Bandwidth	ANSI C63.10-2013	6.9.3

## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	25.2°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (KHz)	Final setting For VBW (KHz)
11b	101.3	101.3	1.0	100.0%	0.000	0.01	0.1
11g	1.392	1.432	0.972	97.2%	0.123	0.72	1.0
11n20	1.308	1.344	0.973	97.3%	0.119	0.76	1.0



Note:


Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.





## 7.2. 6 dB DTS BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	$\geq 500\text{KHz}$	2400-2483.5
ISED RSS-Gen Clause 6.7	99% Occupied Bandwidth	For reporting purposes only.	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6dB Bandwidth :100K For 99% Occupied Bandwidth :1% to 5% of the occupied bandwidth
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$ For 99% Occupied Bandwidth : approximately $3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB and 99% relative to the maximum level measured in the fundamental emission.

### TEST SETUP






**TEST ENVIRONMENT**



Temperature	25.2°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V


**RESULTS****7.2.1. 802.11b MODE**

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	8.64	12.395	≥500	Pass
Middle	8.60	12.405	≥500	Pass
High	8.04	12.395	≥500	Pass















## 7.2.2. 802.11g MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	16.00	16.608	≥500	Pass
Middle	16.36	16.626	≥500	Pass
High	16.36	16.636	≥500	Pass















## 7.2.3. 802.11n HT20 MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	17.60	17.777	≥500	Pass
Middle	17.56	17.760	≥500	Pass
High	17.32	17.787	≥500	Pass









### 7.3. PEAK CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Output Power	1 watt or 30dBm	2400-2483.5

#### TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.


Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.

Measure the power of each channel.

Peak Detector use for Peak result.

AVG Detector use for AVG result.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	25.3°C	Relative Humidity	61%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

## RESULTS

### 7.3.1. 802.11b MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	
Low	18.13	15.76	30
Middle	18.18	15.60	30
High	17.51	15.06	30

### 7.3.2. 802.11g MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	
Low	22.19	14.87	30
Middle	21.64	14.94	30
High	21.39	14.15	30

### 7.3.3. 802.11n HT20 MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	
Low	21.82	13.55	30
Middle	21.61	13.43	30
High	21.24	12.72	30

## 7.4. POWER SPECTRAL DENSITY

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST SETUP






### TEST ENVIRONMENT

Temperature	25.2°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

RESULTS**7.4.1. 802.11b MODE**


Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-3,962	8	PASS
Middle	-5.789	8	PASS
High	-5.036	8	PASS







## 7.4.2. 802.11g MODE


Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-8.390	8	PASS
Middle	-7.203	8	PASS
High	-10.284	8	PASS







## 7.4.3. 802.11n HT20 MODE

Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-11.122	8	PASS
Middle	-11.059	8	PASS
High	-12.516	8	PASS





## 7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100K
VBW	$\geq 3 \times$ RBW
measurement points	$\geq$ span/RBW
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.


**TEST SETUP****TEST ENVIRONMENT**

Temperature	25.2°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V


**RESULTS**

## 7.5.1. 802.11b MODE

## LOW CH BANDEDGE




## LOW CH SPURIOUS EMISSIONS 30M-26G




## MID CH SPURIOUS EMISSIONS REFERENCE




MID CH SPURIOUS EMISSIONS 30M-26G



## HIGH CH BANDEDGE




## HIGH CH SPURIOUS EMISSIONS 30M-26G




## 7.5.2. 802.11g MODE


## LOW CH BANDEDGE




## LOW CH SPURIOUS EMISSIONS 30M-26G




## MID CH SPURIOUS EMISSIONS REFERENCE




## MID CH SPURIOUS EMISSIONS 30M-26G



## HIGH CH BANDEDGE




## HIGH CH SPURIOUS EMISSIONS 30M-26G




## 7.5.3. 802.11n HT20 MODE


## LOW CH BANDEDGE




## LOW CH SPURIOUS EMISSIONS 30M-26G




## MID CH SPURIOUS EMISSIONS REFERENCE




## MID CH SPURIOUS EMISSIONS 30M-26G



## HIGH CH BANDEDGE



## HIGH CH SPURIOUS EMISSIONS 30M-26G



## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209

Please refer to ISED RSS-GEN Clause 8.9 (Transmitter)

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

## Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

IC Restricted bands please refer to ISED RSS-GEN Clause 8.10


FCC Restricted bands of operation:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1G




The setting of the spectrum analyser

RBW	120kHz
VBW	300kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

## ABOVE 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

Note 3: All the EUT's emissions had been evaluated for simultaneous transmission with the other WIFI 2.4GHz, WIFI 5GHz and BT&BLE transmitter and there were no any additional or worse emissions found.

#### TEST ENVIRONMENT


Temperature	22.6°C	Relative Humidity	54%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

## 8.1. RESTRICTED BANDEDGE

### 8.1.1. 802.11b MODE


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

##### PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.82	32.94	62.76	74.00	-11.24	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	18.86	32.94	51.80	54.00	-2.20	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/T_{on}$  where:  $T_{on}$  is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	20.42	32.94	53.36	74.00	-20.64	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	27.61	33.58	61.19	74.00	-12.81	peak
2	2483.900	28.67	33.58	62.25	74.00	-11.75	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	18.73	33.58	52.31	54.00	-1.69	AVG
2	2483.900	16.51	33.58	50.09	54.00	-3.91	AVG


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEdge (HIGH CHANNEL, VERTICAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.63	33.58	51.21	74.00	-22.79	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	5.77	33.58	39.35	54.00	-14.65	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/T_{on}$  where:  $T_{on}$  is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### 8.1.2. 802.11g MODE


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

##### PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	37.14	32.94	70.08	74.00	-3.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	18.73	32.94	51.67	54.00	-2.33	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)PEAK


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	26.93	32.94	59.87	74.00	-14.13	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	8.32	32.94	41.26	54.00	-12.74	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	38.84	33.58	72.42	74.00	-1.58	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	18.83	33.58	52.41	54.00	-1.59	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	25.54	33.58	59.12	74.00	-14.88	peak
2	2483.900	26.36	33.58	59.94	74.00	-14.06	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	6.82	33.58	40.40	54.00	-13.60	AVG
2	2483.900	6.24	33.58	39.82	54.00	-14.18	AVG


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 8.1.3. 802.11n HT20 MODE

RESTRICTED BANDEdge (LOW CHANNEL, HORIZONTAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	40.05	32.94	72.99	74.00	-1.01	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


AVG

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	19.45	32.94	52.39	54.00	-1.61	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


## RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

## PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	30.62	32.94	63.56	74.00	-10.44	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	9.46	32.94	42.40	54.00	-11.60	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)PEAK


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	38.39	33.58	71.97	74.00	-2.03	peak
2	2484.150	39.84	33.58	73.42	74.00	-0.58	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.32	33.58	50.90	54.00	-3.10	AVG
2	2484.150	16.82	33.58	50.40	54.00	-3.60	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.01	33.58	59.59	74.00	-14.41	peak
2	2483.750	27.34	33.58	60.92	74.00	-13.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	5.28	33.58	38.86	54.00	-15.14	AVG
2	2483.750	4.91	33.58	38.49	54.00	-15.51	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 8.2. SPURIOUS EMISSIONS (3~18GHz)

### 8.2.1. 802.11b MODE


#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3615.000	45.33	-3.33	42.00	74.00	-32.00	peak
2	4815.000	44.88	-0.10	44.78	74.00	-29.22	peak
3	7230.000	46.56	7.13	53.69	74.00	-20.31	peak
4	11835.000	36.40	14.33	50.73	74.00	-23.27	peak
5	14400.000	34.87	16.68	51.55	74.00	-22.45	peak
6	18000.000	30.21	23.40	53.61	74.00	-20.39	peak

Note:


1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3555.000	47.80	-3.67	44.13	74.00	-29.87	peak
2	4815.000	45.09	-0.10	44.99	74.00	-29.01	peak
3	7230.000	47.53	7.13	54.66	74.00	-19.34	peak
4	7230.000	39.02	7.13	46.15	54.00	-7.85	AVG
5	11790.000	36.33	14.28	50.61	74.00	-23.39	peak
6	14415.000	35.18	16.67	51.85	74.00	-22.15	peak
7	17715.000	29.86	22.65	52.51	74.00	-21.49	peak

Note:


1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3645.000	45.56	-3.09	42.47	74.00	-31.53	peak
2	4875.000	43.24	0.10	43.34	74.00	-30.66	peak
3	7305.000	47.20	7.35	54.55	74.00	-19.45	peak
4	7305.000	28.26	7.35	35.61	74.00	-38.39	peak
5	11010.000	36.57	13.65	50.22	74.00	-23.78	peak
6	14460.000	34.67	16.65	51.32	74.00	-22.68	peak
7	17340.000	30.89	21.89	52.78	74.00	-21.22	peak

Note:


1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dB <sub>UV</sub> )	Correct (dB/m)	Result (dB <sub>UV</sub> /m)	Limit (dB <sub>UV</sub> /m)	Margin (dB)	Remark
1	4875.000	43.66	0.10	43.76	74.00	-30.24	peak
2	5865.000	39.88	4.80	44.68	74.00	-29.32	peak
3	7305.000	48.05	7.35	55.40	74.00	-18.60	peak
4	7305.000	43.19	7.35	50.54	54.00	-3.46	AVG
5	10980.000	37.04	13.47	50.51	74.00	-23.49	peak
6	15195.000	35.25	16.01	51.26	74.00	-22.74	peak
7	17115.000	31.82	21.07	52.89	74.00	-21.11	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3690.000	45.15	-2.74	42.41	74.00	-31.59	peak
2	4920.000	44.37	0.26	44.63	74.00	-29.37	peak
3	5865.000	40.68	4.80	45.48	74.00	-28.52	peak
4	7380.000	45.98	7.71	53.69	74.00	-20.31	peak
5	11040.000	36.92	13.63	50.55	74.00	-23.45	peak
6	17370.000	31.20	21.78	52.98	74.00	-21.02	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4155.000	46.41	-2.01	44.40	74.00	-29.60	peak
2	4920.000	46.82	0.26	47.08	74.00	-26.92	peak
3	5145.000	44.95	1.32	46.27	74.00	-27.73	peak
4	7380.000	45.67	7.71	53.38	74.00	-20.62	peak
5	14250.000	34.42	16.73	51.15	74.00	-22.85	peak
6	18000.000	30.17	23.40	53.57	74.00	-20.43	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


## 8.2.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3360.000	49.14	-4.28	44.86	74.00	-29.14	peak
2	7230.000	47.74	7.13	54.87	74.00	-19.13	peak
3	7230.000	32.65	7.13	39.78	74.00	-34.22	peak
4	8970.000	38.32	10.17	48.49	74.00	-25.51	peak
5	12720.000	35.32	14.92	50.24	74.00	-23.76	peak
6	14445.000	34.43	16.66	51.09	74.00	-22.91	peak
7	17280.000	31.28	21.89	53.17	74.00	-20.83	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3615.000	45.96	-3.33	42.63	74.00	-31.37	peak
2	7230.000	46.67	7.13	53.80	74.00	-20.20	peak
3	10500.000	37.75	12.31	50.06	74.00	-23.94	peak
4	13605.000	34.52	16.40	50.92	74.00	-23.08	peak
5	14400.000	35.07	16.68	51.75	74.00	-22.25	peak
6	17910.000	29.56	23.33	52.89	74.00	-21.11	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3645.000	44.37	-3.09	41.28	74.00	-32.72	peak
2	5865.000	39.59	4.80	44.39	74.00	-29.61	peak
3	7305.000	47.42	7.35	54.77	74.00	-19.23	peak
4	7305.000	27.61	7.35	34.96	54.00	-19.04	AVG
5	12675.000	35.93	14.61	50.54	74.00	-23.46	peak
6	14400.000	34.55	16.68	51.23	74.00	-22.77	peak
7	16905.000	32.21	20.39	52.60	74.00	-21.40	peak

Note:


1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3555.000	46.90	-3.67	43.23	74.00	-30.77	peak
2	7305.000	50.36	7.35	57.71	74.00	-16.29	peak
3	7305.000	25.70	7.35	33.05	54.00	-20.95	AVG
4	10605.000	36.88	12.88	49.76	74.00	-24.24	peak
5	11805.000	36.59	14.31	50.90	74.00	-23.10	peak
6	13905.000	35.20	16.76	51.96	74.00	-22.04	peak
7	17070.000	32.01	20.99	53.00	74.00	-21.00	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3690.000	44.69	-2.74	41.95	74.00	-32.05	peak
2	7380.000	46.10	7.71	53.81	74.00	-20.19	peak
3	11040.000	36.96	13.63	50.59	74.00	-23.41	peak
4	13635.000	35.77	16.37	52.14	74.00	-21.86	peak
5	16710.000	31.55	20.23	51.78	74.00	-22.22	peak
6	17190.000	31.65	21.24	52.89	74.00	-21.11	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dB <sub>UV</sub> )	Correct (dB/m)	Result (dB <sub>UV</sub> /m)	Limit (dB <sub>UV</sub> /m)	Margin (dB)	Remark
1	4920.000	41.43	0.26	41.69	74.00	-32.31	peak
2	7395.000	45.84	7.79	53.63	74.00	-20.37	peak
3	11505.000	36.30	14.50	50.80	74.00	-23.20	peak
4	14430.000	34.69	16.66	51.35	74.00	-22.65	peak
5	16650.000	32.55	19.97	52.52	74.00	-21.48	peak
6	17610.000	30.93	22.00	52.93	74.00	-21.07	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


## 8.2.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	42.27	-0.10	42.17	74.00	-31.83	peak
2	7230.000	44.18	7.13	51.31	74.00	-22.69	peak
3	11865.000	36.31	14.33	50.64	74.00	-23.36	peak
4	13800.000	33.58	17.60	51.18	74.00	-22.82	peak
5	17055.000	31.38	20.95	52.33	74.00	-21.67	peak
6	17655.000	31.20	22.26	53.46	74.00	-20.54	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3555.000	50.91	-3.67	47.24	74.00	-26.76	peak
2	5865.000	40.12	4.80	44.92	74.00	-29.08	peak
3	7230.000	45.89	7.13	53.02	74.00	-20.98	peak
4	13125.000	35.59	15.28	50.87	74.00	-23.13	peak
5	13980.000	34.96	16.66	51.62	74.00	-22.38	peak
6	17820.000	29.94	23.34	53.28	74.00	-20.72	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3750.000	45.08	-2.68	42.40	74.00	-31.60	peak
2	7305.000	45.72	7.35	53.07	74.00	-20.93	peak
3	11040.000	36.55	13.63	50.18	74.00	-23.82	peak
4	11910.000	36.93	14.37	51.30	74.00	-22.70	peak
5	14385.000	33.97	16.67	50.64	74.00	-23.36	peak
6	17250.000	31.53	21.65	53.18	74.00	-20.82	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3645.000	43.77	-3.09	40.68	74.00	-33.32	peak
2	5730.000	39.46	3.13	42.59	74.00	-31.41	peak
3	7305.000	47.67	7.35	55.02	74.00	-18.98	peak
4	7305.000	31.03	7.35	38.38	54.00	-15.62	AVG
5	11745.000	36.88	14.16	51.04	74.00	-22.96	peak
6	14205.000	33.99	16.83	50.82	74.00	-23.18	peak
7	16920.000	32.35	20.46	52.81	74.00	-21.19	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3555.000	46.10	-3.67	42.43	74.00	-31.57	peak
2	5880.000	40.24	5.10	45.34	74.00	-28.66	peak
3	7395.000	44.92	7.79	52.71	74.00	-21.29	peak
4	11835.000	36.10	14.33	50.43	74.00	-23.57	peak
5	14475.000	34.69	16.64	51.33	74.00	-22.67	peak
6	17970.000	29.56	23.38	52.94	74.00	-21.06	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dB <sub>UV</sub> )	Correct (dB/m)	Result (dB <sub>UV</sub> /m)	Limit (dB <sub>UV</sub> /m)	Margin (dB)	Remark
1	4455.000	42.23	-1.44	40.79	74.00	-33.21	peak
2	7380.000	44.79	7.71	52.50	74.00	-21.50	peak
3	10755.000	36.70	12.62	49.32	74.00	-24.68	peak
4	12720.000	36.10	14.92	51.02	74.00	-22.98	peak
5	14460.000	34.64	16.65	51.29	74.00	-22.71	peak
6	17430.000	31.03	21.61	52.64	74.00	-21.36	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### 8.3. SPURIOUS EMISSIONS (1~3GHz)

#### 8.3.1. 802.11b MODE


##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	55.03	-13.02	42.01	74.00	-31.99	peak
2	1782.000	49.91	-10.29	39.62	74.00	-34.38	peak
3	1980.000	54.98	-10.03	44.95	74.00	-29.05	peak
4	2412.000	54.32	-7.86	46.46	/	/	fundamental
5	2564.000	46.40	-7.58	38.82	74.00	-35.18	peak
6	2772.000	44.73	-6.38	38.35	74.00	-35.65	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	53.61	-13.02	40.59	74.00	-33.41	peak
2	1782.000	55.11	-10.29	44.82	74.00	-29.18	peak
3	1980.000	53.67	-10.03	43.64	74.00	-30.36	peak
4	2178.000	54.25	-8.92	45.33	74.00	-28.67	peak
5	2412.000	54.02	-7.86	46.16	/	/	fundamental
6	2576.000	54.82	-7.64	47.18	74.00	-26.82	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	54.28	-13.02	41.26	74.00	-32.74	peak
2	1782.000	50.59	-10.29	40.30	74.00	-33.70	peak
3	1980.000	54.56	-10.03	44.53	74.00	-29.47	peak
4	2178.000	49.72	-8.92	40.80	74.00	-33.20	peak
5	2437.000	58.77	-7.71	51.06	/	/	fundamental
6	2516.000	47.12	-7.32	39.80	74.00	-34.20	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1386.000	51.19	-12.61	38.58	74.00	-35.42	peak
2	1782.000	54.87	-10.29	44.58	74.00	-29.42	peak
3	1980.000	53.34	-10.03	43.31	74.00	-30.69	peak
4	2178.000	54.44	-8.92	45.52	74.00	-28.48	peak
5	2437.000	52.95	-7.71	45.24	/	/	fundamental
6	2574.000	53.35	-7.62	45.73	74.00	-28.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	54.70	-13.02	41.68	74.00	-32.32	peak
2	1584.000	47.03	-11.74	35.29	74.00	-38.71	peak
3	1782.000	49.82	-10.29	39.53	74.00	-34.47	peak
4	1980.000	55.17	-10.03	45.14	74.00	-28.86	peak
5	2462.000	56.09	-7.46	48.63	/	/	fundamental
6	2510.000	54.59	-7.29	47.30	74.00	-26.70	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	54.04	-13.02	41.02	74.00	-32.98	peak
2	1782.000	55.09	-10.29	44.80	74.00	-29.20	peak
3	1980.000	52.39	-10.03	42.36	74.00	-31.64	peak
4	2178.000	55.15	-8.92	46.23	74.00	-27.77	peak
5	2462.000	52.14	-7.49	44.65	/	/	fundamental
6	2574.000	52.15	-7.62	44.53	74.00	-29.47	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


## 8.3.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	55.46	-13.02	42.44	74.00	-31.56	peak
2	1782.000	49.78	-10.29	39.49	74.00	-34.51	peak
3	1980.000	55.01	-10.03	44.98	74.00	-29.02	peak
4	2336.000	48.29	-8.18	40.11	74.00	-33.89	peak
5	2412.000	55.59	-7.86	47.73	/	/	fundamental
6	2774.000	44.32	-6.35	37.97	74.00	-36.03	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1186.000	53.82	-13.05	40.77	74.00	-33.23	peak
2	1782.000	54.39	-10.29	44.10	74.00	-29.90	peak
3	1980.000	54.53	-10.03	44.50	74.00	-29.50	peak
4	2178.000	53.55	-8.92	44.63	74.00	-29.37	peak
5	2412.000	53.57	-7.88	45.69	/	/	fundamental
6	2576.000	54.34	-7.64	46.70	74.00	-27.30	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	54.42	-13.02	41.40	74.00	-32.60	peak
2	1782.000	49.31	-10.29	39.02	74.00	-34.98	peak
3	1980.000	54.72	-10.03	44.69	74.00	-29.31	peak
4	2178.000	47.26	-8.92	38.34	74.00	-35.66	peak
5	2437.000	52.72	-7.71	45.01	/	/	fundamental
6	2514.000	45.09	-7.31	37.78	74.00	-36.22	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1780.000	54.67	-10.32	44.35	74.00	-29.65	peak
2	1980.000	54.04	-10.03	44.01	74.00	-29.99	peak
3	2178.000	54.55	-8.92	45.63	74.00	-28.37	peak
4	2437.000	52.67	-7.71	44.96	/	/	fundamental
5	2576.000	53.56	-7.64	45.92	74.00	-28.08	peak
6	2972.000	47.13	-5.35	41.78	74.00	-32.22	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	55.18	-13.02	42.16	74.00	-31.84	peak
2	1782.000	50.06	-10.29	39.77	74.00	-34.23	peak
3	1980.000	55.24	-10.03	45.21	74.00	-28.79	peak
4	2462.000	57.31	-7.46	49.85	/	/	fundamental
5	2504.000	52.38	-7.27	45.11	74.00	-28.89	peak
6	2978.000	42.65	-5.34	37.31	74.00	-36.69	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1186.000	52.92	-13.05	39.87	74.00	-34.13	peak
2	1782.000	53.65	-10.29	43.36	74.00	-30.64	peak
3	1980.000	54.12	-10.03	44.09	74.00	-29.91	peak
4	2178.000	54.91	-8.92	45.99	74.00	-28.01	peak
5	2462.000	55.35	-7.48	47.87	/	/	fundamental
6	2772.000	48.39	-6.38	42.01	74.00	-31.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


## 8.3.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	54.65	-13.02	41.63	74.00	-32.37	peak
2	1584.000	48.26	-11.74	36.52	74.00	-37.48	peak
3	1782.000	49.38	-10.29	39.09	74.00	-34.91	peak
4	1980.000	53.39	-10.03	43.36	74.00	-30.64	peak
5	2412.000	56.67	-7.86	48.81	/	/	fundamental
6	2564.000	45.87	-7.58	38.29	74.00	-35.71	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1186.000	53.62	-13.05	40.57	74.00	-33.43	peak
2	1782.000	55.60	-10.29	45.31	74.00	-28.69	peak
3	1980.000	54.04	-10.03	44.01	74.00	-29.99	peak
4	2178.000	54.06	-8.92	45.14	74.00	-28.86	peak
5	2412.000	54.47	-7.86	46.61	/	/	fundamental
6	2576.000	54.38	-7.64	46.74	74.00	-27.26	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	54.03	-13.02	41.01	74.00	-32.99	peak
2	1782.000	50.83	-10.29	40.54	74.00	-33.46	peak
3	1980.000	54.90	-10.03	44.87	74.00	-29.13	peak
4	2437.000	49.61	-7.71	41.90	/	/	fundamental
5	2514.000	45.04	-7.31	37.73	74.00	-36.27	peak
6	2774.000	43.50	-6.35	37.15	74.00	-36.85	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	52.89	-13.02	39.87	74.00	-34.13	peak
2	1782.000	55.38	-10.29	45.09	74.00	-28.91	peak
3	1980.000	53.68	-10.03	43.65	74.00	-30.35	peak
4	2178.000	53.12	-8.92	44.20	74.00	-29.80	peak
5	2437.000	52.67	-7.71	44.96	/	/	fundamental
6	2576.000	53.62	-7.64	45.98	74.00	-28.02	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	55.33	-13.02	42.31	74.00	-31.69	peak
2	1782.000	51.32	-10.29	41.03	74.00	-32.97	peak
3	1980.000	56.52	-10.03	46.49	74.00	-27.51	peak
4	2462.000	51.90	-7.46	44.44	/	/	fundamental
5	2508.000	53.28	-7.29	45.99	74.00	-28.01	peak
6	2868.000	43.18	-5.71	37.47	74.00	-36.53	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	53.15	-13.02	40.13	74.00	-33.87	peak
2	1782.000	52.11	-10.29	41.82	74.00	-32.18	peak
3	1980.000	54.20	-10.03	44.17	74.00	-29.83	peak
4	2178.000	52.90	-8.92	43.98	74.00	-30.02	peak
5	2462.000	54.58	-7.48	47.10	/	/	fundamental
6	2576.000	53.88	-7.64	46.24	74.00	-27.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

## 8.4. WORST-CASE CO-LOCATION

### 8.4.1. BT GFSK MODE AND 802.11n HT20 MIMO MODE (TRANSMIT SIMULTANEOUSLY)


#### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	54.65	-13.02	41.63	74.00	-32.37	peak
2	1584.000	50.76	-11.74	39.02	74.00	-34.98	peak
3	1782.000	51.38	-10.29	41.09	74.00	-32.91	peak
4	1980.000	53.39	-10.03	43.36	74.00	-30.64	peak
5	2338.000	47.67	-8.17	39.50	74.00	-34.50	peak
6	2412.000	56.28	-7.85	48.43	/	/	fundamental

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)1-3GHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1186.000	54.62	-13.05	41.57	74.00	-32.43	peak
2	1782.000	57.60	-10.29	47.31	74.00	-26.69	peak
3	1980.000	55.04	-10.03	45.01	74.00	-28.99	peak
4	2178.000	57.06	-8.92	48.14	74.00	-25.86	peak
5	2412.000	55.48	-7.87	47.61	/	/	fundamental
6	2576.000	55.88	-7.64	48.24	74.00	-25.76	peak

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)3-18GHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3615.000	45.91	-3.33	42.58	74.00	-31.42	peak
2	4815.000	43.27	-0.10	43.17	74.00	-30.83	peak
3	7230.000	45.68	7.13	52.81	74.00	-21.19	peak
4	10380.000	37.14	11.91	49.05	74.00	-24.95	peak
5	12540.000	35.44	14.88	50.32	74.00	-23.68	peak
6	16770.000	32.52	20.28	52.80	74.00	-21.20	peak


Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)3-18GHz


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3555.000	52.91	-3.67	49.24	74.00	-24.76	peak
2	3750.000	49.07	-2.68	46.39	74.00	-27.61	peak
3	7230.000	45.89	7.13	53.02	74.00	-20.98	peak
4	10605.000	38.24	12.88	51.12	74.00	-22.88	peak
5	13125.000	36.09	15.28	51.37	74.00	-22.63	peak
6	16920.000	31.80	20.46	52.26	74.00	-21.74	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

RESTRICTED BANDEDGE (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)PEAK


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.005	39.53	32.94	72.47	74.00	-1.53	peak
2	2390.000	38.49	32.94	71.43	74.00	-2.57	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.005	18.04	32.94	50.98	54.00	-3.02	AVG
2	2390.000	19.69	32.94	52.63	54.00	-1.37	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.120	33.65	32.94	66.59	74.00	-7.41	peak
2	2390.000	32.86	32.94	65.80	74.00	-8.20	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


No.	Frequency (MHz)	Reading (dB <sub>UV</sub> )	Correct (dB/m)	Result (dB <sub>UV</sub> /m)	Limit (dB <sub>UV</sub> /m)	Margin (dB)	Remark
1	2389.120	13.33	32.94	46.27	54.00	-7.73	AVG
2	2390.000	13.97	32.94	46.91	54.00	-7.09	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG: VBW=1/Ton where: ton is transmit duration.  
4. For transmit duration, please refer to clause 7.1.  
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 8.6. SPURIOUS EMISSIONS (18~26GHz)


### 8.6.1. 802.11g MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18544.000	51.26	-4.46	46.80	74.00	-27.20	peak
2	20072.000	50.34	-4.51	45.83	74.00	-28.17	peak
3	21024.000	51.12	-5.30	45.82	74.00	-28.18	peak
4	22256.000	52.45	-6.06	46.39	74.00	-27.61	peak
5	24824.000	47.77	-1.69	46.08	74.00	-27.92	peak
6	25784.000	47.73	-1.49	46.24	74.00	-27.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. The preamplifier only effect to the above 18GHz signal and no filter added to the measurement chain.

**SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18784.000	51.05	-4.84	46.21	74.00	-27.79	peak
2	19720.000	50.50	-4.39	46.11	74.00	-27.89	peak
3	21576.000	52.32	-5.77	46.55	74.00	-27.45	peak
4	23304.000	51.87	-5.16	46.71	74.00	-27.29	peak
5	24688.000	49.39	-2.11	47.28	74.00	-26.72	peak
6	25784.000	48.58	-1.49	47.09	74.00	-26.91	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. The preamplifier only effect to the above 18GHz signal and no filter added to the measurement chain.

Note: All the test modes have been tested, only the worst data record in the report.

## 8.7. SPURIOUS EMISSIONS (0.03 ~ 1 GHz)


### 8.7.1. 802.11g MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	44.5500	29.27	-18.05	11.22	40.00	-28.78	QP
2	216.2400	31.67	-16.67	15.00	46.00	-31.00	QP
3	395.6900	31.49	-12.47	19.02	46.00	-26.98	QP
4	540.2199	33.13	-9.59	23.54	46.00	-22.46	QP
5	688.6300	25.52	-6.89	18.63	46.00	-27.37	QP
6	831.2199	26.12	-4.85	21.27	46.00	-24.73	QP

Note: 1. Result Level = Read Level + Correct Factor.  
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	43.5800	28.95	-18.04	10.91	40.00	-29.09	QP
2	158.0399	23.85	-17.84	6.01	43.50	-37.49	QP
3	450.9800	24.75	-11.41	13.34	46.00	-32.66	QP
4	644.0100	25.89	-7.66	18.23	46.00	-27.77	QP
5	839.9500	26.58	-4.64	21.94	46.00	-24.06	QP
6	952.4700	27.71	-3.36	24.35	46.00	-21.65	QP

Note: 1. Result Level = Read Level + Correct Factor.  
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the test modes have been tested, only the worst data record in the report.

## 8.8. SPURIOUS EMISSIONS BELOW 30M

### 8.8.1. 802.11g MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

0.09kHz~ 150kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0111	71.95	-101.39	-29.44	46.69	-76.13	peak
2	0.0165	68.34	-101.37	-33.03	43.25	-76.28	peak
3	0.0221	66.13	-101.35	-35.22	40.71	-75.93	peak
4	0.0410	60.24	-101.44	-41.20	35.35	-76.55	peak
5	0.0719	57.84	-101.58	-43.74	30.47	-74.21	peak
6	0.0926	54.39	-101.74	-47.35	28.27	-75.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.


3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150kHz ~ 490kHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1570	72.53	-101.65	-29.12	23.68	-52.80	peak
2	0.1800	68.12	-101.68	-33.56	22.50	-56.06	peak
3	0.2472	62.45	-101.80	-39.35	19.74	-59.09	peak
4	0.2741	61.03	-101.83	-40.80	18.84	-59.64	peak
5	0.3421	59.10	-101.90	-42.80	16.92	-59.72	peak
6	0.4158	55.69	-101.98	-46.29	15.22	-61.51	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490kHz ~ 30MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6753	62.47	-62.10	0.37	31.01	-30.64	peak
2	1.1627	58.05	-62.20	-4.15	26.30	-30.45	peak
3	3.6493	51.10	-61.42	-10.32	29.54	-39.86	peak
4	8.6348	51.10	-60.99	-9.89	29.54	-39.43	peak
5	13.5629	50.48	-60.95	-10.47	29.54	-40.01	peak
6	23.4783	50.74	-60.56	-9.82	29.54	-39.36	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.  
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the test modes have been tested, only the worst data record in the report.


## 9. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE



The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST ENVIRONMENT

Temperature	25.3°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V


TEST RESULTS

## 9.1. 802.11g MODE

LINE N RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1510	37.66	9.60	47.26	65.94	-18.68	QP
2	0.1510	17.29	9.60	26.89	55.94	-29.05	AVG
3	0.1672	36.50	9.60	46.10	65.10	-19.00	QP
4	0.1672	18.34	9.60	27.94	55.10	-27.16	AVG
5	0.1744	33.83	9.60	43.43	64.75	-21.32	QP
6	0.1744	14.59	9.60	24.19	54.75	-30.56	AVG
7	0.4815	27.74	9.60	37.34	56.31	-18.97	QP
8	0.4815	19.00	9.60	28.60	46.31	-17.71	AVG
9	28.5829	29.63	9.93	39.56	60.00	-20.44	QP
10	28.5829	29.16	9.93	39.09	50.00	-10.91	AVG
11	29.9430	29.57	9.87	39.44	60.00	-20.56	QP
12	29.9430	28.50	9.87	38.37	50.00	-11.63	AVG

Note: 1. Result = Reading +Correct Factor.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

LINE L RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1519	42.32	9.61	51.93	65.90	-13.97	QP
2	0.1519	25.56	9.61	35.17	55.90	-20.73	AVG
3	0.1580	41.67	9.61	51.28	65.57	-14.29	QP
4	0.1580	24.75	9.61	34.36	55.57	-21.21	AVG
5	0.1840	35.89	9.61	45.50	64.30	-18.80	QP
6	0.1840	21.09	9.61	30.70	54.30	-23.60	AVG
7	0.4968	27.59	9.60	37.19	56.05	-18.86	QP
8	0.4968	18.81	9.60	28.41	46.05	-17.64	AVG
9	25.8563	27.82	9.93	37.75	60.00	-22.25	QP
10	25.8563	25.78	9.93	35.71	50.00	-14.29	AVG
11	28.5784	29.35	9.84	39.19	60.00	-20.81	QP
12	28.5784	28.57	9.84	38.41	50.00	-11.59	AVG

Note: 1. Result = Reading +Correct Factor.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

Note: All test modes have been tested, only the worst data record in the report.

## 10. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

## END OF REPORT