



## FCC Test Report

**Report No.:** ACHJ-19JU1631LTSHPB-1

**FCC ID:** 2AUXM-MSSLA19

**Product:** SMART WIFI BULB

**Model:** MS-A19-9.5W-RGBCW

**Serial Model:** Refer to model list

**Received Date:** Jun.17, 2019

**Test Date:** Jun.20 to Jul.02, 2019

**Issued Date:** Dec.12, 2019

**Applicant:** Haining Mingshuai Technology Lighting Co.,Ltd

**Address:** Building 1, No.327 Chuangye Road, Chang'an Town, Haining City, Jiaxing, China

**Issued By:** BUREAU VERITAS ADT (Shanghai) Corporation

**Lab Address:** No. 829, Xinzhuan Road, Shanghai, P.R.China (201612)

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



## Table of Contents

|                                                                     |    |
|---------------------------------------------------------------------|----|
| Release Control Record .....                                        | 4  |
| 1 Certificate of Conformity .....                                   | 5  |
| 2 Summary of Test Results .....                                     | 6  |
| 2.1 Test Instruments .....                                          | 7  |
| 2.2 Measurement Uncertainty .....                                   | 8  |
| 2.3 Modification Record .....                                       | 8  |
| 3 General Information .....                                         | 9  |
| 3.1 General Description of EUT .....                                | 9  |
| 3.2 Model List .....                                                | 10 |
| 3.3 Description of Test Modes .....                                 | 11 |
| 3.3.1 Test Mode Applicability: .....                                | 12 |
| 3.3.2 Test Condition: .....                                         | 13 |
| 3.4 Duty Cycle of Test Signal .....                                 | 13 |
| 3.5 General Description of Applied Standards .....                  | 14 |
| 4 Test Procedure and Results .....                                  | 15 |
| 4.1 6dB Bandwidth Measurement .....                                 | 15 |
| 4.1.1 Limit .....                                                   | 15 |
| 4.1.2 Test Setup .....                                              | 15 |
| 4.1.3 Test Procedures .....                                         | 15 |
| 4.1.4 Deviation of Test Standard .....                              | 15 |
| 4.1.5 Test Results .....                                            | 16 |
| 4.2 Conducted Output Power Measurement .....                        | 22 |
| 4.2.1 Limit .....                                                   | 22 |
| 4.2.2 Test Setup .....                                              | 22 |
| 4.2.3 Test Procedures .....                                         | 22 |
| 4.2.4 Deviation of Test Standard .....                              | 23 |
| 4.2.5 Test Results .....                                            | 24 |
| Note: Duty Cycle Factor= $10 \cdot \log(1/\text{duty cycle})$ ..... | 29 |
| 4.3 Power Spectral Density Measurement .....                        | 30 |
| 4.3.1 Limit .....                                                   | 30 |
| 4.3.2 Test Setup .....                                              | 30 |
| 4.3.3 Test Procedures .....                                         | 30 |



|       |                                                                      |    |
|-------|----------------------------------------------------------------------|----|
| 4.3.4 | Deviation of Test Standard.....                                      | 31 |
| 4.3.5 | Test Results .....                                                   | 31 |
|       | Note: Duty Cycle Factor= $10 \cdot \log (1/\text{duty cycle})$ ..... | 36 |
| 4.4   | Emissions in non-restricted frequency bands .....                    | 37 |
| 4.4.1 | Limit .....                                                          | 37 |
| 4.4.2 | Test Setup.....                                                      | 37 |
| 4.4.3 | Test Procedures.....                                                 | 37 |
| 4.4.4 | Deviation of Test Standard.....                                      | 38 |
| 4.4.5 | Test Results .....                                                   | 39 |
| 4.5   | Radiated Emission Measurement .....                                  | 57 |
| 4.5.1 | Limits .....                                                         | 57 |
| 4.5.2 | Test Procedures.....                                                 | 57 |
| 4.5.3 | Deviation from Test Standard .....                                   | 59 |
| 4.5.4 | Test Setup.....                                                      | 60 |
| 4.5.5 | EUT Operating Conditions.....                                        | 61 |
| 4.5.6 | Test Results .....                                                   | 61 |
| 4.6   | Conducted Emission Measurement .....                                 | 70 |
| 4.6.1 | Limits .....                                                         | 70 |
| 4.6.2 | Test Procedures.....                                                 | 70 |
| 4.6.3 | Deviation from Test Standard .....                                   | 70 |
| 4.6.4 | Test Setup.....                                                      | 71 |
| 4.6.5 | EUT Operating Conditions.....                                        | 71 |
| 4.6.6 | Test Results .....                                                   | 72 |
| 5     | Pictures of Test Arrangements .....                                  | 74 |



### Release Control Record

| Issue No.             | Description      | Date Issued  |
|-----------------------|------------------|--------------|
| ACHJ-19JU1631LTSHPB-1 | Original release | Dec.12, 2019 |



## 1 Certificate of Conformity

**Product:** SMART WIFI BULB

**Brand:** --

**Model:** MS-A19-9.5W-RGBCW

**Serial Model:** Refer to model list

**Applicant:** Haining Mingshuai Technology Lighting Co.,Ltd

**Test Date:** Jun.26 to Jul.02, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


**Prepared by :**

**, Date:** Dec.12, 2019

Will Yan

Project Engineer

**Approved by :**



**, Date:** Dec.12, 2019

Daniel Sun

RF Supervisor



## 2 Summary of Test Results

The EUT has been tested according to the following specifications:

| 47 CFR FCC Part 15, Subpart C (SECTION 15.247) |                                             |        |                                |
|------------------------------------------------|---------------------------------------------|--------|--------------------------------|
| FCC Clause                                     | Test Item                                   | Result | Remarks                        |
| 15.207                                         | AC Power Conducted Emission                 | PASS   | Meet the requirement of limit. |
| 15.205 /<br>15.209 /<br>15.247(d)              | Radiated Emissions Measurement              | PASS   | Meet the requirement of limit. |
| 15.247(d)                                      | Emissions in non-restricted frequency bands | PASS   | Meet the requirement of limit. |
| 15.247(a)(2)                                   | 6dB bandwidth                               | PASS   | Meet the requirement of limit. |
| 15.247(b)                                      | Conducted power                             | PASS   | Meet the requirement of limit. |
| 15.247(e)                                      | Power Spectral Density                      | PASS   | Meet the requirement of limit. |
| 15.203                                         | Antenna Requirement                         | PASS   | No antenna connector is used.  |

## 2.1 Test Instruments

| Equipment                     | Manufacturer | Model No.           | Serial No. | Last Cal.  | Next Cal.  |
|-------------------------------|--------------|---------------------|------------|------------|------------|
| Hybrid antenna(25MHz-1.5GHz)  | Schwarzbeck  | VULB9168            | E1A1012    | Feb.10,19  | Feb.08,20  |
| Horn Antenna(1GHz -18GHz)     | Schwarzbeck  | BBHA9120D           | E1A1017    | Aug.27,18  | Aug.26,19  |
| Pre-Amplifier(100kHz-1.3GHz)  | Agilent      | 8447D               | E1A2001    | Oct.19,18  | Oct.18,19  |
| Pre-Amplifier(1GHz-26.5GHz)   | Agilent      | 8449B               | E1A2002    | Mar. 26,19 | Mar.25,20  |
| EMI test receiver             | R&S          | ESR7                | E1R1005    | Dec.05,18  | Dec.04,19  |
| Spectrum Analyzer             | Keysight     | N9030B              | E1S1003    | Jul.24,18  | Jul.23 19  |
| EMI test receiver             | R&S          | ESCS30              | E1R1001    | Mar.26,19  | Mar.25,20  |
| LISN                          | R&S          | ENV216              | E1L1011    | Jul.19,18  | Jul.18, 19 |
| Test Receiver ROHDE & SCHWARZ | R&S          | ESCS30              | E1R1001    | Mar.05,19  | Mar.04, 20 |
| Humidity&Temp Tester          | Baolima      | WS508               | E1H1011    | Apr.04,19  | Apr.03,20  |
| Test Software                 | ADT          | ADT_COND_V<br>7.3.1 | N/A        | N/A        | N/A        |
| Test Software                 | Toscend      | JS32-RE             | N/A        | N/A        | N/A        |
| Test Software                 | Toscend      | JS1120              | N/A        | N/A        | N/A        |

## 2.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

| Measurement                        | Frequency      | Expanded Uncertainty<br>( $k=2$ ) ( $\pm$ ) |
|------------------------------------|----------------|---------------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 1.83 dB                                     |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 1GHz   | 5.36 dB                                     |
| Radiated Emissions above 1 GHz     | 1GHz ~ 6GHz    | 3.47 dB                                     |
|                                    | 6GHz ~ 18GHz   | 3.75 dB                                     |
|                                    | 18GHz ~ 40GHz  | 3.30 dB                                     |

## 2.3 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Product               | SMART WIFI BULB                                                 |
| Brand                 | --                                                              |
| Test Model            | MS-A19-9.5W-RGBCW                                               |
| Serial Model:         | Refer to model list                                             |
| Power Rating          | 120Vac 60Hz                                                     |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM |
| Modulation Technology | DSSS, OFDM                                                      |
| Operating Frequency   | See clause 3.2                                                  |
| Number of Channel     | See clause 3.2                                                  |
| Antenna Type          | PCB Antenna                                                     |
| Antenna Connector     | --                                                              |
| Antenna Gain          | 2.5dBi                                                          |

Note:

1. The EUT incorporated a MIMO function. Physically, the EUT provides one completed transmitter and one receivers.
2. The difference of models refer to the model list.

| Modulation Mode | TX /RX Function |
|-----------------|-----------------|
| 802.11b         | 1TX / 1RX       |
| 802.11g         | 1TX / 1RX       |
| 802.11n (HT20)  | 1TX / 1RX       |

### 3.2 Model List

| Main Model No     | Serial Model No                    | Difference1                                                                                                                                                                       | Difference2                                                                                                                              |
|-------------------|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| MS-A19-9.5W-RGBCW | MS-A19-7W-RGBCW<br>MS-A19-5W-RGBCW | 9.5W is all same as 7W and 5W except for different LED quantity in same LED PWB and different component ratings in same driver PWB ( The driver difference, please refer to BOM ) | RGBCW is all same as RGBW except RGBCW has more LEDs(cold colour temperature) in same LED PWB and has more components in same driver PWB |
| MS-A19-9.5W-RGBW  | MS-A19-7W-RGBW<br>MS-A19-5W-RGBW   |                                                                                                                                                                                   |                                                                                                                                          |
| MS-A19-9.5W-CW    | MS-A19-7W-CW<br>MS-A19-5W-CW       |                                                                                                                                                                                   | CW is all same as W except CW has more LEDs(cold colour temperature) in same LED PWB and has more components in same driver PWB          |

### 3.3 Description of Test Modes

13 channels are provided for 802.11b, 802.11g and 802.11n (HT20)

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   | -       | -         |



### 3.3.1 Test Mode Applicability:

| EUT<br>Configure<br>Mode | Applicable to |         |     |      | Description |
|--------------------------|---------------|---------|-----|------|-------------|
|                          | RE ≥ 1G       | RE < 1G | PLC | APCM |             |
| -                        | √             | √       | √   | √    | -           |

Where **RE≥1G**: Radiated Emission above 1GHz

**RE≤1G**: Radiated Emission below 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

#### Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE           | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA RATE<br>(Mbps) |
|--------------------------|----------------|----------------------|-------------------|--------------------------|--------------------|---------------------|
| -                        | 802.11b        | 1 to 13              | 1, 6, 11          | DSSS                     | DBPSK              | 1.0                 |
| -                        | 802.11g        | 1 to 13              | 1, 6, 11          | OFDM                     | BPSK               | 6.0                 |
| -                        | 802.11n (HT20) | 1 to 13              | 1, 6, 11          | OFDM                     | BPSK               | 6.5                 |

#### Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

#### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE    | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA RATE<br>(Mbps) |
|--------------------------|---------|----------------------|-------------------|--------------------------|--------------------|---------------------|
| -                        | 802.11b | 1 to 11              | 1                 | DSSS                     | DBPSK              | 1.0                 |

### Antenna Port Conducted Measurement

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.


| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              |
| -                  | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              |
| -                  | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              |

### 3.3.2 Test Condition:

| Applicable to | Normal Environmental Conditions | Normal Input Power |
|---------------|---------------------------------|--------------------|
| RE ≥ 1G       | 25deg. C, 60%RH                 | 120Vac, 60Hz       |
| RE < 1G       | 25deg. C, 60%RH                 | 120Vac, 60Hz       |
| PLC           | 25deg. C, 60%RH                 | 120Vac, 60Hz       |
| APCM          | 25deg. C, 60%RH                 | 120Vac, 60Hz       |

### 3.4 Duty Cycle of Test Signal

The Duty Cycle of the EUT is 88.54%.





#### Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standard:

**FCC Part 15, Subpart C (15.247)**

**KDB 558074 D01 DTS Meas Guidance v05r02**

**ANSI C63.10:2013**

All relaxed test items have been performed and recorded as per the above standard.


## 4 Test Procedure and Results

### 4.1 6dB Bandwidth Measurement

#### 4.1.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz

#### 4.1.2 Test Setup



#### 4.1.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 8.2).

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW  $\geq$  3 RBW, peak detector with maximum hold) is implemented by the instrumentation function.

#### 4.1.4 Deviation of Test Standard

No deviation.


#### 4.1.5 Test Results

##### 802.11b

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|------------------------------|----------------------|---------------------|-------------|
| 1       | 2412            | 10.509                       | 8.086                | 0.5                 | Pass        |
| 6       | 2437            | 10.507                       | 8.547                | 0.5                 | Pass        |
| 11      | 2462            | 10.521                       | 8.082                | 0.5                 | Pass        |


#### Spectrum Plot

##### 802.11b(2412MHz)





## 802.11b(2437MHz)



## 802.11b(2462MHz)




## 802.11g

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|------------------------------|----------------------|---------------------|-------------|
| 1       | 2412            | 16.359                       | 16.310               | 0.5                 | Pass        |
| 6       | 2437            | 16.360                       | 16.310               | 0.5                 | Pass        |
| 11      | 2462            | 16.358                       | 16.310               | 0.5                 | Pass        |


## Spectrum Plot

### 802.11g(2412MHz)






## 802.11g(2437MHz)



## 802.11g(2462MHz)




## 802.11n(HT20)

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|------------------------------|----------------------|---------------------|-------------|
| 1       | 2412            | 17.437                       | 16.570               | 0.5                 | Pass        |
| 6       | 2437            | 17.433                       | 16.570               | 0.5                 | Pass        |
| 11      | 2462            | 17.430                       | 16.580               | 0.5                 | Pass        |


## Spectrum Plot

### 802.11n(HT20)(2412MHz)






## 802.11n(HT20)(2437MHz)



## 802.11n(HT20)(2462MHz)




## 4.2 Conducted Output Power Measurement

### 4.2.1 Limit

For systems using digital modulation in the 2400 – 2483.5 MHz bands: 1 Watt (30 dBm)

### 4.2.2 Test Setup



### 4.2.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 9.2.2.4).

- a) Measure the duty cycle,  $x$ , of the transmitter output signal as described in Section 6.0.
- b) Set span to at least 1.5 OBW.
- c) Set RBW = 1 % to 5 % of the OBW, not to exceed 1 MHz.
- d) Set VBW  $\geq$  3 RBW.
- e) Number of points in sweep  $\geq$  2 span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- f) Sweep time = auto.
- g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- h) Do not use sweep triggering. Allow the sweep to “free run”.
- i) Trace average at least 100 traces in power averaging (i.e., RMS) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the on and off periods of the transmitter.
- j) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
- k) Add  $10 \log (1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on- and off-times of the transmission). For example, add  $10 \log (1/0.25) = 6 \text{ dB}$  if the duty cycle is 25 %.

#### 4.2.4 Deviation of Test Standard

No deviation.


## 4.2.5 Test Results

### 802.11b

| Channel | Frequency (MHz) | Average Power (dBm) | Duty Cycle Factor | Final Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|-------------------|-------------------|-------------|-------------|
| 1       | 2412            | 12.03               | 0.53              | 12.56             | 30          | Pass        |
| 6       | 2437            | 11.92               | 0.53              | 12.45             | 30          | Pass        |
| 11      | 2462            | 10.35               | 0.53              | 10.88             | 30          | Pass        |

### Spectrum Plot

### 802.11b(2412MHz)





## 802.11b(2437MHz)



## 802.11b(2462MHz)




## 802.11g

| Channel | Frequency (MHz) | Average Power (dBm) | Duty Cycle Factor | Final Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|-------------------|-------------------|-------------|-------------|
| 1       | 2412            | 11.93               | 0.53              | 12.46             | 30          | Pass        |
| 6       | 2437            | 11.13               | 0.53              | 11.66             | 30          | Pass        |
| 11      | 2462            | 10.64               | 0.53              | 11.17             | 30          | Pass        |

### Spectrum Plot

#### 802.11g(2412MHz)






## 802.11g(2437MHz)



## 802.11b(2462MHz)




## 802.11n (HT20)


| Channel | Frequency (MHz) | Average Power (dBm) | Duty Cycle Factor | Final Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|-------------------|-------------------|-------------|-------------|
| 1       | 2412            | 11.92               | 0.53              | 12.45             | 30          | Pass        |
| 6       | 2437            | 11.05               | 0.53              | 11.58             | 30          | Pass        |
| 11      | 2462            | 10.67               | 0.53              | 11.20             | 30          | Pass        |

### Spectrum Plot


#### 802.11n(HT20)(2412MHz)



### 802.11n(HT20)(2437MHz)



### 802.11n(HT20)(2462MHz)




**Note: Duty Cycle Factor=10\*log (1/duty cycle)**

### 4.3 Power Spectral Density Measurement

#### 4.3.1 Limit

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz band.

#### 4.3.2 Test Setup



#### 4.3.3 Test Procedures

The power output per FCC § 15.247(e) was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 10.5) for compliance to FCC 47CFR 15.247 requirements.

- a) Measure the duty cycle (x) of the transmitter output signal.
- b) Set instrument center frequency to DTS channel center frequency.
- c) Set span to at least 1.5 OBW.
- d) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- e) Set VBW  $\geq 3 \text{ RBW}$ .
- f) Detector = power averaging (RMS) or sample detector (when RMS not available).
- g) Ensure that the number of measurement points in the sweep  $\geq 2 \text{ span/RBW}$ .
- h) Sweep time = auto couple.
- i) Do not use sweep triggering. Allow sweep to “free run”.
- j) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k) Use the peak marker function to determine the maximum amplitude level.
- l) Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.
- m) If resultant value exceeds the limit, then reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

#### 4.3.4 Deviation of Test Standard

No deviation.

#### 4.3.5 Test Results

##### 802.11b

| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Duty Cycle Factor | Final Power (dBm) | Limit (dBm/3kHz) | Pass / Fail |
|---------|-----------------|----------------|-------------------|-------------------|------------------|-------------|
| 1       | 2412            | -10.27         | 0.53              | -9.74             | 8                | Pass        |
| 6       | 2437            | -10.84         | 0.53              | -10.31            | 8                | Pass        |
| 11      | 2462            | -12.04         | 0.53              | -11.51            | 8                | Pass        |

#### Spectrum Plot

##### 802.11b(2412MHz)





## 802.11b(2437MHz)



## 802.11b(2462MHz)




## 802.11g

| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Duty Cycle Factor | Final Power (dBm) | Limit (dBm/3kHz) | Pass / Fail |
|---------|-----------------|----------------|-------------------|-------------------|------------------|-------------|
| 1       | 2412            | -12.49         | 0.53              | -11.96            | 8                | Pass        |
| 6       | 2437            | -13.22         | 0.53              | -12.69            | 8                | Pass        |
| 11      | 2462            | -14.62         | 0.53              | -14.09            | 8                | Pass        |

### Spectrum Plot


#### 802.11g(2412MHz)



### 802.11g(2437MHz)



### 802.11g(2462MHz)






## 802.11n (HT20)


| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Duty Cycle Factor | Final Power (dBm) | Limit (dBm/3kHz) | Pass / Fail |
|---------|-----------------|----------------|-------------------|-------------------|------------------|-------------|
| 1       | 2412            | -12.44         | 0.53              | -11.91            | 8                | Pass        |
| 6       | 2437            | -13.19         | 0.53              | -12.66            | 8                | Pass        |
| 11      | 2462            | -14.48         | 0.53              | -13.95            | 8                | Pass        |

## Spectrum Plot


### 802.11n(HT20)(2412MHz)



### 802.11n(HT20)(2437MHz)



### 802.11n(HT20)(2462MHz)




**Note: Duty Cycle Factor=10\*log (1/duty cycle)**

#### 4.4 Emissions in non-restricted frequency bands

##### 4.4.1 Limit

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

##### 4.4.2 Test Setup



##### 4.4.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 11.0) for compliance to FCC 47CFR 15.247 requirements.

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.



6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

#### **4.4.4 Deviation of Test Standard**

No deviation.

#### 4.4.5 Test Results

##### 802.11b

| Channel | Frequency<br>(MHz) | Pass / Fail |
|---------|--------------------|-------------|
| 1       | 2412               | Pass        |
| 6       | 2437               | Pass        |
| 11      | 2462               | Pass        |

#### Spectrum Plot

##### 802.11b(2412MHz)





## 802.11b(2437MHz)




## 802.11b(2462MHz)






## Spectrum Plot

### 802.11b(2412MHz) Band Edge





### 802.11b(2462MHz) Band Edge





## Spectrum Plot



### 802.11b(2412MHz) Out-of-Band Emissions





## Spectrum Plot



### 802.11b(2437MHz) Out-of-Band Emissions





## Spectrum Plot

### 802.11b(2462MHz) Out-of-Band Emissions






## 802.11g


| Channel | Frequency<br>(MHz) | Pass / Fail |
|---------|--------------------|-------------|
| 1       | 2412               | Pass        |
| 6       | 2437               | Pass        |
| 11      | 2462               | Pass        |

## Spectrum Plot

### 802.11g(2412MHz)




### 802.11g(2437MHz)





## Spectrum Plot

802.11g(2462MHz)





## Spectrum Plot

### 802.11g(2412MHz) Band Edge





### 802.11g(2462MHz) Band Edge





## Spectrum Plot



### 802.11g(2412MHz) Out-of-Band Emissions





## Spectrum Plot



### 802.11g(2437MHz) Out-of-Band Emissions





## Spectrum Plot

### 802.11g(2462MHz) Out-of-Band Emissions






## 802.11n(HT20)

| Channel | Frequency<br>(MHz) | Pass / Fail |
|---------|--------------------|-------------|
| 1       | 2412               | Pass        |
| 6       | 2437               | Pass        |
| 11      | 2462               | Pass        |

## Spectrum Plot

### 802.11n(HT20)(2412MHz)




### 802.11n(HT20)(2437MHz)





## Spectrum Plot

802.11n(HT20)(2462MHz)





## Spectrum Plot

### 802.11n(HT20)(2412MHz) Band Edge





### 802.11n(HT20)(2462MHz) Band Edge





## Spectrum Plot



### 802.11n(HT20)(2412MHz) Out-of-Band Emissions





## Spectrum Plot



### 802.11n(HT20)(2437MHz) Out-of-Band Emissions





## Spectrum Plot

### 802.11n(HT20)(2462MHz) Out-of-Band Emissions



## 4.5 Radiated Emission Measurement

### 4.5.1 Limits

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490        | 2400/F (kHz)                         | 300                              |
| 0.490 ~ 1.705        | 24000/F (kHz)                        | 30                               |
| 1.705 ~ 30.0         | 30                                   | 30                               |
| 30 ~ 88              | 100                                  | 3                                |
| 88 ~ 216             | 150                                  | 3                                |
| 216 ~ 960            | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

### 4.5.2 Test Procedures

#### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degree to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotate table was turned from

0 degree to 360 degree to find the maximum reading.

- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**Note:**

The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1/T for RMS Average (Duty cycle < 98 %) for Peak detection at frequency above 1 GHz.
- 4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle  $\geq$  98 %) for Average detection (AV) at frequency above 1 GHz.
- 5. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.5.3 Deviation from Test Standard


No deviation.

#### 4.5.4 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



#### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.5.5 EUT Operating Conditions

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

#### 4.5.6 Test Results

##### Radiated Emissions Range 9kHz~30MHz

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

## Radiated Emissions Range 30MHz~1GHz


|                 |                 |                   |                 |
|-----------------|-----------------|-------------------|-----------------|
| Mode            | 802.11b-2412MHz | Detector Function | Quasi-Peak (QP) |
| Frequency Range | 30MHz ~ 1GHz    | Antenna Polarity  | Horizontal      |

| Spurious Emission Level |                 |                         |                |             |                          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) |
| 1                       | 30.97           | 29.99                   | 40.00          | -10.01      | -10.59                   |
| 2                       | 32.91           | 28.01                   | 40.00          | -11.99      | -10.35                   |
| 3                       | 69.96           | 25.64                   | 40.00          | -14.36      | -12.10                   |
| 4                       | 480.0           | 36.10                   | 46.50          | -10.40      | -5.64                    |
| 5                       | 560.0           | 34.26                   | 46.50          | -12.24      | -5.18                    |
| 6                       | 639.9           | 32.79                   | 46.50          | -13.71      | -3.26                    |

### REMARKS:

1. Emission Level(dBuV/m) = Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Test Plot:






|                        |                 |                          |                 |
|------------------------|-----------------|--------------------------|-----------------|
| <b>Mode</b>            | 802.11b-2412MHz | <b>Detector Function</b> | Quasi-Peak (QP) |
| <b>Frequency Range</b> | 30MHz ~ 1GHz    | <b>Antenna Polarity</b>  | Vertical        |

| Spurious Emission Level |                 |                         |                |             |                          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) |
| 1                       | 66.27           | 22.60                   | 40.00          | -17.40      | -11.53                   |
| 2                       | 104.1           | 21.78                   | 43.50          | -21.72      | -12.90                   |
| 3                       | 196.4           | 25.96                   | 43.50          | -17.54      | -12.21                   |
| 4                       | 399.9           | 27.83                   | 46.50          | -18.67      | -7.84                    |
| 5                       | 480.0           | 33.60                   | 46.50          | -12.90      | -5.64                    |
| 6                       | 560.0           | 27.44                   | 46.50          | -19.06      | -5.18                    |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

#### Test Plot:





## Radiated Emission Range 1GHz~10th Harmonic

### 802.11b

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| Channel         | TX Channel 1 | Detector Function | Peak (PK)    |
| Frequency Range | 1GHz ~ 25GHz |                   | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4824.15         | 50.94                   | 74             | -23.06      | -9.40                    | H                | PK       |
| 2                       | 4824.15         | 48.02                   | 54             | -5.98       | -9.40                    | H                | AV       |
| 3                       | 4824.15         | 48.91                   | 74             | -25.09      | -9.40                    | V                | PK       |
| 4                       | 4825.00         | 45.53                   | 54             | -8.47       | -9.40                    | V                | AV       |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| Channel         | TX Channel 6 | Detector Function | Peak (PK)    |
| Frequency Range | 1GHz ~ 25GHz |                   | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4873.45         | 48.83                   | 74             | -25.17      | -9.33                    | H                | PK       |
| 2                       | 4874.30         | 46.52                   | 54             | -7.48       | -9.33                    | H                | AV       |
| 3                       | 4874.30         | 46.45                   | 74             | -27.55      | -9.33                    | V                | PK       |
| 4                       | 4874.30         | 43.76                   | 54             | -10.24      | -9.33                    | V                | AV       |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>Channel</b>         | TX Channel 11 | <b>Detector Function</b> | Peak (PK)    |
| <b>Frequency Range</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4923.60         | 45.64                   | 74             | -28.36      | -9.27                    | H                | PK       |
| 2                       | 4924.45         | 43.75                   | 54             | -10.25      | -9.27                    | H                | AV       |
| 3                       | 4921.05         | 43.69                   | 74             | -30.31      | -9.27                    | V                | PK       |
| 4                       | 4924.45         | 39.88                   | 54             | -14.12      | -9.27                    | V                | AV       |

**REMARKS:**

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



### 802.11g

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| Channel         | TX Channel 1 | Detector Function | Peak (PK)    |
| Frequency Range | 1GHz ~ 25GHz |                   | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4823.30         | 49.21                   | 74.00          | -24.79      | -4.42                    | H                | PK       |
| 2                       | 4824.15         | 42.17                   | 54.00          | -11.83      | -4.42                    | H                | AV       |
| 3                       | 4825.85         | 41.55                   | 54.00          | -12.45      | -4.42                    | V                | PK       |
| 4                       | 4829.25         | 46.98                   | 74.00          | -27.02      | -4.42                    | V                | AV       |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| Channel         | TX Channel 6 | Detector Function | Peak (PK)    |
| Frequency Range | 1GHz ~ 25GHz |                   | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4863.25         | 44.40                   | 74.00          | -29.60      | -9.33                    | H                | PK       |
| 2                       | 4873.45         | 38.52                   | 54.00          | -15.48      | -9.33                    | H                | AV       |
| 3                       | 4874.30         | 46.40                   | 74.00          | -27.60      | -9.33                    | V                | PK       |
| 4                       | 4874.30         | 39.26                   | 54.00          | -14.74      | -9.33                    | V                | AV       |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| Channel         | TX Channel 11 | Detector Function | Peak (PK)    |
| Frequency Range | 1GHz ~ 25GHz  |                   | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4924.45         | 42.52                   | 74.00          | -31.48      | -9.26                    | H                | PK       |
| 2                       | 4925.30         | 37.39                   | 54.00          | -16.61      | -9.26                    | H                | AV       |
| 3                       | 4943.15         | 44.96                   | 74.00          | -29.04      | -9.26                    | V                | PK       |
| 4                       | 4943.15         | 44.96                   | 74.00          | -29.04      | -9.26                    | V                | AV       |

**REMARKS:**

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



### 802.11n (HT20)

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| Channel         | TX Channel 1 | Detector Function | Peak (PK)    |
| Frequency Range | 1GHz ~ 25GHz |                   | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4820.75         | 46.17                   | 74.00          | -27.83      | -9.40                    | H                | PK       |
| 2                       | 4828.40         | 40.89                   | 54.00          | -13.11      | -9.40                    | H                | AV       |
| 3                       | 4819.90         | 45.49                   | 74.00          | -28.51      | -9.40                    | V                | PK       |
| 4                       | 4827.55         | 40.04                   | 54.00          | -13.96      | -9.40                    | V                | AV       |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| Channel         | TX Channel 6 | Detector Function | Peak (PK)    |
| Frequency Range | 1GHz ~ 25GHz |                   | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4872.60         | 44.94                   | 74.00          | -29.06      | -9.33                    | H                | PK       |
| 2                       | 4875.15         | 39.48                   | 54.00          | -14.52      | -9.33                    | H                | AV       |
| 3                       | 4938.05         | 47.70                   | 74.00          | -26.30      | -9.33                    | V                | PK       |
| 4                       | 4938.90         | 40.38                   | 54.00          | -13.62      | -9.33                    | V                | AV       |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>Channel</b>         | TX Channel 11 | <b>Detector Function</b> | Peak (PK)    |
| <b>Frequency Range</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| Spurious Emission Level |                 |                         |                |             |                          |                  |          |
|-------------------------|-----------------|-------------------------|----------------|-------------|--------------------------|------------------|----------|
| No.                     | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Correction Factor (dB/m) | Antenna Polarity | Detector |
| 1                       | 4923.60         | 41.80                   | 74.00          | -32.20      | -9.26                    | H                | PK       |
| 2                       | 4923.60         | 36.48                   | 54.00          | -17.52      | -9.26                    | H                | AV       |
| 3                       | 4925.30         | 43.93                   | 74.00          | -30.07      | -9.26                    | V                | PK       |
| 4                       | 4926.15         | 36.59                   | 54.00          | -17.41      | -9.26                    | V                | AV       |

#### REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.6 Conducted Emission Measurement

### 4.6.1 Limits

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.6.2 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

### 4.6.3 Deviation from Test Standard

No deviation.

#### 4.6.4 Test Setup



**Note: 1.Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.6.5 EUT Operating Conditions

Same as 4.1.6.

#### 4.6.6 Test Results

##### Working While Charging


| Phase | Line (L) | Detector Function | Quasi-Peak (QP) /<br>Average (AV) |
|-------|----------|-------------------|-----------------------------------|
|-------|----------|-------------------|-----------------------------------|

| No | Freq.  | Corr.  | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|--------|--------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
|    |        | Factor | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    | [MHz]  | (dB)   | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.15   | 9.84   | 28.16         | 12.72 | 38.00          | 22.56 | 66.00     | 56.00 | -28.00 | -33.44 |
| 2  | 1.05   | 9.60   | 13.89         | 7.31  | 23.49          | 16.91 | 56.00     | 46.00 | -32.51 | -29.09 |
| 3  | 3.99   | 9.96   | 20.80         | 15.76 | 30.76          | 25.72 | 56.00     | 46.00 | -25.24 | -20.28 |
| 4  | 7.185  | 10.20  | 22.08         | 16.67 | 32.28          | 26.87 | 60.00     | 50.00 | -27.72 | -23.13 |
| 5  | 8.78   | 10.31  | 24.18         | 18.77 | 34.49          | 29.08 | 60.00     | 50.00 | -25.51 | -20.92 |
| 6  | 17.555 | 10.29  | 24.57         | 20.41 | 34.86          | 30.70 | 60.00     | 50.00 | -25.14 | -19.30 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.

Test Plot:




|       |             |                   |                                   |
|-------|-------------|-------------------|-----------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) /<br>Average (AV) |
|-------|-------------|-------------------|-----------------------------------|

| No | Freq. | Corr.  | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|-------|--------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
|    |       | Factor | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    | [MHz] | (dB)   | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.15  | 9.85   | 28.38         | 12.72 | 38.23          | 22.57 | 66.00     | 56.00 | -27.77 | -33.43 |
| 2  | 0.195 | 9.80   | 24.56         | 8.85  | 34.36          | 18.65 | 63.82     | 53.82 | -29.46 | -35.17 |
| 3  | 1.05  | 9.89   | 13.50         | 2.48  | 23.39          | 12.37 | 56.00     | 46.00 | -32.61 | -33.63 |
| 4  | 3.995 | 9.87   | 17.89         | 13.25 | 27.76          | 23.12 | 56.00     | 46.00 | -28.24 | -22.88 |
| 5  | 8.785 | 10.29  | 20.63         | 17.40 | 30.92          | 27.69 | 60.00     | 50.00 | -29.08 | -22.31 |
| 6  | 15.97 | 10.34  | 20.38         | 15.32 | 30.72          | 25.66 | 60.00     | 50.00 | -29.28 | -24.34 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.

#### Test Plot:





## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).



----- END -----