



RF Exposure evaluation

Model: ICC10in

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Limits specified per RSS-102, Issue 5.

Frequency range (MHz)	Power density (W/m ²)	Power density (mW/cm ²)
300 – 6000	$0.02619 f^{0.6834}$	$mW/cm^2 = W/m^2 * 0.1$

Equation OET bulletin 65, page 18, edition 97-01: $S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna = 20cm



Operational Bands	Frequency (MHz)	Antenna Gain (dBi)	Antenna Gain -numeric- (mW/cm ²)	Output Power -conducted- (dBm)	Output Power -conducted- (mW)	Output Power (EIRP) (mW)	IC Limit (mW/cm ²)	FCC Limit (mW/cm ²)	Power Density value (mW/cm ²)	Margin to FCC Limit (mW/cm ²)	Margin to IC Limit (mW/cm ²)
Bluetooth (BT Smartphone)	2441	1.82	1.5205	2.00	1.58	2.41	0.5410	1.00	0.0005	0.9995	0.5405
Bluetooth (BT Headset)	2441	3.22	2.0989	-0.30	0.93	1.96	0.5410	1.00	0.0004	0.9996	0.5406
WLAN 2.4 GHz	2412	3.65	2.3174	12.20	16.60	38.46	0.5366	1.00	0.0077	0.9923	0.5290

Co-Location Considerations

The calculation below is used to consider situations in which simultaneous exposure to fields of different frequencies occur. The calculation is performed by the sum of each relative exposure for each equipment according to the following criteria.

$$\sum_{1}^N \frac{S_{eqn}}{S_{Limn}} = \frac{S_{eq1}}{S_{Lim1}} + \frac{S_{eq2}}{S_{Lim2}} + \dots + \frac{S_{eqN}}{S_{LimN}} \leq 1$$

Where:

S_{eq} is the power density of the electromagnetic field at a given distance by a specific transmitter and a defined frequency.

S_{lim} is the MPE limit for the frequency being evaluated.



Assessment of Co-Location transmission for FCC

	BT Classic (BT Smartphone)	BT Classic (BT Headset)	WLAN 2.4
(S_{eq} / S_{Lim})	0.0005	0.0004	0.0077
Sum of (S_{eqn} / S_{Limn})	0.0086		
Limit	1		
Assessment	passed		

Assessment of Co-Location transmission for IC

	BT Classic (BT Smartphone)	BT Classic (BT Headset)	WLAN 2.4
(S_{eq} / S_{Lim})	0.0009	0.0007	0.0144
Sum of (S_{eqn} / S_{Limn})	0.016		
Limit	1		
Assessment	passed		

Yours sincerely,

A handwritten signature in blue ink that reads 'T. S. Sunar'.

Teoman Soner Sunar