

ISED CABid: ES1909
Lab. Company Number: 4621A

Test Report No:
83206RRF.007

Partial Test Report

USA FCC 15.31(h), 15.209, 15.247, 15.407
CANADA RSS-247, RSS-Gen

(*) Identification of item tested	Central In-Vehicle Infotainment Computer
(*) Trademark	BOSCH
(*) Model and /or type reference	MBCI2LS3PN1
Other identification of the product	FCC ID: 2AUXS-MBCI2LS3PN2 IC: 25847-MBCI2LS3PN1
(*) Features	AM/FM/DAB/SIRIUS, GNSS, 2.4/5GHz WLAN, Bluetooth 5.1, Video/Audio HW version: D22 SW version: E326
Applicant	Robert Bosch GmbH Robert-Bosch-Strasse 200, 31139, Hildesheim, Germany
Test method requested, standard	USA FCC Part 15.31(h) (10-1-23 Edition): Measurement standard. USA FCC Part 15.209 (10-1-23 Edition): Radiated emission limits; general requirements. USA FCC Part 15.247 (10-1-23 Edition): Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.407 (10-1-23 Edition): Unlicensed National Information Infrastructure (U-NII) Devices. General technical requirements. Band U-NII-3 (5725 MHz – 5850 MHz). CANADA RSS-247 Issue 3, Aug. 2023. CANADA RSS-Gen Issue 5, Amendment 2, Feb. 2021. - Emission limitations radiated with simultaneous transmissions. Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum: System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. Guidance for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices 789033 D02 General U-NII Test Procedures New Rules v02r01 dated Dec. 14, 2017.

	Measurement Guidance for Certification of Licensed Digital Transmitters. 971168 D01 Power Meas License Digital Systems v03r01 dated April 9, 2018. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices. ANSI C63.26-2015 IEEE/ANSI Standard for Testing of Transmitters Used in Licensed Radio Services.
Approved by (name / position & signature)	Antonio José Jurado Ruiz Industrial & Automotive EMC Lab. Manager
Date of issue	2025-08-14
Report template No.	FDT08_25 (*) "Data provided by the client"

Index

Competences and guarantees4

General conditions4

Uncertainty4

Data provided by the client.....5

Usage of samples6

Test sample description7

Identification of the client.....7

Testing period and place.....8

Document history8

Environmental conditions8

Remarks and comments9

Testing verdicts.....10

Summary10

Appendix A: Test results11

Competences and guarantees

DEKRA Testing and Certification is an FCC-recognized accredited testing laboratory with appropriate scope of accreditation that covers the performed tests in this report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory, CABid: ES1909, Company Number: 4621A, with the appropriate scope of accreditation that covers the performed tests in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

The total uncertainty of the measurement system for the radiated emissions of the EUT from 30 MHz to 1 GHz is: Measurement uncertainty $\leq \pm 5.35$ dB (with factor $k=2$).

The total uncertainty of the measurement system for the radiated emissions of the EUT from 1 to 17 GHz is: Measurement uncertainty $\leq \pm 4.32$ dB (with factor $k=2$).

The total uncertainty of the measurement system for the radiated emissions of the EUT from 17 to 40 GHz is: Measurement uncertainty $\leq \pm 5.51$ dB (with factor $k=2$).

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample consists of a CIVIC Central In-Vehicle Infotainment Computer, including WLAN/ Bluetooth, GPS, AM/FM/DAB receiver.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results. The laboratory is not responsible for such information and it is not covered by accreditation.

Usage of samples

Samples undergoing test have been selected by: The client.

Id	Control Number	Description	Model	Serial N°	Date of Reception	Application
S/01	82544C_3.1	Headunit A- PREMIUM USA	MBCI2LS3PN1	0759610	2025-05-13	Element Under Test
S/01	76719D_20.1	Antenna	-	-	2024-04-04	Auxiliary Element
S/01	76719D_83.1	Antenna	A1779052902/002	-	2024-04-17	Auxiliary Element
S/01	76719D_9.1	Fakra - 4 Fakra Cable	-	-	2024-04-04	Auxiliary Element
S/01	76719D_91.1	Antenna	A1779052902/002	-	2024-04-17	Auxiliary Element
S/01	76719D_92.1	Antenna	A1779052902/002	-	2024-04-17	Auxiliary Element
S/01	80633C_4.1	Ethernet- CAN interface	VN5610A	-	2024-12-18	Auxiliary Element
S/01	80633C_9.1	Harness	-	-	2024-12-18	Auxiliary Element
S/01	82341B_13.1	Fakra Cable	-	-	2025-04-09	Auxiliary Element

Notes referenced to samples during the project:

Id	Type
S/01	Radiated tests.

Test sample description

Ports..... :	Port name and description	Cable											
		Specified max length [m]	Attached during test	Shielded									
	Main Connector	2m	[X]	[]									
	Main Connector	2m	[X]	[]									
	Fakra Quad Connector AM/FM/DAB Fakra Single Connector GPS	-	[X]	[X]									
	Fakra Quad Connector WLAN/BT	-	[X]	[X]									
Supplementary information to the ports..... :	--												
Rated power supply :	Voltage and Frequency		Reference poles										
			L1	L2	L3	N	PE						
	[]	AC:											
	[X]	DC: 9-16V nominal 12 VDC by vehicle battery											
Rated Power..... :	--												
Clock frequencies..... :	--												
Other parameters :	--												
Software version..... :	E326												
Hardware version :	D22												
Dimensions in cm (W x H x D) ... :	--												
Mounting position :	[]	Table top equipment											
	[]	Wall/Ceiling mounted equipment											
	[]	Floor standing equipment											
	[]	Hand-held equipment											
	[X]	Other: Cluster in the car											
Modules/parts..... :	Module/parts of test item		Type		Manufacturer								
	--		--		--								
Accessories (not part of the test item) :	Description		Type		Manufacturer								
	Antennas		--		--								
	HUD		--		--								
	SA2 Panel		--		--								
	Cameras		--		--								
Documents as provided by the applicant :	Description		File name		Issue date								
	--		--		--								

Identification of the client

Robert Bosch GmbH
Robert-Bosch-Strasse 200, 31139 Hildesheim, Germany

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2025-07-27
Date (finish)	2025-07-28

Document history

Report number	Date	Description
83206RRF.007	2025-08-14	First release.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semi-anechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

Remarks and comments

The tests have been performed by the technical personnel: Antonio Maireles, Carmen Vázquez Perez, Pablo Redondo Reyes and Valentin Andarias Diaz.

Used instrumentation:

Control No.	Equipment	Model	Manufacturer	Next Calibration
06791	SEMIANECHOIC ABSORBER LINED CHAMBER IV	FACT 3 200 STP	ETS LINDGREN	N/A
06792	SHIELDED ROOM	S101	ETS LINDGREN	N/A
06609	ETHERNET TEMPERATURE AND HUMIDITY LOGGER	HWg-STE	HW GROUP	2026-04-21
06615	ETHERNET TEMPERATURE AND HUMIDITY LOGGER	HWg-STE	HW GROUP	2026-04-24
06143	HYBRID BILOG ANTENNA 30MHz-6GHz	3142E	ETS LINDGREN	2027-01-22
06142	PRE-AMPLIFIER G>38dB 30MHz-6GHz	BLNA 0360-01N	BONN ELEKTRONIK	2025-07-25
06496	HORN ANTENNA 1-18GHz	BBHA 9120 D	SCHWARZBECK	2026-12-01
03783	PRE-AMPLIFIER G>30dB 1GHz-18GHz	BLMA 0118-3A	BONN ELEKTRONIK	2026-03-17
04657	HORN ANTENNA 18-40GHz	BBHA 9170	SCHWARZBECK	2026-06-12
10537	PRE-AMPLIFIER G>46dB 18-40 GHz	BLMA 1840-5G	BONN ELEKTRONIK	2026-03-07
07817	EMI TEST RECEIVER 2Hz-44GHz	ESW44	ROHDE AND SCHWARZ	2026-07-01
07445	DC POWER SUPPLY 30V/5A	U8002A	KEYSIGHT TECHNOLOGIES	N/A
07760	DIGITAL MULTIMETER	175	FLUKE	2025-11-07
06157	SIGNAL AND SPECTRUM ANALYZER 10 Hz - 40 GHz	FSV40	ROHDE AND SCHWARZ	2027-03-17
10573	PRE-AMPLIFIER G>46dB 18-40 GHz	BLMA 1840-5G	BONN ELEKTRONIK	2026-03-07
04848	SOFTWARE FOR EMC/RF TESTING	EMC32	ROHDE AND SCHWARZ	N/A

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

FCC 15 / CANADA RSS-247, RSS-Gen PARAGRAPH		
Requirement – Test case	Verdict	Remark
FCC 15.31 (h), 15.209 (a), 15.247 (d), 15.407 (b) / RSS-247 5.5, 6.2.1.2 and 6.2.2.2, RSS-Gen 8.9	P	(1)
Supplementary information and remarks:		
(1) Only simultaneous transmission radiated spurious emission test was requested.		

Appendix A: Test results

INDEX

INDEX.....12

TEST CONDITIONS.....13

FCC 15.31 (h), 15.209 (a), 15.247 (d), 15.407 (b), 22.917 (a), 24.238 (a), 27.53 (m) (4) RSS-132 5.5,
RSS-133 6.5, RSS-199 5.6, RSS-247 5.5, 6.2.1.2 and 6.2.2.2, RSS-Gen 8.9 Emission limitations
radiated (Transmitter).....15

TEST CONDITIONS

(*): Data provided by the Applicant.

POWER SUPPLY (*):

Vnominal: 12 Vdc
 Type of Power Supply: Battery

ANTENNA (*):

Technologies	Antenna Gain (dBi)	Type of Antenna
BT EDR	+0.1	Internal (printed circuit board)
WLAN 2.4 GHz	+0.1	External
WLAN 5 GHz	+5.1	External

TEST FREQUENCIES:

Frequency range	Technologies	Modulations	Worst case
2.4 GHz	Bluetooth EDR	Bluetooth EDR (GFSK, Pi/4-DQPSK, 8DPSK)	Bluetooth EDR (High Channel, 8DPSK)
	WLAN 2.4 GHz	WLAN 2.4 GHz (802.11 bgn20)	WLAN 2.4 GHz (Low Channel, 802.11 n20)
f > 5 GHz	Wi-Fi 5 GHz U-NII-1	WLAN 5 GHz (a, ac, n)	WLAN 5 GHz Band U-NII-3, ax20, RU26, 0, Low Channel)

The test set-up was made according to the general provisions of FCC 558074 D01 15.247 Meas Guidance v05r02 dated April 2, 2019.

The EUT was tested in the following operating mode during the transmitter tests:

TEST FREQUENCIES FOR SIMULTANEOUS TRANSMISSION MODE RADIATED TESTS:

The EUT was configured to simultaneously transmit the following signals at maximum output power:

1. Simultaneous transmission mode BT EDR, WLAN 2.4 GHz:

BT EDR:	Low Channel (2402 MHz). 8DPSK.
WLAN 2.4 GHz:	Low Channel (2412 MHz). 802.11 ax20. RU26. 0. BW: 20 MHz.

2. Simultaneous transmission mode BT EDR, WLAN 5 GHz U-NI-1:

BT EDR:	Low Channel (2402 MHz). 8DPSK.
WLAN 5 GHz U-NI-1:	High Channel (5240 MHz). 802.11 ax20. RU26. 8. BW: 20 MHz.

FCC 15.31 (h), 15.209 (a), 15.247 (d), 15.407 (b), 22.917 (a), 24.238 (a), 27.53 (m) (4)
RSS-132 5.5, RSS-133 6.5, RSS-199 5.6, RSS-247 5.5, 6.2.1.2 and 6.2.2.2, RSS-Gen 8.9
Emission limitations radiated (Transmitter)

Limits:

BT EDR, WLAN 2.4 GHz, WLAN 5 GHz:

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function corresponding to 20 dB above the indicated values in the table above.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz (68.23 dBµV/m at 3 m distance) at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Method:

The measurement was performed with the EUT inside a semi-anechoic chamber.

The spectrum was scanned from 30 MHz to at least the 10th harmonic of the highest frequency of the co-located radios up to 40 GHz.

The EUT was placed on a non-conductive stand at a 3-meter distance from the measuring antenna for measurements up to 17 GHz and at 1.5-meter distance for measurements above 17 GHz.

Detected emissions were maximized at each frequency by rotating the EUT and adjusting the measuring antenna height and polarization. The maximum meter reading was recorded. Measurements were made in both horizontal and vertical planes of polarization.


The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

For radiated measurements above 17 GHz performed at a distance closer than the distance specified in standard, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


These measurements have been performed in order to check the impact of the Co-Location of all radio interfaces (that can transmit simultaneously).

Test setup:


Radiated measurements below 1 GHz.



Radiated measurements between 1 GHz and 17 GHz.



Radiated measurements above 17 GHz.



Results:

1. Simultaneous transmission mode BT EDR, WLAN 2.4 GHz:

BT EDR: Low Channel (2402 MHz). 8DPSK.
WLAN 2.4 GHz: Low Channel (2412 MHz). 802.11 ax20. RU26. 0. BW: 20 MHz.

Frequency range 30 MHz - 1 GHz:

Spurious frequencies at less than 20 dB below the limit:

Frequency (MHz)	QuasiPeak (dBµV/m)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Polarization
32.134000	---	31.79	---	---	V
32.134000	26.35	---	40.00	13.65	V
64.047000	---	26.68	---	---	H
64.047000	17.86	---	40.00	22.14	H
79.373000	26.55	---	40.00	13.45	V
79.373000	---	29.94	---	---	V
237.095000	24.86	---	46.00	21.14	H
237.095000	---	30.86	---	---	H
480.807500	---	30.67	---	---	V
480.807500	26.35	---	46.00	19.65	V
594.006500	---	36.95	---	---	V
594.006500	31.33	---	46.00	14.67	V

Frequency range 1 - 26 GHz:

Spurious frequencies at less than 20 dB below the limit:


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Polarization
2353.700000	58.84	---	74.00	15.16	V
2353.700000	---	51.38	54.00	2.62	V
2389.700000	67.42	---	74.00	6.58	V
2389.700000	---	44.01	54.00	9.99	V

Verdict


Pass

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	30.312 kHz	PK+	100 kHz	1 s	0 dB
1 GHz - 3 GHz	30.769 kHz	PK+ ; AVG	1 MHz	1 s	0 dB
3 GHz - 17 GHz	140 kHz	PK+ ; AVG	1 MHz	1 s	30 dB
17 GHz - 26 GHz	300 kHz	PK+ ; AVG	1 MHz	1 s	0 dB



FREQUENCY RANGE 30 MHz - 1 GHz:



FREQUENCY RANGE 1 - 26 GHz:



The peaks above the limit are the BT EDR carrier frequency (2402 MHz), the WLAN 2.4 GHz carrier frequency (2412 MHz).



2. Simultaneous transmission mode BT EDR, WLAN 5 GHz U-NII-1:

BT EDR: Low Channel (2402 MHz). 8DPSK.
WLAN 5 GHz U-NII-1: High Channel (5240 MHz). 802.11 ax20. RU26. 8. BW: 20 MHz.

Frequency range 30 MHz - 1 GHz:

Spurious frequencies at less than 20 dB below the limit:

Frequency (MHz)	QuasiPeak (dBµV/m)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Polarization
31.455000	26.56	---	40.00	13.44	V
31.455000	---	32.43	---	---	V
45.326000	---	24.69	---	---	V
45.326000	18.84	---	40.00	21.16	V
79.276000	---	31.35	---	---	V
79.276000	27.66	---	40.00	12.34	V
208.043500	20.48	---	43.50	23.02	V
208.043500	---	28.32	---	---	V
233.554500	24.94	---	46.00	21.06	H
233.554500	---	30.43	---	---	H
310.233000	---	29.54	---	---	V
310.233000	21.15	---	46.00	24.85	V
482.068500	---	31.94	---	---	H
482.068500	28.15	---	46.00	17.86	H
600.020500	29.19	---	46.00	16.81	V
600.020500	---	32.56	---	---	V

Frequency range 1 - 26 GHz:


No spurious frequencies at less than 20 dB below the limit.

Verdict

Pass


Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	30.312 kHz	PK+	100 kHz	1 s	0 dB
1 GHz - 3 GHz	30.769 kHz	PK+ ; AVG	1 MHz	1 s	0 dB
3 GHz - 17 GHz	140 kHz	PK+ ; AVG	1 MHz	1 s	30 dB
17 GHz - 40 GHz	300 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

FREQUENCY RANGE 30 MHz - 1 GHz:




FREQUENCY RANGE 1 - 26 GHz:

Full Spectrum



The peak above the limit is the BT EDR carrier frequency (2402 MHz).

Full Spectrum



The highest peak near the limit is the WLAN 5 GHz carrier frequency (5240 MHz).

Full Spectrum

