



# FCC Part 15C Test Report

## FCC ID: 2AUY6-DS121JL

Applicant: Shenzhen Dianling Intelligent Technology Co.,Ltd

Address: 305, Building A, Tianyou Maker Industrial Park, No. 2 Lixin Road, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Manufacturer: Shenzhen Dianling Intelligent Technology Co.,Ltd

Address: 305, Building A, Tianyou Maker Industrial Park, No. 2 Lixin Road, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Product: Smart Switch

Trade Mark: N/A

Model No.: DS-121JL  
DS-1211AL, DS-1211YL, DS-1211ML, DS-1261WL, DS-1271WL, DS-12B1WL,  
DS-12C1WL, DS-12D1WL, DS-1241CL, DS-1211HL, DS-1211AN, DS-1211YN,  
DS-1211MN, DS-1261WN, DS-1271WN, DS-12B1WN, DS-12C1WN, DS-12D1WN,  
DS-1241CN, DS-1211HN, DS-121, DS-1211ZC, DS-1211ZN, DS-12AHWN, DS-12AHWL,  
DS-12AIWN, DS-12AIWL, DS-121KWN, DS-121KWL, DS-121KQN, DS-121KQL

Date of Receipt: Apr. 19, 2025

Test Date: Apr. 19, 2025 - Apr. 29, 2025

Date of Report: Apr. 29, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

Applicable Standards: FCC PART 15 C 15.249  
ANSI C63.10:2013

Test Result: Pass

Report Number: DLE-250419018R

Prepared (Test Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



*This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.*



Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>4</b>
<b>1.1 MEASUREMENT UNCERTAINTY</b>	4
<b>2 . GENERAL INFORMATION</b>	<b>5</b>
<b>2.1 GENERAL DESCRIPTION OF EUT</b>	5
<b>2.2 DESCRIPTION OF TEST MODES</b>	6
<b>2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	6
<b>2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)</b>	7
<b>2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING</b>	7
<b>2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS</b>	8
<b>3 . EMC EMISSION TEST</b>	<b>9</b>
<b>3.1 CONDUCTED EMISSION MEASUREMENT</b>	9
<b>3.1.1 POWER LINE CONDUCTED EMISSION LIMITS</b>	9
<b>3.1.2 TEST PROCEDURE</b>	9
<b>3.1.3 DEVIATION FROM TEST STANDARD</b>	9
<b>3.1.4 TEST SETUP</b>	10
<b>3.1.5 EUT OPERATING CONDITIONS</b>	10
<b>3.1.6 TEST RESULTS</b>	10
<b>3.2 RADIATED EMISSION MEASUREMENT</b>	13
<b>3.2.1 RADIATED EMISSION LIMITS</b>	13
<b>3.2.2 TEST PROCEDURE</b>	14
<b>3.2.3 DEVIATION FROM TEST STANDARD</b>	14
<b>3.2.4 TEST SETUP</b>	15
<b>3.2.5 EUT OPERATING CONDITIONS</b>	16
<b>3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)</b>	17
<b>3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)</b>	18
<b>3.2.8 TEST RESULTS (1GHZ~25GHZ)</b>	20
<b>3.3 RADIATED BAND EMISSION MEASUREMENT</b>	21
<b>3.3.1 TEST REQUIREMENT:</b>	21
<b>3.3.2 TEST PROCEDURE</b>	21
<b>3.3.3 DEVIATION FROM TEST STANDARD</b>	21
<b>3.3.4 TEST SETUP</b>	22
<b>3.3.5 EUT OPERATING CONDITIONS</b>	22
<b>4 . BANDWIDTH TEST</b>	<b>24</b>
<b>4.1 APPLIED PROCEDURES / LIMIT</b>	24
<b>4.1.1 TEST PROCEDURE</b>	24
<b>4.1.2 DEVIATION FROM STANDARD</b>	24
<b>4.1.3 TEST SETUP</b>	24
<b>4.1.4 EUT OPERATION CONDITIONS</b>	24



---

Table of Contents	Page
<b>4.1.5 TEST RESULTS</b>	<b>25</b>
<b>5 . ANTENNA REQUIREMENT</b>	<b>26</b>
<b>5.1 STANDARD REQUIREMENT</b>	<b>26</b>
<b>5.2 EUT ANTENNA</b>	<b>26</b>
<b>6 . TEST SEUUP PHOTO</b>	<b>26</b>
<b>7 . EUT PHOTO</b>	<b>26</b>



## 1.. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.205(a), 15.209(a) 15.249(a), 15.249(c)	Fundamental &Radiated Spurious Emission Measurement	PASS	
15.249(d)	Band Edge Emission	PASS	
15.215(c)	20dB Bandwidth	PASS	
15.203	Antenna Requirement	PASS	

### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Test lab: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1  
Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen,  
China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

### 1.1. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ ,providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$
8	20dB Bandwidth	$\pm 0.2\%$



## 2.. GENERAL INFORMATION

### 2.1. GENERAL DESCRIPTION OF EUT

Product Name:	Smart Switch
Trademark	N/A
Model No.:	DS-121JL DS-1211AL, DS-1211YL, DS-1211ML, DS-1261WL, DS-1271WL, DS-12B1WL, DS-12C1WL, DS-12D1WL, DS-1241CL, DS-1211HL, DS-1211AN, DS-1211YN, DS-1211MN, DS-1261WN, DS-1271WN, DS-12B1WN, DS-12C1WN, DS-12D1WN, DS-1241CN, DS-1211HN, DS-121, DS-1211ZC, DS-1211ZN, DS-12AHWN, DS-12AHWL, DS-12AIWN, DS-12AIWL, DS-121KWN, DS-121KWL, DS-121KQN, DS-121KQL
Model Difference:	All models only differ in the shape of the shell frame, the number of buttons, but the internal structure, PCB board and circuit principle are the same.
Operation Frequency:	2402~2480MHz
Channel numbers:	40 Channels
Channel separation:	2MHz
Modulation technology:	GFSK
Antenna Type:	Internal Antenna
Antenna gain:	1.37dBi
Power Supply:	AC 100-240V, 50/60Hz

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. The EUT's all information provided by client.

3.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	27	2456
01	2404	15	2432	28	2458
02	2406	16	2434	29	2460
03	2408	17	2436	30	2462
04	2410	18	2438	31	2464
05	2412	19	2440	32	2466
06	2414	20	2442	33	2468
07	2416	21	2444	34	2470
08	2418	22	2446	35	2472
09	2420	23	2448	36	2474
10	2422	24	2450	37	2476
11	2424	25	2452	38	2478
12	2426	26	2454	39	2480
13	2428	/	/	/	/



## 2.2. DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description	
Mode 1	CH00	GFSK
Mode 2	CH19	
Mode 3	CH39	
Mode 4	Link Mode	


For Conducted & Radiated Emission		
Final Test Mode	Description	
Mode 1	CH00	GFSK
Mode 2	CH19	
Mode 3	CH39	
Mode 4	Link Mode	

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) A new fully charged battery was used for testing during the test.

## 2.3. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Power Line Conducted Emission Test





## 2.4. DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Smart Switch	DS-121JL	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) For detachable type I/O cable should be specified the length in cm in «Length» column.

## 2.5. TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Test software Version	Test program: CB3S		
Frequency	2402 MHz	2440 MHz	2480 MHz
Power Setting of Softwave	10	10	10

**2.6. EQUIPMENTS LIST FOR ALL TEST ITEMS**

Radiation test, Band-edge test and 20db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 01, 2024	Oct. 31, 2025
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 01, 2024	Oct. 31, 2025
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 01, 2024	Oct. 31, 2025
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 01, 2024	Oct. 31, 2025
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 01, 2024	Oct. 31, 2025
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 01, 2024	Oct. 31, 2025
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 01, 2024	Oct. 31, 2025
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 01, 2024	Oct. 31, 2025
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 01, 2024	Oct. 31, 2025
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 01, 2024	Oct. 31, 2025
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 01, 2024	Oct. 31, 2025
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 01, 2024	Oct. 31, 2025
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 01, 2024	Oct. 31, 2025
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 01, 2024	Oct. 31, 2025
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 01, 2024	Oct. 31, 2025
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 01, 2024	Oct. 31, 2025

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
2	EMI Receiver	R&S	ESR	101421	Nov. 01, 2024	Oct. 31, 2025
3	LISN	R&S	ENV216	102417	Nov. 01, 2024	Oct. 31, 2025
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 01, 2024	Oct. 31, 2025

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



### 3.. EMC EMISSION TEST

#### 3.1. CONDUCTED EMISSION MEASUREMENT

##### 3.1.1. POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


#### 3.1.2. TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.1.3. DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4. TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.5. EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

### 3.1.6. TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4




## Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	52.15	9.99	62.14	66.00	-3.86	QP	P	
2	0.1500	34.03	9.99	44.02	56.00	-11.98	AVG	P	
3 *	0.5053	42.99	9.87	52.86	56.00	-3.14	QP	P	
4	0.5053	22.45	9.87	32.32	46.00	-13.68	AVG	P	
5	1.0140	40.50	9.97	50.47	56.00	-5.53	QP	P	
6	1.0140	17.88	9.97	27.85	46.00	-18.15	AVG	P	
7	4.0830	41.08	9.90	50.98	56.00	-5.02	QP	P	
8	4.0830	23.52	9.90	33.42	46.00	-12.58	AVG	P	
9	8.6370	31.68	9.94	41.62	60.00	-18.38	QP	P	
10	8.6370	12.47	9.94	22.41	50.00	-27.59	AVG	P	
11	15.7783	25.65	9.98	35.63	60.00	-24.37	QP	P	
12	15.7783	3.50	9.98	13.48	50.00	-36.52	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4



## Remark:

Margin = Limit – Level, Correct Factor = Cable loss + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2084	47.88	9.93	57.81	63.27	-5.46	QP	P	
2	0.2084	30.37	9.93	40.30	53.27	-12.97	AVG	P	
3 *	0.5053	42.66	9.87	52.53	56.00	-3.47	QP	P	
4	0.5053	21.83	9.87	31.70	46.00	-14.30	AVG	P	
5	1.0183	41.17	9.97	51.14	56.00	-4.86	QP	P	
6	1.0183	20.81	9.97	30.78	46.00	-15.22	AVG	P	
7	3.7950	36.42	9.91	46.33	56.00	-9.67	QP	P	
8	3.7950	19.80	9.91	29.71	46.00	-16.29	AVG	P	
9	6.2970	28.97	9.99	38.96	60.00	-21.04	QP	P	
10	6.2970	9.56	9.99	19.55	50.00	-30.45	AVG	P	
11	24.1035	18.04	10.17	28.21	60.00	-31.79	QP	P	
12	24.1035	1.37	10.17	11.54	50.00	-38.46	AVG	P	



### 3.2. RADIATED EMISSION MEASUREMENT

#### 3.2.1. RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in &15.209, whichever is the lesser attenuation.

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 - 928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

### 3.2.2. TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber.
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3. DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4. TEST SETUP


#### (A) Radiated Emission Test-UP Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5. EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



### 3.2.6. TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



### 3.2.7. TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV	dB	dB
1		58.6126	31.74	-14.79	16.95	40.00	-23.05
2		86.2001	36.12	-19.42	16.70	40.00	-23.30
3		143.3261	41.68	-20.32	21.36	43.50	-22.14
4		212.2695	41.82	-16.61	25.21	43.50	-18.29
5		280.0237	33.75	-14.89	18.86	46.00	-27.14
6	*	948.7610	31.48	-2.72	28.76	46.00	-17.24

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV	dB	dB
1	!	58.6126	49.40	-14.79	34.61	40.00	-5.39
2	*	84.9995	56.40	-19.44	36.96	40.00	-3.04
3	!	109.0286	56.65	-16.69	39.96	43.50	-3.54
4	!	133.1511	60.08	-19.92	40.16	43.50	-3.34
5	!	160.9089	59.21	-19.60	39.61	43.50	-3.89
6		280.0237	36.31	-14.89	21.42	46.00	-24.58

## Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

**3.2.8. TEST RESULTS (1GHZ~25GHZ)**

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
<b>operation frequency:2402</b>									
V	2402.00	113.68	52.16	2.78	27.41	91.71	114	-22.29	PK
V	2402.00	105.81	52.16	2.78	27.41	83.84	94	-10.16	AV
V	4804.00	77.28	51.74	3.08	31.25	59.87	74	-14.13	PK
V	4804.00	60.83	51.74	3.08	31.25	43.42	54	-10.58	AV
V	16132.00	54.24	51.56	7.36	41.57	51.61	74	-22.39	PK
H	2402.00	113.17	52.16	2.78	27.41	91.2	114	-22.8	PK
H	2402.00	104.56	52.16	2.78	27.41	82.59	94	-11.41	AV
H	4804.00	76.85	51.74	3.08	31.25	59.44	74	-14.56	PK
H	4804.00	59.12	51.74	3.08	31.25	41.71	54	-12.29	AV
H	16132.00	55.89	51.56	7.36	41.57	53.26	74	-20.74	PK
<b>operation frequency:2440</b>									
V	2440.00	112.52	52.11	2.82	27.47	90.7	114	-23.3	PK
V	2440.00	105.44	52.11	2.82	27.47	83.62	94	-10.38	AV
V	4880.00	77.53	51.77	3.03	31.34	60.13	74	-13.87	PK
V	4880.00	60.14	51.77	3.03	31.34	42.74	54	-11.26	AV
V	16132.00	54.58	51.56	7.36	41.57	51.95	74	-22.05	PK
H	2440.00	112.76	52.11	2.82	27.47	90.94	114	-23.06	PK
H	2440.00	104.28	52.11	2.82	27.47	82.46	94	-11.54	AV
H	4880.00	76.55	51.77	3.03	31.34	59.15	74	-14.85	PK
H	4880.00	59.84	51.77	3.03	31.34	42.44	54	-11.56	AV
H	16132.00	55.85	51.56	7.36	41.57	53.22	74	-20.78	PK
<b>operation frequency:2480</b>									
V	2480.00	113.63	52.23	2.86	27.44	91.7	114	-22.3	PK
V	2480.00	106.21	52.23	2.86	27.44	84.28	94	-9.72	AV
V	4960.00	78.27	51.69	3.05	31.39	61.02	74	-12.98	PK
V	4960.00	60.35	51.69	3.05	31.39	43.1	54	-10.9	AV
V	16132.00	54.86	51.56	7.36	41.57	52.23	74	-21.77	PK
H	2480.00	113.85	52.23	2.86	27.44	91.92	114	-22.08	PK
H	2480.00	105.24	52.23	2.86	27.44	83.31	94	-10.69	AV
H	4960.00	77.28	51.69	3.05	31.39	60.03	74	-13.97	PK
H	4960.00	59.36	51.69	3.05	31.39	42.11	54	-11.89	AV
H	16132.00	54.54	51.56	7.36	41.57	51.91	74	-22.09	PK

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



### 3.3 RADIATED BAND EMISSION MEASUREMENT

#### 3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

#### 3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

#### 3.3.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



### 3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



### 3.3.6 TEST RESULT

GFSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2390.00	76.63	52.12	2.73	27.38	54.62	74	-19.38	PK
V	2390.00	65.84	52.12	2.73	27.38	43.83	54	-10.17	AV
V	2400.00	77.85	52.16	2.78	27.41	55.88	74	-18.12	PK
V	2400.00	65.63	52.16	2.78	27.41	43.66	54	-10.34	AV
H	2390.00	77.61	52.12	2.73	27.38	55.6	74	-18.4	PK
H	2390.00	65.47	52.12	2.73	27.38	43.46	54	-10.54	AV
H	2400.00	76.22	52.16	2.78	27.41	54.25	74	-19.75	PK
H	2400.00	65.89	52.16	2.78	27.41	43.92	54	-10.08	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2480									
V	2483.50	75.52	52.23	2.86	27.44	53.59	74	-20.41	PK
V	2483.50	66.64	52.23	2.86	27.44	44.71	54	-9.29	AV
V	2500.00	75.14	52.26	2.88	27.49	53.25	74	-20.75	PK
V	2500.00	65.69	52.26	2.88	27.49	43.8	54	-10.2	AV
H	2483.50	75.25	52.23	2.86	27.44	53.32	74	-20.68	PK
H	2483.50	64.52	52.23	2.86	27.44	42.59	54	-11.41	AV
H	2500.00	75.44	52.26	2.88	27.49	53.55	74	-20.45	PK
H	2500.00	66.68	52.26	2.88	27.49	44.79	54	-9.21	AV

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



#### 4.. BANDWIDTH TEST

##### 4.1. APPLIED PROCEDURES / LIMIT

FCC Part15 (15.215) , Subpart C	
Section	Test Item
15.215	Bandwidth


##### 4.1.1. TEST PROCEDURE

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW)  $\geq$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

##### 4.1.2. DEVIATION FROM STANDARD

No deviation.

##### 4.1.3. TEST SETUP



##### 4.1.4. EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



#### 4.1.5. TEST RESULTS

Temperature:	25°C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode /CH00, CH19, CH39		

	Frequency (MHz)	20dB Bandwidth (MHz)	Result
GFSK	2402	1.172	Pass
	2440	1.147	Pass
	2480	1.156	Pass





## 5.. ANTENNA REQUIREMENT

### 5.1. STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 5.2. EUT ANTENNA

The EUT antenna is internal antenna, It comply with the standard requirement.

## 6.. TEST SEUUP PHOTO

Reference to the appendix I for details.

## 7.. EUT PHOTO

Reference to the appendix II for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*