

FCC REPORT

Applicant: AVS Electronics (HK) Ltd.

Address of Applicant: 16D Hollywood Centre 77-91 Queens Road West, Sheung Wan, Hong Kong SAR

Manufacturer: AVS Electronics (HK) Ltd.

Address of Manufacturer: 16D Hollywood Centre 77-91 Queens Road West, Sheung Wan, Hong Kong SAR

Factory: AVS Electronics (HK) Ltd.

Address of Factory: 16D Hollywood Centre 77-91 Queens Road West, Sheung Wan, Hong Kong SAR

Equipment Under Test (EUT)

Product Name: 8-inch Tablet PC

Model No.: SuitePad-8

FCC ID: 2AUYC-SUITEPAD-8

Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407

Date of sample receipt: September 16, 2019

Date of Test: September 16- September 29, 2019

Date of report issue: September 29, 2019

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	September 29	Original

Prepared By:

Date:

September 29

Project Engineer

Check By:

Date:

September 29

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 TEST FACILITY	7
5.4 TEST LOCATION	7
5.5 DESCRIPTION OF SUPPORT UNITS	7
5.6 DEVIATION FROM STANDARDS	7
5.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.8 ADDITIONAL INSTRUCTIONS	8
6 TEST INSTRUMENTS LIST	9
7 TEST RESULTS AND MEASUREMENT DATA	11
7.1 ANTENNA REQUIREMENT:	11
7.2 CONDUCTED EMISSIONS	12
7.3 EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	15
7.4 PEAK TRANSMIT POWER	22
7.5 POWER SPECTRAL DENSITY	24
7.6 BAND EDGE	31
7.7 RADIATED EMISSION	37
7.8 FREQUENCY STABILITY	49
8 TEST SETUP PHOTO	52
9 EUT CONSTRUCTIONAL DETAILS	54

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	PASS
AC Power Line Conducted Emission	15.207	PASS
Peak Transmit Power	15.407(a)(1)	PASS
Power Spectral Density	15.407(a)(1)	PASS
Undesirable Emission	15.407(b)(6), 15.205/15.209	PASS
Radiated Emission	15.205/15.209	PASS
Band Edge	15.407(b)(1)	PASS
Frequency Stability	15.407(g)	PASS

Remark:

Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 3.8039\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 3.9679\text{dB}$	(1)
Radiated Emission	1GHz ~ 40GHz	$\pm 4.29\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.44\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

Remark: Test according to ANSI C63.10:2013 and ANSI C63.4:2014

5 General Information

5.1 General Description of EUT

Product Name:	8-inch Tablet PC			
Model No.:	SuitePad-8			
Test Model No:	SuitePad-8			
Remark:/				
Serial No.:	PSJS500G			
Hardware Version:	HV1.0			
Software Version:	SV1.0			
Test sample(s) ID:	GTS201909000200-1			
Sample(s) Status:	Engineer sample			
Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	U-NII Band I	IEEE 802.11a	5180-5240	4
		IEEE 802.11n/ac 20MHz	5180-5240	4
		IEEE 802.11n/ac 40MHz	5190-5230	2
		IEEE 802.11ac 80MHz	5210	1
Modulation technology:	OFDM			
Antenna Type:	FPCB Antenna			
Antenna gain:	1.0 dBi			
Power supply:	AC120V 60Hz			

Channel list for 802.11a/n/ac(HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	40	5200MHz	44	5220MHz	48	5240MHz

Channel list for 802.11n(HT40)/ac(HT40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz				

Channel list for 802.11ac(HT80)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210MHz						

5.2 Test mode

Transmitting mode	Keep the EUT in transmitting with modulation..
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11a/n/ac(HT20)	6/6.5 Mbps
802.11n/ac(HT40)	13.5 Mbps
802.11ac(HT80)	29.3 Mbps

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

● **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.4 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.5 Description of Support Units

None.

5.6 Deviation from Standards

None.

5.7 Abnormalities from Standard Conditions

None.

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 26 2019	June. 25 2020
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 26 2019	June. 25 2020
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 26 2019	June. 25 2020
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 26 2019	June. 25 2020
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 26 2019	June. 25 2020
9	Coaxial Cable	GTS	N/A	GTS211	June. 26 2019	June. 25 2020
10	Coaxial cable	GTS	N/A	GTS210	June. 26 2019	June. 25 2020
11	Coaxial Cable	GTS	N/A	GTS212	June. 26 2019	June. 25 2020
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 26 2019	June. 25 2020
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 26 2019	June. 25 2020
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 26 2019	June. 25 2020
15	Band filter	Amindeon	82346	GTS219	June. 26 2019	June. 25 2020
16	Power Meter	Anritsu	ML2495A	GTS540	June. 26 2019	June. 25 2020
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 26 2019	June. 25 2020
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 26 2019	June. 25 2020
19	Splitter	Agilent	11636B	GTS237	June. 26 2019	June. 25 2020
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 26 2019	June. 25 2020
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 20 2018	Oct. 19 2019
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 20 2018	Oct. 19 2019
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 20 2018	Oct. 19 2019
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 26 2019	June. 25 2020

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 26 2019	June. 25 2020
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 26 2019	June. 25 2020
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 26 2019	June. 25 2020
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 26 2019	June. 25 2020
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 26 2019	June. 25 2020

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 26 2019	June. 25 2020
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 26 2019	June. 25 2020
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 26 2019	June. 25 2020
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 26 2019	June. 25 2020
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 26 2019	June. 25 2020
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 26 2019	June. 25 2020
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 26 2019	June. 25 2020

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 26 2019	June. 25 2020
2	Barometer	ChangChun	DYM3	GTS255	June. 26 2019	June. 25 2020

7 Test results and Measurement Data

7.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
<i>15.203 requirement:</i> <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
<i>The antennas are FPCB antenna, the best case gain of the antennas are 1.0dBi</i> 	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test procedure	The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test setup:	Reference Plane LISN AUX Equipment E.U.T 40cm 80cm EMI Receiver Filter AC power Test table/Insulation plane <i>Remark:</i> <i>E.U.T: Equipment Under Test</i> <i>LISN: Line Impedance Stabilization Network</i> <i>Test table height=0.8m</i>					
Test Instruments:	Refer to section 5.10 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.


Measurement data:

Line:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1819	38.58	9.66	48.24	64.39	-16.15	QP	
2		0.1819	21.23	9.66	30.89	54.39	-23.50	AVG	
3		0.4060	36.86	9.67	46.53	57.73	-11.20	QP	
4		0.4060	19.46	9.67	29.13	47.73	-18.60	AVG	
5		1.0700	36.77	9.69	46.46	56.00	-9.54	QP	
6		1.0700	15.92	9.69	25.61	46.00	-20.39	AVG	
7		2.3940	34.68	9.72	44.40	56.00	-11.60	QP	
8		2.3940	17.00	9.72	26.72	46.00	-19.28	AVG	
9		6.3380	34.08	9.78	43.86	60.00	-16.14	QP	
10		6.3380	18.68	9.78	28.46	50.00	-21.54	AVG	
11	*	13.0460	45.44	9.84	55.28	60.00	-4.72	QP	
12		13.0460	25.14	9.84	34.98	50.00	-15.02	AVG	

Neutral:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.4060	40.34	9.67	50.01	57.73	-7.72	QP
2		0.4060	29.46	9.67	39.13	47.73	-8.60	AVG
3		0.5060	43.89	9.68	53.57	56.00	-2.43	QP
4	*	0.5060	34.40	9.68	44.08	46.00	-1.92	AVG
5		0.7820	40.22	9.68	49.90	56.00	-6.10	QP
6		0.7820	27.79	9.68	37.47	46.00	-8.53	AVG
7		1.0460	38.76	9.69	48.45	56.00	-7.55	QP
8		1.0460	26.42	9.69	36.11	46.00	-9.89	AVG
9		1.3500	38.03	9.70	47.73	56.00	-8.27	QP
10		1.3500	25.85	9.70	35.55	46.00	-10.45	AVG
11		13.8940	45.77	9.85	55.62	60.00	-4.38	QP
12		13.8940	28.34	9.85	38.19	50.00	-11.81	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

7.3 Emission Bandwidth and 99% Occupied Bandwidth

Test Requirement:	FCC Part15 E Section 15.407
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.
Test procedure:	According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data:


CH. No.	Frequency (MHz)	6dB Occupied Bandwidth (MHz)			26dB Occupied Bandwidth (MHz)		
		802.11a	802.11n (HT20)	802.11ac (HT20)	802.11a	802.11n (HT20)	802.11ac (HT20)
36	5180	17.5925	17.5700	17.5826	23.7525	22.9025	23.0637
44	5220	17.5688	17.5713	17.5663	22.0937	22.4137	22.5137
48	5240	17.5563	17.5688	17.5588	22.1300	23.0075	22.3050


CH. No.	Frequency (MHz)	6dB Occupied Bandwidth (MHz)		26dB Occupied Bandwidth (MHz)	
		802.11n(HT40)	802.11ac(HT40)	802.11n(HT40)	802.11ac(HT40)
38	5190	36.2950	36.3025	45.5150	45.1375
46	5230	36.3038	36.2925	44.0300	44.7950

CH. No.	Frequency (MHz)	6dB Occupied Bandwidth (MHz)	26dB Occupied Bandwidth (MHz)
		802.11ac(HT80)	802.11ac(HT80)
42	5210	75.9563	87.8100


Test plots as followed:









5240





7.4 Peak Transmit Power

Test Requirement:	FCC Part15 E Section 15.407	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Limit:	Frequency band (MHz)	Limit
	5150-5250	$\leq 1\text{W}(30\text{dBm})$ for master device
		$\leq 250\text{mW}(23.98\text{dBm})$ for client device
	5250-5350	$\leq 250\text{mW}(23.98\text{dBm})$ for client device or $11\text{dBm}+10\log B^*$
	5470-5725	$\leq 250\text{mW}(23.98\text{dBm})$ for client device or $11\text{dBm}+10\log B^*$
Remark: *Where B is the 26dB emission bandwidth in MHz. The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.		
Test setup:		
Test procedure:	Measurement using an RF average power meter (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied a) The EUT is configured to transmit continuously or to transmit with a constant duty cycle. b) At all times when the EUT is transmitting, it must be transmitting at its maximum power control level. c) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five. (ii) If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section B). (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter. (iv) Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10\log(1/0.25)$ if the duty cycle is 25 percent).	
Test Instruments:	Refer to section 5.10 for details	
Test mode:	Refer to section 5.2 for details	
Test results:	Pass	

Measurement Data


Modulation	Duty cycle	Duty Factor
802.11a	98.8%	0.05
802.11n(HT20)	98.8%	0.05
802.11n(HT40)	97.5%	0.11
802.11ac(HT20)	98.9%	0.05
802.11ac(HT40)	97.4%	0.11
802.11ac(HT80)	95.2%	0.21

802.11a mode						
CH No.	Frequency (MHz)	Measured Power (dBm)	Duty Factor	Output Power (dBm)	Limit (dBm)	Result
36	5180	15.28	0.05	15.33	23.98	Pass
40	5200	15.81	0.05	15.86	23.98	Pass
48	5240	15.46	0.05	15.51	23.98	Pass
802.11n(HT20) mode						
CH No.	Frequency (MHz)	Measured Power (dBm)	Duty Factor	Output Power (dBm)	Limit (dBm)	Result
36	5180	15.88	0.05	15.93	23.98	Pass
40	5200	15.37	0.05	15.42	23.98	Pass
48	5240	15.49	0.05	15.54	23.98	Pass
802.11ac(HT20) mode						
CH No.	Frequency (MHz)	Measured Power (dBm)	Duty Factor	Output Power (dBm)	Limit (dBm)	Result
36	5180	16.79	0.05	16.84	23.98	Pass
40	5200	16.13	0.05	16.18	23.98	Pass
48	5240	16.28	0.05	16.33	23.98	Pass
802.11n(HT40) mode						
CH No.	Frequency (MHz)	Measured Power (dBm)	Duty Factor	Output Power (dBm)	Limit (dBm)	Result
38	5190	15.57	0.11	15.68	23.98	Pass
46	5230	15.22	0.11	15.33	23.98	Pass
802.11 ac(HT40) mode						
CH No.	Frequency (MHz)	Measured Power (dBm)	Duty Factor	Output Power (dBm)	Limit (dBm)	Result
38	5190	16.43	0.11	16.54	23.98	Pass
46	5230	16.75	0.11	16.86	23.98	Pass
802.11 ac(HT80)						
CH No.	Frequency (MHz)	Measured Power (dBm)	Duty Factor	Output Power (dBm)	Limit (dBm)	Result
42	5210	14.18	0.21	14.39	23.98	Pass

Note: Output Power = Measured Power + Duty Factor

Duty Factor = 10 log (1/Duty Cycle)

7.5 Power Spectral Density

Test Requirement:	FCC Part15 E Section 15.407	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Limit:	Frequency band (MHz)	Limit
	5150-5250	≤17dBm in 1MHz for master device
		≤11dBm in 1MHz for client device
	5250-5350	≤11dBm in 1MHz for client device
	5470-5725	≤11dBm in 1MHz for client device
Remark: The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.		
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.	
Test procedure:	1) Create an average power spectrum for the EUT operating mode being tested by following the instructions in section E)2) for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power..." 2) Use the peak search function on the instrument to find the peak of the spectrum. 3) Make the following adjustments to the peak value of the spectrum, if applicable: a) If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum. b) If Method SA-3 Alternative was used and the linear mode was used in step E)2)g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging. 4) The result is the PSD.	
Test Instruments:	Refer to section 5.10 for details	
Test mode:	Refer to section 5.2 for details	
Test results:	Pass	


Measurement Data

Modulation		Duty cycle		Duty Factor		
802.11a		98.8%		0.05		
802.11n(HT20)		98.8%		0.05		
802.11n(HT40)		97.5%		0.11		
802.11ac(HT20)		98.9%		0.05		
802.11ac(HT40)		97.4%		0.11		
802.11ac(HT80)		95.2%		0.21		
802.11a mode						
CH No.	Frequency (MHz)	Measured PSD (dBm/MHz)	Duty Factor	Total PSD Power(dBm/MHz)	Limit (dBm/MHz)	Result
36	5180	-5.86	0.05	-5.81	11	Pass
40	5200	-5.57	0.05	-5.52	11	Pass
48	5240	-5.55	0.05	-5.50	11	Pass
802.11n(HT20) mode						
CH No.	Frequency (MHz)	Measured PSD (dBm/MHz)	Duty Factor	Total PSD Power(dBm/MHz)	Limit (dBm/MHz)	Result
36	5180	-5.55	0.05	-5.50	11	Pass
40	5220	-6.27	0.05	-6.22	11	Pass
48	5240	-6.23	0.05	-6.18	11	Pass
802.11ac(HT20) mode						
CH No.	Frequency (MHz)	Measured PSD (dBm/MHz)	Duty Factor	Total PSD Power(dBm/MHz)	Limit (dBm/MHz)	Result
36	5180	-5.39	0.05	-5.34	11	Pass
40	5220	-5.75	0.05	-5.70	11	Pass
48	5240	-6.02	0.05	-5.97	11	Pass
802.11n(HT40) mode						
CH No.	Frequency (MHz)	Measured PSD (dBm/MHz)	Duty Factor	Total PSD Power(dBm/MHz)	Limit (dBm/MHz)	Result
38	5190	-8.68	0.11	-8.63	11	Pass
46	5230	-7.53	0.11	-7.48	11	Pass
802.11 ac(HT40) mode						
CH No.	Frequency (MHz)	Measured PSD (dBm/MHz)	Duty Factor	Total PSD Power(dBm/MHz)	Limit (dBm/MHz)	Result
38	5190	-8.59	0.11	-8.54	11	Pass
46	5230	-7.50	0.11	-7.45	11	Pass
802.11 ac(HT80)						
CH No.	Frequency (MHz)	Measured PSD (dBm/MHz)	Duty Factor	Total PSD Power(dBm/MHz)	Limit (dBm/MHz)	Result
42	5210	-11.18	0.21	-11.13	11	Pass


Note: Output Power = Measured Power + Duty Factor

Duty Factor = 10 log (1/Duty Cycle)


Test plots as followed:




802.11n(HT20) mode



5180




5220




5240


802.11ac(HT20) mode



5180




5220




5240

802.11n(HT40) mode




5190




5230

802.11ac(HT40) mode




5190



5230


802.11ac(HT80) mode



5210

7.6 Band Edge


Test Requirement:	FCC Part15 E Section 15.407 and 5.205																								
Test Method:	ANSI C63.10:2013																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>AV</td><td>1MHz</td><td>3MHz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	AV	1MHz	3MHz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	AV	1MHz	3MHz	Average Value																					
Limit:	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>68.2</td><td>Peak Value</td></tr></table> Undesirable emission limits: (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band. (3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	68.2	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	68.2	Peak Value																							
Test Procedure:	a. The EUT was placed on the top of a rotating table 1.5 m above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not																								

	have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test setup:	For radiated emissions above 1GHz 
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Remarks:

- Only the worst case Main Antenna test data.
- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
- According to KDB 789033 D02 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2;$
For example, if $\text{EIRP} = -27\text{dBm}$
 $E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$


Measurement Data:




802.11a(HT20)			AVG		
Frequency	Read Level	Correct	Result	Limit	Margin
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
5150.00	37.16	-0.13	37.03	54.00	-16.97




802.11n(HT20)			Peak		
Frequency	Read Level	Correct	Result	Limit	Margin
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
5090.5	53.7	-0.26	53.44	74.00	-20.56




802.11a(HT20)			AVG		
Frequency	Read Level	Correct	Result	Limit	Margin
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
5148.050	37.69	-0.13	37.56	54.00	-16.44




802.11n(HT40)			Peak		
Frequency	Read Level	Correct	Result	Limit	Margin
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
5131.55	59.21	-0.14	59.07	74.00	-14.93



802.11n(HT40)			AVG		
Frequency	Read Level	Correct	Result	Limit	Margin
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
5150.000	38.05	-0.13	37.92	54.00	-16.08




802.11ac(HT80)			Peak		
Frequency	Read Level	Correct	Result	Limit	Margin
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
5149.350	62.96	-0.13	62.83	74.00	-11.17





802.11ac(HT80)			AVG		
Frequency	Read Level	Correct	Result	Limit	Margin
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
5150.000	38.93	-0.13	38.80	54.00	-15.20

7.7 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 40GHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9kHz-150KHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		AV	1MHz	3MHz	Average Value
Limit:					
	Frequency	Limit (uV/m)		Value	Measurement Distance
	0.009MHz-0.490MHz	2400/F(KHz)		QP	300m
	0.490MHz-1.705MHz	24000/F(KHz)		QP	300m
	1.705MHz-30MHz	30		QP	30m
	30MHz-88MHz	100		QP	3m
	88MHz-216MHz	150		QP	
	216MHz-960MHz	200		QP	
	960MHz-1GHz	500		QP	
	Above 1GHz	500		Average	
		5000		Peak	
Test Procedure:	Substitution method was performed to determine the actual ERP emission levels of the EUT. The following test procedure as below: 1>.Below 1GHz test procedure:				
	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 2> Above 1GHz test procedure:				

	1. On the test site as test setup graph above, the EUT shall be placed at the 0.8m support on the turntable and in the position closest to normal use as declared by the provider. 2. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter. The output of the test antenna shall be connected to the measuring receiver. 3. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the transmitter under test. 4. The test antenna shall be raised and lowered from 1m to 4m until a maximum signal level is detected by the measuring receiver. Then the turntable should be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. 5. Repeat step 4 for test frequency with the test antenna polarized horizontally. 6. Remove the transmitter and replace it with a substitution antenna 7. Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a nonradiating cable. With the antennas at both ends vertically polarized, and with the signal generator tuned to a particular test frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output. 8. Repeat step 7 with both antennas horizontally polarized for each test frequency. 9. Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps 7 and 8 by the power loss in the cable between the generator and the antenna, and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna by the following formula: $\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$ where: Pg is the generator output power into the substitution antenna.
Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to 1GHz

									
For radiated emissions above 1GHz									
									
		Test Instruments:		Refer to section 5.10 for details					
Test mode:		Refer to section 5.2 for details							
Test environment:		Temp.:	25 °C	Humid.:	52%	Press.: 1012mbar			
Test voltage:		AC 120V, 60Hz							
Test results:		Pass							

Remarks:

1. Only the worst case Main Antenna test data.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


Measurement Data:

9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


30MHz~ 1GHz

Horizontal:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV/m	dB/m	dB	
1	*	41.7129	24.64	-15.19	9.45	40.00	-30.55	QP
2		54.0711	23.07	-14.89	8.18	40.00	-31.82	QP
3		64.4331	23.92	-16.72	7.20	40.00	-32.80	QP
4		91.1746	25.52	-17.91	7.61	43.50	-35.89	QP
5		110.5687	23.81	-16.55	7.26	43.50	-36.24	QP
6		202.8104	24.25	-15.71	8.54	43.50	-34.96	QP

Vertical:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV/m	dB/m	dB	
1		41.5670	23.09	-15.25	7.84	40.00	-32.16	QP
2	*	49.8814	23.86	-14.75	9.11	40.00	-30.89	QP
3		57.1914	23.49	-15.73	7.76	40.00	-32.24	QP
4		91.4949	24.22	-17.84	6.38	43.50	-37.12	QP
5		106.3850	22.81	-16.24	6.57	43.50	-36.93	QP
6		267.5455	23.23	-13.15	10.08	46.00	-35.92	QP

Above 1GHz:

802.11a(HT20) 5180MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.00	41.71	39.67	14.62	32.65	63.35	74.00	-10.65	Vertical
15540.00	40.55	38.60	17.66	34.46	62.35	74.00	-11.65	Vertical
10360.00	42.34	39.67	14.62	32.65	63.98	74.00	-10.02	Horizontal
15540.00	43.38	38.60	17.66	34.46	65.18	74.00	-8.82	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.00	21.69	39.67	14.62	32.65	43.33	54.00	-10.67	Vertical
15540.00	20.38	38.60	17.66	34.46	42.18	54.00	-11.82	Vertical
10360.00	21.51	39.67	14.62	32.65	43.15	54.00	-10.85	Horizontal
15540.00	22.58	38.60	17.66	34.46	44.38	54.00	-9.62	Horizontal

802.11a(HT20) 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400.00	41.75	39.75	14.63	32.71	63.42	74.00	-10.58	Vertical
15600.00	40.39	38.33	17.67	34.17	62.22	74.00	-11.78	Vertical
10400.00	42.82	39.75	14.63	32.71	64.49	74.00	-9.51	Horizontal
15600.00	43.15	38.33	17.67	34.17	64.98	74.00	-9.02	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400.00	20.80	39.75	14.63	32.71	42.47	54.00	-11.53	Vertical
15600.00	20.25	38.33	17.67	34.17	42.08	54.00	-11.92	Vertical
10400.00	20.73	39.75	14.63	32.71	42.40	54.00	-11.60	Horizontal
15600.00	21.19	38.33	17.67	34.17	43.02	54.00	-10.98	Horizontal

802.11a(HT20) 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480.00	42.35	39.82	14.68	32.86	63.99	74.00	-10.01	Vertical
15720.00	41.51	38.09	17.73	33.66	63.67	74.00	-10.33	Vertical
10480.00	42.28	39.82	14.68	32.86	63.92	74.00	-10.08	Horizontal
15720.00	42.51	38.09	17.73	33.66	64.67	74.00	-9.33	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480.00	21.26	39.82	14.68	32.86	42.90	54.00	-11.10	Vertical
15720.00	21.79	38.09	17.73	33.66	43.95	54.00	-10.05	Vertical
10480.00	20.55	39.82	14.68	32.86	42.19	54.00	-11.81	Horizontal
15720.00	21.92	38.09	17.73	33.66	44.08	54.00	-9.92	Horizontal

802.11n(HT20) 5180MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.00	41.29	39.67	14.62	32.65	62.93	74.00	-11.07	Vertical
15540.00	40.85	38.60	17.66	34.46	62.65	74.00	-11.35	Vertical
10360.00	41.47	39.67	14.62	32.65	63.11	74.00	-10.89	Horizontal
15540.00	41.93	38.60	17.66	34.46	63.73	74.00	-10.27	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.00	20.36	39.67	14.62	32.65	42.00	54.00	-12.00	Vertical
15540.00	20.45	38.60	17.66	34.46	42.25	54.00	-11.75	Vertical
10360.00	20.29	39.67	14.62	32.65	41.93	54.00	-12.07	Horizontal
15540.00	21.86	38.60	17.66	34.46	43.66	54.00	-10.34	Horizontal

802.11n(HT20) 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400.00	42.18	39.75	14.63	32.71	63.85	74.00	-10.15	Vertical
15600.00	41.76	38.33	17.67	34.17	63.59	74.00	-10.41	Vertical
10400.00	41.95	39.75	14.63	32.71	63.62	74.00	-10.38	Horizontal
15600.00	42.24	38.33	17.67	34.17	64.07	74.00	-9.93	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400.00	21.16	39.75	14.63	32.71	42.83	54.00	-11.17	Vertical
15600.00	21.35	38.33	17.67	34.17	43.18	54.00	-10.82	Vertical
10400.00	20.87	39.75	14.63	32.71	42.54	54.00	-11.46	Horizontal
15600.00	21.41	38.33	17.67	34.17	43.24	54.00	-10.76	Horizontal

802.11n(HT20) 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480.00	40.69	39.82	14.68	32.86	62.33	74.00	-11.67	Vertical
15720.00	42.86	38.09	17.73	33.66	65.02	74.00	-8.98	Vertical
10480.00	43.93	39.82	14.68	32.86	65.57	74.00	-8.43	Horizontal
15720.00	41.15	38.09	17.73	33.66	63.31	74.00	-10.69	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480.00	20.47	39.82	14.68	32.86	42.11	54.00	-11.89	Vertical
15720.00	21.15	38.09	17.73	33.66	43.31	54.00	-10.69	Vertical
10480.00	21.66	39.82	14.68	32.86	43.30	54.00	-10.70	Horizontal
15720.00	20.89	38.09	17.73	33.66	43.05	54.00	-10.95	Horizontal

802.11ac(HT20) 5180MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.00	41.28	39.67	14.62	32.65	62.92	74.00	-11.08	Vertical
15540.00	40.49	38.60	17.66	34.46	62.29	74.00	-11.71	Vertical
10360.00	42.75	39.67	14.62	32.65	64.39	74.00	-9.61	Horizontal
15540.00	43.61	38.60	17.66	34.46	65.41	74.00	-8.59	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.00	21.36	39.67	14.62	32.65	43.00	54.00	-11.00	Vertical
15540.00	20.58	38.60	17.66	34.46	42.38	54.00	-11.62	Vertical
10360.00	21.29	39.67	14.62	32.65	42.93	54.00	-11.07	Horizontal
15540.00	22.18	38.60	17.66	34.46	43.98	54.00	-10.02	Horizontal

802.11ac(HT20) 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400.00	40.29	39.75	14.63	32.71	61.96	74.00	-12.04	Vertical
15600.00	41.96	38.33	17.67	34.17	63.79	74.00	-10.21	Vertical
10400.00	41.36	39.75	14.63	32.71	63.03	74.00	-10.97	Horizontal
15600.00	41.21	38.33	17.67	34.17	63.04	74.00	-10.96	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400.00	20.59	39.75	14.63	32.71	42.26	54.00	-11.74	Vertical
15600.00	20.46	38.33	17.67	34.17	42.29	54.00	-11.71	Vertical
10400.00	20.73	39.75	14.63	32.71	42.40	54.00	-11.60	Horizontal
15600.00	21.27	38.33	17.67	34.17	43.10	54.00	-10.90	Horizontal

802.11ac(HT20) 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480.00	42.35	39.82	14.68	32.86	63.99	74.00	-10.01	Vertical
15720.00	41.76	38.09	17.73	33.66	63.92	74.00	-10.08	Vertical
10480.00	40.58	39.82	14.68	32.86	62.22	74.00	-11.78	Horizontal
15720.00	41.35	38.09	17.73	33.66	63.51	74.00	-10.49	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480.00	20.36	39.82	14.68	32.86	42.00	54.00	-12.00	Vertical
15720.00	21.85	38.09	17.73	33.66	44.01	54.00	-9.99	Vertical
10480.00	20.23	39.82	14.68	32.86	41.87	54.00	-12.13	Horizontal
15720.00	21.96	38.09	17.73	33.66	44.12	54.00	-9.88	Horizontal

802.11n(HT40) 5190MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10380.00	41.65	39.71	14.63	32.68	63.31	74.00	-10.69	Vertical
15570.00	41.26	38.46	17.67	34.32	63.07	74.00	-10.93	Vertical
10380.00	40.93	39.71	14.63	32.68	62.59	74.00	-11.41	Horizontal
15570.00	40.72	38.46	17.67	34.32	62.53	74.00	-11.47	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10380.00	20.53	39.71	14.63	32.68	42.19	54.00	-11.81	Vertical
15570.00	20.78	38.46	17.67	34.32	42.59	54.00	-11.41	Vertical
10380.00	20.22	39.71	14.63	32.68	41.88	54.00	-12.12	Horizontal
15570.00	21.36	38.46	17.67	34.32	43.17	54.00	-10.83	Horizontal

802.11n(HT40) 5230MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10460.00	40.12	39.75	14.65	32.74	61.78	74.00	-12.22	Vertical
15690.00	41.31	38.33	17.69	34.03	63.30	74.00	-10.70	Vertical
10460.00	41.29	39.75	14.65	32.74	62.95	74.00	-11.05	Horizontal
15690.00	42.88	38.33	17.69	34.03	64.87	74.00	-9.13	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10460.00	20.41	39.75	14.65	32.74	42.07	54.00	-11.93	Vertical
15690.00	20.36	38.33	17.69	34.03	42.35	54.00	-11.65	Vertical
10460.00	20.48	39.75	14.65	32.74	42.14	54.00	-11.86	Horizontal
15690.00	21.96	38.33	17.69	34.03	43.95	54.00	-10.05	Horizontal

802.11acHT40) 5190MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10380.00	40.69	39.71	14.63	32.68	62.35	74.00	-11.65	Vertical
15570.00	41.46	38.46	17.67	34.32	63.27	74.00	-10.73	Vertical
10380.00	41.78	39.71	14.63	32.68	63.44	74.00	-10.56	Horizontal
15570.00	42.23	38.46	17.67	34.32	64.04	74.00	-9.96	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10380.00	20.12	39.71	14.63	32.68	41.78	54.00	-12.22	Vertical
15570.00	20.99	38.46	17.67	34.32	42.80	54.00	-11.20	Vertical
10380.00	20.72	39.71	14.63	32.68	42.38	54.00	-11.62	Horizontal
15570.00	21.63	38.46	17.67	34.32	43.44	54.00	-10.56	Horizontal

802.11ac(HT40) 5230MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10460.00	40.28	39.75	14.65	32.74	61.94	74.00	-12.06	Vertical
15690.00	40.94	38.33	17.69	34.03	62.93	74.00	-11.07	Vertical
10460.00	41.83	39.75	14.65	32.74	63.49	74.00	-10.51	Horizontal
15690.00	41.72	38.33	17.69	34.03	63.71	74.00	-10.29	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10460.00	20.66	39.75	14.65	32.74	42.32	54.00	-11.68	Vertical
15690.00	20.75	38.33	17.69	34.03	42.74	54.00	-11.26	Vertical
10460.00	20.21	39.75	14.65	32.74	41.87	54.00	-12.13	Horizontal
15690.00	21.38	38.33	17.69	34.03	43.37	54.00	-10.63	Horizontal

802.11ac(HT80) 5210MHz


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10420.00	40.28	39.82	14.66	32.80	61.96	74.00	-12.04	Vertical
15630.00	41.93	38.09	17.71	33.81	63.92	74.00	-10.08	Vertical
10420.00	40.85	39.82	14.66	32.80	62.53	74.00	-11.47	Horizontal
15630.00	41.79	38.09	17.71	33.81	63.78	74.00	-10.22	Horizontal

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10420.00	20.72	39.82	14.66	32.80	42.40	54.00	-11.60	Vertical
15630.00	20.10	38.09	17.71	33.81	42.09	54.00	-11.91	Vertical
10420.00	20.34	39.82	14.66	32.80	42.02	54.00	-11.98	Horizontal
15630.00	21.58	38.09	17.71	33.81	43.57	54.00	-10.43	Horizontal

Notes:

1. Level = Read Level + Antenna Factor+ Cable loss- Preamp Factor.
2. The test trace is same as the ambient noise (the test frequency range: 18GHz~40GHz), therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

7.8 Frequency stability

Test Requirement:	FCC Part15 C Section 15.407(g)
Test Method:	ANSI C63.10:2013, FCC Part 2.1055
Limit:	Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Test Procedure:	The EUT was setup to ANSI C63.4, 2003; tested to 2.1055 for compliance to FCC Part 15.407(g) requirements.
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remark: Set the EUT transmits at un-modulation mode to test frequency stability.



Measurement data:

Frequency stability versus Temp.					
Power Supply: DC 3.7V					
Temp. (°C)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
-30	5180	5180.0045	5180.0045	5180.0045	5180.0045
	5200	5200.0045	5200.0045	5200.0045	5200.0045
	5220	5220.0045	5220.0045	5220.0045	5220.0045
	5240	5240.0045	5240.0045	5240.0045	5240.0045
-20	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
-10	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0035	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
0	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
10	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
20	5180	5180.0015	5180.0015	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
30	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
40	5180	5180.0025	5180.0025	5180.0025	5180.0025
	5200	5200.0025	5200.0025	5200.0025	5200.0025
	5220	5220.0025	5220.0025	5220.0025	5220.0025
	5240	5240.0025	5240.0025	5240.0025	5240.0025
50	5180	5180.0025	5180.0025	5180.0025	5180.0025
	5200	5200.0025	5200.0025	5200.0025	5200.0025
	5220	5220.0025	5220.0025	5220.0025	5220.0025
	5240	5240.0025	5240.0025	5240.0025	5240.0025

Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VDC)	Operating Frequency (MHz)	0 minute	2 minute	5 minute	10 minute
		Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)
3.3	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
3.7	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000
4.2	5180	5180.0000	5180.0000	5180.0000	5180.0000
	5200	5200.0000	5200.0000	5200.0000	5200.0000
	5220	5220.0000	5220.0000	5220.0000	5220.0000
	5240	5240.0000	5240.0000	5240.0000	5240.0000

8 Test Setup Photo





9 EUT Constructional Details

Reference to test report GTS201909000200-1.

---END---