

FCC

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Mobile Phone

ISSUED TO
Realme Chongqing Mobile Telecommunications Corp., Ltd.

No.2 Building, No.24 Nchang Boulevard, Huixing Block, Yubei District,
Chongqing, China



Tested by:

Heng Aiping
(Engineer)

Date

Dec. 24, 2019

Approved by:

Wei Yanquan
(Chief Engineer)

Date

Dec. 24, 2019

Report No.: BL-SZ19A0595-601

EUT Name: Mobile Phone

Model Name: RMX1971

Brand Name: realme

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: 2AUYFRMX1971

Test conclusion: Pass

Test Date: Nov. 01, 2019 ~ Nov. 13, 2019

Date of Issue: Dec. 24, 2019

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Dec. 06, 2019</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Dec. 24, 2019</u>	<u>Corrected limit on page 32</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	6
1.1	Identification of the Testing Laboratory	6
1.2	Identification of the Responsible Testing Location	6
1.3	Laboratory Condition	6
1.4	Announce	6
2	PRODUCT INFORMATION	7
2.1	Applicant Information	7
2.2	Manufacturer Information	7
2.3	Factory Information	7
2.4	General Description for Equipment under Test (EUT)	7
2.5	Technical Information	8
2.6	Additional Instructions	10
3	SUMMARY OF TEST RESULTS	11
3.1	Test Standards	11
3.2	Verdict	11
4	GENERAL TEST CONFIGURATIONS	12
4.1	Test Environments	12
4.2	Test Equipment List	12
4.3	Measurement Uncertainty	13
4.4	Description of Test Setup	14
4.4.1	For Antenna Port Test	14
4.4.2	For AC Power Supply Port Test	14
4.4.3	For Radiated Test (Below 30 MHz)	15
4.4.4	For Radiated Test (30 MHz-1 GHz)	15
4.4.5	For Radiated Test (Above 1 GHz)	16
4.5	Measurement Results Explanation Example	17

4.5.1	For conducted test items:	17
5	TEST ITEMS.....	18
5.1	Antenna Requirements.....	18
5.1.1	Relevant Standards.....	18
5.1.2	Antenna Anti-Replacement Construction	18
5.1.3	Antenna Gain	18
5.2	Frequency Hopping Systems	19
5.2.1	Relevant Standards.....	19
5.2.2	Description of the systems	19
5.3	Number of Hopping Frequencies	20
5.3.1	Limit.....	20
5.3.2	Test Setup	20
5.3.3	Test Procedure	20
5.3.4	Test Result	20
5.4	Peak Output Power and E.I.R.P.....	21
5.4.1	Test Limit.....	21
5.4.2	Test Setup	21
5.4.3	Test Procedure	21
5.4.4	Test Result	21
5.5	Occupied Bandwidth	22
5.5.1	Limit.....	22
5.5.2	Test Setup	22
5.5.3	Test Procedure	22
5.5.4	Test Result	22
5.6	Carrier Frequency Separation	23
5.6.1	Limit.....	23
5.6.2	Test Setup	23
5.6.3	Test Procedure	23
5.6.4	Test Result	23
5.7	Time of Occupancy (Dwell time)	24
5.7.1	Limit.....	24
5.7.2	Test Setup	24
5.7.3	Test Procedure	24

5.7.4	Test Result	25
5.8	Conducted Spurious Emission & Authorized-band band-edge	26
5.8.1	Limit.....	26
5.8.2	Test Setup	26
5.8.3	Test Procedure	26
5.8.4	Test Result	26
5.9	Conducted Emission	27
5.9.1	Limit.....	27
5.9.2	Test Setup	27
5.9.3	Test Procedure	27
5.9.4	Test Result	27
5.10	Radiated Spurious Emission	28
5.10.1	Limit.....	28
5.10.2	Test Setup	28
5.10.3	Test Procedure	28
5.10.4	Test Result	29
5.11	Band Edge (Restricted-band band-edge).....	30
5.11.1	Limit.....	30
5.11.2	Test Setup	30
5.11.3	Test Procedure	30
5.11.4	Test Result	30
ANNEX A	TEST RESULT	31
A.1	Number of Hopping Frequency	31
A.2	Peak Output Power	32
A.3	20 dB and 99% bandwidth	35
A.4	Hopping Frequency Separation.....	40
A.5	Average Time of Occupancy	41
A.6	Conducted Spurious Emissions & Authorized-band band-edge	44
A.7	Conducted Emissions.....	51
A.8	Radiated Spurious Emission	53
A.9	Band Edge (Restricted-band band-edge).....	71
ANNEX B	TEST SETUP PHOTOS	74
ANNEX C	EUT EXTERNAL PHOTOS.....	74

ANNEX D	EUT INTERNAL PHOTOS	74
---------	---------------------------	----

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v5.7.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address	No.2 Building, No.24 Nichang Boulevard, Huixing Block, Yubei District, Chongqing, China

2.2 Manufacturer Information

Manufacturer	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address	No.2 Building, No.24 Nichang Boulevard, Huixing Block, Yubei District, Chongqing, China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	RMX1971
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	11
Software Version	ColorOS V6.0
Dimensions (Approx.)	157.0 mm × 74.2 mm × 8.9 mm
Weight (Approx.)	184 g(with battery)

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/900/1800/1900 MHz 3G Network WCDMA/HSDPA/HSUPA/HSPA+ Band 1/5/8 4G Network FDD LTE Band 1/3/5/7/8/20/28 TDD LTE Band 38/40/41 LTE CA Downlink (DL): 1C/ 3C/ 38C/ 40C/ 41C Bluetooth 5.0 (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(HT20/40) and 802.11ac(VHT20/ 40/ 80) GPS, GLONASS, BDS, FM
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	PIFA Antenna
Antenna Gain	-3 dBi (In test items related to antenna gain, the final results reflect this figure.)
Antenna Impedance	50 Ω
Antenna System(MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	2402	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	78	2480
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	39	2441	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

2.6 Additional Instructions

EUT Software Settings:

Mode	☒ Bluetooth test mode loop back enabled. EUT is controlled over CBT / CMW.
------	---

Power level setup in software			
Test Software Version	N/A		
Mode	Channel	Frequency (MHz)	Soft Set
DH5	CH0	2402	TX LEVEL is built-in set parameters and cannot be changed and selected.
	CH39	2441	
	CH78	2480	
2DH5	CH0	2402	
	CH39	2441	
	CH78	2480	
3DH5	CH0	2402	
	CH39	2441	
	CH78	2480	

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-17 Edition)	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	--	Pass	Note ¹
2	Number of Hopping Frequencies	15.247(a)	Hopping Mode	ANNEX A.1	Pass	Note ²
3	Peak Output Power	15.247(b)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.3	Pass	Note ²
5	Carrier Frequency Separation	15.247(a)	Hopping Mode	ANNEX A.4	Pass	Note ²
6	Time of Occupancy (Dwell time)	15.247(a)	Hopping Mode	ANNEX A.5	Pass	Note ²
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Low/Middle/High	ANNEX A.6	Pass	Note ²
8	Conducted Emission	15.207	Low/Middle/High	ANNEX A.7	Pass	Note ²
9	Radiated Spurious Emission	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.8	Pass	Note ²
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.9	Pass	Note ²
11	Receiver Spurious Emissions	--	--	--	N/A	Note ³

Note ¹: Please refer to section 5.1

Note ²: $\Pi/4$ -DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in $\Pi/4$ -DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

Note ³: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.85 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2019.06.13	2020.06.12
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2019.06.13	2020.06.12
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2019.10.29	2020.10.28
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2019.06.13	2020.06.12
LISN	SCHWARZBECK	NSLK 8127	8127-687	2019.06.13	2020.06.12
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2019.06.13	2020.06.12
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2019.06.18	2020.06.17
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2019.06.13	2020.06.12
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	2019.01.09	2020.01.08
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	2019.01.09	2020.01.08
Temperature Chamber	AHK	SP20	1412	2019.06.24	2020.06.23
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.11.09	2020.11.08
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2018.08.22	2020.08.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2018.07.11	2020.07.10
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2019.01.05	2021.01.04
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2020.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.07.19	2020.07.18
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2019.08.23	2020.08.22
Power Amplifier	OPHIR RF	5225F	1037	2019.02.28	2020.02.27
Power Amplifier	OPHIR RF	5273F	1016	2019.02.28	2020.02.27
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Sound Level Meter	B&K	NL-20	00844023	2018.11.15	2019.11.14
Ear Simulator	B&K	4185	2409449	2018.11.15	2019.11.14

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Ear Simulator	B&K	4195	2418189	2018.11.15	2019.11.14
Audio analyzer	B&K	UPL 16	100129	2018.11.15	2019.11.14
Software	BALUN	BL410	-	-	-
Cable	ROHDE&SCHWARZ	JUNFLON	APR0914004	2019.01.09	2020.01.08

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Occupied Channel Bandwidth	$\pm 4\%$
RF output power, conducted	± 1.4 dB
Power Spectral Density, conducted	± 2.5 dB
Unwanted Emissions, conducted	± 2.8 dB
All emissions, radiated	± 5.4 dB
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 4\%$


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).

Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.


Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.

For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.

Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.



3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-

random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.

4. The input bandwidth and transmitted bandwidth are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (d)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.3.4 Test Result

Please refer to ANNEX A.1.

5.4 Peak Output Power and E.I.R.P

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (b)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.2.

5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (a)

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Please refer to ANNEX A.3.

5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.6.4 Test Result

Please refer to ANNEX A.4.

5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a); RSS-247, 5.1 (d)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

Span: Zero span, centered on a hopping channel

RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel

Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel

Detector function: Peak

Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:

For GFSK and 8-DPSK:

For DH1 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH3 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH5 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For AFH Mode:

For DH1 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (800 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH3 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (800 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

{Period} = 0.4 s * {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.7.4 Test Result

Please refer to ANNEX A.5

5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.8.4 Test Result

Please refer to ANNEX A.6.

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: $54\text{dB}\mu\text{V/m}@3\text{m}$ (AV) and $74\text{dB}\mu\text{V/m}@3\text{m}$ (PK).

5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.8.

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test plots


GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power


Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK		dBm	mW	
	dBm	mW			
Low	11.92	15.56	21	125	Pass
Middle	11.38	13.74			Pass
High	11.40	13.80			Pass

Channel	Measured Output Peak Power				Limit		Verdict
	π/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW			
Low	11.56	14.32	11.70	14.79	21	125	Pass
Middle	10.82	12.08	11.12	12.94			Pass
High	11.02	12.65	11.21	13.21			Pass


Test plots

GFSK LOW CHANNEL




Date: 12.NOV.2019 15:58:26

GFSK MIDDLE CHANNEL




Date: 12.NOV.2019 16:05:38

GFSK HIGH CHANNEL




Date: 12.NOV.2019 16:08:01

II/4-DQPSK LOW CHANNEL




Date: 12.NOV.2019 16:11:11

II/4-DQPSK MIDDLE CHANNEL




Date: 12.NOV.2019 16:14:34

II/4-DQPSK HIGH CHANNEL



Date: 12 NOV 2019 16:16:10

8-DPSK LOW CHANNEL




Date: 12 NOV 2019 16:17:26

8-DPSK MIDDLE CHANNEL



Date: 12 NOV 2019 16:21:21

8-DPSK HIGH CHANNEL



Date: 12 NOV 2019 16:23:34

A.3 20 dB and 99% bandwidth


Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.956543	0.850941
Middle	0.956543	0.850941
High	0.956543	0.850941
π/4-DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.317383	1.180897
Middle	1.295654	1.176556
High	1.317383	1.185239
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.308594	1.189580
Middle	1.308594	1.185239
High	1.308594	1.193922

Test plots


20 dB Bandwidth

GFSK LOW CHANNEL




Date: 12 NOV 2019 15:58:41

GFSK MIDDLE CHANNEL




Date: 12 NOV 2019 16:05:53

GFSK HIGH CHANNEL




Date: 12 NOV 2019 16:08:16

II/4-DQPSK LOW CHANNEL




Date: 12 NOV 2019 16:11:26

II/4-DQPSK MIDDLE CHANNEL




Date: 12 NOV 2019 16:14:48

II/4-DQPSK HIGH CHANNEL




Date: 12 NOV 2019 16:16:25

8-DPSK LOW CHANNEL




Date: 12.NOV.2019 16:17:41

8-DPSK MIDDLE CHANNEL



Date: 12.NOV.2019 16:21:35

8-DPSK HIGH CHANNEL



Date: 12.NOV.2019 16:23:48

99% Bandwidth

GFSK LOW CHANNEL




Date: 12.NOV.2019 15:58:56

GFSK MIDDLE CHANNEL




Date: 12.NOV.2019 16:08:07


GFSK HIGH CHANNEL




II/4-DQPSK LOW CHANNEL




II/4-DQPSK MIDDLE CHANNEL



II/4-DQPSK HIGH CHANNEL




8-DPSK LOW CHANNEL




Date: 12 NOV 2019 16:17:55

8-DPSK MIDDLE CHANNEL



Date: 12 NOV 2019 16:21:50

8-DPSK HIGH CHANNEL



Date: 12 NOV 2019 16:24:03


A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	Max 2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.0033	0.637695	Pass
8-DPSK	1.0033	0.872396	Pass


Test Plots

GFSK



Date: 12.NOV.2019 16:29:40

8-DPSK



Date: 12.NOV.2019 16:34:51


A.5 Average Time of Occupancy

Test Data


GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38250	122.400	0.4	Pass
DH 3	1.64050	262.480	0.4	Pass
DH 5	2.89170	308.448	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38700	123.840	0.4	Pass
DH 3	1.63633	261.813	0.4	Pass
DH 5	2.89830	309.152	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38100	60.960	0.4	Pass
DH 3	1.63567	130.854	0.4	Pass
DH 5	2.87830	153.509	0.4	Pass

Test Plots


GFSK DH1



GFSK DH3




GFSK DH5




Date: 12.NOV.2019 16:42:29

8-DPSK DH1




Date: 12.NOV.2019 16:47:43

8-DPSK DH3




Date: 12.NOV.2019 16:48:10

8-DPSK DH5




Date: 12.NOV.2019 16:49:20


AFH Mode DH1



AFH Mode DH3



AFH Mode DH5




A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-26.80	11.82	-8.18	Pass
Middle	-27.23	11.26	-8.74	Pass
High	-27.19	11.22	-8.78	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-27.46	10.30	-9.70	Pass
Middle	-26.93	9.11	-10.89	Pass
High	-27.11	9.71	-10.29	Pass
Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-27.52	11.78	-8.22	Pass
8-DPSK	-26.90	9.73	-10.27	Pass


Test Plots

GFSK LOW CHANNEL, CARRIER LEVEL




Date: 12 NOV 2019 16:01:46

GFSK LOW CHANNEL, BAND EDGE




Date: 12 NOV 2019 16:04:07

GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 12 NOV 2019 16:02:09

GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




Date: 12 NOV 2019 16:02:42

GFSK MIDDLE CHANNEL, CARRIER LEVEL




Date: 12 NOV 2019 16:06:30

GFSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 12.NOV.2019 16:07:12

GFSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




Date: 12.NOV.2019 16:07:31

GFSK HIGH CHANNEL, CARRIER LEVEL




Date: 12.NOV.2019 16:08:44

GFSK HIGH CHANNEL , BAND EDGE




Date: 12.NOV.2019 16:10:21

GFSK HIGH CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 12.NOV.2019 16:09:14

GFSK HIGH CHANNEL , SPURIOUS 3 GHz ~ 25 GHz



Date: 12.NOV.2019 16:09:37

8-DPSK LOW CHANNEL, CARRIER LEVEL




Date: 12.NOV.2019 16:18:27

8-DPSK LOW CHANNEL, BAND EDGE




Date: 12.NOV.2019 16:20:44

8-DPSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 12.NOV.2019 16:19:54

8-DPSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




Date: 12.NOV.2019 16:20:13

8-DPSK MIDDLE CHANNEL, CARRIER LEVEL




Date: 12.NOV.2019 16:22:08

8-DPSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 12.NOV.2019 16:22:43

8-DPSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




Date: 12.NOV.2019 16:23:04

8-DPSK HIGH CHANNEL , CARRIER LEVEL




Date: 12.NOV.2019 16:26:07

8-DPSK HIGH CHANNEL , BAND EDGE




Date: 12.NOV.2019 16:27:42

8-DPSK HIGH CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 12.NOV.2019 16:26:43

8-DPSK HIGH CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




Date: 12.NOV.2019 16:26:58

GFSK HOPPING, CARRIER LEVEL




Date: 12 NOV 2019 16:30:58

GFSK HOPPING BAND EDGE (LOW)




Date: 12 NOV 2019 16:32:25

GFSK HOPPING BAND EDGE (HIGH)




Date: 12 NOV 2019 16:32:47

GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz




Date: 12 NOV 2019 16:31:31

GFSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz




Date: 12 NOV 2019 16:31:55


8-DPSK HOPPING, CARRIER LEVEL




8-DPSK Hopping BAND EDGE (LOW)




8-DPSK Hopping BAND EDGE (HIGH)



8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz



A.7 Conducted Emissions


Note¹: The EUT is working in the Normal link mode.

Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.160	48.30	10.40	65.46	-17.16	Peak	L	Pass
1**	0.160	38.31	10.40	55.46	-17.15	AV	L	Pass
2	0.232	50.25	10.36	62.38	-12.13	Peak	L	Pass
2**	0.232	39.33	10.36	52.38	-13.05	AV	L	Pass
3	0.264	49.33	10.34	61.30	-11.97	Peak	L	Pass
3**	0.264	39.65	10.34	51.30	-11.65	AV	L	Pass
4	0.592	45.66	10.28	56.00	-10.34	Peak	L	Pass
4**	0.592	34.27	10.28	46.00	-11.73	AV	L	Pass
5	1.390	44.35	10.25	56.00	-11.65	Peak	L	Pass
5**	1.390	31.97	10.25	46.00	-14.03	AV	L	Pass
6	10.932	45.24	10.37	60.00	-14.76	Peak	L	Pass
6**	10.932	35.72	10.37	50.00	-14.28	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.222	46.18	10.37	62.74	-16.56	Peak	N	Pass
1**	0.222	36.64	10.37	52.74	-16.10	AV	N	Pass
2	0.526	45.59	10.30	56.00	-10.41	Peak	N	Pass
2**	0.526	33.84	10.30	46.00	-12.16	AV	N	Pass
3	0.616	45.13	10.28	56.00	-10.87	Peak	N	Pass
3**	0.616	30.49	10.28	46.00	-15.51	AV	N	Pass
4	0.882	45.82	10.25	56.00	-10.18	Peak	N	Pass
4**	0.882	32.25	10.25	46.00	-13.75	AV	N	Pass
5	1.326	43.36	10.24	56.00	-12.64	Peak	N	Pass
5**	1.326	30.98	10.24	46.00	-15.02	AV	N	Pass
6	10.504	42.81	10.37	60.00	-17.19	Peak	N	Pass
6**	10.504	33.30	10.37	50.00	-16.70	AV	N	Pass

A.8 Radiated Spurious Emission

Test Data and Plots

Note¹: The symbol of "--" in the table which means not application.


Note²: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note³: The EUT is working in the Normal link mode below 1 GHz.

Note⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	42.465	30.96	-23.42	40.0	-9.04	Peak	316.60	100	Vertical	Pass
2	59.876	32.19	-23.97	40.0	-7.81	Peak	142.70	100	Vertical	Pass
3	82.815	32.54	-28.19	40.0	-7.46	Peak	213.00	108	Vertical	N/A
3*	82.815	29.40	-28.19	40.0	-10.60	QP	213.00	108	Vertical	Pass
4	161.387	29.68	-27.18	43.5	-13.82	Peak	0.90	100	Vertical	Pass
5	199.120	22.45	-24.14	43.5	-21.05	Peak	180.10	100	Vertical	Pass
6	599.972	31.02	-14.57	46.0	-14.98	Peak	2.00	100	Vertical	Pass

30 MHz to 1 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.672	24.83	-22.50	40.0	-15.17	Peak	1.00	100	Horizontal	Pass
2	84.174	27.91	-27.78	40.0	-12.09	Peak	185.10	200	Horizontal	Pass
3	158.525	30.69	-27.53	43.5	-12.81	Peak	231.20	200	Horizontal	Pass
4	201.544	24.05	-23.86	43.5	-19.45	Peak	74.50	100	Horizontal	Pass
5	366.590	24.03	-19.86	46.0	-21.97	Peak	360.00	100	Horizontal	Pass
6	599.972	30.86	-14.57	46.0	-15.14	Peak	8.90	200	Horizontal	Pass

Test Data and Plots (1 GHz ~ 10th Harmonic)

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.


GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1359.000	40.07	-17.18	74.0	-33.93	Peak	58.00	150	Vertical	Pass
1**	1359.000	24.04	-17.18	54.0	-29.96	AV	58.00	150	Vertical	Pass
2	2402.000	94.59	-11.82	74.0	20.59	Peak	131.00	150	Vertical	N/A
2**	2402.000	89.94	-11.82	54.0	35.94	AV	131.00	150	Vertical	N/A
3	4256.000	48.31	-4.88	74.0	-25.69	Peak	346.00	150	Vertical	Pass
3**	4256.000	32.96	-4.88	54.0	-21.04	AV	346.00	150	Vertical	Pass
4	6003.000	53.13	-0.95	74.0	-20.87	Peak	92.00	150	Vertical	Pass
4**	6003.000	36.07	-0.95	54.0	-17.93	AV	92.00	150	Vertical	Pass
5	10651.250	50.15	-0.17	74.0	-23.85	Peak	0.00	150	Vertical	Pass
5**	10651.250	38.95	-0.17	54.0	-15.05	AV	0.00	150	Vertical	Pass
6	16927.688	55.42	2.45	74.0	-18.58	Peak	169.00	150	Vertical	Pass
6**	16927.688	43.71	2.45	54.0	-10.29	AV	169.00	150	Vertical	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1425.000	40.69	-17.35	74.0	-33.31	Peak	107.00	150	Horizontal	Pass
1**	1425.000	23.40	-17.35	54.0	-30.60	AV	107.00	150	Horizontal	Pass
2	2402.000	107.58	-11.82	74.0	33.58	Peak	87.00	150	Horizontal	N/A
2**	2402.000	102.54	-11.82	54.0	48.54	AV	87.00	150	Horizontal	N/A
3	4904.000	50.43	-2.55	74.0	-23.57	Peak	326.00	150	Horizontal	Pass
3**	4904.000	33.98	-2.55	54.0	-20.02	AV	326.00	150	Horizontal	Pass
4	6998.000	54.20	0.91	74.0	-19.80	Peak	223.00	150	Horizontal	Pass
4**	6998.000	37.85	0.91	54.0	-16.15	AV	223.00	150	Horizontal	Pass
5	10204.188	50.73	0.77	74.0	-23.27	Peak	83.00	150	Horizontal	Pass
5**	10204.188	38.65	0.77	54.0	-15.35	AV	83.00	150	Horizontal	Pass
6	16199.250	54.49	2.72	74.0	-19.51	Peak	209.00	150	Horizontal	Pass
6**	16199.250	43.41	2.72	54.0	-10.59	AV	209.00	150	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1390.500	40.33	-17.22	74.0	-33.67	Peak	0.00	150	Vertical	Pass
1**	1390.500	24.46	-17.22	54.0	-29.54	AV	0.00	150	Vertical	Pass
2	2441.000	92.40	-12.60	74.0	18.40	Peak	114.00	150	Vertical	N/A
2**	2441.000	87.22	-12.60	54.0	33.22	AV	114.00	150	Vertical	N/A
3	4626.000	49.37	-3.93	74.0	-24.63	Peak	234.00	150	Vertical	Pass
3**	4626.000	33.98	-3.93	54.0	-20.02	AV	234.00	150	Vertical	Pass
4	6295.000	54.51	0.07	74.0	-19.49	Peak	72.00	150	Vertical	Pass
4**	6295.000	37.47	0.07	54.0	-16.53	AV	72.00	150	Vertical	Pass
5	10202.750	50.11	0.81	74.0	-23.89	Peak	135.00	150	Vertical	Pass
5**	10202.750	39.05	0.81	54.0	-14.95	AV	135.00	150	Vertical	Pass
6	15838.312	54.43	2.02	74.0	-19.57	Peak	353.00	150	Vertical	Pass
6**	15838.312	42.45	2.02	54.0	-11.55	AV	353.00	150	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1482.500	40.36	-17.29	74.0	-33.64	Peak	287.00	150	Horizontal	Pass
1**	1482.500	23.33	-17.29	54.0	-30.67	AV	287.00	150	Horizontal	Pass
2	2441.000	106.65	-12.60	74.0	32.65	Peak	80.00	150	Horizontal	N/A
2**	2441.000	101.41	-12.60	54.0	47.41	AV	80.00	150	Horizontal	N/A
3	4750.000	49.79	-3.56	74.0	-24.21	Peak	174.00	150	Horizontal	Pass
3**	4750.000	34.57	-3.56	54.0	-19.43	AV	174.00	150	Horizontal	Pass
4	6274.000	53.88	-0.05	74.0	-20.12	Peak	263.00	150	Horizontal	Pass
4**	6274.000	37.22	-0.05	54.0	-16.78	AV	263.00	150	Horizontal	Pass
5	10654.125	50.41	-0.14	74.0	-23.59	Peak	360.00	150	Horizontal	Pass
5**	10654.125	39.01	-0.14	54.0	-14.99	AV	360.00	150	Horizontal	Pass
6	17413.313	55.38	4.67	74.0	-18.62	Peak	269.00	150	Horizontal	Pass
6**	17413.313	44.61	4.67	54.0	-9.39	AV	269.00	150	Horizontal	Pass


GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1625.000	41.38	-17.15	74.0	-32.62	Peak	329.00	150	Vertical	Pass
1**	1625.000	24.11	-17.15	54.0	-29.89	AV	329.00	150	Vertical	Pass
2	2480.000	94.71	-11.99	74.0	20.71	Peak	114.00	150	Vertical	N/A
2**	2480.000	89.61	-11.99	54.0	35.61	AV	114.00	150	Vertical	N/A
3	5952.000	52.99	-1.23	74.0	-21.01	Peak	123.00	150	Vertical	Pass
3**	5952.000	36.55	-1.23	54.0	-17.45	AV	123.00	150	Vertical	Pass
4	9624.875	50.32	0.17	74.0	-23.68	Peak	168.00	150	Vertical	Pass
4**	9624.875	38.27	0.17	54.0	-15.73	AV	168.00	150	Vertical	Pass
5	12840.563	51.73	1.84	74.0	-22.27	Peak	325.00	150	Vertical	Pass
5**	12840.563	40.65	1.84	54.0	-13.35	AV	325.00	150	Vertical	Pass
6	17881.874	55.90	4.19	74.0	-18.10	Peak	246.00	150	Vertical	Pass
6**	17881.874	44.10	4.19	54.0	-9.90	AV	246.00	150	Vertical	Pass


GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1271.500	40.02	-17.27	74.0	-33.98	Peak	170.00	150	Horizontal	Pass
1**	1271.500	23.45	-17.27	54.0	-30.55	AV	170.00	150	Horizontal	Pass
2	2480.000	107.03	-11.99	74.0	33.03	Peak	81.00	150	Horizontal	N/A
2**	2480.000	102.02	-11.99	54.0	48.02	AV	81.00	150	Horizontal	N/A
3	5593.000	52.40	-2.21	74.0	-21.60	Peak	247.00	150	Horizontal	Pass
3**	5593.000	35.62	-2.21	54.0	-18.38	AV	247.00	150	Horizontal	Pass
4	8219.000	49.28	-1.51	74.0	-24.72	Peak	203.00	150	Horizontal	Pass
4**	8219.000	37.18	-1.51	54.0	-16.82	AV	203.00	150	Horizontal	Pass
5	11993.875	50.96	1.40	74.0	-23.04	Peak	101.00	150	Horizontal	Pass
5**	11993.875	39.22	1.40	54.0	-14.78	AV	101.00	150	Horizontal	Pass
6	17173.125	55.82	3.22	74.0	-18.18	Peak	362.00	150	Horizontal	Pass
6**	17173.125	44.00	3.22	54.0	-10.00	AV	362.00	150	Horizontal	Pass


8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1393.500	40.11	-17.11	74.0	-33.89	Peak	275.00	150	Horizontal	Pass
1**	1393.500	23.42	-17.11	54.0	-30.58	AV	275.00	150	Horizontal	Pass
2	2402.000	106.28	-11.82	74.0	32.28	Peak	82.00	150	Horizontal	N/A
2**	2402.000	100.86	-11.82	54.0	46.86	AV	82.00	150	Horizontal	N/A
3	5060.000	51.96	-2.72	74.0	-22.04	Peak	326.00	150	Horizontal	Pass
3**	5060.000	34.40	-2.72	54.0	-19.60	AV	326.00	150	Horizontal	Pass
4	6688.000	53.85	-0.00	74.0	-20.15	Peak	143.00	150	Horizontal	Pass
4**	6688.000	38.65	-0.00	54.0	-15.35	AV	143.00	150	Horizontal	Pass
5	10658.437	50.76	-0.14	74.0	-23.24	Peak	230.00	150	Horizontal	Pass
5**	10658.437	39.02	-0.14	54.0	-14.98	AV	230.00	150	Horizontal	Pass
6	17141.625	55.07	3.12	74.0	-18.93	Peak	243.00	150	Horizontal	Pass
6**	17141.625	43.79	3.12	54.0	-10.21	AV	243.00	150	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1484.500	40.16	-17.30	74.0	-33.84	Peak	59.00	150	Vertical	Pass
1**	1484.500	23.63	-17.30	54.0	-30.37	AV	59.00	150	Vertical	Pass
2	2441.000	90.73	-12.60	74.0	16.73	Peak	110.00	150	Vertical	N/A
2**	2441.000	85.04	-12.60	54.0	31.04	AV	110.00	150	Vertical	N/A
3	4651.000	49.86	-3.79	74.0	-24.14	Peak	85.00	150	Vertical	Pass
3**	4651.000	33.76	-3.79	54.0	-20.24	AV	85.00	150	Vertical	Pass
4	6716.000	53.21	-0.85	74.0	-20.79	Peak	36.00	150	Vertical	Pass
4**	6716.000	37.78	-0.85	54.0	-16.22	AV	36.00	150	Vertical	Pass
5	10253.062	50.44	1.20	74.0	-23.56	Peak	79.00	150	Vertical	Pass
5**	10253.062	39.07	1.20	54.0	-14.93	AV	79.00	150	Vertical	Pass
6	14977.313	54.33	1.85	74.0	-19.67	Peak	345.00	150	Vertical	Pass
6**	14977.313	42.42	1.85	54.0	-11.58	AV	345.00	150	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1295.500	39.68	-17.02	74.0	-34.32	Peak	247.00	150	Horizontal	Pass
1**	1295.500	23.26	-17.02	54.0	-30.74	AV	247.00	150	Horizontal	Pass
2	2441.000	104.95	-12.60	74.0	30.95	Peak	81.00	150	Horizontal	N/A
2**	2441.000	99.16	-12.60	54.0	45.16	AV	81.00	150	Horizontal	N/A
3	4071.000	47.51	-5.68	74.0	-26.49	Peak	255.00	150	Horizontal	Pass
3**	4071.000	31.47	-5.68	54.0	-22.53	AV	255.00	150	Horizontal	Pass
4	6176.000	52.57	-1.33	74.0	-21.43	Peak	294.00	150	Horizontal	Pass
4**	6176.000	37.37	-1.33	54.0	-16.63	AV	294.00	150	Horizontal	Pass
5	10859.688	50.29	0.61	74.0	-23.71	Peak	102.00	150	Horizontal	Pass
5**	10859.688	38.29	0.61	54.0	-15.71	AV	102.00	150	Horizontal	Pass
6	16208.437	55.15	2.50	74.0	-18.85	Peak	103.00	150	Horizontal	Pass
6**	16208.437	43.93	2.50	54.0	-10.07	AV	103.00	150	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1450.000	40.34	-17.05	74.0	-33.66	Peak	258.00	150	Vertical	Pass
1**	1450.000	23.65	-17.05	54.0	-30.35	AV	258.00	150	Vertical	Pass
2	2479.500	93.49	-11.99	74.0	19.49	Peak	113.00	150	Vertical	N/A
2**	2479.500	80.12	-11.99	54.0	26.12	AV	113.00	150	Vertical	N/A
3	4817.000	49.68	-3.26	74.0	-24.32	Peak	0.00	150	Vertical	Pass
3**	4817.000	34.78	-3.26	54.0	-19.22	AV	0.00	150	Vertical	Pass
4	6666.000	53.17	-0.03	74.0	-20.83	Peak	209.00	150	Vertical	Pass
4**	6666.000	37.93	-0.03	54.0	-16.07	AV	209.00	150	Vertical	Pass
5	11184.562	49.74	-0.27	74.0	-24.26	Peak	360.00	150	Vertical	Pass
5**	11184.562	38.49	-0.27	54.0	-15.51	AV	360.00	150	Vertical	Pass
6	16195.313	54.54	2.72	74.0	-19.46	Peak	28.00	150	Vertical	Pass
6**	16195.313	43.30	2.72	54.0	-10.70	AV	28.00	150	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1645.500	39.92	-17.08	74.0	-34.08	Peak	306.00	150	Horizontal	Pass
1**	1645.500	24.34	-17.08	54.0	-29.66	AV	306.00	150	Horizontal	Pass
2	2480.000	105.59	-11.99	74.0	31.59	Peak	87.00	150	Horizontal	N/A
2**	2480.000	100.31	-11.99	54.0	46.31	AV	87.00	150	Horizontal	N/A
3	4632.000	49.78	-3.83	74.0	-24.22	Peak	339.00	150	Horizontal	Pass
3**	4632.000	33.46	-3.83	54.0	-20.54	AV	339.00	150	Horizontal	Pass
4	6290.000	54.27	0.20	74.0	-19.73	Peak	0.00	150	Horizontal	Pass
4**	6290.000	37.18	0.20	54.0	-16.82	AV	0.00	150	Horizontal	Pass
5	11700.625	50.74	0.75	74.0	-23.26	Peak	112.00	150	Horizontal	Pass
5**	11700.625	39.32	0.75	54.0	-14.68	AV	112.00	150	Horizontal	Pass
6	17433.000	55.90	4.44	74.0	-18.10	Peak	303.00	150	Horizontal	Pass
6**	17433.000	44.55	4.44	54.0	-9.45	AV	303.00	150	Horizontal	Pass

Hopping Mode:


GFSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1769.500	41.45	-16.86	74.0	-32.55	Peak	64.00	150	Vertical	Pass
1**	1769.500	24.28	-16.86	54.0	-29.72	AV	64.00	150	Vertical	Pass
2	2403.000	91.73	-11.82	74.0	17.73	Peak	28.00	150	Vertical	N/A
2**	2403.000	86.39	-11.82	54.0	32.39	AV	28.00	150	Vertical	N/A
3	2477.500	93.05	-12.00	74.0	19.05	Peak	40.00	150	Vertical	N/A
3**	2477.500	92.35	-12.00	54.0	38.35	AV	40.00	150	Vertical	N/A
4	6289.000	53.22	0.30	74.0	-20.78	Peak	55.00	150	Vertical	Pass
4**	6289.000	37.45	0.30	54.0	-16.55	AV	55.00	150	Vertical	Pass
5	11342.687	51.24	0.49	74.0	-22.76	Peak	360.00	150	Vertical	Pass
5**	11342.687	38.23	0.49	54.0	-15.77	AV	360.00	150	Vertical	Pass
6	17524.875	55.21	3.32	74.0	-18.79	Peak	268.00	150	Vertical	Pass
6**	17524.875	44.11	3.32	54.0	-9.89	AV	268.00	150	Vertical	Pass

GFSK MODE 1 GHz to 18 GHz, ANT H


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1536.000	40.37	-17.35	74.0	-33.63	Peak	17.00	150	Horizontal	Pass
1**	1536.000	23.55	-17.35	54.0	-30.45	AV	17.00	150	Horizontal	Pass
2	2402.500	96.57	-11.82	74.0	22.57	Peak	52.00	150	Horizontal	N/A
2**	2402.500	96.47	-11.82	54.0	42.47	AV	52.00	150	Horizontal	N/A
3	2478.000	100.05	-11.96	74.0	26.05	Peak	28.00	150	Horizontal	N/A
3**	2478.000	94.81	-11.96	54.0	40.81	AV	28.00	150	Horizontal	N/A
4	6275.000	53.16	-0.09	74.0	-20.84	Peak	153.00	150	Horizontal	Pass
4**	6275.000	36.86	-0.09	54.0	-17.14	AV	153.00	150	Horizontal	Pass
5	10767.688	50.43	-0.14	74.0	-23.57	Peak	51.00	150	Horizontal	Pass
5**	10767.688	38.43	-0.14	54.0	-15.57	AV	51.00	150	Horizontal	Pass
6	17170.500	55.95	3.22	74.0	-18.05	Peak	41.00	150	Horizontal	Pass
6**	17170.500	43.71	3.22	54.0	-10.29	AV	41.00	150	Horizontal	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT V


RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1294.500	40.29	-16.97	74.0	-33.71	Peak	41.00	150	Vertical	Pass
1**	1294.500	24.30	-16.97	54.0	-29.70	AV	41.00	150	Vertical	Pass
2	2402.500	88.40	-11.82	74.0	14.40	Peak	323.00	150	Vertical	N/A
2**	2402.500	78.73	-11.82	54.0	24.73	AV	323.00	150	Vertical	N/A
3	2477.000	93.06	-12.04	74.0	19.06	Peak	108.00	150	Vertical	N/A
3**	2477.000	88.43	-12.04	54.0	34.43	AV	108.00	150	Vertical	N/A
4	5957.000	53.14	-0.94	74.0	-20.86	Peak	79.00	150	Vertical	Pass
4**	5957.000	36.24	-0.94	54.0	-17.76	AV	79.00	150	Vertical	Pass
5	8868.750	49.98	-0.36	74.0	-24.02	Peak	320.00	150	Vertical	Pass
5**	8868.750	38.33	-0.36	54.0	-15.67	AV	320.00	150	Vertical	Pass
6	16322.625	54.60	1.74	74.0	-19.40	Peak	240.00	150	Vertical	Pass
6**	16322.625	42.98	1.74	54.0	-11.02	AV	240.00	150	Vertical	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT H

RE Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1326.000	39.75	-17.09	74.0	-34.25	Peak	47.00	150	Horizontal	Pass
1**	1326.000	23.62	-17.09	54.0	-30.38	AV	47.00	150	Horizontal	Pass
2	2402.000	100.11	-11.82	74.0	26.11	Peak	62.00	150	Horizontal	N/A
2**	2402.000	95.06	-11.82	54.0	41.06	AV	62.00	150	Horizontal	N/A
3	2480.000	105.57	-11.99	74.0	31.57	Peak	75.00	150	Horizontal	N/A
3**	2480.000	100.28	-11.99	54.0	46.28	AV	75.00	150	Horizontal	N/A
4	6619.000	54.51	0.48	74.0	-19.49	Peak	360.00	150	Horizontal	Pass
4**	6619.000	37.51	0.48	54.0	-16.49	AV	360.00	150	Horizontal	Pass
5	11069.563	50.39	-0.65	74.0	-23.61	Peak	128.00	150	Horizontal	Pass
5**	11069.563	39.21	-0.65	54.0	-14.79	AV	128.00	150	Horizontal	Pass
6	15287.063	54.66	1.72	74.0	-19.34	Peak	261.00	150	Horizontal	Pass
6**	15287.063	42.17	1.72	54.0	-11.83	AV	261.00	150	Horizontal	Pass

A.9 Band Edge (Restricted-band band-edge)

Note¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


Note³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note⁴: The Level (dBuV/m) has been corrected by factor.


Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	2390.00	53.304	32.61	74	20.696	PEAK	Pass
		2390.00	N/A	N/A	54	N/A	AVERAGE	Pass
GFSK	HIGH	2483.50	57.964	32.54	74	16.036	PEAK	Pass
		2483.50	44.512	32.54	54	9.488	AVERAGE	Pass
8-DPSK	Low	2390.00	53.469	32.61	74	20.531	PEAK	Pass
		2390.00	N/A	N/A	54	N/A	AVERAGE	Pass
8-DPSK	HIGH	2483.50	56.903	32.54	74	17.097	PEAK	Pass
		2483.50	45.161	32.54	54	8.839	AVERAGE	Pass
GFSK(Hopping)	Low	2390.00	53.656	32.61	74	20.344	PEAK	Pass
		2390.00	N/A	N/A	54	N/A	AVERAGE	Pass
GFSK(Hopping)	HIGH	2483.50	53.709	32.54	74	20.291	PEAK	Pass
		2483.50	N/A	N/A	54	N/A	AVERAGE	Pass
8-DPSK (Hopping)	Low	2390.00	53.370	32.61	74	20.630	PEAK	Pass
		2390.00	N/A	N/A	54	N/A	AVERAGE	Pass
8-DPSK (Hopping)	HIGH	2483.50	53.148	32.54	74	20.852	PEAK	Pass
		2483.50	N/A	N/A	54	N/A	AVERAGE	Pass

Test Plots


GFSK LOW CHANNEL , PEAK




GFSK HIGH CHANNEL , PEAK




GFSK HIGH CHANNEL , AV




8-DPSK LOW CHANNEL , PEAK



8-DPSK HIGH CHANNEL , PEAK




8-DPSK HIGH CHANNEL , AV




Hopping Mode:


GFSK LOW FREQUENCY BAND, PEAK




GFSK HIGH FREQUENCY BAND, PEAK



8-DPSK LOW FREQUENCY BAND, PEAK



8-DPSK HIGH FREQUENCY BAND, PEAK



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ19A0595-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ19A0595-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ19A0595-AI.PDF”.

--END OF REPORT--