

TEST REPORT

Application No.: SZCR2410003954WM
Applicant: Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address of Applicant: No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Manufacturer: Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address of Manufacturer: No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Equipment Under Test (EUT):
EUT Description: Mobile Phone
Model No.: RMX5051
Trade Mark: realme
FCC ID: 2AUYFRMX5051
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2024-10-25
Date of Test: 2024-11-06 to 2024-11-22
Date of Issue: 2024-12-03

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (EMC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 2 of 498

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2024-12-03		Original

Authorized for issue by:				
		Sherlock Fang		
		Sherlock Fang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass
Transmission in the Absence of Data		N/A	47 CFR Part 15, Subpart E 15.407 (c)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Maximum Conducted output power		KDB 789033 D02 II E	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Radiated Emissions (Below 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Channel Move Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
Duty Cycle		KDB 789033 D02 II B 1	KDB 789033 D02 II B 1	Pass
99% Bandwidth		KDB 789033 D02 II D	N/A	Pass
26dB Emission bandwidth		KDB 789033 D02 II C 1	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band)		KDB 789033 D02 II C 2	47 CFR Part 15, Subpart E 15.407 (e)	Pass
Peak Power spectrum density		KDB 789033 D02 II F	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Frequency Stability		ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart E 15.407 (g)	Pass
Non-occupancy period		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
Channel Closing Transmission Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information.....	7
4.1 Details of E.U.T.	7
4.2 Environment Parameter	8
4.3 Description of Support Units	9
4.4 Measurement Uncertainty	9
4.5 Test Location.....	10
4.6 Test Facility	10
4.7 Deviation from Standards.....	10
4.8 Abnormalities from Standard Conditions	10
5 Equipment List	11
6 Radio Spectrum Technical Requirement	14
6.1 Antenna Requirement	14
6.1.1 Test Requirement:	14
6.1.2 Conclusion	14
6.2 Transmission in the Absence of Data	15
6.2.1 Test Requirement:	15
6.2.2 Conclusion	15
7 Radio Spectrum Matter Test Results	16
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	16
7.1.1 E.U.T. Operation	16
7.1.2 Test Mode Description	16
7.1.3 Test Setup Diagram.....	17
7.1.4 Measurement Procedure and Data.....	17
7.2 Maximum Conducted output power	20
7.2.1 E.U.T. Operation	20
7.2.2 Test Mode Description	20
7.2.3 Test Setup Diagram.....	21
7.2.4 Measurement Procedure and Data.....	21
7.3 Radiated Emissions (Below 1GHz).....	22
7.3.1 E.U.T. Operation	22
7.3.2 Test Mode Description	22
7.3.3 Test Setup Diagram.....	23
7.3.4 Measurement Procedure and Data.....	24
7.4 Radiated Emissions (Above 1GHz).....	27
7.4.1 E.U.T. Operation	27
7.4.2 Test Mode Description	28



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 5 of 498

7.4.3	Test Setup Diagram.....	28
7.4.4	Measurement Procedure and Data.....	29
7.5	Radiated Emissions which fall in the restricted bands.....	78
7.5.1	E.U.T. Operation.....	78
7.5.2	Test Mode Description.....	79
7.5.3	Test Setup Diagram.....	79
7.5.4	Measurement Procedure and Data.....	80
7.6	Channel Move Time.....	255
7.6.1	E.U.T. Operation.....	255
7.6.2	Test Setup Diagram.....	256
7.6.3	Measurement Procedure and Data.....	257
7.7	Duty Cycle.....	258
7.7.1	E.U.T. Operation.....	258
7.7.2	Test Mode Description.....	258
7.7.3	Test Setup Diagram.....	258
7.7.4	Measurement Procedure and Data.....	258
7.8	99% Bandwidth.....	259
7.8.1	E.U.T. Operation.....	259
7.8.2	Test Mode Description.....	259
7.8.3	Test Setup Diagram.....	259
7.8.4	Measurement Procedure and Data.....	259
7.9	26dB Emission bandwidth.....	260
7.9.1	E.U.T. Operation.....	260
7.9.2	Test Mode Description.....	260
7.9.3	Test Setup Diagram.....	260
7.9.4	Measurement Procedure and Data.....	260
7.10	Minimum 6 dB bandwidth (5.725-5.85 GHz band).....	261
7.10.1	E.U.T. Operation.....	261
7.10.2	Test Mode Description.....	261
7.10.3	Test Setup Diagram.....	261
7.10.4	Measurement Procedure and Data.....	261
7.11	Peak Power spectrum density.....	262
7.11.1	E.U.T. Operation.....	262
7.11.2	Test Mode Description.....	262
7.11.3	Test Setup Diagram.....	263
7.11.4	Measurement Procedure and Data.....	263
7.12	Frequency Stability.....	264
7.12.1	Measurement Procedure and Data.....	264
7.13	Non-occupancy period.....	265
7.13.1	E.U.T. Operation.....	265
7.13.2	Test Setup Diagram.....	266
7.13.3	Measurement Procedure and Data.....	267
7.14	Channel Closing Transmission Time.....	268
7.14.1	E.U.T. Operation.....	268
7.14.2	Test Setup Diagram.....	269
7.14.3	Measurement Procedure and Data.....	270
8	Test Setup Photo.....	271
9	EUT Constructional Details (EUT Photos).....	271



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center (CCC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 6 of 498

10	Appendix.....	272
----	---------------	-----



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

EUT Description:	Mobile Phone	
Model No.:	RMX5051	
Trade Mark:	realme	
Hardware Version:	11	
Software Version:	realme UI 6.0	
Power Supply:	DC 3.92V from internal rechargeable battery which can be charged by AC/DC adapter	
WLAN Mode Supported:	802.11a:	20 MHz channel bandwidth
	802.11n:	20 MHz / 40 MHz channel bandwidth
	802.11ac:	20 MHz / 40 MHz / 80 MHz channel bandwidth
	802.11ax:	20 MHz / 40 MHz / 80 MHz channel bandwidth
Operation Frequency:	5150MHz to 5250MHz	
	5250MHz to 5350MHz	
	5470MHz to 5725MHz	
	5725MHz to 5850MHz	
Modulation Type:	802.11a:	OFDM (BPSK, QPSK, 16QAM, 64QAM)
	802.11n:	OFDM (BPSK, QPSK, 16QAM, 64QAM)
	802.11ac:	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
	802.11ax:	OFDM/OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Channel Spacing:	20MHz:	802.11a/n(HT20)/ac(VHT20)/ax(HE20)
	40MHz:	802.11n(HT40)/ac(VHT40)/ax(HE40)
	80MHz:	802.11ac(VHT80)/ax(HE80)
Antenna Type:	PIFA Antenna	
Antenna Gain:	5150MHz to 5250MHz: -2.9(Ant12); 5250MHz to 5350MHz: -3.1(Ant12); 5470MHz to 5725MHz: -3.3(Ant12); 5725MHz to 5850MHz: -3.2(Ant12);	
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.	
Smart System:	☒ SISO	802.11a/n/ac/ax
	☐ MIMO	802.11a/n/ac/ax: Tx & Rx
	☐ Diversity	CDD: 802.11a: Tx & Rx



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 8 of 498

TPC Function:	☐ Support, ☒ Not Support		
DFS Function:	☐ Master		
	☐ Slave with radar detection	☒ Slave without radar detection	
RF Cable:	4900MHz ~ 5250MHz(1.6dB)		5250MHz ~ 5350MHz(1.7dB)
	5470MHz ~ 5725MHz(1.8dB)		5725MHz ~ 5850MHz (2dB)
Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.			

4.2 Environment Parameter

Environment Parameter	1020 mbar Selected Values During Tests	
Relative Humidity	36.7-50.8 % RH Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	22.5~24.5	3.92
Note: NV:Normal Voltage LV:Low Extreme Test Voltage HV:High Extreme Test Voltage NT:Normal Temperature LT:Low Extreme Test Temperature HT:High Extreme Test Temperature		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 9 of 498

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Router	NETGEAR	R7800	SZ-WRG-A-072

4.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.1\text{dB}$
Maximum Conducted output power	$\pm 0.75\text{dB}$
Radiated Emissions (Below 1GHz)	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Emissions (Above 1GHz)	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (below 1GHz); $\pm 4.6\text{dB}$ (above 1GHz);
Duty Cycle	$\pm 0.37\%$
99% Bandwidth	$\pm 3\%$
26dB Emission bandwidth	$\pm 3\%$
Minimum 6 dB bandwidth (5.725-5.85 GHz band)	$\pm 3\%$
Peak Power spectrum density	$\pm 2.84\text{dB}$
Frequency Stability	$\pm 7.25 \times 10^{-8}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 10 of 498

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2022-05-14	2025-05-13
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2024-01-30	2025-01-29
Matching Pad	N/A	N/A	SEM021-23	2024-03-20	2025-03-19
Matching Pad	N/A	N/A	SEM021-24	2024-03-20	2025-03-19
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2024-07-06	2025-07-05
LISN	Rohde&Schwarz	ENV216	SEM007-01	2024-08-15	2025-08-14
LISN	ETS-LINDGREN	3816/2	SEM007-02	2024-03-14	2025-03-13

Maximum Conducted output power					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2024-03-27	2025-03-26
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2024-03-14	2025-03-13
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2024-08-14	2025-08-13
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2024-03-14	2025-03-13
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2024-09-14	2025-09-13
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2024-07-06	2025-07-05
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2024-03-27	2025-03-26
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2024-03-19	2025-03-18

Radiated Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2024-08-14	2025-08-13
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2023-09-16	2025-09-15
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2024-03-14	2025-03-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2024-07-06	2025-07-05



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 12 of 498

Radiated Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2024-01-30	2025-01-29
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2024-01-30	2025-01-29
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2024-01-30	2025-01-29
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120D	SZ-WRG-M-055	2023-12-21	2025-12-20
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2023-12-25	2025-12-24
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2022-01-05	2025-01-04
Humidity and Temperature Indicator	deli	8838	SEM002-46	2024-07-24	2025-07-23

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2024-01-30	2025-01-29
Low Noise Amplifier 30M-8GHz	Tonscend	TAP30M8G30	SZ-WRG-M-050	2024-01-30	2025-01-29
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120D	SZ-WRG-M-055	2023-12-21	2025-12-20
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2023-12-25	2025-12-24
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2022-01-05	2025-01-04
Humidity and Temperature Indicator	deli	8838	SEM002-46	2024-07-24	2025-07-23



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 13 of 498

DFS					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Manual Step Attenuator	KEYSIGHT	8494B	SEM021-05	2024-03-27	2025-03-26
Manual Step Attenuator	KEYSIGHT	8496B	SEM021-06	2024-03-27	2025-03-26
Measurement Software	KEYSIGHT	Signal Studio for DFS Radar Profiles V2.2.0.0	N/A	N/A	N/A
Measurement Software	Agilent	ISMonitor10	N/A	N/A	N/A
MXG Vector Signal Generator	Agilent	N5182A	SEM006-21	2024-03-27	2025-03-26
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-22	2024-03-14	2025-03-13
Router	NETGEAR	R7800	SZ-WRG-A-072	NCR	NCR

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2024-08-14	2025-08-13
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2024-03-14	2025-03-13
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2024-09-14	2025-09-13
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2024-07-06	2025-07-05
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2024-03-27	2025-03-26
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2024-03-19	2025-03-18

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2024-07-24	2025-07-23
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2024-07-24	2025-07-23
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2024-03-18	2025-03-17



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is an PIFA Antenna, and the connection port is fixed with glue, and the antenna cannot be replaced.

The best case gain of the antenna is

5150MHz to 5250MHz: -2.9(Ant12); *

5250MHz to 5350MHz: -3.1(Ant12); *

5470MHz to 5725MHz: -3.3(Ant12); *

5725MHz to 5850MHz: -3.2(Ant12); *

**Note:*

The antenna gain are derived from the gain information report provided by the manufacturer.

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.



6.2 Transmission in the Absence of Data

6.2.1 Test Requirement:

47 CFR Part 15, Subpart E 15.407 (c)

6.2.2 Conclusion

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

WIFI chip support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C

Humidity: 44.3 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 18 of 498

Test Mode: 14; Line: Live line



Site : Shielding Room
Condition: Line
Job No. : 03954WM
Test mode: 14

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1508	0.06	9.81	39.73	49.60	65.96	-16.36	QP
2	0.1508	0.06	9.81	14.36	24.23	55.96	-31.73	Average
3	0.3183	0.07	9.75	30.84	40.66	59.75	-19.09	QP
4	0.3183	0.07	9.75	11.05	20.87	49.75	-28.88	Average
5	0.9839	0.09	9.71	24.06	33.86	56.00	-22.14	QP
6	0.9839	0.09	9.71	17.71	27.51	46.00	-18.49	Average
7	1.6537	0.10	9.67	24.61	34.38	56.00	-21.62	QP
8	1.6537	0.10	9.67	19.69	29.46	46.00	-16.54	Average
9	2.1439	0.10	9.66	24.48	34.24	56.00	-21.76	QP
10 *	2.1439	0.10	9.66	19.75	29.51	46.00	-16.49	Average
11	13.5509	0.24	10.07	22.30	32.61	60.00	-27.39	QP
12	13.5509	0.24	10.07	16.64	26.95	50.00	-23.05	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 19 of 498

Test Mode: 14; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 03954WM
Test mode: 14

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1516	0.06	9.82	39.67	49.55	65.91	-16.36	QP
2	0.1516	0.06	9.82	14.73	24.61	55.91	-31.30	Average
3	0.3149	0.07	9.78	28.08	37.93	59.84	-21.91	QP
4	0.3149	0.07	9.78	6.49	16.34	49.84	-33.50	Average
5	0.9331	0.09	9.73	23.31	33.13	56.00	-22.87	QP
6	0.9331	0.09	9.73	17.09	26.91	46.00	-19.09	Average
7	1.7529	0.10	9.70	24.54	34.34	56.00	-21.66	QP
8 *	1.7529	0.10	9.70	19.78	29.58	46.00	-16.42	Average
9	2.0990	0.10	9.69	24.65	34.44	56.00	-21.56	QP
10	2.0990	0.10	9.69	19.74	29.53	46.00	-16.47	Average
11	13.9146	0.25	10.14	22.85	33.24	60.00	-26.76	QP
12	13.9146	0.25	10.14	16.99	27.38	50.00	-22.62	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II E

Limit:

Frequency band(MHz)	Limit
5150-5250	≤1W(30dBm) for master device
	≤250mW(24dBm) for client device
5250-5350	≤250mW(24dBm) or 11dBm+10logB*
5470-5725	≤250mW(24dBm) or 11dBm+10logB*
5725-5850	≤1W(30dBm)
Remark:	* Where B is the 26dB emission bandwidth in MHz. The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.2 °C

Humidity: 36.7 % RH


Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.



7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 22 of 498

7.3 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 45.5 % RH

Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3.3 Test Setup Diagram



Below 30MHz

30MHz-1GHz



7.3.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
3. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Test Mode: 14; Polarity: Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : 03954WM
Test Mode: 14


	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	33.799	19.52	0.72	27.78	27.44	19.90	40.00	-20.10 QP
2	85.898	11.15	1.13	27.63	30.91	15.56	40.00	-24.44 QP
3	155.364	13.55	1.56	27.36	33.29	21.04	43.50	-22.46 QP
4	223.733	15.58	1.88	27.07	30.44	20.83	46.00	-25.17 QP
5	303.544	18.30	2.22	26.76	33.46	27.22	46.00	-18.78 QP
6 q	607.787	24.61	3.27	27.95	27.88	27.81	46.00	-18.19 QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 14; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 03954WM
Test Mode: 14

	Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	40.988	15.91	0.79	27.76	32.47	21.41	40.00	-18.59 QP
2 q	47.160	13.59	0.84	27.74	35.48	22.17	40.00	-17.83 QP
3	84.702	10.98	1.12	27.63	36.85	21.32	40.00	-18.68 QP
4	182.559	14.17	1.69	27.24	34.38	23.00	43.50	-20.50 QP
5	277.094	17.00	2.11	26.85	31.46	23.72	46.00	-22.28 QP
6	554.825	23.65	3.10	27.79	26.52	25.48	46.00	-20.52 QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.4 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1GHz	500	3
*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C

Humidity: 50.8 % RH


Atmospheric Pressure: 1020 mbar



7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
6. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
7. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



11a_TX_CH_36_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5180 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6902.598	11.37	36.19	56.72	56.22	47.06	68.20	-21.14 peak
2	8393.547	11.64	38.61	55.55	52.82	47.52	74.00	-26.48 peak
3	9284.084	12.19	38.45	54.74	52.43	48.33	68.20	-19.87 peak
4	10360.000	13.60	39.00	53.88	49.10	47.82	68.20	-20.38 peak
5	15540.000	17.00	38.56	54.14	46.78	48.20	74.00	-25.80 peak
6	pp16608.340	17.64	39.22	54.18	47.97	50.65	68.20	-17.55 peak



11a_TX_CH_36_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5180 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6902.598	11.37	36.19	56.72	59.08	49.92	68.20 -18.28 peak
2	8385.002	11.65	38.63	55.55	53.28	48.01	74.00 -25.99 peak
3	8850.100	12.23	38.50	55.13	52.44	48.04	68.20 -20.16 peak
4	10360.000	13.60	39.00	53.88	49.70	48.42	68.20 -19.78 peak
5	15540.000	17.00	38.56	54.14	47.04	48.46	74.00 -25.54 peak
6	pp16574.540	17.67	39.12	54.17	48.47	51.09	68.20 -17.11 peak



11a_TX_CH_44_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5220 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6959.073	11.37	36.12	56.71	57.56	48.34	68.20 -19.86 peak
2	8453.606	11.99	38.39	55.49	52.39	47.28	74.00 -26.72 peak
3	8592.505	11.99	38.47	55.37	52.97	48.06	68.20 -20.14 peak
4	10440.000	13.63	39.04	53.84	49.00	47.83	68.20 -20.37 peak
5	15660.000	17.23	38.56	54.10	47.95	49.64	74.00 -24.36 peak
6	pp16693.140	17.59	39.39	54.21	47.72	50.49	68.20 -17.71 peak



11a_TX_CH_44_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5220 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6959.073	11.37	36.12	56.71	59.41	50.19	68.20	-18.01 peak
2	8427.813	11.82	38.49	55.51	52.11	46.91	74.00	-27.09 peak
3	9096.867	12.12	38.60	54.91	52.35	48.16	74.00	-25.84 peak
4	10440.000	13.63	39.04	53.84	48.85	47.68	68.20	-20.52 peak
5	15660.000	17.23	38.56	54.10	47.80	49.49	74.00	-24.51 peak
6	pp16881.220	18.04	39.60	54.26	47.10	50.48	68.20	-17.72 peak



11a_TX_CH_48_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5240 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6888.550	11.37	36.15	56.72	53.55	44.35	68.20 -23.85 peak
2	8453.606	11.99	38.39	55.49	51.67	46.56	74.00 -27.44 peak
3	8841.090	12.24	38.50	55.14	51.39	46.99	68.20 -21.21 peak
4	10480.000	13.64	39.08	53.81	47.72	46.63	68.20 -21.57 peak
5	15720.000	17.22	38.58	54.08	45.95	47.67	74.00 -26.33 peak
6	pp17002.020	18.08	39.70	54.30	45.72	49.20	68.20 -19.00 peak



11a_TX_CH_48_Veritical



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5180 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6902.598	11.37	36.19	56.72	56.77	47.61	68.20 -20.59 peak
2	8453.606	11.99	38.39	55.49	52.43	47.32	74.00 -26.68 peak
3	8913.427	12.21	38.57	55.08	52.61	48.31	68.20 -19.89 peak
4	10360.000	13.60	39.00	53.88	49.89	48.61	68.20 -19.59 peak
5	15540.000	17.00	38.56	54.14	47.31	48.73	74.00 -25.27 peak
6	pp16915.650	18.16	39.62	54.27	47.09	50.60	68.20 -17.60 peak



11ax_20M_TX_CH_36_Horizontal



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5180 TX RSE

: 5GWIFI 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 6902.598	11.37	36.19	56.72	58.42	49.26	68.20	-18.94	peak
2	8266.280	11.70	37.83	55.66	53.51	47.38	74.00	-26.62	peak
3	8680.473	12.06	38.52	55.29	52.84	48.13	68.20	-20.07	peak
4	10360.000	13.60	39.00	53.88	48.95	47.67	68.20	-20.53	peak
5	15540.000	17.00	38.56	54.14	47.86	49.28	74.00	-24.72	peak
6	16092.110	17.08	38.51	54.03	48.94	50.50	74.00	-23.50	peak



11ax_20M_TX_CH_36_Vertical



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5220 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6959.073	11.37	36.12	56.71	57.86	48.64	68.20 -19.56 peak
2	8488.119	12.23	38.32	55.46	52.73	47.82	74.00 -26.18 peak
3	8751.494	12.17	38.50	55.22	52.53	47.98	68.20 -20.22 peak
4	10440.000	13.63	39.04	53.84	49.87	48.70	68.20 -19.50 peak
5	15660.000	17.23	38.56	54.10	47.61	49.30	74.00 -24.70 peak
6	pp16898.430	18.17	39.60	54.27	47.05	50.55	68.20 -17.65 peak



11ax_20M_TX_CH_44_Horizontal



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5220 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6959.073	11.37	36.12	56.71	59.30	50.08	68.20 -18.12 peak
2	8359.419	11.68	38.68	55.58	52.66	47.44	74.00 -26.56 peak
3	8505.428	12.29	38.30	55.45	52.92	48.06	68.20 -20.14 peak
4	10440.000	13.63	39.04	53.84	49.82	48.65	68.20 -19.55 peak
5	15660.000	17.23	38.56	54.10	47.98	49.67	74.00 -24.33 peak
6	pp16373.180	17.18	38.75	54.11	48.61	50.43	68.20 -17.77 peak



11ax_20M_TX_CH_44_Vertical



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5240 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7420.276	11.45	36.74	56.36	53.96	45.79	74.00 -28.21 peak
2	8496.769	12.29	38.31	55.45	51.43	46.58	74.00 -27.42 peak
3	9436.627	12.40	38.80	54.61	50.94	47.53	74.00 -26.47 peak
4	10480.000	13.64	39.08	53.81	47.85	46.76	68.20 -21.44 peak
5	15720.000	17.22	38.58	54.08	46.19	47.91	74.00 -26.09 peak
6	pp16557.660	17.69	39.07	54.17	47.46	50.05	68.20 -18.15 peak



11ax_20M_TX_CH_48_Horizontal



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5240 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7292.895	11.51	36.69	56.47	53.39	45.12	74.00 -28.88 peak
2	8367.938	11.67	38.66	55.57	51.71	46.47	74.00 -27.53 peak
3	8913.427	12.21	38.57	55.08	51.62	47.32	68.20 -20.88 peak
4	10480.000	13.64	39.08	53.81	48.27	47.18	68.20 -21.02 peak
5	15720.000	17.22	38.58	54.08	46.22	47.94	74.00 -26.06 peak
6	pp16864.040	17.92	39.60	54.26	46.83	50.09	68.20 -18.11 peak



11ax_20M_TX_CH_48_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5240 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7315.214	11.51	36.73	56.45	53.13	44.92	74.00	-29.08 peak
2	8190.848	11.56	37.98	55.73	52.42	46.23	74.00	-27.77 peak
3	8904.353	12.22	38.59	55.09	51.76	47.48	68.20	-20.72 peak
4	10480.000	13.64	39.08	53.81	47.16	46.07	68.20	-22.13 peak
5	15720.000	17.22	38.58	54.08	45.89	47.61	74.00	-26.39 peak
6	pp16608.340	17.64	39.22	54.18	47.44	50.12	68.20	-18.08 peak



11a_TX_CH_52_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5260 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7016.012	11.47	36.23	56.69	58.63	49.64	68.20	-18.56 peak
2	8496.769	12.29	38.31	55.45	52.20	47.35	74.00	-26.65 peak
3	9699.749	12.70	38.70	54.37	50.72	47.75	68.20	-20.45 peak
4	10520.000	13.63	39.14	53.79	48.62	47.60	68.20	-20.60 peak
5	15780.000	17.08	38.52	54.07	46.57	48.10	74.00	-25.90 peak
6	pp16744.220	17.53	39.49	54.22	47.97	50.77	68.20	-17.43 peak



11a_TX_CH_52_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5260 TX RSE

: 5GWIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 7016.012	11.47	36.23	56.69	60.37	51.38	68.20	-16.82 peak
2	8496.769	12.29	38.31	55.45	52.28	47.43	74.00	-26.57 peak
3	8913.427	12.21	38.57	55.08	52.47	48.17	68.20	-20.03 peak
4	10520.000	13.63	39.14	53.79	49.42	48.40	68.20	-19.80 peak
5	15780.000	17.08	38.52	54.07	47.15	48.68	74.00	-25.32 peak
6	16557.660	17.69	39.07	54.17	47.80	50.39	68.20	-17.81 peak



11a_TX_CH_60_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5300 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7109.531	11.95	36.42	56.61	54.48	46.24	68.20 -21.96 peak
2	8496.769	12.29	38.31	55.45	52.31	47.46	74.00 -26.54 peak
3	9504.150	12.55	38.89	54.55	51.03	47.92	68.20 -20.28 peak
4	10600.000	13.59	39.30	53.74	49.35	48.50	68.20 -19.70 peak
5	15900.000	17.28	38.70	54.03	47.31	49.26	74.00 -24.74 peak
6	pp16625.260	17.63	39.25	54.19	47.95	50.64	68.20 -17.56 peak



11a_TX_CH_60_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5300 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7285.470	11.51	36.67	56.47	53.73	45.44	74.00	-28.56 peak
2	8479.478	12.17	38.34	55.47	51.96	47.00	74.00	-27.00 peak
3	9939.788	12.88	38.90	54.15	50.31	47.94	68.20	-20.26 peak
4	10600.000	13.59	39.30	53.74	48.69	47.84	68.20	-20.36 peak
5	15900.000	17.28	38.70	54.03	47.51	49.46	74.00	-24.54 peak
6	pp16898.430	18.17	39.60	54.27	46.93	50.43	68.20	-17.77 peak



11a_TX_CH_64_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM

Mode : 5320 TX RSE

: 5GWIFI 11A


	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7095.063	11.96	36.39	56.62	54.64	46.37	68.20 -21.83 peak
2	8453.606	11.99	38.39	55.49	52.11	47.00	74.00 -27.00 peak
3	9303.017	12.17	38.80	54.73	50.70	46.94	74.00 -27.06 peak
4	10640.000	13.77	39.34	53.72	47.16	46.55	74.00 -27.45 peak
5	15960.000	17.20	38.64	54.01	46.55	48.38	74.00 -25.62 peak
6	pp16456.780	17.49	38.86	54.14	47.54	49.75	68.20 -18.45 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

11a_TX_CH_64_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5320 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7095.063	11.96	36.39	56.62	53.33	45.06	68.20 -23.14 peak
2	8009.345	11.55	37.80	55.89	52.49	45.95	68.20 -22.25 peak
3	9446.244	12.42	38.80	54.60	51.23	47.85	74.00 -26.15 peak
4	10640.000	13.77	39.34	53.72	47.29	46.68	74.00 -27.32 peak
5	15960.000	17.20	38.64	54.01	46.51	48.34	74.00 -25.66 peak
6	pp16795.470	17.47	39.59	54.24	46.23	49.05	68.20 -19.15 peak



11ax_20M_TX_CH_52_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5260 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6959.073	11.37	36.12	56.71	54.38	45.16	68.20 -23.04 peak
2	8488.119	12.23	38.32	55.46	51.17	46.26	74.00 -27.74 peak
3	8850.100	12.23	38.50	55.13	52.17	47.77	68.20 -20.43 peak
4	10520.000	13.63	39.14	53.79	48.33	47.31	68.20 -20.89 peak
5	15780.000	17.08	38.52	54.07	45.25	46.78	74.00 -27.22 peak
6	pp16591.430	17.66	39.17	54.18	48.97	51.62	68.20 -16.58 peak



11ax_20M_TX_CH_52_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5260 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6959.073	11.37	36.12	56.71	54.48	45.26	68.20	-22.94 peak
2	8436.402	11.88	38.45	55.51	51.30	46.12	74.00	-27.88 peak
3	9960.058	12.93	38.90	54.14	49.98	47.67	68.20	-20.53 peak
4	10520.000	13.63	39.14	53.79	48.45	47.43	68.20	-20.77 peak
5	15780.000	17.08	38.52	54.07	46.46	47.99	74.00	-26.01 peak
6	pp16761.290	17.51	39.52	54.23	46.76	49.56	68.20	-18.64 peak



11ax_20M_TX_CH_60_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5300 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6959.073	11.37	36.12	56.71	54.41	45.19	68.20 -23.01 peak
2	8436.402	11.88	38.45	55.51	51.91	46.73	74.00 -27.27 peak
3	9970.208	12.95	38.90	54.13	50.00	47.72	68.20 -20.48 peak
4	10600.000	13.59	39.30	53.74	48.05	47.20	68.20 -21.00 peak
5	15900.000	17.28	38.70	54.03	45.98	47.93	74.00 -26.07 peak
6	pp16507.140	17.73	38.92	54.15	47.13	49.63	68.20 -18.57 peak



11ax_20M_TX_CH_60_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5300 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7263.242	11.51	36.63	56.49	53.32	44.97	74.00 -29.03 peak
2	8385.002	11.65	38.63	55.55	51.92	46.65	74.00 -27.35 peak
3	9970.208	12.95	38.90	54.13	50.09	47.81	68.20 -20.39 peak
4	10600.000	13.59	39.30	53.74	48.63	47.78	68.20 -20.42 peak
5	15900.000	17.28	38.70	54.03	46.76	48.71	74.00 -25.29 peak
6	pp16881.220	18.04	39.60	54.26	46.70	50.08	68.20 -18.12 peak



11ax_20M_TX_CH_64_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5320 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6959.073	11.37	36.12	56.71	54.64	45.42	68.20 -22.78 peak
2	8342.406	11.70	38.58	55.59	51.89	46.58	74.00 -27.42 peak
3	8886.231	12.22	38.57	55.10	51.30	46.99	68.20 -21.21 peak
4	10640.000	13.77	39.34	53.72	47.63	47.02	74.00 -26.98 peak
5	15960.000	17.20	38.64	54.01	46.89	48.72	74.00 -25.28 peak
6	pp16846.870	17.80	39.60	54.25	46.70	49.85	68.20 -18.35 peak



11ax_20M_TX_CH_64_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5320 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6895.570	11.37	36.18	56.72	54.26	45.09	68.20 -23.11 peak
2	8342.406	11.70	38.58	55.59	51.75	46.44	74.00 -27.56 peak
3	8769.341	12.20	38.50	55.21	52.81	48.30	68.20 -19.90 peak
4	10640.000	13.77	39.34	53.72	47.64	47.03	74.00 -26.97 peak
5	15960.000	17.20	38.64	54.01	48.13	49.96	74.00 -24.04 peak
6	pp16881.220	18.04	39.60	54.26	46.77	50.15	68.20 -18.05 peak



11a_TX_CH_100_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5500 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6951.989	11.37	36.10	56.71	54.63	45.39	68.20 -22.81 peak
2	8488.119	12.23	38.32	55.46	52.27	47.36	74.00 -26.64 peak
3	8742.585	12.16	38.51	55.23	52.93	48.37	68.20 -19.83 peak
4	10437.830	13.63	39.04	53.84	49.86	48.69	68.20 -19.51 peak
5	11000.000	14.17	39.40	53.50	48.21	48.28	74.00 -25.72 peak
6	pp16500.000	17.74	38.90	54.15	47.10	49.59	68.20 -18.61 peak



11a_TX_CH_100_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5500 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7138.557	11.81	36.48	56.59	53.52	45.22	68.20	-22.98 peak
2	8325.429	11.73	38.31	55.61	53.24	47.67	74.00	-26.33 peak
3	9096.867	12.12	38.60	54.91	51.92	47.73	74.00	-26.27 peak
4	9970.208	12.95	38.90	54.13	51.86	49.58	68.20	-18.62 peak
5	11000.000	14.17	39.40	53.50	48.34	48.41	74.00	-25.59 peak
6	pp16500.000	17.74	38.90	54.15	47.61	50.10	68.20	-18.10 peak



11a_TX_CH_116_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5580 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7337.601	11.51	36.78	56.43	53.22	45.08	74.00 -28.92 peak
2	8174.179	11.54	37.95	55.74	52.31	46.06	74.00 -27.94 peak
3	8868.147	12.23	38.54	55.12	52.28	47.93	68.20 -20.27 peak
4	10405.990	13.62	39.01	53.86	49.15	47.92	68.20 -20.28 peak
5	11160.000	14.72	39.56	53.55	47.78	48.51	74.00 -25.49 peak
6	pp16740.000	17.54	39.48	54.22	45.15	47.95	68.20 -20.25 peak



11a_TX_CH_116_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5580 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7315.214	11.51	36.73	56.45	52.65	44.44	74.00 -29.56 peak
2	8376.465	11.66	38.65	55.56	51.28	46.03	74.00 -27.97 peak
3	8886.231	12.22	38.57	55.10	52.00	47.69	68.20 -20.51 peak
4	10384.810	13.61	39.00	53.87	48.87	47.61	68.20 -20.59 peak
5	11160.000	14.72	39.56	53.55	47.86	48.59	74.00 -25.41 peak
6	pp16740.000	17.54	39.48	54.22	45.17	47.97	68.20 -20.23 peak



11a_TX_CH_140_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5700 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7315.214	11.51	36.73	56.45	53.36	45.15	74.00 -28.85 peak
2	8249.458	11.66	37.80	55.68	52.76	46.54	74.00 -27.46 peak
3	9446.244	12.42	38.80	54.60	50.22	46.84	74.00 -27.16 peak
4	10437.830	13.63	39.04	53.84	48.62	47.45	68.20 -20.75 peak
5	11400.000	14.21	39.70	53.62	46.32	46.61	74.00 -27.39 peak
6	pp17100.000	18.47	39.80	54.32	43.93	47.88	68.20 -20.32 peak



11a_TX_CH_140_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5700 TX RSE

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6888.550	11.37	36.15	56.72	53.78	44.58	68.20 -23.62 peak
2	8445.000	11.94	38.42	55.50	51.51	46.37	74.00 -27.63 peak
3	8904.353	12.22	38.59	55.09	51.25	46.97	68.20 -21.23 peak
4	10374.240	13.61	39.00	53.88	48.82	47.55	68.20 -20.65 peak
5	11400.000	14.21	39.70	53.62	46.94	47.23	74.00 -26.77 peak
6	pp17100.000	18.47	39.80	54.32	44.44	48.39	68.20 -19.81 peak



11ax_20M_TX_CH_100_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5500 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	6777.197	11.38	35.81	56.74	55.06	45.51	68.20 -22.69 peak
2	8249.458	11.66	37.80	55.68	54.83	48.61	74.00 -25.39 peak
3	8832.090	12.24	38.50	55.15	52.37	47.96	68.20 -20.24 peak
4	10010.910	13.04	38.92	54.09	50.82	48.69	68.20 -19.51 peak
5	11000.000	14.17	39.40	53.50	50.19	50.26	74.00 -23.74 peak
6	pp16500.000	17.74	38.90	54.15	47.31	49.80	68.20 -18.40 peak



11ax_20M_TX_CH_100_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5500 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7051.834	11.69	36.30	56.66	54.74	46.07	68.20 -22.13 peak
2	8427.813	11.82	38.49	55.51	52.83	47.63	74.00 -26.37 peak
3	8922.510	12.20	38.55	55.07	52.67	48.35	68.20 -19.85 peak
4	9970.208	12.95	38.90	54.13	51.43	49.15	68.20 -19.05 peak
5	11000.000	14.17	39.40	53.50	49.00	49.07	74.00 -24.93 peak
6	pp16500.000	17.74	38.90	54.15	47.23	49.72	68.20 -18.48 peak



11ax_20M_100_TX_CH_116_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5580 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7131.289	11.84	36.46	56.59	53.21	44.92	68.20 -23.28 peak
2	8445.000	11.94	38.42	55.50	51.69	46.55	74.00 -27.45 peak
3	8913.427	12.21	38.57	55.08	51.54	47.24	68.20 -20.96 peak
4	pp10021.110	13.06	38.94	54.09	50.29	48.20	68.20 -20.00 peak
5	11160.000	14.72	39.56	53.55	47.54	48.27	74.00 -25.73 peak
6	16740.000	17.54	39.48	54.22	44.83	47.63	68.20 -20.57 peak



11ax_20M_100_TX_CH_116_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5580 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7427.838	11.42	36.76	56.36	53.25	45.07	74.00 -28.93 peak
2	8091.342	11.46	37.80	55.82	52.87	46.31	74.00 -27.69 peak
3	9303.017	12.17	38.80	54.73	50.74	46.98	74.00 -27.02 peak
4	10021.110	13.06	38.94	54.09	49.62	47.53	68.20 -20.67 peak
5	11160.000	14.72	39.56	53.55	47.04	47.77	74.00 -26.23 peak
6	pp16740.000	17.54	39.48	54.22	45.09	47.89	68.20 -20.31 peak



11ax_20M_100_TX_CH_140_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5700 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6930.778	11.37	36.14	56.71	54.77	45.57	68.20	-22.63 peak
2	8325.429	11.73	38.31	55.61	52.03	46.46	74.00	-27.54 peak
3	8742.585	12.16	38.51	55.23	51.99	47.43	68.20	-20.77 peak
4	10041.550	13.12	38.98	54.08	49.57	47.59	68.20	-20.61 peak
5	11400.000	14.21	39.70	53.62	47.84	48.13	74.00	-25.87 peak
6	pp17100.000	18.47	39.80	54.32	44.99	48.94	68.20	-19.26 peak



11ax_20M_100_TX_CH_140_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5700 TX RSE

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7270.644	11.51	36.64	56.48	53.66	45.33	74.00 -28.67 peak
2	8488.119	12.23	38.32	55.46	51.91	47.00	74.00 -27.00 peak
3	8707.038	12.10	38.59	55.26	52.41	47.84	68.20 -20.36 peak
4	10416.590	13.62	39.02	53.85	49.10	47.89	68.20 -20.31 peak
5	11400.000	14.21	39.70	53.62	47.29	47.58	74.00 -26.42 peak
6	pp17170.000	18.47	39.80	54.32	44.61	48.56	68.20 -19.64 peak



11a_TX_CH_149_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5745 TX RSE

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7488.611	11.26	36.80	56.31	53.96	45.71	74.00	-28.29	peak
2	7658.314	11.30	36.90	56.17	56.08	48.11	74.00	-25.89	peak
3	9949.918	12.90	38.90	54.15	51.13	48.78	68.20	-19.42	peak
4	11005.580	14.20	39.41	53.50	48.96	49.07	74.00	-24.93	peak
5	11490.000	14.97	39.61	53.65	49.60	50.53	74.00	-23.47	peak
6	pp17235.000	17.83	40.01	54.35	45.94	49.43	68.20	-18.77	peak



11a_TX_CH_149_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5745 TX RSE

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7480.987	11.28	36.80	56.32	55.93	47.69	74.00	-26.31	peak
2	8488.119	12.23	38.32	55.46	52.76	47.85	74.00	-26.15	peak
3	8742.585	12.16	38.51	55.23	52.75	48.19	68.20	-20.01	peak
4	10960.830	14.09	39.36	53.52	49.69	49.62	74.00	-24.38	peak
5	11490.000	14.97	39.61	53.65	47.72	48.65	74.00	-25.35	peak
6	pp17235.000	17.83	40.01	54.35	45.68	49.17	68.20	-19.03	peak



11a_TX_CH_157_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5785 TX RSE

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7352.564	11.50	36.79	56.42	53.54	45.41	74.00	-28.59	peak
2	7713.113	11.43	36.93	56.13	55.54	47.77	74.00	-26.23	peak
3	8832.090	12.24	38.50	55.15	52.69	48.28	68.20	-19.92	peak
4	10620.150	13.68	39.32	53.73	49.98	49.25	74.00	-24.75	peak
5	11570.000	14.78	39.60	53.67	48.89	49.60	74.00	-24.40	peak
6	pp17355.000	18.00	40.31	54.37	45.94	49.88	68.20	-18.32	peak



11a_TX_CH_157_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5785 TX RSE

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7496.243	11.24	36.80	56.30	56.41	48.15	74.00	-25.85	peak
2	8496.769	12.29	38.31	55.45	52.11	47.26	74.00	-26.74	peak
3	10000.720	13.01	38.90	54.10	49.92	47.73	68.20	-20.47	peak
4	11005.580	14.20	39.41	53.50	48.92	49.03	74.00	-24.97	peak
5	11570.000	14.78	39.60	53.67	48.03	48.74	74.00	-25.26	peak
6	pp17355.000	18.00	40.31	54.37	46.01	49.95	68.20	-18.25	peak



11a_TX_CH_165_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5825 TX RSE

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7255.848	11.51	36.61	56.50	53.63	45.25	74.00	-28.75	peak
2	8488.119	12.23	38.32	55.46	51.66	46.75	74.00	-27.25	peak
3	9949.918	12.90	38.90	54.15	49.27	46.92	68.20	-21.28	peak
4	10395.390	13.62	39.00	53.86	49.26	48.02	68.20	-20.18	peak
5	11650.000	14.69	39.55	53.69	46.95	47.50	74.00	-26.50	peak
6	pp17475.000	18.35	40.78	54.40	45.27	50.00	68.20	-18.20	peak



11a_TX_CH_165_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5825 TX RSE

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7278.053	11.51	36.66	56.48	52.81	44.50	74.00	-29.50	peak
2	8496.769	12.29	38.31	55.45	51.26	46.41	74.00	-27.59	peak
3	9769.155	12.97	38.60	54.31	49.68	46.94	68.20	-21.26	peak
4	10783.650	13.74	39.32	53.63	49.17	48.60	74.00	-25.40	peak
5	11650.000	14.69	39.55	53.69	47.22	47.77	74.00	-26.23	peak
6	pp17475.000	18.35	40.78	54.40	45.13	49.86	68.20	-18.34	peak



11ax_20M_TX_CH_149_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5745 TX RSE

: 5.8GWIFI 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7337.601	11.51	36.78	56.43	54.21	46.07	74.00	-27.93	peak
2	7658.314	11.30	36.90	56.17	56.68	48.71	74.00	-25.29	peak
3	9630.836	12.51	38.74	54.43	51.25	48.07	68.20	-20.13	peak
4	pp10598.530	13.59	39.30	53.74	50.12	49.27	68.20	-18.93	peak
5	11490.000	14.97	39.61	53.65	47.99	48.92	74.00	-25.08	peak
6	17235.000	17.83	40.01	54.35	45.49	48.98	68.20	-19.22	peak



11ax_20M_TX_CH_149_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5745 TX RSE

: 5.8GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7167.700	11.67	36.54	56.57	54.35	45.99	68.20 -22.21 peak
2	7658.314	11.30	36.90	56.17	56.43	48.46	74.00 -25.54 peak
3	8707.038	12.10	38.59	55.26	52.66	48.09	68.20 -20.11 peak
4	10620.150	13.68	39.32	53.73	50.12	49.39	74.00 -24.61 peak
5	11490.000	14.97	39.61	53.65	48.09	49.02	74.00 -24.98 peak
6	pp17235.000	17.83	40.01	54.35	46.88	50.37	68.20 -17.83 peak



11ax_20M_TX_CH_157_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM

Mode : 5785 TX RSE

: 5.8GWIFI 11AX20


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7167.700	11.67	36.54	56.57	53.69	45.33	68.20	-22.87	peak
2	8359.419	11.68	38.68	55.58	51.26	46.04	74.00	-27.96	peak
3	8698.174	12.09	38.59	55.27	51.66	47.07	68.20	-21.13	peak
4	10927.390	14.02	39.33	53.54	48.74	48.55	74.00	-25.45	peak
5	11570.000	14.78	39.60	53.67	47.24	47.95	74.00	-26.05	peak
6	pp17355.000	18.00	40.31	54.37	45.37	49.31	68.20	-18.89	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

11ax_20M_TX_CH_157_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5785 TX RSE

: 5.8GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7488.611	11.26	36.80	56.31	52.66	44.41	74.00 -29.59 peak
2	8470.845	12.11	38.36	55.48	51.54	46.53	74.00 -27.47 peak
3	9552.678	12.49	38.80	54.50	50.17	46.96	68.20 -21.24 peak
4	10363.680	13.61	39.00	53.88	49.70	48.43	68.20 -19.77 peak
5	11570.000	14.78	39.60	53.67	47.37	48.08	74.00 -25.92 peak
6	pp17355.000	18.00	40.31	54.37	45.12	49.06	68.20 -19.14 peak



11ax_20M_TX_CH_165_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM

Mode : 5825 TX RSE

: 5.8GWIFI 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6895.570	11.37	36.18	56.72	53.82	44.65	68.20	-23.55	peak
2	8367.938	11.67	38.66	55.57	51.59	46.35	74.00	-27.65	peak
3	9889.295	12.83	38.66	54.20	50.18	47.47	68.20	-20.73	peak
4	10739.810	13.90	39.36	53.66	48.37	47.97	74.00	-26.03	peak
5	11650.000	14.69	39.55	53.69	46.42	46.97	74.00	-27.03	peak
6	pp17475.000	18.35	40.78	54.40	44.68	49.41	68.20	-18.79	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11ax_20M_TX_CH_165_Vertical



Condition: 3m VERTICAL

Job No : 03954WM

Mode : 5825 TX RSE

: 5.8GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7488.611	11.26	36.80	56.31	53.29	45.04	74.00 -28.96 peak
2	8333.913	11.72	38.44	55.60	51.61	46.17	74.00 -27.83 peak
3	9041.442	12.14	38.60	54.96	51.48	47.26	74.00 -26.74 peak
4	10972.000	14.11	39.37	53.52	48.30	48.26	74.00 -25.74 peak
5	11650.000	14.69	39.55	53.69	46.59	47.14	74.00 -26.86 peak
6	pp17475.000	18.35	40.78	54.40	45.20	49.93	68.20 -18.27 peak



7.5 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C

Humidity: 50.8 % RH


Atmospheric Pressure: 1020 mbar



7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 3. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



11a_TX_CH_36_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.458	10.14	32.40	30.84	31.53	43.23	54.00	-10.77 Average
2 pp	5149.980	10.14	32.40	30.84	31.65	43.35	54.00	-10.65 Average
3	5180.000	10.25	32.46	30.83	86.37	98.25	-----	----- Average



11a_TX_CH_36_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5147.358	10.13	32.39	30.84	46.45	58.13	74.00	-15.87 peak
2	5149.980	10.14	32.40	30.84	45.91	57.61	74.00	-16.39 peak
3	pp 5180.000	10.25	32.46	30.83	96.46	108.34	68.20	40.14 peak



11a_TX_CH_36_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5137.173	10.09	32.37	30.85	46.43	58.04	74.00	-15.96 peak
2	5149.980	10.14	32.40	30.84	45.35	57.05	74.00	-16.95 peak
3	pp 5180.000	10.25	32.46	30.83	93.27	105.15	68.20	36.95 peak



11a_TX_CH_36_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5149.458	10.14	32.40	30.84	30.90	42.60	54.00	-11.40 Average
2	pp 5149.980	10.14	32.40	30.84	30.94	42.64	54.00	-11.36 Average
3	5180.000	10.25	32.46	30.83	83.88	95.76	-----	----- Average



11ac_HT(20M)_TX_CH_36_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5140.666	10.10	32.38	30.84	46.69	58.33	74.00 -15.67 peak
2	5149.980	10.14	32.40	30.84	47.17	58.87	74.00 -15.13 peak
3 pp	5180.000	10.25	32.46	30.83	94.25	106.13	68.20 37.93 peak



11ac_HT(20M)_TX_CH_36_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5149.458	10.14	32.40	30.84	31.11	42.81	54.00	-11.19 Average
2 pp	5149.980	10.14	32.40	30.84	31.16	42.86	54.00	-11.14 Average
3	5180.000	10.25	32.46	30.83	84.16	96.04	-----	----- Average



11ac_HT(20M)_TX_CH_36_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5142.662	10.11	32.39	30.84	47.05	58.71	74.00 -15.29 peak
2	5149.980	10.14	32.40	30.84	46.43	58.13	74.00 -15.87 peak
3 pp	5180.000	10.25	32.46	30.83	92.30	104.18	68.20 35.98 peak



11ac_HT(20M)_TX_CH_36_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.458	10.14	32.40	30.84	30.83	42.53	54.00	-11.47 Average
2 pp	5149.980	10.14	32.40	30.84	30.89	42.59	54.00	-11.41 Average
3	5180.000	10.25	32.46	30.83	82.54	94.42	-----	----- Average



11ac_HT(40M)_TX_CH_38_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5146.229	10.13	32.39	30.84	50.16	61.84	74.00	-12.16 peak
2	5149.980	10.14	32.40	30.84	50.35	62.05	74.00	-11.95 peak
3	pp 5190.000	10.29	32.48	30.82	92.97	104.92	68.20	36.72 peak



11ac_HT(40M)_TX_CH_38_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.461	10.14	32.40	30.84	36.95	48.65	54.00 -5.35 Average
2 pp	5149.980	10.14	32.40	30.84	37.21	48.91	54.00 -5.09 Average
3	5190.000	10.29	32.48	30.82	83.09	95.04	----- Average



11ac_HT(40M)_TX_CH_38_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5147.905	10.13	32.40	30.84	48.25	59.94	74.00 -14.06 peak
2	5149.980	10.14	32.40	30.84	47.61	59.31	74.00 -14.69 peak
3	pp 5190.000	10.29	32.48	30.82	89.48	101.43	68.20 33.23 peak



11ac_HT(40M)_TX_CH_38_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.461	10.14	32.40	30.84	34.36	46.06	54.00 -7.94 Average
2	pp 5149.980	10.14	32.40	30.84	34.63	46.33	54.00 -7.67 Average
3	5190.000	10.29	32.48	30.82	79.41	91.36	----- Average



11ac_VHT(80M)_TX_CH_42_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5145.339	10.12	32.39	30.84	49.48	61.15	74.00 -12.85 peak
2	pp 5210.000	10.32	32.52	30.82	89.08	101.10	68.20 32.90 peak
3	5357.069	10.47	32.80	30.76	46.88	59.39	74.00 -14.61 peak



11ac_VHT(80M)_TX_CH_42_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5149.947	10.14	32.40	30.84	36.37	48.07	54.00	-5.93 Average
2	5210.000	10.32	32.52	30.82	78.65	90.67	-----	----- Average
3	5358.934	10.48	32.80	30.76	31.41	43.93	54.00	-10.07 Average



11ac_VHT(80M)_TX_CH_42_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5148.667	10.13	32.40	30.84	47.82	59.51	74.00	-14.49 peak
2 pp	5210.000	10.32	32.52	30.82	85.62	97.64	68.20	29.44 peak
3	5355.471	10.47	32.80	30.76	47.04	59.55	74.00	-14.45 peak



11ac_VHT(80M)_TX_CH_42_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5149.947	10.14	32.40	30.84	34.10	45.80	54.00	-8.20 Average
2	5210.000	10.32	32.52	30.82	75.76	87.78	-----	----- Average
3	5357.335	10.47	32.80	30.76	31.19	43.70	54.00	-10.30 Average



11ax_20M_TX_CH_36_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5144.959	10.12	32.39	30.84	46.84	58.51	74.00	-15.49 peak
2	5149.980	10.14	32.40	30.84	46.08	57.78	74.00	-16.22 peak
3	pp 5180.000	10.25	32.46	30.83	97.51	109.39	68.20	41.19 peak



11ax_20M_TX_CH_36_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.458	10.14	32.40	30.84	32.38	44.08	54.00	-9.92 Average
2 pp	5149.980	10.14	32.40	30.84	32.53	44.23	54.00	-9.77 Average
3	5180.000	10.25	32.46	30.83	85.41	97.29	-----	----- Average



11ax_20M_TX_CH_36_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5130.494	10.07	32.36	30.85	46.74	58.32	74.00 -15.68 peak
2	5149.980	10.14	32.40	30.84	45.42	57.12	74.00 -16.88 peak
3	pp 5180.000	10.25	32.46	30.83	91.94	103.82	68.20 35.62 peak



11ax_20M_TX_CH_36_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.458	10.14	32.40	30.84	30.90	42.60	54.00 -11.40 Average
2 pp	5149.980	10.14	32.40	30.84	30.94	42.64	54.00 -11.36 Average
3	5180.000	10.25	32.46	30.83	80.27	92.15	----- Average



11ax_40M_TX_CH_38_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5148.264	10.13	32.40	30.84	50.08	61.77	74.00 -12.23 peak
2	5149.980	10.14	32.40	30.84	50.76	62.46	74.00 -11.54 peak
3	pp 5190.000	10.29	32.48	30.82	94.20	106.15	68.20 37.95 peak



11ax_40M_TX_CH_38_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.461	10.14	32.40	30.84	36.73	48.43	54.00 -5.57 Average
2 pp	5149.980	10.14	32.40	30.84	36.97	48.67	54.00 -5.33 Average
3	5190.000	10.29	32.48	30.82	81.91	93.86	----- Average



11ax_40M_TX_CH_38_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5146.468	10.13	32.39	30.84	48.12	59.80	74.00	-14.20 peak
2	5149.980	10.14	32.40	30.84	47.98	59.68	74.00	-14.32 peak
3	pp 5190.000	10.29	32.48	30.82	91.03	102.98	68.20	34.78 peak



11ax_40M_TX_CH_38_Vetical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.461	10.14	32.40	30.84	34.45	46.15	54.00	-7.85 Average
2 pp	5149.980	10.14	32.40	30.84	34.63	46.33	54.00	-7.67 Average
3	5190.000	10.29	32.48	30.82	78.24	90.19	-----	----- Average



11ax_80M_TX_CH_42_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5147.643	10.13	32.40	30.84	49.61	61.30	74.00 -12.70 peak
2	pp 5210.000	10.32	32.52	30.82	91.35	103.37	68.20 35.17 peak
3	5351.212	10.45	32.80	30.76	47.03	59.52	74.00 -14.48 peak



11ax_80M_TX_CH_42_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AX80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5149.947	10.14	32.40	30.84	37.19	48.89	54.00	-5.11 Average
2	5210.000	10.32	32.52	30.82	79.29	91.31	-----	----- Average
3	5350.148	10.45	32.80	30.76	31.74	44.23	54.00	-9.77 Average



11ax_80M_TX_CH_42_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5148.410	10.13	32.40	30.84	47.93	59.62	74.00 -14.38 peak
2	pp 5210.000	10.32	32.52	30.82	87.41	99.43	68.20 31.23 peak
3	5356.270	10.47	32.80	30.76	46.89	59.40	74.00 -14.60 peak



11ax_80M_TX_CH_42_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AX80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5149.947	10.14	32.40	30.84	34.07	45.77	54.00	-8.23 Average
2	5210.000	10.32	32.52	30.82	75.17	87.19	-----	----- Average
3	5359.201	10.48	32.80	30.76	31.20	43.72	54.00	-10.28 Average



11ax_20M_Partial_RU106_TX_CH_36_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.458	10.14	32.40	30.84	47.08	58.78	74.00	-15.22 peak
2	5149.980	10.14	32.40	30.84	46.09	57.79	74.00	-16.21 peak
3 pp	5180.000	10.25	32.46	30.83	98.84	110.72	68.20	42.52 peak



11ax_20M_Partial_RU106_TX_CH_36_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5148.257	10.13	32.40	30.84	32.65	44.34	54.00	-9.66 Average
2 pp	5149.980	10.14	32.40	30.84	32.72	44.42	54.00	-9.58 Average
3	5180.000	10.25	32.46	30.83	85.90	97.78	-----	----- Average



11ax_20M_Partial_RU106_TX_CH_36_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5148.558	10.13	32.40	30.84	45.85	57.54	74.00	-16.46 peak
2	5149.980	10.14	32.40	30.84	44.98	56.68	74.00	-17.32 peak
3	pp 5180.000	10.25	32.46	30.83	94.29	106.17	68.20	37.97 peak



11ax_20M_Partial_RU106_TX_CH_36_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5180 Band edge

: 5GWIFI 11AX20_RU106

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5144.460	10.12	32.39	30.84	32.44	44.11	54.00	-9.89	Average
2	5149.980	10.14	32.40	30.84	32.38	44.08	54.00	-9.92	Average
3	5180.000	10.25	32.46	30.83	81.22	93.10	-----	-----	Average



11ax_40M_Partial_RU106_TX_CH_38_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5145.391	10.12	32.39	30.84	55.71	67.38	74.00 -6.62 peak
2	5149.980	10.14	32.40	30.84	50.97	62.67	74.00 -11.33 peak
3 pp	5190.000	10.29	32.48	30.82	98.64	110.59	68.20 42.39 peak



11ax_40M_Partial_RU106_TX_CH_38_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AX40_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5146.468	10.13	32.39	30.84	33.61	45.29	54.00	-8.71 Average
2	5149.980	10.14	32.40	30.84	33.11	44.81	54.00	-9.19 Average
3	5190.000	10.29	32.48	30.82	85.77	97.72	-----	----- Average



11ax_40M_Partial_RU106_TX_CH_38_Vetical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5190 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5145.271	10.12	32.39	30.84	53.31	64.98	74.00 -9.02 peak
2	5149.980	10.14	32.40	30.84	49.01	60.71	74.00 -13.29 peak
3	pp 5190.000	10.29	32.48	30.82	94.56	106.51	68.20 38.31 peak



11ax_40M_Partial_RU106_TX_CH_38_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM

Mode : 5190 Band edge

: 5GWIFI 11AX40_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5145.870	10.12	32.39	30.84	33.07	44.74	54.00	-9.26 Average
2	5149.980	10.14	32.40	30.84	32.76	44.46	54.00	-9.54 Average
3	5190.000	10.29	32.48	30.82	81.56	93.51	-----	----- Average




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 117 of 498

11ax_80M_Partial_RU106_TX_CH_42_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM

Mode : 5210 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5123.893	10.04	32.35	30.85	55.86	67.40	74.00 -6.60 peak
2	pp 5210.000	10.32	32.52	30.82	98.33	110.35	68.20 42.15 peak
3	5357.069	10.47	32.80	30.76	46.86	59.37	74.00 -14.63 peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11ax_80M_Partial_RU106_TX_CH_42_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5142.270	10.11	32.38	30.84	34.29	45.94	54.00	-8.06 Average
2 5210.000	10.32	32.52	30.82	85.36	97.38	-----	----- Average
3 pp 5358.401	10.48	32.80	30.76	33.75	46.27	54.00	-7.73 Average



11ax_80M_Partial_RU106_TX_CH_42_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5141.248	10.11	32.38	30.84	52.72	64.37	74.00 -9.63 peak
2	pp 5210.000	10.32	32.52	30.82	93.97	105.99	68.20 37.79 peak
3	5355.737	10.47	32.80	30.76	46.84	59.35	74.00 -14.65 peak



11ax_80M_Partial_RU106_TX_CH_42_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5210 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5143.805	10.12	32.39	30.84	33.53	45.20	54.00	-8.80	Average
2 5210.000	10.32	32.52	30.82	80.97	92.99	-----	-----	Average
3 pp 5358.667	10.48	32.80	30.76	33.79	46.31	54.00	-7.69	Average



11a_TX_CH_64_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5320.000	10.35	32.74	30.77	96.12	108.44	68.20	40.24 peak
2 5350.020	10.45	32.80	30.76	46.86	59.35	74.00	-14.65 peak
3 5388.405	10.58	32.80	30.74	46.94	59.58	74.00	-14.42 peak



11a_TX_CH_64_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5320.000	10.35	32.74	30.77	85.50	97.82	----- Average
2	pp 5350.020	10.45	32.80	30.76	31.86	44.35	54.00 -9.65 Average
3	5350.566	10.45	32.80	30.76	31.76	44.25	54.00 -9.75 Average



11a_TX_CH_64_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5320.000	10.35	32.74	30.77	92.12	104.44	68.20	36.24 peak
2	5350.020	10.45	32.80	30.76	45.51	58.00	74.00	-16.00 peak
3	5379.347	10.55	32.80	30.75	46.87	59.47	74.00	-14.53 peak



11a_TX_CH_64_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5320.000	10.35	32.74	30.77	82.71	95.03	-----	----- Average
2 pp 5350.020	10.45	32.80	30.76	31.22	43.71	54.00	-10.29 Average
3 5350.566	10.45	32.80	30.76	31.16	43.65	54.00	-10.35 Average



11ac_HT(20M)_TX_CH_64_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5320.000	10.35	32.74	30.77	94.23	106.55	68.20	38.35	peak
2	5350.020	10.45	32.80	30.76	46.50	58.99	74.00	-15.01	peak
3	5394.653	10.60	32.80	30.74	46.55	59.21	74.00	-14.79	peak



11ac_HT(20M)_TX_CH_64_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5320.000	10.35	32.74	30.77	84.01	96.33	-----	Average
2 pp	5350.020	10.45	32.80	30.76	31.70	44.19	54.00	-9.81 Average
3	5350.566	10.45	32.80	30.76	31.58	44.07	54.00	-9.93 Average



11ac_HT(20M)_TX_CH_64_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5320.000	10.35	32.74	30.77	91.05	103.37	68.20	35.17	peak
2	5350.020	10.45	32.80	30.76	46.00	58.49	74.00	-15.51	peak
3	5397.074	10.61	32.80	30.74	46.69	59.36	74.00	-14.64	peak



11ac_HT(20M)_TX_CH_64_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5320.000	10.35	32.74	30.77	81.23	93.55	-----	-----	Average
2 pp	5350.020	10.45	32.80	30.76	31.20	43.69	54.00	-10.31	Average
3	5350.566	10.45	32.80	30.76	31.14	43.63	54.00	-10.37	Average



11ac_HT(40M)_TX_CH_62_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5310.000	10.31	32.72	30.78	91.11	103.36	68.20	35.16 peak
2	5350.020	10.45	32.80	30.76	49.09	61.58	74.00	-12.42 peak
3	5352.518	10.46	32.80	30.76	49.11	61.61	74.00	-12.39 peak



11ac_HT(40M)_TX_CH_62_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5310.000	10.31	32.72	30.78	81.45	93.70	----- Average
2	pp 5350.020	10.45	32.80	30.76	36.08	48.57	54.00 -5.43 Average
3	5350.474	10.45	32.80	30.76	35.83	48.32	54.00 -5.68 Average



11ac_HT(40M)_TX_CH_62_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5310.000	10.31	32.72	30.78	87.94	100.19	68.20	31.99 peak
2	5350.020	10.45	32.80	30.76	47.49	59.98	74.00	-14.02 peak
3	5352.999	10.46	32.80	30.76	48.84	61.34	74.00	-12.66 peak



11ac_HT(40M)_TX_CH_62_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5310.000	10.31	32.72	30.78	77.70	89.95	----- Average
2	pp 5350.020	10.45	32.80	30.76	33.82	46.31	54.00 -7.69 Average
3	5350.474	10.45	32.80	30.76	33.66	46.15	54.00 -7.85 Average



11ac_VHT(80M)_TX_CH_58_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5149.209	10.14	32.40	30.84	45.67	57.37	74.00	-16.63 peak
2 pp 5290.000	10.28	32.68	30.78	89.28	101.46	68.20	33.26 peak
3 5355.124	10.47	32.80	30.76	49.62	62.13	74.00	-11.87 peak



11ac_VHT(80M)_TX_CH_58_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5149.798	10.14	32.40	30.84	30.50	42.20	54.00	-11.80 Average
2 5290.000	10.28	32.68	30.78	79.10	91.28	-----	----- Average
3 pp 5350.535	10.45	32.80	30.76	36.45	48.94	54.00	-5.06 Average



11ac_VHT(80M)_TX_CH_58_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AC80

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5104.667	9.97	32.31	30.86	45.90	57.32	74.00	-16.68	peak
2	5290.000	10.28	32.68	30.78	85.12	97.30	68.20	29.10	peak
3	5356.042	10.47	32.80	30.76	48.74	61.25	74.00	-12.75	peak



11ac_VHT(80M)_TX_CH_58_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5149.798	10.14	32.40	30.84	30.23	41.93	54.00	-12.07 Average
2	5290.000	10.28	32.68	30.78	75.47	87.65	-----	----- Average
3	pp 5350.229	10.45	32.80	30.76	33.79	46.28	54.00	-7.72 Average



11ax_20M_TX_CH_64_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5320.000	10.35	32.74	30.77	96.01	108.33	68.20	40.13 peak
2	5350.020	10.45	32.80	30.76	45.16	57.65	74.00	-16.35 peak
3	5389.210	10.58	32.80	30.74	46.98	59.62	74.00	-14.38 peak



11ax_20M_TX_CH_64_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5320.000	10.35	32.74	30.77	83.75	96.07	-----	Average
2 pp	5350.020	10.45	32.80	30.76	31.86	44.35	54.00	-9.65 Average
3	5350.566	10.45	32.80	30.76	31.73	44.22	54.00	-9.78 Average



11ax_20M_TX_CH_64_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5320.000	10.35	32.74	30.77	90.75	103.07	68.20	34.87	peak
2	5350.020	10.45	32.80	30.76	45.92	58.41	74.00	-15.59	peak
3	5383.773	10.56	32.80	30.75	46.73	59.34	74.00	-14.66	peak



11ax_20M_TX_CH_64_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5320.000	10.35	32.74	30.77	79.01	91.33	-----	Average
2 pp 5350.020	10.45	32.80	30.76	31.03	43.52	54.00	-10.48 Average
3 5356.370	10.47	32.80	30.76	30.96	43.47	54.00	-10.53 Average



11ax_40M_TX_CH_62_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5310.000	10.31	32.72	30.78	93.19	105.44	68.20	37.24	peak
2	5350.020	10.45	32.80	30.76	49.17	61.66	74.00	-12.34	peak
3	5351.436	10.45	32.80	30.76	48.22	60.71	74.00	-13.29	peak



11ax_40M_TX_CH_62_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5310.000	10.31	32.72	30.78	80.90	93.15	----- Average
2	pp 5350.020	10.45	32.80	30.76	35.22	47.71	54.00 -6.29 Average
3	5350.474	10.45	32.80	30.76	34.93	47.42	54.00 -6.58 Average



11ax_40M_TX_CH_62_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5310.000	10.31	32.72	30.78	88.22	100.47	68.20	32.27 peak
2	5350.020	10.45	32.80	30.76	46.13	58.62	74.00	-15.38 peak
3	5386.546	10.57	32.80	30.75	47.56	60.18	74.00	-13.82 peak



11ax_40M_TX_CH_62_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5310.000	10.31	32.72	30.78	75.95	88.20	----- Average
2	pp 5350.020	10.45	32.80	30.76	32.42	44.91	54.00 -9.09 Average
3	5350.474	10.45	32.80	30.76	32.25	44.74	54.00 -9.26 Average



11ax_80M_TX_CH_58_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5128.941	10.06	32.36	30.85	45.77	57.34	74.00 -16.66 peak
2	pp 5290.000	10.28	32.68	30.78	90.82	103.00	68.20 34.80 peak
3	5353.899	10.46	32.80	30.76	49.04	61.54	74.00 -12.46 peak



11ax_80M_TX_CH_58_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5149.798	10.14	32.40	30.84	30.53	42.23	54.00	-11.77 Average
2 5290.000	10.28	32.68	30.78	78.39	90.57	-----	----- Average
3 pp 5350.229	10.45	32.80	30.76	35.89	48.38	54.00	-5.62 Average



11ax_80M_TX_CH_58_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5141.856	10.11	32.38	30.84	45.82	57.47	74.00	-16.53	peak
2	5290.000	10.28	32.68	30.78	87.05	99.23	68.20	31.03	peak
3	5352.370	10.46	32.80	30.76	48.16	60.66	74.00	-13.34	peak



11ax_80M_TX_CH_58_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.798	10.14	32.40	30.84	30.36	42.06	54.00 -11.94 Average
2	5290.000	10.28	32.68	30.78	74.80	86.98	----- Average
3	pp 5350.229	10.45	32.80	30.76	33.88	46.37	54.00 -7.63 Average



11ax_20M_Partial_RU106_TX_CH_64_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 5320.000	10.35	32.74	30.77	96.93	109.25	68.20	41.05	peak
2 5350.020	10.45	32.80	30.76	45.37	57.86	74.00	-16.14	peak
3 5377.538	10.54	32.80	30.75	46.64	59.23	74.00	-14.77	peak



11ax_20M_Partial_RU106_TX_CH_64_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5320.000	10.35	32.74	30.77	83.89	96.21	-----	----- Average
2 5350.020	10.45	32.80	30.76	32.37	44.86	54.00	-9.14 Average
3 pp 5382.264	10.56	32.80	30.75	32.62	45.23	54.00	-8.77 Average



11ax_20M_Partial_RU106_TX_CH_64_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5320.000	10.35	32.74	30.77	94.23	106.55	68.20	38.35 peak
2 5350.020	10.45	32.80	30.76	45.19	57.68	74.00	-16.32 peak
3 5391.326	10.59	32.80	30.74	46.03	58.68	74.00	-15.32 peak



11ax_20M_Partial_RU106_TX_CH_64_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5320 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5320.000	10.35	32.74	30.77	81.20	93.52	-----	----- Average
2 5350.020	10.45	32.80	30.76	32.47	44.96	54.00	-9.04 Average
3 pp 5397.780	10.61	32.80	30.74	32.54	45.21	54.00	-8.79 Average



11ax_40M_Partial_RU106_TX_CH_62_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5310.000	10.31	32.72	30.78	98.07	110.32	68.20	42.12 peak
2	5350.020	10.45	32.80	30.76	49.57	62.06	74.00	-11.94 peak
3	5351.917	10.46	32.80	30.76	53.16	65.66	74.00	-8.34 peak



11ax_40M_Partial_RU106_TX_CH_62_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5310.000	10.31	32.72	30.78	84.49	96.74	----- Average
2	5350.020	10.45	32.80	30.76	33.26	45.75	54.00 -8.25 Average
3	pp 5352.638	10.46	32.80	30.76	33.42	45.92	54.00 -8.08 Average



11ax_40M_Partial_RU106_TX_CH_62_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5310.000	10.31	32.72	30.78	94.82	107.07	68.20	38.87 peak
2	5350.020	10.45	32.80	30.76	48.34	60.83	74.00	-13.17 peak
3	5352.157	10.46	32.80	30.76	51.38	63.88	74.00	-10.12 peak



11ax_40M_Partial_RU106_TX_CH_62_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5310 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5310.000	10.31	32.72	30.78	81.20	93.45	-----	Average
2	5350.020	10.45	32.80	30.76	32.91	45.40	54.00	-8.60 Average
3	pp 5382.312	10.56	32.80	30.75	33.10	45.71	54.00	-8.29 Average



11ax_80M_Partial_RU106_TX_CH_58_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5126.596	10.05	32.35	30.85	45.72	57.27	74.00 -16.73 peak
2	5290.000	10.28	32.68	30.78	97.27	109.45	68.20 41.25 peak
3	5352.981	10.46	32.80	30.76	53.61	66.11	74.00 -7.89 peak



11ax_80M_Partial_RU106_TX_CH_58_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5141.856	10.11	32.38	30.84	32.56	44.21	54.00 -9.79 Average
2	5290.000	10.28	32.68	30.78	84.18	96.36	----- Average
3	pp 5352.370	10.46	32.80	30.76	34.65	47.15	54.00 -6.85 Average



11ax_80M_Partial_RU106_TX_CH_58_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5133.047	10.08	32.37	30.85	45.84	57.44	74.00 -16.56 peak
2	5290.000	10.28	32.68	30.78	93.35	105.53	68.20 37.33 peak
3	5352.370	10.46	32.80	30.76	48.58	61.08	74.00 -12.92 peak



11ax_80M_Partial_RU106_TX_CH_58_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5290 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5146.267	10.13	32.39	30.84	32.28	43.96	54.00	-10.04 Average
2	5290.000	10.28	32.68	30.78	80.23	92.41	-----	----- Average
3	pp 5354.512	10.47	32.80	30.76	33.93	46.44	54.00	-7.56 Average



11a_TX_CH_100_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5427.248	10.61	32.85	30.73	46.44	59.17	74.00 -14.83 peak
2	5464.352	10.59	32.90	30.71	46.83	59.61	68.20 -8.59 peak
3	pp 5500.000	10.58	32.90	30.70	93.33	106.11	68.20 37.91 peak



11a_TX_CH_100_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.670	10.60	32.90	30.72	31.21	43.99	54.00	-10.01 Average
2 5500.000	10.58	32.90	30.70	83.11	95.89	-----	----- Average



11a_TX_CH_100_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5423.313	10.61	32.85	30.73	46.88	59.61	74.00 -14.39 peak
2	5466.875	10.59	32.90	30.71	46.15	58.93	68.20 -9.27 peak
3 pp	5500.000	10.58	32.90	30.70	88.04	100.82	68.20 32.62 peak



11a_TX_CH_100_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 5459.910	10.60	32.90	30.72	30.84	43.62	54.00	-10.38	Average
2 5500.000	10.58	32.90	30.70	78.91	91.69	-----	-----	Average



11a_TX_CH_140_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM

Mode : 5700 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5700.000	10.56	33.20	30.62	90.52	103.66	68.20	35.46 peak
2 5725.000	10.68	33.25	30.61	46.18	59.50	68.20	-8.70 peak
3 5730.782	10.70	33.26	30.61	46.12	59.47	68.20	-8.73 peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 166 of 498

11a_TX_CH_140_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM

Mode : 5700 Band edge

: 5GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5700.000	10.56	33.20	30.62	83.92	97.06	68.20	28.86 peak
2 5725.000	10.68	33.25	30.61	45.31	58.63	68.20	-9.57 peak
3 5745.403	10.77	33.29	30.60	46.09	59.55	68.20	-8.65 peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11ac_HT(20M)_TX_CH_100_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5412.000	10.62	32.82	30.74	47.17	59.87	74.00 -14.13 peak
2	5462.191	10.60	32.90	30.72	46.54	59.32	68.20 -8.88 peak
3	pp 5500.000	10.58	32.90	30.70	90.46	103.24	68.20 35.04 peak



11ac_HT(20M)_TX_CH_100_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.910	10.60	32.90	30.72	31.05	43.83	54.00	-10.17 Average
2 5500.000	10.58	32.90	30.70	80.23	93.01	-----	----- Average



11ac_HT(20M)_TX_CH_100_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5412.477	10.62	32.82	30.74	46.26	58.96	74.00 -15.04 peak
2	5467.115	10.59	32.90	30.71	46.39	59.17	68.20 -9.03 peak
3	pp 5500.000	10.58	32.90	30.70	88.39	101.17	68.20 32.97 peak



11ac_HT(20M)_TX_CH_100_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5458.471	10.60	32.90	30.72	30.91	43.69	54.00	-10.31 Average
2 5500.000	10.58	32.90	30.70	78.37	91.15	-----	----- Average



11ac_HT(20M)_TX_CH_140_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5700 Band edge

: 5GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5700.000	10.56	33.20	30.62	88.08	101.22	68.20	33.02 peak
2 5725.000	10.68	33.25	30.61	46.00	59.32	68.20	-8.88 peak
3 5737.086	10.73	33.27	30.61	46.33	59.72	68.20	-8.48 peak



11ac_HT(20M)_TX_CH_140_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5700 Band edge

: 5GWIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5700.000	10.56	33.20	30.62	85.22	98.36	68.20	30.16	peak
2	5725.000	10.68	33.25	30.61	45.45	58.77	68.20	-9.43	peak
3	5743.598	10.76	33.29	30.60	46.33	59.78	68.20	-8.42	peak



11ac_HT(40M)_TX_CH_102_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5459.761	10.60	32.90	30.72	47.63	60.41	74.00 -13.59 peak
2	5466.613	10.59	32.90	30.71	50.00	62.78	68.20 -5.42 peak
3 pp	5510.000	10.56	32.90	30.70	89.60	102.36	68.20 34.16 peak



11ac_HT(40M)_TX_CH_102_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5459.901	10.60	32.90	30.72	34.40	47.18	54.00	-6.82 Average
2	5510.000	10.56	32.90	30.70	79.11	91.87	-----	----- Average



11ac_HT(40M)_TX_CH_102_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5426.603	10.61	32.85	30.73	46.86	59.59	74.00 -14.41 peak
2	5467.033	10.59	32.90	30.71	47.98	60.76	68.20 -7.44 peak
3 pp	5510.000	10.56	32.90	30.70	84.57	97.33	68.20 29.13 peak



11ac_HT(40M)_TX_CH_102_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.901	10.60	32.90	30.72	32.58	45.36	54.00	-8.64 Average
2 5510.000	10.56	32.90	30.70	74.75	87.51	-----	----- Average



11ac_HT(40M)_TX_CH_134_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5670 Band edge

: 5GWIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5670.000	10.52	33.14	30.63	85.87	98.90	68.20	30.70 peak
2	5725.000	10.68	33.25	30.61	45.37	58.69	68.20	-9.51 peak
3	5759.910	10.84	33.32	30.60	46.24	59.80	68.20	-8.40 peak



11ac_HT(40M)_TX_CH_134_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5670 Band edge

: 5GWIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5670.000	10.52	33.14	30.63	81.77	94.80	68.20	26.60	peak
2	5725.000	10.68	33.25	30.61	45.57	58.89	68.20	-9.31	peak
3	5762.312	10.85	33.32	30.60	45.87	59.44	68.20	-8.76	peak



11ac_VHT(80M)_TX_CH_106_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5456.244	10.60	32.90	30.72	48.94	61.72	74.00 -12.28 peak
2	5466.989	10.59	32.90	30.71	49.36	62.14	68.20 -6.06 peak
3 pp	5530.000	10.53	32.90	30.69	85.32	98.06	68.20 29.86 peak



11ac_VHT(80M)_TX_CH_106_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.823	10.60	32.90	30.72	34.91	47.69	54.00	-6.31 Average
2 5530.000	10.53	32.90	30.69	75.12	87.86	-----	----- Average



11ac_VHT(80M)_TX_CH_106_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5458.749	10.60	32.90	30.72	47.73	60.51	74.00 -13.49 peak
2	5468.781	10.59	32.90	30.71	47.51	60.29	68.20 -7.91 peak
3	pp 5530.000	10.53	32.90	30.69	80.68	93.42	68.20 25.22 peak



11ac_VHT(80M)_TX_CH_106_Vertical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.823	10.60	32.90	30.72	32.51	45.29	54.00	-8.71 Average
2 5530.000	10.53	32.90	30.69	70.27	83.01	-----	----- Average



11ac_VHT(80M)_TX_CH_122_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5610 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5610.000	10.43	33.02	30.66	83.18	95.97	68.20	27.77 peak
2 5730.357	10.70	33.26	30.61	46.45	59.80	68.20	-8.40 peak



11ac_VHT(80M)_TX_CH_122_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5610 Band edge

: 5GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5610.000	10.43	33.02	30.66	80.00	92.79	68.20	24.59 peak
2 5760.000	10.84	33.32	30.60	46.10	59.66	68.20	-8.54 peak



11ax_20M_TX_CH_100_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5416.999	10.61	32.83	30.73	47.02	59.73	74.00 -14.27 peak
2	5462.071	10.60	32.90	30.72	46.83	59.61	68.20 -8.59 peak
3 pp	5500.000	10.58	32.90	30.70	94.01	106.79	68.20 38.59 peak



11ax_20M_TX_CH_100_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 5459.910	10.60	32.90	30.72	31.38	44.16	54.00	-9.84	Average
2 5500.000	10.58	32.90	30.70	82.13	94.91	-----	-----	Average



11ax_20M_TX_CH_100_Veritical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5445.529	10.60	32.89	30.72	45.89	58.66	74.00 -15.34 peak
2	5467.836	10.59	32.90	30.71	46.10	58.88	68.20 -9.32 peak
3	pp 5500.000	10.58	32.90	30.70	89.49	102.27	68.20 34.07 peak



11ax_20M_TX_CH_100_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.311	10.60	32.90	30.72	30.90	43.68	54.00	-10.32 Average
2 5500.000	10.58	32.90	30.70	77.66	90.44	-----	----- Average



11ax_20M_TX_CH_140_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5700 Band edge

: 5GWIFI 11AX20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5700.000	10.56	33.20	30.62	90.92	104.06	68.20	35.86 peak
2	5725.000	10.68	33.25	30.61	46.13	59.45	68.20	-8.75 peak
3	5735.284	10.72	33.27	30.61	46.56	59.94	68.20	-8.26 peak



11ax_20M_TX_CH_140_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5700 Band edge

: 5GWIFI 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5700.000	10.56	33.20	30.62	85.31	98.45	68.20	30.25	peak
2	5725.000	10.68	33.25	30.61	46.00	59.32	68.20	-8.88	peak
3	5762.776	10.85	33.33	30.59	46.73	60.32	68.20	-7.88	peak



11ax_40M_TX_CH_102_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5459.901	10.60	32.90	30.72	47.59	60.37	74.00 -13.63 peak
2	5469.272	10.59	32.90	30.71	48.88	61.66	68.20 -6.54 peak
3 pp	5510.000	10.56	32.90	30.70	90.28	103.04	68.20 34.84 peak



11ax_40M_TX_CH_102_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5459.901	10.60	32.90	30.72	33.04	45.82	54.00	-8.18 Average
2	5510.000	10.56	32.90	30.70	78.26	91.02	-----	----- Average



11ax_40M_TX_CH_102_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5427.575	10.61	32.86	30.73	46.52	59.26	74.00 -14.74 peak
2	5468.992	10.59	32.90	30.71	46.62	59.40	68.20 -8.80 peak
3 pp	5510.000	10.56	32.90	30.70	87.24	100.00	68.20 31.80 peak



11ax_40M_TX_CH_102_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5459.901	10.60	32.90	30.72	31.99	44.77	54.00	-9.23 Average
2	5510.000	10.56	32.90	30.70	74.93	87.69	-----	----- Average



11ax_40M_TX_CH_134_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5670 Band edge

: 5GWIFI 11AX40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5670.000	10.52	33.14	30.63	88.45	101.48	68.20	33.28	peak
2	5725.000	10.68	33.25	30.61	46.52	59.84	68.20	-8.36	peak
3	5741.861	10.75	33.28	30.60	46.26	59.69	68.20	-8.51	peak



11ax_40M_TX_CH_134_Veritical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5670 Band edge

: 5GWIFI 11AX40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5670.000	10.52	33.14	30.63	83.72	96.75	68.20	28.55 peak
2	5725.000	10.68	33.25	30.61	44.62	57.94	68.20	-10.26 peak
3	5749.328	10.79	33.30	30.60	46.23	59.72	68.20	-8.48 peak



11ax_80M_TX_CH_106_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5458.749	10.60	32.90	30.72	48.49	61.27	74.00 -12.73 peak
2	5463.942	10.59	32.90	30.71	48.82	61.60	68.20 -6.60 peak
3	pp 5530.000	10.53	32.90	30.69	87.78	100.52	68.20 32.32 peak



11ax_80M_TX_CH_106_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.823	10.60	32.90	30.72	35.11	47.89	54.00	-6.11 Average
2 5530.000	10.53	32.90	30.69	74.70	87.44	-----	----- Average



11ax_80M_TX_CH_106_Vetical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5446.234	10.60	32.89	30.72	46.92	59.69	74.00 -14.31 peak
2	5469.678	10.59	32.90	30.71	48.08	60.86	68.20 -7.34 peak
3	pp 5530.000	10.53	32.90	30.69	83.06	95.80	68.20 27.60 peak



11ax_80M_TX_CH_106_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM

Mode : 5530 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5459.823	10.60	32.90	30.72	32.96	45.74	54.00	-8.26 Average
2 5530.000	10.53	32.90	30.69	70.17	82.91	-----	----- Average




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 201 of 498

11ax_80M_TX_CH_122_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM

Mode : 5610 Band edge

: 5GWIFI 11AX80

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5610.000	10.43	33.02	30.66	86.56	99.35	68.20	31.15	peak
2	5752.677	10.80	33.31	30.60	46.03	59.54	68.20	-8.66	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11ax_80M_TX_CH_122_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5610 Band edge

: 5GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5610.000	10.43	33.02	30.66	81.78	94.57	68.20	26.37 peak
2 5756.744	10.82	33.31	30.60	46.71	60.24	68.20	-7.96 peak



11ax_20M_Partial_RU106_TX_CH_100_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5440.624	10.60	32.88	30.72	46.86	59.62	74.00	-14.38 peak
2	5464.953	10.59	32.90	30.71	46.19	58.97	68.20	-9.23 peak
3	pp 5500.000	10.58	32.90	30.70	95.58	108.36	68.20	40.16 peak



11ax_20M_Partial_RU106_TX_CH_100_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 5455.112	10.60	32.90	30.72	32.68	45.46	54.00	-8.54	Average
2 5500.000	10.58	32.90	30.70	82.60	95.38	-----	-----	Average



11ax_20M_Partial_RU106_TX_CH_100_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5404.037	10.62	32.81	30.74	46.44	59.13	74.00 -14.87 peak
2	5469.279	10.59	32.90	30.71	46.03	58.81	68.20 -9.39 peak
3	pp 5500.000	10.58	32.90	30.70	91.48	104.26	68.20 36.06 peak



11ax_20M_Partial_RU106_TX_CH_100_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5500 Band edge

: 5GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5444.093	10.60	32.89	30.72	32.62	45.39	54.00	-8.61 Average
2 5500.000	10.58	32.90	30.70	78.16	90.94	-----	----- Average



11ax_20M_Partial_RU106_TX_CH_140_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5700 Band edge

: 5GWIFI 11AX20_RU106

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5700.000	10.56	33.20	30.62	90.99	104.13	68.20	35.93	peak
2	5725.000	10.68	33.25	30.61	49.04	62.36	68.20	-5.84	peak
3	5725.883	10.68	33.25	30.61	48.18	61.50	68.20	-6.70	peak



11ax_20M_Partial_RU106_TX_CH_140_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5700 Band edge

: 5GWIFI 11AX20_RU106

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5700.000	10.56	33.20	30.62	86.77	99.91	68.20	31.71	peak
2	5725.000	10.68	33.25	30.61	45.41	58.73	68.20	-9.47	peak
3	5758.151	10.83	33.32	30.60	46.91	60.46	68.20	-7.74	peak



11ax_40M_Partial_RU106_TX_CH_102_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5459.761	10.60	32.90	30.72	47.30	60.08	74.00	-13.92 peak
2	5462.277	10.60	32.90	30.72	50.40	63.18	68.20	-5.02 peak
3	pp 5510.000	10.56	32.90	30.70	93.93	106.69	68.20	38.49 peak



11ax_40M_Partial_RU106_TX_CH_102_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5454.872	10.60	32.90	30.72	32.72	45.50	54.00	-8.50 Average
2 5510.000	10.56	32.90	30.70	80.85	93.61	-----	----- Average



11ax_40M_Partial_RU106_TX_CH_102_Vertical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5458.643	10.60	32.90	30.72	47.47	60.25	74.00 -13.75 peak
2	5468.852	10.59	32.90	30.71	47.76	60.54	68.20 -7.66 peak
3	pp 5510.000	10.56	32.90	30.70	89.36	102.12	68.20 33.92 peak



11ax_40M_Partial_RU106_TX_CH_102_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5510 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5458.503	10.60	32.90	30.72	32.64	45.42	54.00	-8.58 Average
2 5510.000	10.56	32.90	30.70	76.28	89.04	-----	----- Average



11ax_40M_Partial_RU106_TX_CH_134_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5670 Band edge

: 5GWIFI 11AX40_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5670.000	10.52	33.14	30.63	93.85	106.88	68.20	38.68 peak
2 5725.000	10.68	33.25	30.61	45.31	58.63	68.20	-9.57 peak
3 5737.920	10.73	33.28	30.60	49.78	63.19	68.20	-5.01 peak



11ax_40M_Partial_RU106_TX_CH_134_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5670 Band edge

: 5GWIFI 11AX40_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5670.000	10.52	33.14	30.63	88.80	101.83	68.20	33.63 peak
2	5725.000	10.68	33.25	30.61	45.69	59.01	68.20	-9.19 peak
3	5731.452	10.70	33.26	30.61	47.33	60.68	68.20	-7.52 peak



11ax_80M_Partial_RU106_TX_CH_106_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5440.879	10.60	32.88	30.72	50.45	63.21	74.00 -10.79 peak
2	5463.763	10.59	32.90	30.71	50.21	62.99	68.20 -5.21 peak
3	pp 5530.000	10.53	32.90	30.69	92.79	105.53	68.20 37.33 peak



11ax_80M_Partial_RU106_TX_CH_106_Horizontal-Avg



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5458.570	10.60	32.90	30.72	33.05	45.83	54.00	-8.17 Average
2 5530.000	10.53	32.90	30.69	79.78	92.52	-----	----- Average



11ax_80M_Partial_RU106_TX_CH_106_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5436.599	10.61	32.87	30.73	46.90	59.65	74.00 -14.35 peak
2	5466.809	10.59	32.90	30.71	47.20	59.98	68.20 -8.22 peak
3	pp 5530.000	10.53	32.90	30.69	87.59	100.33	68.20 32.13 peak



11ax_80M_Partial_RU106_TX_CH_106_Verical-Avg



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5530 Band edge

: 5GWIFI 11AX80_RU106

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 5456.244	10.60	32.90	30.72	32.68	45.46	54.00	-8.54 Average
2 5530.000	10.53	32.90	30.69	74.47	87.21	-----	----- Average



11ax_80M_Partial_RU106_TX_CH_122_Horizontal-Peak



Condition: 3m HORIZONTAL

Job No : 03945WM


Mode : 5610 Band edge

: 5GWIFI 11AX80_RU106

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 5610.000	10.43	33.02	30.66	94.96	107.75	68.20	39.55	peak
2	5725.095	10.68	33.25	30.61	44.46	57.78	68.20	-10.42	Peak
3	5755.320	10.81	33.31	30.60	47.81	61.33	68.20	-6.87	peak



11ax_80M_Partial_RU106_TX_CH_122_Verical-Peak



Condition: 3m VERTICAL

Job No : 03945WM


Mode : 5610 Band edge

: 5GWIFI 11AX80_RU106

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5610.000	10.43	33.02	30.66	88.98	101.77	68.20	33.57	peak
2	5725.095	10.68	33.25	30.61	44.99	58.31	68.20	-9.89	Peak
3	5735.828	10.72	33.27	30.61	46.25	59.63	68.20	-8.57	peak



11a_TX_CH_149_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM

Mode : 5745 Band edge

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5640.415	10.47	33.08	30.64	46.48	59.39	68.20	-8.81 peak
2	5715.000	10.63	33.23	30.61	52.44	65.69	109.40	-43.71 peak
3	5725.000	10.68	33.25	30.61	64.35	77.67	122.20	-44.53 peak
4	5745.000	10.77	33.29	30.60	94.40	107.86	-----	----- peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 222 of 498

11a_TX_CH_149_Vertical



Condition: 3m VERTICAL

Job No : 03954WM

Mode : 5745 Band edge

: 5.8GWIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5647.750	10.48	33.10	30.64	46.40	59.34	68.20	-8.86 peak
2	5715.000	10.63	33.23	30.61	48.75	62.00	109.40	-47.40 peak
3	5725.000	10.68	33.25	30.61	58.13	71.45	122.20	-50.75 peak
4	5745.000	10.77	33.29	30.60	89.88	103.34	-----	----- peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11a_TX_CH_165_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5825 Band edge

: 5.8GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5825.000	10.99	33.50	30.57	91.14	105.06	-----	----- peak
2 5850.000	10.95	33.60	30.56	52.30	66.29	122.20	-55.91 peak
3 5860.000	10.94	33.58	30.56	46.73	60.69	109.40	-48.71 peak
4 pp 5928.062	10.87	33.56	30.53	46.31	60.21	68.20	-7.99 peak



11a_TX_CH_165_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5825 Band edge

: 5.8GWIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5825.000	10.99	33.50	30.57	86.58	100.50	-----	----- peak
2 5850.000	10.95	33.60	30.56	47.37	61.36	122.20	-60.84 peak
3 5860.000	10.94	33.58	30.56	45.55	59.51	109.40	-49.89 peak
4 pp 5936.996	10.86	33.57	30.53	47.04	60.94	68.20	-7.26 peak



11ac_HT(20M)_TX_CH_149_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5745 Band edge

: 5.8GWIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5646.919	10.48	33.09	30.64	45.98	58.91	68.20	-9.29 peak
2	5715.000	10.63	33.23	30.61	49.63	62.88	109.40	-46.52 peak
3	5725.000	10.68	33.25	30.61	59.71	73.03	122.20	-49.17 peak
4	5745.000	10.77	33.29	30.60	93.20	106.66	-----	----- peak



11ac_HT(20M)_TX_CH_149_Vercal



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5745 Band edge

: 5.8GWIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5645.534	10.48	33.09	30.64	45.51	58.44	68.20	-9.76 peak
2	5715.000	10.63	33.23	30.61	48.90	62.15	109.40	-47.25 peak
3	5725.000	10.68	33.25	30.61	57.60	70.92	122.20	-51.28 peak
4	5745.000	10.77	33.29	30.60	88.73	102.19	-----	----- peak



11ac_HT(20M)_TX_CH_165_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5825 Band edge

: 5.8GWIFI 11AC20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5825.000	10.99	33.50	30.57	90.84	104.76	----- peak
2	5850.000	10.95	33.60	30.56	51.48	65.47	122.20 -56.73 peak
3	5860.000	10.94	33.58	30.56	45.76	59.72	109.40 -49.68 peak
4	pp 5940.290	10.86	33.58	30.52	46.20	60.12	68.20 -8.08 peak



11ac_HT(20M)_TX_CH_165_Vertical



Condition: 3m VERTICAL

Job No : 03954WM

Mode : 5825 Band edge

: 5.8GWIFI 11AC20


	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5825.000	10.99	33.50	30.57	85.97	99.89	-----	----- peak
2 5850.000	10.95	33.60	30.56	47.16	61.15	122.20	-61.05 peak
3 5860.000	10.94	33.58	30.56	46.16	60.12	109.40	-49.28 peak
4 pp 5931.195	10.87	33.56	30.53	46.88	60.78	68.20	-7.42 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

11ac_HT(40M)_TX_CH_151_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5755 Band edge

: 5.8GWIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5645.201	10.48	33.09	30.64	45.69	58.62	68.20	-9.58 peak
2	5715.000	10.63	33.23	30.61	59.85	73.10	109.40	-36.30 peak
3	5725.000	10.68	33.25	30.61	62.51	75.83	122.20	-46.37 peak
4	5755.000	10.81	33.31	30.60	90.29	103.81	-----	----- peak



11ac_HT(40M)_TX_CH_151_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5755 Band edge

: 5.8GWIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5642.141	10.47	33.08	30.64	45.86	58.77	68.20	-9.43 peak
2	5715.000	10.63	33.23	30.61	54.19	67.44	109.40	-41.96 peak
3	5725.000	10.68	33.25	30.61	57.08	70.40	122.20	-51.80 peak
4	5755.000	10.81	33.31	30.60	85.88	99.40	-----	----- peak



11ac_HT(40M)_TX_CH_159_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5795 Band edge

: 5.8GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	11.00	33.39	30.58	87.07	100.88	----- peak
2	5850.000	10.95	33.60	30.56	46.18	60.17	122.20 -62.03 peak
3	5860.000	10.94	33.58	30.56	45.43	59.39	109.40 -50.01 peak
4	pp 5935.649	10.86	33.57	30.53	46.29	60.19	68.20 -8.01 peak



11ac_HT(40M)_TX_CH_159_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5795 Band edge

: 5.8GWIFI 11AC40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	11.00	33.39	30.58	85.01	98.82	----- peak
2	5850.000	10.95	33.60	30.56	45.63	59.62	122.20 -62.58 peak
3	5860.000	10.94	33.58	30.56	45.80	59.76	109.40 -49.64 peak
4	pp 5928.341	10.87	33.56	30.53	46.50	60.40	68.20 -7.80 peak



11ac_VHT(80M)_TX_CH_155_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM

Mode : 5775 Band edge

: 5.8GWIFI 11AC80


	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5717.460	10.64	33.23	30.61	46.26	59.52	110.09 -50.57 peak
2	5775.000	10.91	33.35	30.59	81.52	95.19	----- -50.57 peak
3	5850.575	10.95	33.60	30.56	46.82	60.81	120.89 -60.08 peak
4	5943.122	10.86	33.59	30.52	47.22	61.15	68.20 -7.05 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

11ac_VHT(80M)_TX_CH_155_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5775 Band edge

: 5.8GWIFI 11AC80

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5723.787	10.67	33.25	30.61	46.61	59.92	119.44	-59.52 peak
2	5775.000	10.91	33.35	30.59	76.99	90.66	-----	----- peak
3	5850.883	10.95	33.60	30.56	46.39	60.38	120.19	-59.81 peak
4 pp	5928.429	10.87	33.56	30.53	47.23	61.13	68.20	-7.07 peak



11ax_20M_TX_CH_149_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5745 Band edge

: 5.8GWIFI 11AX20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5641.937	10.47	33.08	30.64	45.92	58.83	68.20	-9.37 peak
2	5715.000	10.63	33.23	30.61	54.83	68.08	109.40	-41.32 peak
3	5725.000	10.68	33.25	30.61	63.51	76.83	122.20	-45.37 peak
4	5745.000	10.77	33.29	30.60	95.55	109.01	-----	----- peak



11ax_20M_TX_CH_149_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5745 Band edge

: 5.8GWIFI 11AX20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5643.458	10.48	33.09	30.64	46.00	58.93	68.20	-9.27 peak
2	5715.000	10.63	33.23	30.61	48.85	62.10	109.40	-47.30 peak
3	5725.000	10.68	33.25	30.61	57.32	70.64	122.20	-51.56 peak
4	5745.000	10.77	33.29	30.60	91.01	104.47	-----	----- peak



11ax_20M_TX_CH_165_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5825 Band edge

: 5.8GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5825.000	10.99	33.50	30.57	91.62	105.54	-----	----- peak
2 5850.000	10.95	33.60	30.56	55.55	69.54	122.20	-52.66 peak
3 5860.000	10.94	33.58	30.56	48.21	62.17	109.40	-47.23 peak
4 pp 5930.098	10.87	33.56	30.53	46.92	60.82	68.20	-7.38 peak



11ax_20M_TX_CH_165_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5825 Band edge

: 5.8GWIFI 11AX20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5825.000	10.99	33.50	30.57	88.21	102.13	-----	----- peak
2 5850.000	10.95	33.60	30.56	49.76	63.75	122.20	-58.45 peak
3 5860.000	10.94	33.58	30.56	45.45	59.41	109.40	-49.99 peak
4 pp 5942.488	10.86	33.58	30.52	46.59	60.51	68.20	-7.69 peak



11ax_40M_TX_CH_151_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5755 Band edge

: 5.8GWIFI 11AX40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	5649.948	10.48	33.10	30.64	45.75	58.69	68.20	-9.51	peak
2	5715.000	10.63	33.23	30.61	57.87	71.12	109.40	-38.28	peak
3	5725.000	10.68	33.25	30.61	60.54	73.86	122.20	-48.34	peak
4	5755.000	10.81	33.31	30.60	92.58	106.10	-----	-----	peak



11ax_40M_TX_CH_151_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5755 Band edge

: 5.8GWIFI 11AX40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5648.569	10.48	33.10	30.64	45.57	58.51	68.20	-9.69 peak
2	5715.000	10.63	33.23	30.61	52.91	66.16	109.40	-43.24 peak
3	5725.000	10.68	33.25	30.61	55.97	69.29	122.20	-52.91 peak
4	5755.000	10.81	33.31	30.60	85.82	99.34	-----	----- peak



11ax_40M_TX_CH_159_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5795 Band edge

: 5.8GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	11.00	33.39	30.58	89.16	102.97	----- peak
2	5850.000	10.95	33.60	30.56	45.76	59.75	122.20 -62.45 peak
3	5860.000	10.94	33.58	30.56	45.80	59.76	109.40 -49.64 peak
4	pp 5935.446	10.86	33.57	30.53	46.50	60.40	68.20 -7.80 peak



11ax_40M_TX_CH_159_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5795 Band edge

: 5.8GWIFI 11AX40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	11.00	33.39	30.58	86.94	100.75	----- peak
2	5850.000	10.95	33.60	30.56	46.33	60.32	122.20 -61.88 peak
3	5860.000	10.94	33.58	30.56	45.40	59.36	109.40 -50.04 peak
4	pp 5928.138	10.87	33.56	30.53	46.83	60.73	68.20 -7.47 peak



11ax_80M_TX_CH_155_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5775 Band edge

: 5.8GWIFI 11AX80

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5646.539	10.48	33.09	30.64	46.32	59.25	68.20	-8.95 Peak
2	5719.870	10.65	33.24	30.61	58.03	71.31	110.76	-39.45 peak
3	5775.000	10.91	33.35	30.59	87.63	101.30	-----	----- peak
4	5849.958	10.96	33.60	30.56	60.34	74.34	-----	----- peak
5 pp	5933.426	10.86	33.57	30.53	47.79	61.69	68.20	-6.51 peak



11ax_80M_TX_CH_155_Vertical



Condition: 3m VERTICAL

Job No : 03954WM

Mode : 5775 Band edge

: 5.8GWIFI 11AX80


	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5644.754	10.48	33.09	30.64	45.47	58.40	68.20	-9.80 Peak
2	5724.390	10.67	33.25	30.61	53.67	66.98	120.81	-53.83 peak
3	5775.000	10.91	33.35	30.59	83.76	97.43	-----	----- peak
4	5849.650	10.96	33.60	30.56	56.12	70.12	-----	----- peak
5 pp	5944.061	10.85	33.59	30.52	46.68	60.60	68.20	-7.60 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

11ax_20M_Partial_RU106_TX_CH_149_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5745 Band edge

: 5.8GWIFI 11AX20_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5645.950	10.48	33.09	30.64	45.60	58.53	68.20	-9.67 peak
2	5715.000	10.63	33.23	30.61	55.51	68.76	109.40	-40.64 peak
3	5725.000	10.68	33.25	30.61	67.88	81.20	122.20	-41.00 peak
4	5745.000	10.77	33.29	30.60	97.90	111.36	-----	----- peak



11ax_20M_Partial_RU106_TX_CH_149_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5745 Band edge

: 5.8GWIFI 11AX20_RU106

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5644.150	10.48	33.09	30.64	45.69	58.62	68.20	-9.58 peak
2	5715.000	10.63	33.23	30.61	49.38	62.63	109.40	-46.77 peak
3	5725.000	10.68	33.25	30.61	61.84	75.16	122.20	-47.04 peak
4	5745.000	10.77	33.29	30.60	92.95	106.41	-----	----- peak



11ax_20M_Partial_RU106_TX_CH_165_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5825 Band edge

: 5.8GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5825.000	10.99	33.50	30.57	96.61	110.53	-----	peak
2	5850.000	10.95	33.60	30.56	65.54	79.53	122.20	-42.67 peak
3	5860.000	10.94	33.58	30.56	56.18	70.14	109.40	-39.26 peak
4	pp 5925.870	10.87	33.55	30.53	46.06	59.95	68.20	-8.25 peak



11ax_20M_Partial_RU106_TX_CH_165_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5825 Band edge

: 5.8GWIFI 11AX20_RU106

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5825.000	10.99	33.50	30.57	92.52	106.44	-----	-----	peak
2 5850.000	10.95	33.60	30.56	62.77	76.76	122.20	-45.44	peak
3 5860.000	10.94	33.58	30.56	53.23	67.19	109.40	-42.21	peak
4 pp 5939.035	10.86	33.58	30.52	46.66	60.58	68.20	-7.62	peak



11ax_40M_Partial_RU242_TX_CH_151_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5755 Band edge

: 5.8GWIFI 11AX40_RU242

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	5648.569	10.48	33.10	30.64	47.33	60.27	68.20	-7.93 peak
2	5715.000	10.63	33.23	30.61	63.64	76.89	109.40	-32.51 peak
3	5725.000	10.68	33.25	30.61	66.36	79.68	122.20	-42.52 peak
4	5755.000	10.81	33.31	30.60	93.65	107.17	-----	----- peak



11ax_40M_Partial_RU242_TX_CH_151_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5755 Band edge

: 5.8GWIFI 11AX40_RU242

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5645.813	10.48	33.09	30.64	45.69	58.62	68.20	-9.58 peak
2	5715.000	10.63	33.23	30.61	56.56	69.81	109.40	-39.59 peak
3	5725.000	10.68	33.25	30.61	60.61	73.93	122.20	-48.27 peak
4	5755.000	10.81	33.31	30.60	88.12	101.64	-----	----- peak



11ax_40M_Partial_RU242_TX_CH_159_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5795 Band edge

: 5.8GWIFI 11AX40_RU242

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5795.000	11.00	33.39	30.58	91.19	105.00	-----	peak
2	5850.000	10.95	33.60	30.56	56.26	70.25	122.20	-51.95 peak
3	5860.000	10.94	33.58	30.56	58.59	72.55	109.40	-36.85 peak
4	pp 5938.494	10.86	33.58	30.52	48.05	61.97	68.20	-6.23 peak



11ax_40M_Partial_RU242_TX_CH_159_Vertical



Condition: 3m VERTICAL

Job No : 03954WM


Mode : 5795 Band edge

: 5.8GWIFI 11AX40_RU242

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	11.00	33.39	30.58	85.88	99.69	----- peak
2	5850.000	10.95	33.60	30.56	51.38	65.37	122.20 -56.83 peak
3	5860.000	10.94	33.58	30.56	53.66	67.62	109.40 -41.78 peak
4	pp 5944.187	10.85	33.59	30.52	46.56	60.48	68.20 -7.72 peak



11ax_80M_Partial_RU242_TX_CH_155_Horizontal



Condition: 3m HORIZONTAL

Job No : 03954WM


Mode : 5775 Band edge

: 5.8GWIFI 11AX80_RU242

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5645.349	10.48	33.09	30.64	46.30	59.23	68.20	-8.97 Peak
2	5724.691	10.67	33.25	30.61	61.30	74.61	121.50	-46.89 peak
3	5775.000	10.91	33.35	30.59	91.07	104.74	-----	----- peak
4	5849.650	10.96	33.60	30.56	58.24	72.24	-----	----- peak
5 pp	5931.552	10.86	33.56	30.53	47.91	61.80	68.20	-6.40 peak



11ax_80M_Partial_RU242_TX_CH_155_Vertical



Condition: 3m VERTICAL

Job No : 03954WM

Mode : 5775 Band edge

: 5.8GWIFI 11AX80_RU242

	Cable	Ant	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5644.160	10.48	33.09	30.64	45.73	58.66	68.20	-9.54 Peak
2	5724.993	10.67	33.25	30.61	57.03	70.34	122.18	-51.84 peak
3	5775.000	10.91	33.35	30.59	86.27	99.94	-----	----- peak
4	5849.958	10.96	33.60	30.56	53.33	67.33	-----	----- peak
5 pp	5932.802	10.86	33.57	30.53	46.40	60.30	68.20	-7.90 peak



7.6 Channel Move Time

Test Requirement KDB 905462 D02 Section 5.1
Test Method: KDB 905462 D02 Section 7.8.3

Limit:

Test item	Limit	Applicability	
		Master Device or client with Radar Detection	Client without Radar Detection
Non-occupancy period	Minimum 30 minutes	Yes	Not required
Channel Availability Check Time	60 seconds	Yes	Not required
Channel Move Time	10 seconds See Note 1.	Yes	Yes
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.	Yes	Yes
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.	Yes	Not required

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.




7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.2 °C Humidity: 36.7 % RH Atmospheric Pressure: 1020 mbar



7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

- 1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- 2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- 3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- 6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8) Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

Please Refer to Appendix for Details



7.7 Duty Cycle

Test Requirement KDB 789033 D02 II B 1

Test Method: KDB 789033 D02 II B 1

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 24.2 °C Humidity: 36.7 % RH Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.8 99% Bandwidth

Test Requirement N/A
Test Method: KDB 789033 D02 II D


7.8.1 E.U.T. Operation

Operating Environment:
Temperature: 24.2 °C Humidity: 36.7 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 26dB Emission bandwidth

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II C 1

7.9.1 E.U.T. Operation


Operating Environment:

Temperature: 24.2 °C Humidity: 36.7 % RH Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.10 Minimum 6 dB bandwidth (5.725-5.85 GHz band)

Test Requirement 47 CFR Part 15, Subpart E 15.407 (e)

Test Method: KDB 789033 D02 II C 2

Limit:

Frequency band(MHz)	Limit
5725-5850	≥ 500 kHz

7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 24.2 °C


Humidity: 36.7 % RH

Atmospheric Pressure: 1020 mbar

7.10.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.10.3 Test Setup Diagram



7.10.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.11 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II F

Limit:

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

7.11.1 E.U.T. Operation

Operating Environment:

Temperature: 24.2 °C

Humidity: 36.7 % RH


Atmospheric Pressure: 1020 mbar

7.11.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.



7.11.3 Test Setup Diagram



7.11.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.12 Frequency Stability

Test Requirement 47 CFR Part 15, Subpart E 15.407 (g)

Test Method: ANSI C63.10 (2013) Section 6.8

7.12.1 Measurement Procedure and Data

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.



7.13 Non-occupancy period

Test Requirement KDB 905462 D02 Section 5.1
Test Method: KDB 905462 D02 Section 7.8.3

Limit:

Test item	Limit	Applicability	
		Master Device or client with Radar Detection	Client without Radar Detection
Non-occupancy period	Minimum 30 minutes	Yes	Not required
Channel Availability Check Time	60 seconds	Yes	Not required
Channel Move Time	10 seconds See Note 1.	Yes	Yes
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.	Yes	Yes
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.	Yes	Not required

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

7.13.1 E.U.T. Operation

Operating Environment:

Temperature: 24.2 °C Humidity: 36.7 % RH Atmospheric Pressure: 1020 mbar






SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.13.2 Test Setup Diagram



7.13.3 Measurement Procedure and Data

- 1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- 2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- 3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- 6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8) Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

Please Refer to Appendix for Details



7.14 Channel Closing Transmission Time

Test Requirement KDB 905462 D02 Section 5.1

Test Method: KDB 905462 D02 Section 7.8.3

Limit:

Test item	Limit	Applicability	
		Master Device or client with Radar Detection	Client without Radar Detection
Non-occupancy period	Minimum 30 minutes	Yes	Not required
Channel Availability Check Time	60 seconds	Yes	Not required
Channel Move Time	10 seconds See Note 1.	Yes	Yes
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.	Yes	Yes
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.	Yes	Not required

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

7.14.1 E.U.T. Operation

Operating Environment:




Temperature: 24.2 °C

Humidity: 36.7 % RH

Atmospheric Pressure: 1020 mbar



7.14.2 Test Setup Diagram



7.14.3 Measurement Procedure and Data

- 1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- 2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- 3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- 6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8) Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

Please Refer to Appendix for Details



8 Test Setup Photo

Please refer to SZCR2410003954 Appendix_Setup Photo

9 EUT Constructional Details (EUT Photos)

Please refer to SZCR2410003954 Appendix_ External Photo and Internal Photo.



10 Appendix

1. Duty Cycle

1.1 Test Result

1.1.1 Ant12

Ant12									
Mode	Tx Type	Frequency (MHz)	RU	RU Pos	T _{on} (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	/	/	2.097	2.113	99.24	0.03	0.03
		5200	/	/	2.098	2.114	99.24	0.03	0.03
		5240	/	/	2.098	2.114	99.24	0.03	0.03
		5260	/	/	2.098	2.114	99.24	0.03	0.03
		5300	/	/	2.098	2.115	99.20	0.04	0.03
		5320	/	/	2.097	2.113	99.24	0.03	0.03
		5500	/	/	2.097	2.113	99.24	0.03	0.03
		5580	/	/	2.096	2.113	99.20	0.04	0.03
		5700	/	/	2.098	2.114	99.24	0.03	0.03
		5745	/	/	2.097	2.113	99.24	0.03	0.03
		5785	/	/	2.097	2.113	99.24	0.03	0.03
		5825	/	/	2.098	2.114	99.24	0.03	0.03
802.11n (HT20)	SISO	5180	/	/	5.329	5.346	99.68	0.01	0.03
		5200	/	/	5.328	5.344	99.70	0.01	0.04
		5240	/	/	5.329	5.346	99.68	0.01	0.03
		5260	/	/	5.329	5.346	99.68	0.01	0.03
		5300	/	/	5.329	5.346	99.68	0.01	0.03
		5320	/	/	5.328	5.344	99.70	0.01	0.04
		5500	/	/	5.328	5.345	99.68	0.01	0.00
		5580	/	/	5.328	5.346	99.66	0.01	0.04
		5700	/	/	5.327	5.344	99.68	0.01	0.04
		5745	/	/	5.328	5.344	99.70	0.01	0.00
		5785	/	/	5.330	5.346	99.70	0.01	0.04
		5825	/	/	3.555	3.570	99.58	0.02	0.00
802.11n (HT40)	SISO	5190	/	/	5.412	5.428	99.71	0.01	0.04
		5230	/	/	5.412	5.428	99.71	0.01	0.04
		5270	/	/	5.413	5.430	99.69	0.01	0.03
		5310	/	/	5.412	5.428	99.71	0.01	0.03



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 273 of 498

		5510	/	/	5.412	5.428	99.71	0.01	0.04
		5550	/	/	5.412	5.428	99.71	0.01	0.00
		5670	/	/	5.412	5.428	99.71	0.01	0.04
		5755	/	/	5.412	5.428	99.71	0.01	0.04
		5795	/	/	5.412	5.428	99.71	0.01	0.04
802.11ac (VHT20)	SISO	5180	/	/	5.332	5.348	99.70	0.01	0.04
		5200	/	/	5.332	5.350	99.66	0.01	0.07
		5240	/	/	5.333	5.350	99.68	0.01	0.03
		5260	/	/	5.333	5.350	99.68	0.01	0.03
		5300	/	/	5.333	5.350	99.68	0.01	0.03
		5320	/	/	5.332	5.348	99.70	0.01	0.04
		5500	/	/	3.556	3.574	99.50	0.02	0.04
		5580	/	/	3.557	3.575	99.50	0.02	0.04
		5700	/	/	3.556	3.573	99.52	0.02	0.04
		5745	/	/	5.334	5.350	99.70	0.01	0.04
		5785	/	/	5.333	5.350	99.68	0.01	0.03
		5825	/	/	3.557	3.573	99.55	0.02	0.04
802.11ac (VHT40)	SISO	5190	/	/	1.981	1.997	99.20	0.03	0.03
		5230	/	/	1.980	1.997	99.15	0.04	0.07
		5270	/	/	1.981	1.997	99.20	0.03	0.03
		5310	/	/	1.980	1.996	99.20	0.03	0.03
		5510	/	/	1.981	1.997	99.20	0.03	0.03
		5550	/	/	1.981	1.998	99.15	0.04	0.03
		5670	/	/	1.981	1.997	99.20	0.03	0.03
		5755	/	/	5.417	5.434	99.69	0.01	0.03
		5795	/	/	5.416	5.432	99.71	0.01	0.04
802.11ac (VHT80)	SISO	5210	/	/	1.201	1.216	98.77	0.05	0.03
		5290	/	/	1.201	1.217	98.69	0.06	0.03
		5530	/	/	1.200	1.216	98.68	0.06	0.03
		5610	/	/	1.201	1.216	98.77	0.05	0.03
		5775	/	/	5.396	5.413	99.69	0.01	0.03
802.11ax (HEW20)	SISO	5180	RU242	Left	4.400	4.416	99.64	0.02	0.04
		5200	RU242	Left	4.400	4.416	99.64	0.02	0.04
		5240	RU242	Left	4.401	4.418	99.62	0.02	0.03
		5260	RU242	Left	4.400	4.418	99.59	0.02	0.04
		5300	RU242	Left	4.401	4.418	99.62	0.02	0.03
		5320	RU242	Left	4.400	4.417	99.62	0.02	0.03
		5500	RU242	Left	4.401	4.418	99.62	0.02	0.03
		5580	RU242	Left	4.399	4.416	99.62	0.02	0.03
		5700	RU242	Left	4.401	4.418	99.62	0.02	0.03



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241000395408

Page: 274 of 498

		5745	RU242	Left	4.400	4.417	99.62	0.02	0.04
		5785	RU242	Left	4.401	4.417	99.64	0.02	0.03
		5825	RU242	Left	4.349	4.589	94.77	0.23	0.03
802.11ax (HEW40)	SISO	5190	RU484	Left	2.213	2.340	94.57	0.24	0.10
		5230	RU484	Left	2.212	2.340	94.53	0.24	0.10
		5270	RU484	Left	2.213	2.341	94.53	0.24	0.13
		5310	RU484	Left	2.212	2.340	94.53	0.24	0.10
		5510	RU484	Left	2.213	2.341	94.53	0.24	0.10
		5550	RU484	Left	2.212	2.340	94.53	0.24	0.10
		5670	RU484	Left	2.213	2.340	94.57	0.24	0.10
		5755	RU484	Left	2.236	2.252	99.29	0.03	0.04
		5795	RU484	Left	2.237	2.253	99.29	0.03	0.04
802.11ax (HEW80)	SISO	5210	RU996	Left	1.097	1.165	94.16	0.26	0.16
		5290	RU996	Left	1.097	1.165	94.16	0.26	0.19
		5530	RU996	Left	1.096	1.164	94.16	0.26	0.16
		5610	RU996	Left	1.096	1.165	94.08	0.27	0.20
		5775	RU996	Left	1.109	1.124	98.67	0.06	0.03



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


1.2 Test Graph

1.2.1 Ant12





802.11a_HCH_5240MHz_Ant12_NTNV



802.11a_LCH_5260MHz_Ant12_NTNV

