

RF Exposure evaluation

FCC ID: 2AUYR-DSDR01A-11D

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

DSDR01A can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	5.8G	FPC Antenna	5.0GHz – 6.0GHz	5.85dBi
Antenna 2	5.8G	FPC Antenna	5.0GHz – 6.0GHz	5.85dBi

5. Conducted power

[5.8GHz WLAN]

Mode	Channel	Frequency	Average Conducted Output Power (dBm)	
			Antenna 1	Antenna 2
802.11a	149	2412	11.19	10.5
	157	2437	10.88	10.99
	165	2462	10.97	10.83
802.11n(HT20)	149	2412	10.9	10.93
	157	2437	10.38	10.76
	165	2462	10.78	10.9
802.11n(HT40)	151	2412	11.02	11.08
	159	2437	10.8	10.79

6. Manufacturing Tolerance

5.8GHz WLAN

IEEE 802.11a (Average)						
Frequency (MHz)	Antenna 1			Antenna 2		
	5745	5785	5825	5745	5785	5825
Target (dBm)	11.0	10.0	10.0	10.0	11.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)						
Frequency (MHz)	Antenna 1			Antenna 2		
	5745	5785	5825	5745	5785	5825
Target (dBm)	10.0	10.0	10.0	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)						
Frequency (MHz)	Antenna 1			Antenna 2		
	5755	5795		5755	5795	
Target (dBm)	11.0	10.0		11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0		1.0	1.0	

7. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna is 2dBi, the RF power density can be obtained.

5.8GHz WLAN Antenna1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	12.00	15.8489	5.85	3.8459	100%	0.0121	1.0000
IEEE 802.11HT20	11.00	12.5893	5.85	3.8459	100%	0.0096	1.0000
IEEE 802.11n HT40	12.00	15.8489	5.85	3.8459	100%	0.0121	1.0000

5.8GHz WLAN Antenna2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	11.00	12.5893	5.85	3.8459	100%	0.0096	1.0000
IEEE 802.11HT20	11.00	12.5893	5.85	3.8459	100%	0.0096	1.0000
IEEE 802.11n HT40	12.00	15.8489	5.85	3.8459	100%	0.0121	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;

3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7.1 Simultaneous Transmission MPE Evaluation

The sample supports 2 antennas for 5G WLAN. The 5.8G WLAN can transmit simultaneous. According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Σ of MPE ratios ≤ 1.0

Modulation Type	Work Frequency Band	Transmit Antenna		Antenna 1 Antenna 2 Synchronization transmit
		Antenna 1	Antenna 2	
IEEE 802.11n HT20	5.8GHz	Yes	Yes	Yes
IEEE 802.11n HT40	5.8GHz	Yes	Yes	Yes

7.3 Summary simultaneous transmission results

Antenna 1 and Antenna 2 for 5.8G WLAN

Modulation Type	MPE Antenna0 (mW/cm ²)	MPE Antenna1 (mW/cm ²)	Σ MPE ratios	Limit	Results
IEEE 802.11n HT20	0.0096	0.0096	0.0192	1.0	Yes
IEEE 802.11n HT40	0.0096	0.0096	0.0192	1.0	Yes

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----