

Appendix B

RF Test Data for BT V5.0(BDR/EDR) (Conducted Measurement)

Product Name: Bluetooth Headphones

Trade Mark: N/A


Test Model: C1

Environmental Conditions

Temperature:	23.4 ° C
Relative Humidity:	54.1%
ATM Pressure:	100.0 kPa
Test Engineer:	David.Luo
Supervised by:	Li Huan

B.1 Duty Cycle

Test Mode	Test Channel	Ant	Duty Cycle[%]	Verdict
BT LE	2440	Ant1	100	PASS




B.2 Maximum Conducted Peak Output Power


Mode	Channel	Conduct Peak Power[dBm]	Limit [dBm]	Verdict
BT LE	LCH	-4.769	30	PASS
BT LE	MCH	-3.645	30	PASS
BT LE	HCH	-3.783	30	PASS

Test Graphs


LCH



MCH



HCH




B.3 Maximum Power Spectral Density


Mode	Channel	PSD [dBm/3KHz]	Limit [dBm/3KHz]	Verdict
BT LE	LCH	-19.485	8	PASS
BT LE	MCH	-18.596	8	PASS
BT LE	HCH	-19.548	8	PASS

Test Graphs


LCH



MCH



HCH




B.4 6dB Bandwidth


Mode	Channel	6dB Bandwidth [MHz]	Limit [MHz]	Verdict
BT LE	LCH	0.6887	≥ 0.5	PASS
BT LE	MCH	0.6892	≥ 0.5	PASS
BT LE	HCH	0.6910	≥ 0.5	PASS

Test Graphs


LCH



MCH




HCH



B.5 RF Conducted Spurious Emissions


Mode	Channel	Pref [dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
BT LE	LCH	-5.191	-36.993	-25.191	PASS
BT LE	MCH	-4.24	-37.015	-24.240	PASS
BT LE	HCH	-4.384	-37.393	-24.384	PASS

BT LE LCH Graphs




BT LE MCH Graphs

Pref/BT LE/MCH




Puw/BT LE/MCH



BT LE HCH Graphs

Pref/BT LE/HCH



Puw/BT LE/HCH




B.6 Band-edge for RF Conducted Emissions

Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
BT LE	LCH	-5.457	-49.836	-25.46	PASS
BT LE	HCH	-4.325	-49.585	-24.33	PASS

Test Graphs

LCH



Frequency

Auto Tune

Center Freq
2.357000000 GHz


Start Freq
2.310000000 GHz

Stop Freq
2.404000000 GHz

CF Step
9.400000 MHz

Freq Offset
0 Hz

HCH



Frequency

Auto Tune

Center Freq
2.489000000 GHz

Start Freq
2.478000000 GHz

Stop Freq
2.500000000 GHz


CF Step
2.200000 MHz

Freq Offset
0 Hz


B.7 Restrict-band band-edge measurements

Test Mode	Test Channel	Ant	Freq.	Power [dBm]	Gain	Ground Factor	E [dBuV/m]	Detector	Limit [dBuV/m]	Verdi
BT LE	2402	Ant1	2310.0	-42.66	2.0	0	54.57	PEAK	74	PASS
		Ant1	2310.0	-53.17	2.0	0	44.06	AV	54	PASS
		Ant1	2390.0	-43.40	2.0	0	53.83	PEAK	74	PASS
		Ant1	2390.0	-52.82	2.0	0	44.41	AV	54	PASS
	2480	Ant1	2483.5	-41.49	2.0	0	55.74	PEAK	74	PASS
		Ant1	2483.5	-52.37	2.0	0	44.86	AV	54	PASS
		Ant1	2500.0	-41.78	2.0	0	55.45	PEAK	74	PASS
		Ant1	2500.0	-52.27	2.0	0	44.96	AV	54	PASS


Restrict-band band-edge measurements_BT LE_2402_Ant1_PEAK



Restrict-band band-edge measurements_BT LE_2402_Ant1_AV



Restrict-band band-edge measurements_BT LE_2480_Ant1_PEAK



Restrict-band band-edge measurements_BT LE_2480_Ant1_AV

