

TEST REPORT

Applicant: Shenzhen Dangs Science and Technology Co., Ltd
Address of Applicant: 901,GDC Building,Keji Mid 3rd Road, Maling Community,
Yuehai Sub-district,Nanshan, Shenzhen, China 518057
Manufacturer: Shenzhen Dangs Science and Technology Co., Ltd
Address of Manufacturer: 901,GDC Building,Keji Mid 3rd Road, Maling Community,
Yuehai Sub-district,Nanshan, Shenzhen, China 518057
Factory: LENOVO(HUIYANG)ELECTRONIC INDUSTRIAL CO.,LTD
Address of Factory: LENOVO SCIENCE & TECHNOLOGY PARK,HUIYANG
ECONOMIC DEVELOPMENT ZONE, HUIZHOU,
GUANGDONG, CHINA

Equipment Under Test (EUT)

Product Name: Smart Projector
Model No.: See section 5.1
FCC ID: 2AV2J-DBX3
IC: 27636-DBX3
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
RSS-Gen Issue 5
RSS-247 Issue 2
Date of sample receipt: August 01, 2021
Date of Test: August 02-19, 2021
Date of report issued: August 20, 2021
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Liu


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	August 20, 2021	Original

Prepared By:




Date:

August 20, 2021

Project Engineer

Check By:



Date:

August 20, 2021

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER	14
7.4 CHANNEL BANDWIDTH	15
7.5 POWER SPECTRAL DENSITY	16
7.6 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS	17
7.6.1 Conducted Emission Method	17
7.6.2 Radiated Emission Method	18
7.7 FREQUENCY STABILITY	39
8 TEST SETUP PHOTO	40
9 EUT CONSTRUCTIONAL DETAILS	40

4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c) RSS-Gen Section 6.8	Pass
AC Power Line Conducted Emission	FCC part 15.207 RSS-Gen Section 8.8	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3) RSS-247 Section 5.4(d)	Pass
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2) RSS-247 Section 5.2(a) & RSS-Gen 6.7	Pass
Power Spectral Density	FCC part 15.247 (e) RSS-247 Section 5.2(b)	Pass
Band Edge	FCC part 15.247(d) RSS-Gen 8.10 & RSS-247 5.5	Pass
Spurious Emission	FCC part 15.205/15.209 RSS-Gen Section 8.9 & 8.10	Pass

Remark: Test according to ANSI C63.10:2013 and RSS-Gen

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Smart Projector
FCC Model No.:	DBX***** (for internal coding and trading purpose, "*****" in model can respectively be 0-9, A-Z, +, -, /, () or blank.)
IC Model No.:	DBX3, DBX3S, DBX3A, DBJG3X, DBJG21A
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The difference is model name for commercial purpose.	
Test Model No.:	DBX3
Test sample(s) ID:	GTS202107000305-1
Sample(s) Status	Engineer sample
Serial No.:	DZLX34211501482
Hardware version:	LF_9652_V11
Software version:	2.1.9.6
Operation Frequency:	802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11 802.11n(HT40): 9
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(HT20) /802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Integral Antenna
Antenna gain:	ANT 1: 4.4dBi ANT 2: 4.2dBi
Power supply:	ADAPTER MODEL: HKA180180A0-6B INPUT: AC 100-240V,60/50Hz 2.5A OUTPUT: DC 18.0V, 10.0A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
-------------------	--

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
Lenovo	Notebook PC	E40	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology SerSvices Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **IC —Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test software provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 24 2021	June. 23 2022
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 24 2021	June. 23 2022
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 24 2021	June. 23 2022
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 24 2021	June. 23 2022
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 24 2021	June. 23 2022
9	Coaxial Cable	GTS	N/A	GTS211	June. 24 2021	June. 23 2022
10	Coaxial cable	GTS	N/A	GTS210	June. 24 2021	June. 23 2022
11	Coaxial Cable	GTS	N/A	GTS212	June. 24 2021	June. 23 2022
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 24 2021	June. 23 2022
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 24 2021	June. 23 2022
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 24 2021	June. 23 2022
15	Band filter	Amindeon	82346	GTS219	June. 24 2021	June. 23 2022
16	Power Meter	Anritsu	ML2495A	GTS540	June. 24 2021	June. 23 2022
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 24 2021	June. 23 2022
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 24 2021	June. 23 2022
19	Splitter	Agilent	11636B	GTS237	June. 24 2021	June. 23 2022
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 24 2021	June. 23 2022
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 18 2020	Oct. 17 2021
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 18 2020	Oct. 17 2021
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 18 2020	Oct. 17 2021
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 24 2021	June. 23 2022

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 24 2021	June. 23 2022
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 24 2021	June. 23 2022
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 24 2021	June. 23 2022
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 24 2021	June. 23 2022
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 24 2021	June. 23 2022
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 24 2021	June. 23 2022
10	High voltage probe	SCHWARZBECK	TK9420	GTS537	July. 09 2021	July. 08 2022

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 24 2021	June. 23 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 24 2021	June. 23 2022
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 24 2021	June. 23 2022
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 24 2021	June. 23 2022
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 24 2021	June. 23 2022
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 24 2021	June. 23 2022
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 24 2021	June. 23 2022
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 24 2021	June. 23 2022

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 24 2021	June. 23 2022
2	Barometer	ChangChun	DYM3	GTS255	June. 24 2021	June. 23 2022

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
Standard requirement:	RSS-Gen Section 6.8
A transmitter can only be sold or operated with antennas with which it was approved. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. For transmitters of RF output power of 10 milliwatts or less, only the portion of the antenna gain that is in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power to demonstrate compliance with the radiated power limits specified in the applicable standard. For transmitters of output power greater than 10 milliwatts, the total antenna gain shall be added to the measured RF output power to demonstrate compliance to the specified radiated power	
EUT Antenna:	
<i>The antenna is integral antenna, reference to the appendix II for details</i>	

7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207 RSS-Gen Section 8.8					
Test Method:	ANSI C63.10:2013 and RSS-Gen					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane <i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i>					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.


Measurement data

Pre-scan all test modes, found worst case at 802.11n(HT20) 2437MHz, and so only show the test result of 802.11n(HT20) 2437MHz

Line:



Neutral:




Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.16	27.50	10.40	0.01	37.91	65.34	-27.43	QP
0.16	24.48	10.40	0.01	34.89	55.34	-20.45	Average
0.28	29.99	10.40	0.01	40.40	60.68	-20.28	QP
0.28	23.50	10.40	0.01	33.91	50.68	-16.77	Average
0.32	30.55	10.39	0.01	40.95	59.80	-18.85	QP
0.32	19.52	10.39	0.01	29.92	49.80	-19.88	Average
0.63	26.04	10.28	0.02	36.34	56.00	-19.66	QP
0.63	17.58	10.28	0.02	27.88	46.00	-18.12	Average
4.36	14.53	10.20	0.06	24.79	56.00	-31.21	QP
4.36	3.65	10.20	0.06	13.91	46.00	-32.09	Average
16.40	18.77	10.23	0.17	29.17	60.00	-30.83	QP
16.40	11.09	10.23	0.17	21.49	50.00	-28.51	Average

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Conducted Peak Output Power

Test Requirement :	FCC Part15 C Section 15.247 (b)(3) RSS-247 Section 5.4(d)
Test Method :	KDB558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013 and RSS-Gen
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A Power Meter is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Power Meter and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for WIFI 2.4G

7.4 Channel Bandwidth

Test Requirement :	FCC Part15 C Section 15.247 (a)(2) RSS-Gen Section 6.7 & RSS-247 Section 5.2(a)
Test Method :	KDB558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013 and RSS-Gen
Limit:	>500KHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WIFI 2.4G


7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e) RSS-247 Section 5.2(b)
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013 and RSS-Gen
Limit:	8dBm/3kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WIFI 2.4G

7.6 Spurious Emission in Non-restricted & restricted Bands




7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d) RSS-247 Section 5.5
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02 RSS-Gen
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WIFI 2.4G

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205 RSS-247 Section 3.3 & RSS-Gen Section 8.9																												
Test Method:	ANSI C63.10:2013 & RSS-Gen																												
Test Frequency Range:	9kHz to 25GHz																												
Test site:	Measurement Distance: 3m																												
Receiver setup:	Frequency	Detector	RBW	VBW	Value																								
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak																								
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak																								
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak																								
	Above 1GHz	Peak	1MHz	3MHz	Peak																								
Peak		1MHz	10Hz	Average																									
FCC Limit:	<table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100**</td><td>3</td></tr><tr><td>88-216</td><td>150**</td><td>3</td></tr><tr><td>216-960</td><td>200**</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>					Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100**	3	88-216	150**	3	216-960	200**	3	Above 960	500	3
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																										
	0.009-0.490	2400/F(kHz)	300																										
	0.490-1.705	24000/F(kHz)	30																										
	1.705-30.0	30	30																										
	30-88	100**	3																										
	88-216	150**	3																										
	216-960	200**	3																										
	Above 960	500	3																										
	The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.																												
IC Limit:	Table 5 – General field strength limits at frequencies above 30 MHz																												
	<table><tr><th>Frequency (MHz)</th><th>Field strength (µV/m at 3 m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 – 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency (MHz)	Field strength (µV/m at 3 m)	30 – 88	100	88 – 216	150	216 – 960	200	Above 960	500																	
	Frequency (MHz)	Field strength (µV/m at 3 m)																											
	30 – 88	100																											
	88 – 216	150																											
	216 – 960	200																											
	Above 960	500																											
	Table 6 – General field strength limits at frequencies below 30 MHz																												
	<table><tr><th>Frequency</th><th>Magnetic field strength (H-Field) (µA/m)</th><th>Measurement distance (m)</th></tr><tr><td>9 - 490 kHz ¹</td><td>6.37/F (F in kHz)</td><td>300</td></tr><tr><td>490 - 1705 kHz</td><td>63.7/F (F in kHz)</td><td>30</td></tr><tr><td>1.705 - 30 MHz</td><td>0.08</td><td>30</td></tr></table>			Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)	9 - 490 kHz ¹	6.37/F (F in kHz)	300	490 - 1705 kHz	63.7/F (F in kHz)	30	1.705 - 30 MHz	0.08	30														
	Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)																										
9 - 490 kHz ¹	6.37/F (F in kHz)	300																											
490 - 1705 kHz	63.7/F (F in kHz)	30																											
1.705 - 30 MHz	0.08	30																											
Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.																													

Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to 1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

	3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test results:	Pass					

Measurement data:

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.
Only shown the worst case test data.


■ 9kHz~30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.


■ Below 1GHz

Pre-scan all test modes, found worst case at 802.11n(HT20) 2437MHz, and so only show the test result of 802.11n(HT20) 2437MHz

Horizontal:



Vertical:



■ Above 1GHz

■ Unwanted Emissions in non-restricted Frequency Bands

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	36.17	31.79	8.62	32.10	44.48	74.00	-29.52	Vertical
7236.00	31.61	36.19	11.68	31.97	47.51	74.00	-26.49	Vertical
9648.00	30.85	38.07	14.16	31.56	51.52	74.00	-22.48	Vertical
4824.00	35.48	31.79	8.62	32.10	43.79	74.00	-30.21	Horizontal
7236.00	31.69	36.19	11.68	31.97	47.59	74.00	-26.41	Horizontal
9648.00	30.57	38.07	14.16	31.56	51.24	74.00	-22.76	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	25.58	31.79	8.62	32.10	33.89	54.00	-20.11	Vertical
7236.00	20.57	36.19	11.68	31.97	36.47	54.00	-17.53	Vertical
9648.00	21.27	38.07	14.16	31.56	41.94	54.00	-12.06	Vertical
4824.00	25.23	31.79	8.62	32.10	33.54	54.00	-20.46	Horizontal
7236.00	20.34	36.19	11.68	31.97	36.24	54.00	-17.76	Horizontal
9648.00	20.38	38.07	14.16	31.56	41.05	54.00	-12.95	Horizontal

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	35.94	31.85	8.66	32.12	44.33	74.00	-29.67	Vertical
7311.00	32.13	36.37	11.71	31.91	48.30	74.00	-25.70	Vertical
9748.00	32.19	38.27	14.25	31.56	53.15	74.00	-20.85	Vertical
4874.00	36.95	31.85	8.66	32.12	45.34	74.00	-28.66	Horizontal
7311.00	31.04	36.37	11.71	31.91	47.21	74.00	-26.79	Horizontal
9748.00	32.20	38.27	14.25	31.56	53.16	74.00	-20.84	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	27.06	31.85	8.66	32.12	35.45	54.00	-18.55	Vertical
7311.00	20.52	36.37	11.71	31.91	36.69	54.00	-17.31	Vertical
9748.00	21.51	38.27	14.25	31.56	42.47	54.00	-11.53	Vertical
4874.00	27.24	31.85	8.66	32.12	35.63	54.00	-18.37	Horizontal
7311.00	20.19	36.37	11.71	31.91	36.36	54.00	-17.64	Horizontal
9748.00	21.97	38.27	14.25	31.56	42.93	54.00	-11.07	Horizontal

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	39.00	31.90	8.70	32.15	47.45	74.00	-26.55	Vertical
7386.00	31.25	36.49	11.76	31.83	47.67	74.00	-26.33	Vertical
9848.00	34.37	38.62	14.31	31.77	55.53	74.00	-18.47	Vertical
4924.00	39.22	31.90	8.70	32.15	47.67	74.00	-26.33	Horizontal
7386.00	30.62	36.49	11.76	31.83	47.04	74.00	-26.96	Horizontal
9848.00	30.75	38.62	14.31	31.77	51.91	74.00	-22.09	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	30.38	31.90	8.70	32.15	38.83	54.00	-15.17	Vertical
7386.00	21.29	36.49	11.76	31.83	37.71	54.00	-16.29	Vertical
9848.00	22.98	38.62	14.31	31.77	44.14	54.00	-9.86	Vertical
4924.00	29.89	31.90	8.70	32.15	38.34	54.00	-15.66	Horizontal
7386.00	20.10	36.49	11.76	31.83	36.52	54.00	-17.48	Horizontal
9848.00	20.10	38.62	14.31	31.77	41.26	54.00	-12.74	Horizontal

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	35.62	31.79	8.62	32.10	43.93	74.00	-30.07	Vertical
7236.00	31.26	36.19	11.68	31.97	47.16	74.00	-26.84	Vertical
9648.00	30.60	38.07	14.16	31.56	51.27	74.00	-22.73	Vertical
4824.00	35.02	31.79	8.62	32.10	43.33	74.00	-30.67	Horizontal
7236.00	31.38	36.19	11.68	31.97	47.28	74.00	-26.72	Horizontal
9648.00	30.34	38.07	14.16	31.56	51.01	74.00	-22.99	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	25.07	31.79	8.62	32.10	33.38	54.00	-20.62	Vertical
7236.00	20.23	36.19	11.68	31.97	36.13	54.00	-17.87	Vertical
9648.00	21.03	38.07	14.16	31.56	41.70	54.00	-12.30	Vertical
4824.00	24.80	31.79	8.62	32.10	33.11	54.00	-20.89	Horizontal
7236.00	20.04	36.19	11.68	31.97	35.94	54.00	-18.06	Horizontal
9648.00	20.16	38.07	14.16	31.56	40.83	54.00	-13.17	Horizontal

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	35.48	31.85	8.66	32.12	43.87	74.00	-30.13	Vertical
7311.00	31.84	36.37	11.71	31.91	48.01	74.00	-25.99	Vertical
9748.00	31.99	38.27	14.25	31.56	52.95	74.00	-21.05	Vertical
4874.00	36.56	31.85	8.66	32.12	44.95	74.00	-29.05	Horizontal
7311.00	30.79	36.37	11.71	31.91	46.96	74.00	-27.04	Horizontal
9748.00	32.01	38.27	14.25	31.56	52.97	74.00	-21.03	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	26.64	31.85	8.66	32.12	35.03	54.00	-18.97	Vertical
7311.00	20.25	36.37	11.71	31.91	36.42	54.00	-17.58	Vertical
9748.00	21.31	38.27	14.25	31.56	42.27	54.00	-11.73	Vertical
4874.00	26.88	31.85	8.66	32.12	35.27	54.00	-18.73	Horizontal
7311.00	19.95	36.37	11.71	31.91	36.12	54.00	-17.88	Horizontal
9748.00	21.78	38.27	14.25	31.56	42.74	54.00	-11.26	Horizontal

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	38.22	31.90	8.70	32.15	46.67	74.00	-27.33	Vertical
7386.00	30.75	36.49	11.76	31.83	47.17	74.00	-26.83	Vertical
9848.00	34.02	38.62	14.31	31.77	55.18	74.00	-18.82	Vertical
4924.00	38.56	31.90	8.70	32.15	47.01	74.00	-26.99	Horizontal
7386.00	30.18	36.49	11.76	31.83	46.60	74.00	-27.40	Horizontal
9848.00	30.42	38.62	14.31	31.77	51.58	74.00	-22.42	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	29.65	31.90	8.70	32.15	38.10	54.00	-15.90	Vertical
7386.00	20.81	36.49	11.76	31.83	37.23	54.00	-16.77	Vertical
9848.00	22.64	38.62	14.31	31.77	43.80	54.00	-10.20	Vertical
4924.00	29.27	31.90	8.70	32.15	37.72	54.00	-16.28	Horizontal
7386.00	19.68	36.49	11.76	31.83	36.10	54.00	-17.90	Horizontal
9848.00	19.78	38.62	14.31	31.77	40.94	54.00	-13.06	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	35.91	31.79	8.62	32.10	44.22	74.00	-29.78	Vertical
7236.00	31.45	36.19	11.68	31.97	47.35	74.00	-26.65	Vertical
9648.00	30.73	38.07	14.16	31.56	51.40	74.00	-22.60	Vertical
4824.00	35.26	31.79	8.62	32.10	43.57	74.00	-30.43	Horizontal
7236.00	31.55	36.19	11.68	31.97	47.45	74.00	-26.55	Horizontal
9648.00	30.46	38.07	14.16	31.56	51.13	74.00	-22.87	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	25.34	31.79	8.62	32.10	33.65	54.00	-20.35	Vertical
7236.00	20.41	36.19	11.68	31.97	36.31	54.00	-17.69	Vertical
9648.00	21.16	38.07	14.16	31.56	41.83	54.00	-12.17	Vertical
4824.00	25.03	31.79	8.62	32.10	33.34	54.00	-20.66	Horizontal
7236.00	20.20	36.19	11.68	31.97	36.10	54.00	-17.90	Horizontal
9648.00	20.28	38.07	14.16	31.56	40.95	54.00	-13.05	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	35.73	31.85	8.66	32.12	44.12	74.00	-29.88	Vertical
7311.00	32.00	36.37	11.71	31.91	48.17	74.00	-25.83	Vertical
9748.00	32.09	38.27	14.25	31.56	53.05	74.00	-20.95	Vertical
4874.00	36.77	31.85	8.66	32.12	45.16	74.00	-28.84	Horizontal
7311.00	30.93	36.37	11.71	31.91	47.10	74.00	-26.90	Horizontal
9748.00	32.11	38.27	14.25	31.56	53.07	74.00	-20.93	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	26.86	31.85	8.66	32.12	35.25	54.00	-18.75	Vertical
7311.00	20.39	36.37	11.71	31.91	36.56	54.00	-17.44	Vertical
9748.00	21.41	38.27	14.25	31.56	42.37	54.00	-11.63	Vertical
4874.00	27.07	31.85	8.66	32.12	35.46	54.00	-18.54	Horizontal
7311.00	20.08	36.37	11.71	31.91	36.25	54.00	-17.75	Horizontal
9748.00	21.88	38.27	14.25	31.56	42.84	54.00	-11.16	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	38.64	31.90	8.70	32.15	47.09	74.00	-26.91	4924.00
7386.00	31.02	36.49	11.76	31.83	47.44	74.00	-26.56	7386.00
9848.00	34.21	38.62	14.31	31.77	55.37	74.00	-18.63	9848.00
4924.00	38.91	31.90	8.70	32.15	47.36	74.00	-26.64	Horizontal
7386.00	30.41	36.49	11.76	31.83	46.83	74.00	-27.17	Horizontal
9848.00	30.59	38.62	14.31	31.77	51.75	74.00	-22.25	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	30.04	31.90	8.70	32.15	38.49	54.00	-15.51	Vertical
7386.00	21.07	36.49	11.76	31.83	37.49	54.00	-16.51	Vertical
9848.00	22.82	38.62	14.31	31.77	43.98	54.00	-10.02	Vertical
4924.00	29.60	31.90	8.70	32.15	38.05	54.00	-15.95	Horizontal
7386.00	19.91	36.49	11.76	31.83	36.33	54.00	-17.67	Horizontal
9848.00	19.95	38.62	14.31	31.77	41.11	54.00	-12.89	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	35.33	31.81	8.63	32.11	43.66	74.00	-30.34	Vertical
7266.00	31.08	36.28	11.69	31.94	47.11	74.00	-26.89	Vertical
9688.00	30.47	38.13	14.21	31.52	51.29	74.00	-22.71	Vertical
4844.00	34.77	31.81	8.63	32.11	43.10	74.00	-30.90	Horizontal
7266.00	31.22	36.28	11.69	31.94	47.25	74.00	-26.75	Horizontal
9688.00	30.22	38.13	14.21	31.52	51.04	74.00	-22.96	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	24.80	31.81	8.63	32.11	33.13	54.00	-20.87	Vertical
7266.00	20.05	36.28	11.69	31.94	36.08	54.00	-17.92	Vertical
9688.00	20.90	38.13	14.21	31.52	41.72	54.00	-12.28	Vertical
4844.00	24.57	31.81	8.63	32.11	32.90	54.00	-21.10	Horizontal
7266.00	19.89	36.28	11.69	31.94	35.92	54.00	-18.08	Horizontal
9688.00	20.04	38.13	14.21	31.52	40.86	54.00	-13.14	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	35.24	31.85	8.66	32.12	43.63	74.00	-30.37	Vertical
7311.00	31.69	36.37	11.71	31.91	47.86	74.00	-26.14	Vertical
9748.00	31.88	38.27	14.25	31.56	52.84	74.00	-21.16	Vertical
4874.00	36.36	31.85	8.66	32.12	44.75	74.00	-29.25	Horizontal
7311.00	30.66	36.37	11.71	31.91	46.83	74.00	-27.17	Horizontal
9748.00	31.91	38.27	14.25	31.56	52.87	74.00	-21.13	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	26.42	31.85	8.66	32.12	34.81	54.00	-19.19	Vertical
7311.00	20.10	36.37	11.71	31.91	36.27	54.00	-17.73	Vertical
9748.00	21.20	38.27	14.25	31.56	42.16	54.00	-11.84	Vertical
4874.00	26.69	31.85	8.66	32.12	35.08	54.00	-18.92	Horizontal
7311.00	19.82	36.37	11.71	31.91	35.99	54.00	-18.01	Horizontal
9748.00	21.69	38.27	14.25	31.56	42.65	54.00	-11.35	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	37.80	31.88	8.68	32.13	46.23	74.00	-27.77	4924.00
7356.00	30.49	36.45	11.75	31.86	46.83	74.00	-27.17	7386.00
9808.00	33.83	38.43	14.29	31.68	54.87	74.00	-19.13	9848.00
4904.00	38.21	31.88	8.68	32.13	46.64	74.00	-27.36	Horizontal
7356.00	29.95	36.45	11.75	31.86	46.29	74.00	-27.71	Horizontal
9808.00	30.24	38.43	14.29	31.68	51.28	74.00	-22.72	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	29.27	31.88	8.68	32.13	37.70	54.00	-16.30	Vertical
7356.00	20.56	36.45	11.75	31.86	36.90	54.00	-17.10	Vertical
9808.00	22.46	38.43	14.29	31.68	43.50	54.00	-10.50	Vertical
4904.00	28.94	31.88	8.68	32.13	37.37	54.00	-16.63	Horizontal
7356.00	19.46	36.45	11.75	31.86	35.80	54.00	-18.20	Horizontal
9808.00	19.61	38.43	14.29	31.68	40.65	54.00	-13.35	Horizontal

Notes:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in restricted Frequency Bands

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	37.80	27.14	6.19	42.04	29.09	74.00	-44.91	Horizontal
2390.00	45.53	27.37	6.31	42.11	37.10	74.00	-36.90	Horizontal
2310.00	36.22	27.14	6.19	42.04	27.51	74.00	-46.49	Vertical
2390.00	46.29	27.37	6.31	42.11	37.86	74.00	-36.14	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	28.67	27.14	6.19	42.04	19.96	54.00	-34.04	Horizontal
2390.00	35.55	27.37	6.31	42.11	27.12	54.00	-26.88	Horizontal
2310.00	27.18	27.14	6.19	42.04	18.47	54.00	-35.53	Vertical
2390.00	37.38	27.37	6.31	42.11	28.95	54.00	-25.05	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	45.81	27.66	6.45	42.01	37.91	74.00	-36.09	Horizontal
2500.00	38.87	27.70	6.47	42.00	31.04	74.00	-42.96	Horizontal
2483.50	45.28	27.66	6.45	42.01	37.38	74.00	-36.62	Vertical
2500.00	39.68	27.70	6.47	42.00	31.85	74.00	-42.15	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.46	27.66	6.45	42.01	27.56	54.00	-26.44	Horizontal
2500.00	32.29	27.70	6.47	42.00	24.46	54.00	-29.54	Horizontal
2483.50	36.06	27.66	6.45	42.01	28.16	54.00	-25.84	Vertical
2500.00	31.02	27.70	6.47	42.00	23.19	54.00	-30.81	Vertical

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	38.14	27.14	6.19	42.04	29.43	74.00	-44.57	Horizontal
2390.00	45.98	27.37	6.31	42.11	37.55	74.00	-36.45	Horizontal
2310.00	36.58	27.14	6.19	42.04	27.87	74.00	-46.13	Vertical
2390.00	46.83	27.37	6.31	42.11	38.40	74.00	-35.60	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	28.91	27.14	6.19	42.04	20.20	54.00	-33.80	Horizontal
2390.00	35.83	27.37	6.31	42.11	27.40	54.00	-26.60	Horizontal
2310.00	27.45	27.14	6.19	42.04	18.74	54.00	-35.26	Vertical
2390.00	37.69	27.37	6.31	42.11	29.26	54.00	-24.74	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.30	27.66	6.45	42.01	38.40	74.00	-35.60	Horizontal
2500.00	39.25	27.70	6.47	42.00	31.42	74.00	-42.58	Horizontal
2483.50	45.84	27.66	6.45	42.01	37.94	74.00	-36.06	Vertical
2500.00	40.12	27.70	6.47	42.00	32.29	74.00	-41.71	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.75	27.66	6.45	42.01	27.85	54.00	-26.15	Horizontal
2500.00	32.52	27.70	6.47	42.00	24.69	54.00	-29.31	Horizontal
2483.50	36.38	27.66	6.45	42.01	28.48	54.00	-25.52	Vertical
2500.00	31.26	27.70	6.47	42.00	23.43	54.00	-30.57	Vertical

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	38.25	27.14	6.19	42.04	29.54	74.00	-44.46	Horizontal
2390.00	46.12	27.37	6.31	42.11	37.69	74.00	-36.31	Horizontal
2310.00	36.70	27.14	6.19	42.04	27.99	74.00	-46.01	Vertical
2390.00	47.01	27.37	6.31	42.11	38.58	74.00	-35.42	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	28.99	27.14	6.19	42.04	20.28	54.00	-33.72	Horizontal
2390.00	35.92	27.37	6.31	42.11	27.49	54.00	-26.51	Horizontal
2310.00	27.54	27.14	6.19	42.04	18.83	54.00	-35.17	Vertical
2390.00	37.78	27.37	6.31	42.11	29.35	54.00	-24.65	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.45	27.66	6.45	42.01	38.55	74.00	-35.45	Horizontal
2500.00	39.37	27.70	6.47	42.00	31.54	74.00	-42.46	Horizontal
2483.50	46.01	27.66	6.45	42.01	38.11	74.00	-35.89	Vertical
2500.00	40.27	27.70	6.47	42.00	32.44	74.00	-41.56	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.84	27.66	6.45	42.01	27.94	54.00	-26.06	Horizontal
2500.00	32.59	27.70	6.47	42.00	24.76	54.00	-29.24	Horizontal
2483.50	36.48	27.66	6.45	42.01	28.58	54.00	-25.42	Vertical
2500.00	31.34	27.70	6.47	42.00	23.51	54.00	-30.49	Vertical

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	38.26	27.14	6.19	42.04	29.55	74.00	-44.45	Horizontal
2390.00	46.14	27.37	6.31	42.11	37.71	74.00	-36.29	Horizontal
2310.00	36.71	27.14	6.19	42.04	28.00	74.00	-46.00	Vertical
2390.00	47.03	27.37	6.31	42.11	38.60	74.00	-35.40	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.00	27.14	6.19	42.04	20.29	54.00	-33.71	Horizontal
2390.00	35.93	27.37	6.31	42.11	27.50	54.00	-26.50	Horizontal
2310.00	27.55	27.14	6.19	42.04	18.84	54.00	-35.16	Vertical
2390.00	37.79	27.37	6.31	42.11	29.36	54.00	-24.64	Vertical

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.47	27.66	6.45	42.01	38.57	74.00	-35.43	Horizontal
2500.00	39.38	27.70	6.47	42.00	31.55	74.00	-42.45	Horizontal
2483.50	46.03	27.66	6.45	42.01	38.13	74.00	-35.87	Vertical
2500.00	40.28	27.70	6.47	42.00	32.45	74.00	-41.55	Vertical


Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.85	27.66	6.45	42.01	27.95	54.00	-26.05	Horizontal
2500.00	32.60	27.70	6.47	42.00	24.77	54.00	-29.23	Horizontal
2483.50	36.50	27.66	6.45	42.01	28.60	54.00	-25.40	Vertical
2500.00	31.35	27.70	6.47	42.00	23.52	54.00	-30.48	Vertical

Remarks:

1. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
2. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

7.7 Frequency stability

Test Requirement:	RSS-Gen Section 6.11& Section 8.11
Test Method:	ANSI C63.10: 2013 & RSS-Gen
Limit:	Manufactures of devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Test Procedure:	The EUT was setup to ANSI C63.10, 2013; tested to 2.1055 for compliance to RSS-Gen requirements.
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remark: Set the EUT transmits at un-modulation mode to test frequency stability.

Measurement Data: The detailed test data see Appendix for WIFI 2.4G

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----