





FCC AND ISED CERTIFICATION TEST REPORT

| | | | |
|--|---|----------------------------|--|
| Applicant: | Shenzhen Dangs Science and Technology Co., Ltd. | | |
| Address: | 1301, Block D1, Chuangzhi Yuncheng, Liuxian Avenue, Nanshan District, Shenzhen, Guangdong Province, China | | |
| Manufacturer: | Guangzhou Shikun Electronics Co., Ltd | | |
| Address: | No.6 Liankun Road, Huangpu District, Guangzhou, China | | |
| Product Description: | Smart Projector | | |
| Brand Name: | Dangbei | | |
| Tested Model/HVIN: | N2mini | | |
| FCC ID: | 2AV2J-N2MINI | | |
| IC: | 27636-N2MINI | | |
| Report No.: | JCF250114121-002 | | |
| Received Date: | Jan. 14, 2025 | | |
| Tested Date: | Jan. 14, 2025 ~ Feb. 12, 2025 | | |
| Issued Date: | Feb. 12, 2025 | | |
| Test Standards: | FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 3 August 2023 | | |
| Test Procedure: | ANSI C63.10:2013, RSS-Gen Issue 5 A2, Feb. 2021 | | |
| Test Result: | Pass | | |
| Prepared By: | | | |
|  | | | |
| <u>Roger Li/Engineer</u> | | Date: Feb. 12, 2025 | |
| Reviewed By: | | | |
|  | | | |
| <u>Kennys Zhang/Engineer</u> | | Date: Feb. 12, 2025 | |
|  | | | |
| Approved By: | | | |
|  | | | |
| <u>Talent Zhang/Engineer</u> | | Date: Feb. 12, 2025 | |

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

Report Revise Record

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|----------------|-------------|---------------|-----------------|-------|
| V1.0 | / | Feb. 12, 2025 | Original Report | / |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. Test Report Declare | 5 |
| 2. Summary of Test Results | 6 |
| 3. Test Laboratory | 6 |
| 4. Equipment Under Test | 7 |
| 4.1. Description of EUT | 7 |
| 4.2. Channel List | 7 |
| 4.3. Test Channel Configuration | 7 |
| 4.4. Test environment conditions | 8 |
| 4.5. The Worse Case Power Setting Parameter | 8 |
| 4.6. Description of Available Antennas | 8 |
| 5. Description of Test Setup | 8 |
| 5.1. Accessory | 8 |
| 5.2. Support Equipment | 8 |
| 5.3. Test Setup | 8 |
| 5.4. Setup Diagram for Tests | 8 |
| 6. Measurement Uncertainty | 9 |
| 7. Measuring Instrument and Software Used | 9 |
| 8. On Time and Duty Cycle | 11 |
| 8.1. Block diagram of test setup | 11 |
| 8.2. Limits | 11 |
| 8.3. Procedure | 11 |
| 8.4. Results | 11 |
| 8.5. Original test data | 11 |
| 9. 6 dB DTS Bandwidth and 99 % Bandwidth | 14 |
| 9.1. Block diagram of test setup | 14 |
| 9.2. Limits | 14 |
| 9.3. Test Procedure | 14 |
| 9.4. Results | 14 |
| 9.5. Original test data | 15 |
| 10. Peak Conducted Output Power | 19 |
| 10.1. Block diagram of test setup | 19 |
| 10.2. Limits | 19 |
| 10.3. Test Procedure | 19 |
| 10.4. Results | 19 |
| 10.5. Original test data | 20 |
| 11. Power Spectral Density | 22 |
| 11.1. Block diagram of test setup | 22 |
| 11.2. Limits | 22 |
| 11.3. Test Procedure | 22 |
| 11.4. Results | 22 |
| 11.5. Original test data | 23 |
| 12. Conducted Bandedge and Spurious Emissions | 25 |
| 12.1. Block diagram of test setup | 25 |
| 12.2. Limits | 25 |
| 12.3. Test Procedure | 25 |
| 12.4. Results | 25 |
| 12.5. Original test data | 26 |
| 13. Radiated Emission | 34 |
| 13.1. Block diagram of test setup | 34 |
| 13.2. Limit | 35 |
| 13.3. Test Procedure | 36 |
| 13.4. Results | 38 |

- 13.5. Original test data 38
- 14. AC Power Line Conducted Emissions 39**
 - 14.1. Block diagram of test setup 39
 - 14.2. Limits 39
 - 14.3. Test procedure 39
 - 14.4. Test result 40
 - 14.5. Original test data 40
- 15. Antenna Requirements 41**
 - 15.1. Limits 41
 - 15.2. Result 41
- APPENDIX A – Radiated Emission Below 1GHz Test Data 42**
- APPENDIX B – Radiated Emission Above 1GHz Test Data 44**
- APPENDIX C – AC Power Line Conducted Emission Test Data 58**

1. Test Report Declare

| | |
|--------------------------------|---|
| Applicant: | Shenzhen Dangs Science and Technology Co., Ltd. |
| Address: | 1301, Block D1, Chuangzhi Yuncheng, Liuxian Avenue, Nanshan District, Shenzhen, Guangdong Province, China |
| Manufacturer: | Guangzhou Shikun Electronics Co., Ltd |
| Address: | No.6 Liankun Road,Huangpu District,Guangzhou, China |
| Product Name: | Smart Projector |
| Brand Name: | Dangbei |
| Model Name: | N2mini |
| Difference Description: | NA |

We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests except as provided information by clients.

2. Summary of Test Results

| Summary of Test Results | | | |
|-------------------------|--|---|--------------|
| Clause | Test Items | FCC/ISED Rules | Test Results |
| 1 | 6 dB Bandwidth and 99 % Occupied Bandwidth | FCC Part 15.247 (a) (2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7 | Pass |
| 2 | Peak Conducted Output Power | FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (d) | Pass |
| 3 | Power Spectral Density | FCC Part 15.247 (e) RSS-247 Clause 5.2 (b) | Pass |
| 4 | Conducted Bandedge and Spurious Emission | FCC Part 15.247 (d) RSS-247 Clause 5.5 | Pass |
| 5 | Radiated Bandedge and Spurious Emission | FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9 | Pass |
| 6 | Conducted Emission Test For AC Power Port | FCC Part 15.207 RSS-GEN Clause 8.8 | Pass |
| 7 | Antenna Requirement | FCC Part 15.203 RSS-GEN Clause 6.8 | Pass |

3. Test Laboratory

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.10, Hefeng No.1 street, Huangpu District, Guangzhou, Guangdong, People's Republic of China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.03

FCC Designation Number: CN1381. Test Firm Registration Number: 486550

IC Test Firm Registration Number: 31808

Conformity Assessment Body identifier: CN0173

4. Equipment Under Test

4.1. Description of EUT

| | |
|----------------------------------|----------------------------------|
| EUT Name: | Smart Projector |
| Model Number: | N2mini |
| EUT Function Description: | Please refer to the user manual |
| Power Supply: | 100-240V~ 50/60Hz 2A |
| Hardware Version: | NA |
| Software Version: | NA |
| Radio Specification: | Bluetooth V5.4 |
| Operation Frequency: | 2402 MHz - 2480 MHz |
| Modulation: | GFSK |
| Data Rate: | 1Mbps, 2Mbps |
| Antenna Type: | FPC Antenna, MAX. Gain: 1.22 dBi |

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

4.2. Channel List

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0 | 2402 | 11 | 2424 | 22 | 2446 | 33 | 2468 |
| 1 | 2404 | 12 | 2426 | 23 | 2448 | 34 | 2470 |
| 2 | 2406 | 13 | 2428 | 24 | 2450 | 35 | 2472 |
| 3 | 2408 | 14 | 2430 | 25 | 2452 | 36 | 2474 |
| 4 | 2410 | 15 | 2432 | 26 | 2454 | 37 | 2476 |
| 5 | 2412 | 16 | 2434 | 27 | 2456 | 38 | 2478 |
| 6 | 2414 | 17 | 2436 | 28 | 2458 | 39 | 2480 |
| 7 | 2416 | 18 | 2438 | 29 | 2460 | / | / |
| 8 | 2418 | 19 | 2440 | 30 | 2462 | / | / |
| 9 | 2420 | 20 | 2442 | 31 | 2464 | / | / |
| 10 | 2422 | 21 | 2444 | 32 | 2468 | / | / |

4.3. Test Channel Configuration

| Tested mode, channel, information | | |
|-----------------------------------|----------|-----------------|
| Mode | Channel | Frequency (MHz) |
| GFSK | LCH:CH0 | 2402 |
| | MCH:CH19 | 2440 |
| | HCH:CH39 | 2480 |

4.4. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|--------------------|------------|
| Temperature range: | 21-25 °C |
| Humidity range: | 40-75% |
| Pressure range: | 86-106 kPa |

4.5. The Worse Case Power Setting Parameter

| The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band | | | | |
|--|-------------------------|-----------------------------|-------|-------|
| Test Software | | MobaXterm | | |
| Modulation Type | Transmit Antenna Number | Test Software Setting Value | | |
| | | CH 00 | CH 39 | CH 78 |
| GFSK_1M | 1 | 48 | 48 | 48 |
| GFSK_2M | 1 | 48 | 48 | 48 |

4.6. Description of Available Antennas

| Test Mode | Transmit and Receive Mode | Description |
|-----------|--|--|
| GFSK_1M | <input checked="" type="checkbox"/> 1TX, 1RX | Antenna 1 can be used as transmitting/receiving antenna. |
| GFSK_2M | <input checked="" type="checkbox"/> 1TX, 1RX | Antenna 1 can be used as transmitting/receiving antenna. |

5. Description of Test Setup

5.1. Accessory

| Description of Accessories | Manufacturer | Model Number | Description | Remark |
|----------------------------|--------------|--------------|-------------|--------|
| N/A | N/A | N/A | N/A | N/A |

5.2. Support Equipment

| Equipment | Brand Name | Model Name | P/N |
|-----------|------------|------------|-----|
| PC | Lenovo | T480 | / |

5.3. Test Setup

The EUT can work in Fixed Frequency mode.

5.4. Setup Diagram for Tests



6. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Item | Uncertainty |
|------------------------------|-------------|
| AC Power Conduction emission | 1.37 dB |
| All Radiated emissions | 5.4dB |
| Conducted emissions | 3.09 dB |
| Occupied Channel Bandwidth | 1.1% |
| Conducted Output power | 0.82dB |
| Power Spectral Density | 0.82dB |

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of $k = 2$.


7. Measuring Instrument and Software Used

| TS Test System | | | | | | |
|-------------------------------------|----------------------------|--------------|-----------|-------------|---------------|---------------|
| Used | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| <input checked="" type="checkbox"/> | Spectrum Analyzer | Keysight | N9030B | MY56320512 | Aug. 22, 2024 | Aug. 21, 2025 |
| <input checked="" type="checkbox"/> | Vector Signal Generator | Keysight | N5182B | MY57300334 | Aug. 22, 2024 | Aug. 21, 2025 |
| <input checked="" type="checkbox"/> | Signal Generator | Keysight | N5171B | MY57280639 | Aug. 22, 2024 | Aug. 21, 2025 |
| <input checked="" type="checkbox"/> | DC POWER | Keysight | E342A | MY59020356 | Aug. 29, 2024 | Aug. 28, 2025 |
| <input checked="" type="checkbox"/> | Incubator thermometer | GWS | EL-02JA | 21107288 | Aug. 15, 2024 | Aug. 14, 2025 |
| <input checked="" type="checkbox"/> | Control unit(Power sensor) | Tonscend | JS0806-2 | / | Aug. 23, 2024 | Aug. 22, 2025 |
| <input checked="" type="checkbox"/> | Spectrum Analyzer | Keysight | N9020B | MY60112206 | Sep. 11, 2024 | Sep. 10, 2025 |
| <input checked="" type="checkbox"/> | Control unit(Power sensor) | Tonscend | JS0806-2 | 21H8060465 | Aug. 22, 2024 | Aug. 21, 2025 |
| <input checked="" type="checkbox"/> | Spectrum Analyzer | Keysight | N9020B | MY60112811 | Aug. 23, 2024 | Aug. 22, 2025 |
| <input checked="" type="checkbox"/> | Signal Generator | Keysight | N5173B | MY62220145 | Aug. 23, 2024 | Aug. 22, 2025 |
| <input checked="" type="checkbox"/> | Vector Signal Generator | Keysight | N5182B | MY61252859 | Aug. 22, 2024 | Aug. 21, 2025 |
| <input checked="" type="checkbox"/> | DC POWER | Keysight | E3642A | MY40005294 | Aug. 30, 2024 | Aug. 29, 2025 |
| <input checked="" type="checkbox"/> | Control unit(Power sensor) | Tonscend | JS0806-2 | 24F80620865 | Aug. 23, 2024 | Aug. 22, 2025 |
| Software | | | | | | |
| Used | Description | Manufacturer | Name | Version | | |
| <input checked="" type="checkbox"/> | Test software | Tonscend | JS1120-3 | V3.3.10 | | |
| RSE Test System | | | | | | |
| Used | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| <input checked="" type="checkbox"/> | EMI Receiver | R&S | ESR26 | 101424 | Sep. 14, 2024 | Sep. 13, 2025 |
| <input checked="" type="checkbox"/> | Hybrid Antenna | Schwarzbeck | VULB9163 | 01416 | May. 22, 2024 | May. 21, 2025 |

| | | | | | | |
|---|---------------------------|--------------|------------------------------------|------------|---------------|---------------|
| <input checked="" type="checkbox"/> | Horn Antenna 1 | Schwarzbeck | BBHA 9120 D | 02910 | Sep. 11, 2024 | Sep. 10, 2025 |
| <input checked="" type="checkbox"/> | Horn Antenna 2 | ETS | BBHA 9170 | 1090 | Sep. 11, 2024 | Sep. 10, 2025 |
| <input checked="" type="checkbox"/> | loop-antenna | Schwarzbeck | FMZB 1513-60 | 00030 | Jan. 12, 2025 | Jan. 11, 2026 |
| <input checked="" type="checkbox"/> | Test path | / | Path2: WIFI-2.4G 1-3GHz | / | Aug. 23, 2024 | Aug. 22, 2025 |
| <input checked="" type="checkbox"/> | Test path | / | Path7: ALL PASS 1-18GHz | / | Aug. 23, 2024 | Aug. 22, 2025 |
| <input checked="" type="checkbox"/> | Test path | / | Path9: 3GHz High PASS 3-18GHz | / | Aug. 23, 2024 | Aug. 22, 2025 |
| <input checked="" type="checkbox"/> | Test path | / | Path16: 30MHz-1GHz ALL PASS NO AMP | / | Aug. 23, 2024 | Aug. 22, 2025 |
| <input checked="" type="checkbox"/> | Signal Pre-Amplifier | ETS | 3116C-PA | 00217677 | Sep. 06, 2024 | Sep. 05, 2025 |
| <input checked="" type="checkbox"/> | 3m Fully-anechoic Chamber | YIHENG | 9m*6m*6m | 001 | Sep. 05, 2023 | Sep. 04, 2026 |
| Software | | | | | | |
| Used | Description | Manufacturer | Name | | Version | |
| <input checked="" type="checkbox"/> | Test software | Tonscend | TS+ | | V5.0.0.0 | |
| Conducted Emission Test For AC Power Port | | | | | | |
| Used | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| <input checked="" type="checkbox"/> | LISN | R&S | ENV216 | 102509 | Aug. 22, 2024 | Aug. 21, 2025 |
| <input checked="" type="checkbox"/> | EMI Receiver | R&S | ESR | 102154 | Aug. 22, 2024 | Aug. 21, 2025 |
| Software | | | | | | |
| Used | Description | Manufacturer | Name | | Version | |
| <input checked="" type="checkbox"/> | Test software | EZ | EZ-EMC | | EMEC-3A1 | |
| Other Instrument | | | | | | |
| Used | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| <input checked="" type="checkbox"/> | Temperature & Humidity | Temperature | HTC-1 | / | Sep. 04, 2024 | Sep. 03, 2025 |

8. On Time and Duty Cycle

8.1. Block diagram of test setup



8.2. Limits

None; for reporting purposes only

8.3. Procedure

KDB 558074 Zero-Span Spectrum Analyzer Method

8.4. Results

| Test Mode | Ant. | Freq. (MHz) | ON Time (ms) | Period (ms) | Duty Cycle (%) | Duty Cycle Factor(dB) |
|-----------|------|-------------|--------------|-------------|----------------|-----------------------|
| BLE_1M | Ant1 | 2402 | 2.12 | 2.50 | 84.80 | 0.72 |
| | | 2440 | 2.13 | 2.50 | 85.20 | 0.70 |
| | | 2480 | 2.13 | 2.50 | 85.20 | 0.70 |
| BLE_2M | Ant1 | 2402 | 1.07 | 1.88 | 56.91 | 2.45 |
| | | 2440 | 1.07 | 1.88 | 56.91 | 2.45 |
| | | 2480 | 1.07 | 1.88 | 56.91 | 2.45 |

Note: Duty Cycle Correction Factor = $10\log(1/x)$.



Where: x is Duty Cycle(Linear)


Where: T is On Time (transmit duration)

If that calculated VBW is not available on the analyzer, then the next higher value should be used.

8.5. Original test data







9. 6 dB DTS Bandwidth and 99 % Bandwidth

9.1. Block diagram of test setup

Same as section 8.1

9.2. Limits

| CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3 | | | |
|---|-------------------------|------------------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a) | 6 dB Bandwidth | >= 500 kHz | 2400-2483.5 |
| ISED RSS-Gen Clause 6.7 | 99 % Occupied Bandwidth | For reporting purposes only. | 2400-2483.5 |

9.3. Test Procedure

Connect the UUT to the spectrum analyzer and use the following settings:

| | |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | For 6 dB Bandwidth :100 kHz For 99 % Occupied Bandwidth :1 % to 5 % of the occupied bandwidth |
| VBW | For 6 dB Bandwidth : $\geq 3 \times$ RBW For 99 % Occupied Bandwidth : $\geq 3 \times$ RBW |
| Trace | Max hold |
| Sweep | Auto couple |

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB/99 % relative to the maximum level measured in the fundamental emission.

9.4. Results


| Test Mode | Ant. | Freq. (MHz) | DTS BW (MHz) | FL (MHz) | FH (MHz) | Limit (MHz) | Verdict |
|-----------|------|-------------|--------------|----------|----------|-------------|---------|
| BLE_1M | Ant1 | 2402 | 0.696 | 2401.644 | 2402.340 | 0.5 | PASS |
| | | 2440 | 0.704 | 2439.632 | 2440.336 | 0.5 | PASS |
| | | 2480 | 0.644 | 2479.664 | 2480.308 | 0.5 | PASS |
| BLE_2M | Ant1 | 2402 | 1.148 | 2401.424 | 2402.572 | 0.5 | PASS |
| | | 2440 | 1.220 | 2439.340 | 2440.560 | 0.5 | PASS |
| | | 2480 | 1.164 | 2479.404 | 2480.568 | 0.5 | PASS |

| Test Mode | Antenna | Frequency (MHz) | OCB (MHz) | FL(MHz) | FH(MHz) | Limit(MHz) | Verdict |
|-----------|---------|-----------------|-----------|-----------|-----------|------------|---------|
| BLE_1M | Ant1 | 2402 | 1.0239 | 2401.4753 | 2402.4992 | --- | --- |
| | | 2440 | 1.0224 | 2439.4758 | 2440.4982 | --- | --- |
| | | 2480 | 1.0248 | 2479.4760 | 2480.5008 | --- | --- |
| BLE_2M | Ant1 | 2402 | 2.0656 | 2400.9686 | 2403.0342 | --- | --- |
| | | 2440 | 2.0595 | 2438.9703 | 2441.0298 | --- | --- |
| | | 2480 | 2.0555 | 2478.9733 | 2481.0288 | --- | --- |

9.5. Original test data

6 dB bandwidth:





99% bandwidth



BLE 2M Ant1 2402



10. Peak Conducted Output Power

10.1. Block diagram of test setup

Same as section 8.1

10.2. Limits

| CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3 | | | |
|--|-------------------|------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d) | Peak Output Power | 1 watt or 30 dBm | 2400 - 2483.5 |

10.3. Test Procedure

Connect EUT's antenna output to spectrum analyzer by RF cable.

99% Bandwidth set the spectrum analyzer as follows:

| | |
|----------------|----------|
| RBW: | 30 kHz |
| VBW: | 100 kHz |
| Detector Mode: | Peak |
| Sweep time: | auto |
| Trace mode | Max hold |

6 dB Bandwidth set the spectrum analyzer as follows:


| | |
|----------------|----------|
| RBW: | 100 kHz |
| VBW: | 300 kHz |
| Detector Mode: | Peak |
| Sweep time: | auto |
| Trace mode | Max hold |

Allow the trace to stabilize, measure the 6 dB and 99% bandwidth of signal.

10.4. Results

| Test Mode | Ant. | Freq (MHz) | Conducted Peak Power (dBm) | Conducted Limit (dBm) | EIRP (dBm) | EIRP Limit (dBm) | Verdict |
|-----------|------|------------|----------------------------|-----------------------|------------|------------------|---------|
| BLE_1M | Ant1 | 2402 | 2.59 | ≤30 | 3.81 | ≤36 | PASS |
| | | 2440 | 2.28 | ≤30 | 3.50 | ≤36 | PASS |
| | | 2480 | 3.19 | ≤30 | 4.41 | ≤36 | PASS |
| BLE_2M | Ant1 | 2402 | 2.91 | ≤30 | 4.13 | ≤36 | PASS |
| | | 2440 | 3.18 | ≤30 | 4.40 | ≤36 | PASS |
| | | 2480 | 2.59 | ≤30 | 3.81 | ≤36 | PASS |

10.5. Original test data





BLE 2M Ant1 2440



BLE 2M Ant1 2480



11. Power Spectral Density

11.1. Block diagram of test setup

Same as section 8.1

11.2. Limits

| CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3 | | | |
|--|------------------------|-------------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b) | Power Spectral Density | 8 dBm in any 3 kHz band | 2400 - 2483.5 |

11.3. Test Procedure

Connect the UUT to the spectrum analyzer and use the following settings:

| | |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ |
| VBW | $\geq 3 \times \text{RBW}$ |
| Span | 1.5 x DTS bandwidth |
| Trace | Max hold |
| Sweep time | Auto couple. |


Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.


If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

11.4. Results

| Test Mode | Ant. | Freq. (MHz) | Result (dBm/3kHz) | Limit (dBm/3kHz) | Verdict |
|-----------|------|-------------|-------------------|------------------|---------|
| BLE_1M | Ant1 | 2402 | -12.92 | ≤ 8.00 | PASS |
| | | 2440 | -14.03 | ≤ 8.00 | PASS |
| | | 2480 | -13.24 | ≤ 8.00 | PASS |
| BLE_2M | Ant1 | 2402 | -15.95 | ≤ 8.00 | PASS |
| | | 2440 | -15.77 | ≤ 8.00 | PASS |
| | | 2480 | -15.82 | ≤ 8.00 | PASS |

11.5. Original test data





12. Conducted Bandedge and Spurious Emissions

12.1. Block diagram of test setup

Same as section 8.1

12.2. Limits

| CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3 | | |
|--|--|---|
| Section | Test Item | Limit |
| CFR 47 FCC §15.247 (d) ISED RSS-247 5.5 | Conducted Band edge and Spurious Emissions | at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power |

12.3. Test Procedure

| | |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| Span | $\geq 1.5 \times \text{DTS bandwidth}$ |
| Trace | Max hold |
| Sweep time | Auto couple |

Connect the UUT to the spectrum analyzer and use the following settings:

Use the peak marker function to determine the maximum peak power level to establish the reference level.

| | |
|--------------------|---|
| Span | Set the center frequency and span to encompass frequency range to be measured |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| measurement points | $\geq \text{span}/\text{RBW}$ |
| Trace | Max hold |
| Sweep time | Auto couple |

Use the peak marker function to determine the maximum amplitude level.

12.4. Results

Band edge


| Test Mode | Ant. | Ch Name | Freq. (MHz) | Ref Level (dBm) | Result (dBm) | Limit (dBm) | Verdict |
|-----------|------|---------|-------------|-----------------|--------------|---------------|---------|
| BLE_1M | Ant1 | Low | 2402 | 3.05 | -47.09 | ≤ -16.95 | PASS |
| | | High | 2480 | 1.78 | -46.89 | ≤ -18.22 | PASS |
| BLE_2M | Ant1 | Low | 2402 | -0.71 | -32.22 | ≤ -20.71 | PASS |
| | | High | 2480 | 0.17 | -46.88 | ≤ -19.83 | PASS |

Spurious Emissions

| Test Mode | Ant. | Freq. (MHz) | Freq Range (MHz) | Ref Level (dBm) | Result (dBm) | Limit (dBm) | Verdict |
|-----------|------|-------------|------------------|-----------------|--------------|-------------|---------|
| BLE_1M | Ant1 | 2402 | Reference | 3.03 | 3.03 | --- | PASS |
| | | | 30~1000 | 3.03 | -58.57 | ≤-16.97 | PASS |
| | | | 1000~26500 | 3.03 | -48.31 | ≤-16.97 | PASS |
| | | 2440 | Reference | 2.19 | 2.19 | --- | PASS |
| | | | 30~1000 | 2.19 | -60.03 | ≤-17.81 | PASS |
| | | | 1000~26500 | 2.19 | -47.67 | ≤-17.81 | PASS |
| | | 2480 | Reference | 2.42 | 2.42 | --- | PASS |
| | | | 30~1000 | 2.42 | -58.01 | ≤-17.58 | PASS |
| | | | 1000~26500 | 2.42 | -46.15 | ≤-17.58 | PASS |
| BLE_2M | Ant1 | 2402 | Reference | 0.87 | 0.87 | --- | PASS |
| | | | 30~1000 | 0.87 | -61.3 | ≤-19.13 | PASS |
| | | | 1000~26500 | 0.87 | -48.56 | ≤-19.13 | PASS |
| | | 2440 | Reference | 1.18 | 1.18 | --- | PASS |
| | | | 30~1000 | 1.18 | -61.13 | ≤-18.82 | PASS |
| | | | 1000~26500 | 1.18 | -49.11 | ≤-18.82 | PASS |
| | | 2480 | Reference | -1.40 | -1.40 | --- | PASS |
| | | | 30~1000 | -1.40 | -60.78 | ≤-21.4 | PASS |
| | | | 1000~26500 | -1.40 | -49.06 | ≤-21.4 | PASS |


12.5. Original test data


Band edge:








Spurious Emissions:

















13. Radiated Emission

13.1. Block diagram of test setup


In 3 m Anechoic Chamber, test setup diagram for 9 kHz - 30 MHz:



In 3 m Anechoic Chamber, test setup diagram for 30 MHz - 1 GHz:



In 3 m Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

13.2. Limit

(1) FCC 15.205 Restricted frequency band

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|------------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| 10.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.1772&4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.2072&4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (²) |
| 13.36-13.41 | | | |

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

(2) FCC 15.209 Limit.

| Frequency MHz | Distance Meters | Field Strengths Limit | |
|------------------|--------------------|---|-----------------------------------|
| | | $\mu\text{V}/\text{m}$ | $\text{dB}(\mu\text{V})/\text{m}$ |
| 0.009 ~ 0.490 | 300 | 2400/F(kHz) | 67.6-20log(F) |
| 0.490 ~ 1.705 | 30 | 24000/F(kHz) | 87.6-20log(F) |
| 1.705 ~ 30.0 | 30 | 30 | 29.54 |
| 30 ~ 88 | 3 | 100 | 40.0 |
| 88 ~ 216 | 3 | 150 | 43.5 |
| 216~960 | 3 | 200 | 46.0 |
| 960~1000 | 3 | 500 | 54.0 |
| Above 1000 | 3 | 74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average) | |

Note: (1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

About Restricted bands of operation please refer to RSS-Gen section 8.10 and FCC § 15.205(a),

13.3. Test Procedure

Below 30 MHz:

The setting of the spectrum Analyzer

| | |
|-------|---|
| RBW | 300 Hz (From 9 kHz to 0.15 MHz)/ 10 kHz (From 0.15 MHz to 30 MHz) |
| VBW | 1 kHz (From 9 kHz to 0.15 MHz)/ 30 kHz (From 0.15 MHz to 30 MHz) |
| Sweep | Auto |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013

2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm meter above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of 1 meter height antenna tower.

5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT

measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz:

The setting of the spectrum Analyzer

| | |
|-------|----------|
| RBW | 100 kHz |
| VBW | 300 kHz |
| Sweep | Auto |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz:

| | |
|----------|--------------------------------|
| RBW | 1 MHz |
| VBW | PEAK: 3 MHz AVG: see note 6 |
| Sweep | Auto |
| Detector | Peak |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 1.5m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.

6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for AVG measurements. For the Duty Cycle please refer to clause 8.1.ON TIME AND DUTY CYCLE.

7. Restriction band: Investigated frequency range from 2310 MHz to 2410 MHz and 2470MHz to 2500 MHz.

All restriction band should comply with 15.209, other emission should be at least 20 dB below the fundamental.

Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT does not support simultaneous transmission.

Note 3: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

13.4. Results

Pass. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limits.

Note1: According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz, so the final test was performed with frequency range from 30 MHz to 26 GHz and recorded in below.

Note2: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in BLE 1MHz mode.

Note3: For emissions above 1 GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.


13.5. Original test data

Below 1 GHz and above 30 MHz test data Refer to appendix A

Above 1 GHz test data Refer to appendix B

14. AC Power Line Conducted Emissions

14.1. Block diagram of test setup



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

14.2. Limits

Please refer to CFR 47 FCC § 15.207 (a) and ISED RSS-Gen Clause 8.8.

| Frequency (MHz) | Quasi-peak | Average |
|-----------------|------------|-----------|
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * |
| 0.50 -5.0 | 56.00 | 46.00 |
| 5.0 -30.0 | 60.00 | 50.00 |

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.3. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.4. Test result

Pass. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

14.5. Original test data

AC Power Line Conducted Emission Test Data Refer to appendix C

15. Antenna Requirements

15.1. Limits

Please refer to FCC § 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC § 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

15.2. Result


The antenna used for this product is FPC antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 1.22 dBi

APPENDIX A – Radiated Emission Below 1GHz Test Data Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| EUT: | Smart Projector | | |
| Customer: | | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-02-06 18:40:30

Test Graph




| Final Data List | | | | | | | | |
|-----------------|-----------------|-------------------|-------------------|----------------|-------------|-----------|------------|---------|
| NO. | Frequency (MHz) | QP Value (dBµV/m) | QP Limit (dBµV/m) | QP Margin (dB) | Height (cm) | Angle (°) | Polarity | Verdict |
| 1 | 31.1641 | 27.96 | 40.00 | 12.04 | 100 | 27 | Horizontal | PASS |
| 2 | 69.2889 | 25.69 | 40.00 | 14.31 | 100 | 27 | Horizontal | PASS |
| 3 | 108.6749 | 27.22 | 43.50 | 16.28 | 100 | 27 | Horizontal | PASS |
| 4 | 239.9290 | 33.37 | 46.00 | 12.63 | 100 | 78 | Horizontal | PASS |
| 5 | 276.8897 | 31.82 | 46.00 | 14.18 | 100 | 121 | Horizontal | PASS |
| 6 | 708.8739 | 35.46 | 46.00 | 10.54 | 100 | 223 | Horizontal | PASS |

Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| EUT: | Smart Projector | | |
| Customer: | | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-02-06 18:41:12

Test Graph




| Final Data List | | | | | | | | |
|-----------------|-----------------|-------------------|-------------------|----------------|-------------|-----------|----------|---------|
| NO. | Frequency (MHz) | QP Value (dBµV/m) | QP Limit (dBµV/m) | QP Margin (dB) | Height (cm) | Angle (°) | Polarity | Verdict |
| 1 | 32.0372 | 31.03 | 40.00 | 8.97 | 100 | 55 | Vertical | PASS |
| 2 | 69.2889 | 29.14 | 40.00 | 10.86 | 100 | 216 | Vertical | PASS |
| 3 | 108.4808 | 31.25 | 43.50 | 12.25 | 100 | 51 | Vertical | PASS |
| 4 | 196.5657 | 29.28 | 43.50 | 14.22 | 100 | 143 | Vertical | PASS |
| 5 | 602.9393 | 34.27 | 46.00 | 11.73 | 100 | 122 | Vertical | PASS |
| 6 | 810.9281 | 37.47 | 46.00 | 8.53 | 100 | 334 | Vertical | PASS |

APPENDIX B – Radiated Emission Above 1GHz Test Data Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2402 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-01-23 16:12:04

Test Graph




| PK Final Data List | | | | | | | | | | |
|--------------------|-----------------|-------------------|-------------------|----------------|-------------------|-------------------|----------------|-------------|-----------|------------|
| NO. | Frequency (MHz) | PK Value (dBµV/m) | PK Limit (dBµV/m) | PK Margin (dB) | AV Value (dBµV/m) | AV Limit (dBµV/m) | AV Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 1061.4031 | 42.03 | 74.00 | 31.97 | 38.88 | 54.00 | 15.12 | 150 | 358 | Horizontal |
| 2 | 1590.7295 | 45.00 | 74.00 | 29.00 | 42.55 | 54.00 | 11.45 | 150 | 346 | Horizontal |
| 3 | 3526.5263 | 41.00 | 74.00 | 33.00 | 38.10 | 54.00 | 15.90 | 150 | 233 | Horizontal |
| 4 | 7206.2103 | 52.66 | 74.00 | 21.34 | 47.99 | 54.00 | 6.01 | 150 | 284 | Horizontal |
| 5 | 12836.7418 | 49.19 | 74.00 | 24.81 | 44.75 | 54.00 | 9.25 | 150 | 136 | Horizontal |
| 6 | 17861.2431 | 54.43 | 74.00 | 19.57 | 49.86 | 54.00 | 4.14 | 150 | 166 | Horizontal |

Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2402 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-01-23 16:13:24

Test Graph




| PK Final Data List | | | | | | | | | | |
|--------------------|-----------------|-------------------|-------------------|----------------|-------------------|-------------------|----------------|-------------|-----------|----------|
| NO. | Frequency (MHz) | PK Value (dBµV/m) | PK Limit (dBµV/m) | PK Margin (dB) | AV Value (dBµV/m) | AV Limit (dBµV/m) | AV Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 1077.3039 | 42.89 | 74.00 | 31.11 | 39.53 | 54.00 | 14.47 | 150 | 306 | Vertical |
| 2 | 2131.0566 | 45.02 | 74.00 | 28.98 | 39.96 | 54.00 | 14.04 | 150 | 207 | Vertical |
| 3 | 3526.5263 | 41.84 | 74.00 | 32.16 | 39.41 | 54.00 | 14.59 | 150 | 358 | Vertical |
| 4 | 5321.3661 | 50.58 | 74.00 | 23.42 | 41.38 | 54.00 | 12.62 | 150 | 336 | Vertical |
| 5 | 7206.2103 | 53.12 | 74.00 | 20.88 | 49.20 | 54.00 | 4.80 | 150 | 113 | Vertical |
| 6 | 14807.0904 | 49.50 | 74.00 | 24.50 | 46.40 | 54.00 | 7.60 | 150 | 336 | Vertical |

Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2440 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-01-23 16:16:46

Test Graph




| PK Final Data List | | | | | | | | | | |
|--------------------|-----------------|-------------------|-------------------|----------------|-------------------|-------------------|----------------|-------------|-----------|------------|
| NO. | Frequency (MHz) | PK Value (dBµV/m) | PK Limit (dBµV/m) | PK Margin (dB) | AV Value (dBµV/m) | AV Limit (dBµV/m) | AV Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 1064.7032 | 43.94 | 74.00 | 30.06 | 39.39 | 54.00 | 14.61 | 150 | 360 | Horizontal |
| 2 | 1590.6295 | 43.69 | 74.00 | 30.31 | 41.21 | 54.00 | 12.79 | 150 | 327 | Horizontal |
| 3 | 2282.2641 | 45.43 | 74.00 | 28.57 | 41.01 | 54.00 | 12.99 | 150 | 158 | Horizontal |
| 4 | 3252.7626 | 43.18 | 74.00 | 30.82 | 41.13 | 54.00 | 12.87 | 150 | 47 | Horizontal |
| 5 | 7319.4660 | 53.27 | 74.00 | 20.73 | 48.78 | 54.00 | 5.22 | 150 | 288 | Horizontal |
| 6 | 10855.1428 | 47.62 | 74.00 | 26.38 | 42.31 | 54.00 | 11.69 | 150 | 189 | Horizontal |

Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2440 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-01-23 16:18:06

Test Graph




| PK Final Data List | | | | | | | | | | |
|--------------------|-----------------|-------------------|-------------------|----------------|-------------------|-------------------|----------------|-------------|-----------|----------|
| NO. | Frequency (MHz) | PK Value (dBµV/m) | PK Limit (dBµV/m) | PK Margin (dB) | AV Value (dBµV/m) | AV Limit (dBµV/m) | AV Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 1333.0167 | 46.30 | 74.00 | 27.70 | 43.04 | 54.00 | 10.96 | 150 | 102 | Vertical |
| 2 | 2318.2659 | 44.89 | 74.00 | 29.11 | 40.53 | 54.00 | 13.47 | 150 | 351 | Vertical |
| 3 | 3984.0492 | 47.21 | 74.00 | 26.79 | 40.98 | 54.00 | 13.02 | 150 | 337 | Vertical |
| 4 | 5332.6166 | 47.37 | 74.00 | 26.63 | 41.66 | 54.00 | 12.34 | 150 | 98 | Vertical |
| 5 | 7319.3060 | 53.06 | 74.00 | 20.94 | 43.23 | 54.00 | 10.77 | 199.6 | 120.2 | Vertical |
| 6 | 13777.2889 | 50.19 | 74.00 | 23.81 | 45.16 | 54.00 | 8.84 | 150 | 116 | Vertical |

Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-01-23 16:36:27

Test Graph




| PK Final Data List | | | | | | | | | | |
|--------------------|-----------------|-------------------|-------------------|----------------|-------------------|-------------------|----------------|-------------|-----------|------------|
| NO. | Frequency (MHz) | PK Value (dBµV/m) | PK Limit (dBµV/m) | PK Margin (dB) | AV Value (dBµV/m) | AV Limit (dBµV/m) | AV Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 1063.4032 | 45.31 | 74.00 | 28.69 | 40.65 | 54.00 | 13.35 | 150 | 359 | Horizontal |
| 2 | 1590.7295 | 45.37 | 74.00 | 28.63 | 40.19 | 54.00 | 13.81 | 150 | 340 | Horizontal |
| 3 | 2480.0740 | 48.33 | 74.00 | 25.67 | 43.89 | 54.00 | 10.11 | 150 | 340 | Horizontal |
| 4 | 3306.0153 | 47.03 | 74.00 | 26.97 | 45.25 | 54.00 | 8.75 | 150 | 52 | Horizontal |
| 5 | 7439.4720 | 52.45 | 74.00 | 21.55 | 49.32 | 54.00 | 4.68 | 150 | 71 | Horizontal |
| 6 | 12880.9941 | 48.69 | 74.00 | 25.31 | 45.22 | 54.00 | 8.78 | 150 | 71 | Horizontal |

Test Report

| Project Information | | | |
|------------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC PART 15 C | | | |

Start of Test:2025-01-23 16:37:49

Test Graph




| PK Final Data List | | | | | | | | | | |
|--------------------|-----------------|-------------------|-------------------|----------------|-------------------|-------------------|----------------|-------------|-----------|----------|
| NO. | Frequency (MHz) | PK Value (dBµV/m) | PK Limit (dBµV/m) | PK Margin (dB) | AV Value (dBµV/m) | AV Limit (dBµV/m) | AV Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 1333.1167 | 45.47 | 74.00 | 28.53 | 41.90 | 54.00 | 12.10 | 150 | 94 | Vertical |
| 2 | 2480.1740 | 48.09 | 74.00 | 25.91 | 44.41 | 54.00 | 9.59 | 150 | 68 | Vertical |
| 3 | 3991.5496 | 54.63 | 74.00 | 19.37 | 42.11 | 54.00 | 11.89 | 150 | 76 | Vertical |
| 4 | 7439.4230 | 53.86 | 74.00 | 20.14 | 45.00 | 54.00 | 9.00 | 188.4 | 120.8 | Vertical |
| 5 | 11712.4356 | 45.75 | 74.00 | 28.25 | 43.14 | 54.00 | 10.86 | 150 | 111 | Vertical |
| 6 | 16577.1789 | 50.43 | 74.00 | 23.57 | 46.85 | 54.00 | 7.15 | 150 | 350 | Vertical |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2402 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:09:51

Test Graph




| Suspected Data List | | | | | | | | |
|---------------------|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|------------|
| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 2350.8204 | 47.75 | 6.90 | 74.00 | 26.25 | 150 | 346 | Horizontal |
| 2 | 2390.0080 | 46.07 | 6.85 | 74.00 | 27.93 | 150 | 197 | Horizontal |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2402 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:10:34

Test Graph




| Suspected Data List | | | | | | | | |
|---------------------|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|----------|
| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 2345.0575 | 47.42 | 6.90 | 74.00 | 26.58 | 150 | 1 | Vertical |
| 2 | 2390.0080 | 45.70 | 6.85 | 74.00 | 28.30 | 150 | 2 | Vertical |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:46:20

Test Graph



Suspected Data List


| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
|-----|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|------------|
| 1 | 2483.5028 | 48.05 | 7.34 | 74.00 | 25.95 | 150 | 28 | Horizontal |
| 2 | 2509.5865 | 49.89 | 7.48 | 74.00 | 24.11 | 150 | 75 | Horizontal |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_1M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:47:04

Test Graph




| Suspected Data List | | | | | | | | |
|---------------------|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|----------|
| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 2483.5028 | 46.86 | 7.34 | 74.00 | 27.14 | 150 | 244 | Vertical |
| 2 | 2495.6819 | 50.11 | 7.40 | 74.00 | 23.89 | 150 | 134 | Vertical |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_2M_2402 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:49:25

Test Graph




| Suspected Data List | | | | | | | | |
|---------------------|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|------------|
| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 2374.9285 | 47.36 | 6.87 | 74.00 | 26.64 | 150 | 266 | Horizontal |
| 2 | 2390.0080 | 45.06 | 6.85 | 74.00 | 28.94 | 150 | 286 | Horizontal |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_2M_2402 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:50:08

Test Graph




| Suspected Data List | | | | | | | | |
|---------------------|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|----------|
| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 2368.7814 | 47.44 | 6.88 | 74.00 | 26.56 | 150 | 200 | Vertical |
| 2 | 2390.0080 | 45.32 | 6.85 | 74.00 | 28.68 | 150 | 82 | Vertical |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_2M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:51:40

Test Graph



Suspected Data List


| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
|-----|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|------------|
| 1 | 2483.5028 | 47.41 | 7.34 | 74.00 | 26.59 | 150 | 45 | Horizontal |
| 2 | 2492.4058 | 50.40 | 7.39 | 74.00 | 23.60 | 150 | 355 | Horizontal |

Test Report

| Project Information | | | |
|----------------------------|----------------------|-----------|-------------|
| Customer: | | | |
| EUT: | Smart Projector | | |
| Model: | N2mini | SN: | |
| Mode: | BLE_2M_2480 | Voltage: | AC120V/60Hz |
| Environment: | Temp: 25°C; Humi:60% | Engineer: | Soho Liu |
| Remark: | Power Set:48 | | |
| Test Standard: FCC Part15C | | | |

Start of Test:2025-01-23 16:52:23

Test Graph



| Suspected Data List | | | | | | | | |
|---------------------|-----------------|----------------|-------------|----------------|-------------|-------------|-----------|----------|
| NO. | Frequency (MHz) | Level (dBµV/m) | Factor (dB) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Angle (°) | Polarity |
| 1 | 2483.5028 | 47.72 | 7.34 | 74.00 | 26.28 | 150 | 106 | Vertical |
| 2 | 2502.9343 | 50.70 | 7.44 | 74.00 | 23.30 | 150 | 95 | Vertical |


APPENDIX C – AC Power Line Conducted Emission Test Data

Conducted Emission Measurement

Data :#3

Date: 2025/2/10

Time: 19:50:50



Site: _____ Phase: **L1** Temperature: 26
 Limit: FCC Part 15 C Class B (QP) Power: AC 120V/60Hz Humidity: 60 %
 EUT: _____
 M/N: N2MINI
 Mode: BLE
 Note: _____


| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1 | | 0.1546 | 37.65 | 9.54 | 47.19 | 65.75 | -18.56 | QP | |
| 2 | | 0.1546 | 11.98 | 9.54 | 21.52 | 55.75 | -34.23 | AVG | |
| 3 | * | 0.1829 | 45.10 | 9.55 | 54.65 | 64.35 | -9.70 | QP | |
| 4 | | 0.1829 | 26.45 | 9.55 | 36.00 | 54.35 | -18.35 | AVG | |
| 5 | | 0.2503 | 35.85 | 9.57 | 45.42 | 61.75 | -16.33 | QP | |
| 6 | | 0.2503 | 21.91 | 9.57 | 31.48 | 51.75 | -20.27 | AVG | |
| 7 | | 0.3844 | 26.92 | 9.58 | 36.50 | 58.18 | -21.68 | QP | |
| 8 | | 0.3844 | 12.93 | 9.58 | 22.51 | 48.18 | -25.67 | AVG | |
| 9 | | 1.7686 | 20.38 | 9.65 | 30.03 | 56.00 | -25.97 | QP | |
| 10 | | 1.7686 | 11.30 | 9.65 | 20.95 | 46.00 | -25.05 | AVG | |
| 11 | | 4.5812 | 20.81 | 9.78 | 30.59 | 56.00 | -25.41 | QP | |
| 12 | | 4.5812 | 13.38 | 9.78 | 23.16 | 46.00 | -22.84 | AVG | |

Conducted Emission Measurement

Data :#4

Date: 2025/2/10

Time: 20:03:54



Site: Phase: **N** Temperature: 26
 Limit: FCC Part 15 C Class B (QP) Power: AC 120V/60Hz Humidity: 60 %
 EUT:
 M/N: N2MINI
 Mode: BLE
 Note:

| No. Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measurement dBuV | Limit dBuV | Over dB | Detector | Comment |
|---------|-----------|--------------------|-------------------|------------------|------------|---------|----------|---------|
| 1 | 0.1530 | 37.86 | 9.53 | 47.39 | 65.84 | -18.45 | QP | |
| 2 | 0.1530 | 11.82 | 9.53 | 21.35 | 55.84 | -34.49 | AVG | |
| 3 * | 0.1819 | 44.70 | 9.54 | 54.24 | 64.40 | -10.16 | QP | |
| 4 | 0.1819 | 25.54 | 9.54 | 35.08 | 54.40 | -19.32 | AVG | |
| 5 | 0.1973 | 43.36 | 9.55 | 52.91 | 63.72 | -10.81 | QP | |
| 6 | 0.1973 | 28.08 | 9.55 | 37.63 | 53.72 | -16.09 | AVG | |
| 7 | 0.2497 | 35.80 | 9.56 | 45.36 | 61.77 | -16.41 | QP | |
| 8 | 0.2497 | 21.43 | 9.56 | 30.99 | 51.77 | -20.78 | AVG | |
| 9 | 0.3300 | 30.78 | 9.57 | 40.35 | 59.45 | -19.10 | QP | |
| 10 | 0.3300 | 20.82 | 9.57 | 30.39 | 49.45 | -19.06 | AVG | |
| 11 | 2.2416 | 24.79 | 9.66 | 34.45 | 56.00 | -21.55 | QP | |
| 12 | 2.2416 | 14.72 | 9.66 | 24.38 | 46.00 | -21.62 | AVG | |

END OF REPORT