

FCC TEST REPORT
For
Zhejiang Yunkai New Energy Technology Co., Ltd.
Contactless Wireless Charger
Test Model: EKR0535

Prepared for

: Zhejiang Yunkai New Energy Technology Co., Ltd.

Address

: No.968, XueFengXi Road, YiWu City, Zhejiang Province, China

Prepared by

: Shenzhen LCS Compliance Testing Laboratory Ltd.

Address

: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing

Street, Baoan District, Shenzhen, China

Tel

: (+86)755-82591330

Fax

: (+86)755-82591332

Web

: www.LCS-cert.com

Mail

: webmaster@LCS-cert.com

Date of receipt of test sample

: September 24, 2020

Number of tested samples

: 1

Sample number

: 200917070A

Serial number

: Prototype

Date of Test

: September 24, 2020 ~ October 14, 2020

Date of Report

: October 14, 2020

FCC TEST REPORT
FCC CFR 47 PART 18

Report Reference No. : LCS200917070AEA

Date Of Issue : October 14, 2020

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China

Testing Location/ Procedure : Full application of Harmonised standards Partial application of Harmonised standards Other standard testing method

Applicant's Name : Zhejiang Yunkai New Energy Technology Co., Ltd.

Address : No.968, XueFengXi Road, YiWu City, Zhejiang Province, China

Test Specification

Standard : FCC CFR 47 PART 18

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description : Contactless Wireless Charger


Trade Mark : EKR

Test Model : EKR0535

Power Supply : Input: DC 24V 1A
Output(Wireless Charging): DC 5V 1A

Result : Positive

Compiled by:




Lh Li/ Administrator

Supervised by:



Jin Wang/ Technique principal

Approved by:



Gavin Liang/ Manager

FCC TEST REPORT

Test Report No. :	LCS200917070AEA	October 14, 2020 Date of issue
-------------------	-----------------	-----------------------------------

Test Model.....	: EKR0535
EUT.....	: Contactless Wireless Charger
Applicant.....	: Zhejiang Yunkai New Energy Technology Co., Ltd.
Address.....	: No.968, XueFengXi Road, YiWu City, Zhejiang Province, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Zhejiang Yunkai New Energy Technology Co., Ltd.
Address.....	: No.968, XueFengXi Road, YiWu City, Zhejiang Province, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Zhejiang Yunkai New Energy Technology Co., Ltd.
Address.....	: No.968, XueFengXi Road, YiWu City, Zhejiang Province, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
-------------	----------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	October 14, 2020	Initial Issue	Gavin Liang

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	6
1.1 Description of Device (EUT)	6
1.2 Support equipment List.....	6
1.3 External I/O Cable	6
1.4 Description of Test Facility	6
1.5 Statement of the Measurement Uncertainty.....	7
1.6 Measurement Uncertainty	7
1.7 Description of Test Modes.....	7
2. TEST METHODOLOGY	8
2.1 EUT Configuration	8
2.2 EUT Exercise.....	8
2.3 General Test Procedures	8
2.3.1 Conducted Emissions	8
2.3.2 Radiated Emissions	8
3. SYSTEM TEST CONFIGURATION.....	9
3.1 Justification	9
3.2 EUT Exercise Software.....	9
3.3 Special Accessories	9
3.4 Block Diagram/Schematics	9
3.5 Equipment Modifications	9
3.6 Test Setup.....	9
4. SUMMARY OF TEST EQUIPMENT	10
5. SUMMARY OF TEST RESULT.....	11
6. POWER LINE CONDUCTED MEASUREMENT	12
7. RADIATED EMISSION MEASUREMENT	15
7.1. Block Diagram of Test Setup.....	15
7.2. Radiated Emission Limit	16
7.3. EUT Configuration on Measurement.....	16
7.4. Operating Condition of EUT.....	16
7.5. Measuring Setting.....	16
7.6. Test Procedure	17
7.7. Test Results.....	18
8. PHOTOGRAPHS OF TEST SETUP.....	23
9. EXTERNAL PHOTOGRAPHS OF THE EUT.....	23
10. INTERNAL PHOTOGRAPHS OF THE EUT.....	23

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT : Contactless Wireless Charger
Test Model : EKR0535
Power Supply : Input: DC 24V 1A
Output(Wireless Charging): DC 5V 1A
Hardware Version : WE9012_20190815_V1.0
Software Version : /
Wireless Charging :
Operating Frequency : 115.0~140.0KHz
Modulation Type : Continuous Wave
Antenna Type : Coil Antenna

1.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen Gao Fan DE Technology Co. LTD	Power Adapter	GFD24-2401000C	--	FCC SDOC
MIUI	Mobile Phone	MI9	--	FCC SDOC

Note: Airpods, adapter and mobile phone are only used test, not shipped

1.3 External I/O Cable

I/O Port Description	Quantity	Cable
DC IN	1	N/A

1.4 Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	3.10dB	(1)
	30MHz~200MHz	2.96dB	(1)
	200MHz~1000MHz	3.10dB	(1)
	1GHz~26.5GHz	3.80dB	(1)
	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	1.63dB	(1)
Power disturbance	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7 Description of Test Modes

Equipment under test was operated during the measurement under the following conditions:

Charging and communication mode

Modulation Type: CW (Continuous Wave)

Test Modes		
Mode 1	AC/DC Adapter (24V/1A) + EUT+ Mobile Phone (Battery Status: <1%)	Record
Mode 2	AC/DC Adapter (24V/1A) + EUT+ Mobile Phone (Battery Status: <50%)	Pre-tested
Mode 3	AC/DC Adapter (24V/1A) + EUT+ Mobile Phone (Battery Status: 100%)	Pre-tested

Note: All test modes were pre-tested, but we only recorded the worst case in this report.

For AC conducted emission, pre-test at both AC 120V/60Hz and AC 240V/50Hz, recorded worst case;

For AC conducted emission, pre-test at both AC charge from power adapter, recorded worst case.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with MP-5, and FCC CFR PART 18.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the charging and compunction mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 18.305 and 18.307 under the FCC Rules Part 18.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in FCC MP-5 for Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in FCC MP-5 for radiated emission.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a normal condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

N/A.

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY49100040	2020-06-22	2021-06-21
2	SPECTRUM ANALYZER	R&S	FSP40	100503	2019-11-14	2020-11-13
3	3m Full Anechoic Chamber	MRDIANZI	FAC-3M	MR009	2020-09-27	2021-09-26
4	Positioning Controller	MF	MF7082	MF78020803	2020-06-22	2021-06-21
5	EMI Test Software	EZ	EZ-EMC	/	N/A	N/A
6	EMI Test Receiver	R&S	ESR 7	101181	2020-06-22	2021-06-21
7	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2018-07-26	2021-07-25
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2018-07-26	2021-07-25
9	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2018-07-02	2021-07-01
10	RF Cable-R03m	Jye Bao	RG142	CB021	2020-06-22	2021-06-21
11	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2020-06-22	2021-06-21
12	EMI Test Receiver	R&S	ESPI	101840	2020-06-22	2021-06-21
13	Artificial Mains	R&S	ENV216	101288	2020-06-22	2021-06-21
14	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2020-06-22	2021-06-21

Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.

5. SUMMARY OF TEST RESULT


Test Item	FCC Rule No.	Temperature conditions	Power source conditions	C	NC	NA	NP	Remark
Radiated Emission	§18.305 (b)	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
AC conducted emission	§18.307 (a)	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-

Remark: The measurement uncertainty is not included in the test result.

N/A – Not Applicable!!!

6. POWER LINE CONDUCTED MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. Standard Applicable

According to §18.307 (b): For all other part 18 consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50


* Decreasing linearly with the logarithm of the frequency

6.3 Test Results

PASS


The test data please refer to following page.

Temperature	22.7°C	Humidity	53.7%
Test Engineer	Kay Hu	Configurations	Transmit

AC Power Line Conducted Emission (Power input to Adapter @ AC 120V/60Hz (Worst Case))**Line**

Site LAB		Phase: L1		Temperature: 22.7		
Limit: FCC PART 18 Conduction(QP)		Power: AC 120V/60Hz		Humidity: 53.7 %		
No.	Mk.	Reading	Correct	Measure-	Limit	Margin
		Level	Factor	ment	dBuV	dB
		MHz	dBuV	dB	dBuV	Detector
1	0.1860	26.41	19.17	45.58	64.21	-18.63 QP
2	0.1874	6.41	19.17	25.58	54.15	-28.57 AVG
3	1.1130	16.58	19.28	35.86	56.00	-20.14 QP
4	1.1130	13.20	19.28	32.48	46.00	-13.52 AVG
5	4.1055	17.18	19.47	36.65	56.00	-19.35 QP
6	4.1325	-1.92	19.47	17.55	46.00	-28.45 AVG
7	6.7965	26.64	19.58	46.22	60.00	-13.78 QP
8	6.7965	-9.14	19.58	10.44	50.00	-39.56 AVG
9	13.2585	27.39	19.97	47.36	60.00	-12.64 QP
10 *	13.2585	21.05	19.97	41.02	50.00	-8.98 AVG
11	23.4645	30.31	20.24	50.55	60.00	-9.45 QP
12	23.5950	18.24	20.23	38.47	50.00	-11.53 AVG

Neutral




Site LAB			Phase: <i>N</i>	Temperature: 22.7			
Limit: FCC PART 18 Conduction(QP)			Power: AC 120V/60Hz	Humidity: 53.7 %			
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin
		MHz	dBuV	dB	dBuV	dBuV	dB
1		0.1905	29.93	19.17	49.10	64.01	-14.91
2		0.1924	12.19	19.17	31.36	53.93	-22.57
3		0.2714	28.23	19.25	47.48	61.07	-13.59
4		0.2714	12.96	19.25	32.21	51.07	-18.86
5		7.0530	27.65	19.57	47.22	60.00	-12.78
6		7.0665	-0.30	19.57	19.27	50.00	-30.73
7		7.8225	27.82	19.62	47.44	60.00	-12.56
8		7.8675	-0.83	19.62	18.79	50.00	-31.21
9		14.1045	27.01	20.05	47.06	60.00	-12.94
10		14.3655	18.86	20.08	38.94	50.00	-11.06
11		23.7165	24.93	20.10	45.03	60.00	-14.97
12	*	23.7165	20.88	20.10	40.98	50.00	-9.02

***Note: Pre-scan all modes and recorded the worst case results in this report.

Margin= Reading level + Correct factor - Limit

7. RADIATED EMISSION MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. Radiated Emission Limit

Except as provided elsewhere in this Subpart 18.305 (b), the field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following table:

Frequency MHz	Distance Meters	Field Strengths Limit	
		dB μ V/m	Remark
0.009~30MHz	3	103.5	Quasi-peak

Remark:

- (1) Emission level dB μ V/m for 0.009~30MHz = $20\log(15) + 40\log(300/3)$ dB μ V/m;
- (2) Calculated according FCC 18.305.
- (3) The smaller limit shall apply at the cross point between two frequency bands.
- (4) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

7.3. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

- (1) Setup the EUT as shown in Section 4.1.
- (2) Let the EUT work in worst test mode (Mode 1) and measure it.

7.5. Measuring Setting

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/Average
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/Average
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

7.6. Test Procedure

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

7.7. Test Results


PASS.

Only report the worst test data (Mode 1) in test report;

The test data please refer to following page:


Temperature	24.6°C	Humidity	54.1%
Test Engineer	Kay Hu	Configurations	Transmit

0.009 MHz – 30 MHz(90 degree)



Limit:	FCC 18.305-9K-30M	Antenna::Horizontal	Temperature(C):24.6(C)
Power Rating:	AC 120V/60Hz	Humidity(%):54.1%	


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.0099	34.63	20.64	55.27	103.50	-48.23	QP
2	0.0153	43.84	20.59	64.43	103.50	-39.07	QP
3	0.0234	21.91	20.64	42.55	103.50	-60.95	QP
4	0.0355	34.35	20.70	55.05	103.50	-48.45	QP
5	0.0641	20.95	20.62	41.57	103.50	-61.93	QP
6 *	0.1246	76.85	20.47	97.32	103.50	-6.18	QP



Limit:	FCC 18.305-9K-30M	Antenna::Horizontal	Temperature(C):24.6(C)
Power Rating:	AC 120V/60Hz	Humidity(%):54.1%	


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	0.2481	51.89	20.28	72.17	103.50	-31.33	QP
2	0.3731	39.25	20.28	59.53	103.50	-43.97	QP
3	0.6205	34.17	20.28	54.45	103.50	-49.05	QP
4	0.7470	31.61	20.28	51.89	103.50	-51.61	QP
5	1.1173	25.59	20.27	45.86	103.50	-57.64	QP
6	2.8998	16.11	20.24	36.35	103.50	-67.15	QP

0.009 MHz – 30 MHz(0 degree)



Limit:	FCC 18.305-9K-30M	Antenna::Horizontal	Temperature(C):24.6(C)
Power Rating:	AC 120V/60Hz		Humidity(%):54.1%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.0099	34.21	20.64	54.85	103.50	-48.65	QP
2	0.0153	43.70	20.59	64.29	103.50	-39.21	QP
3	0.0184	23.50	20.62	44.12	103.50	-59.38	QP
4	0.0355	34.26	20.70	54.96	103.50	-48.54	QP
5	0.0669	18.62	20.62	39.24	103.50	-64.26	QP
6 *	0.1256	70.03	20.47	90.50	103.50	-13.00	QP




Limit:	FCC 18.305-9K-30M	Antenna::Horizontal	Temperature(C):24.6(C)
Power Rating:	AC 120V/60Hz		Humidity(%):54.1%

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	0.2508	46.60	20.28	66.88	103.50	-36.62	QP
2	0.3751	32.46	20.28	52.74	103.50	-50.76	QP
3	0.6271	30.56	20.28	50.84	103.50	-52.66	QP
4	1.1233	25.14	20.27	45.41	103.50	-58.09	QP
5	2.0768	18.72	20.23	38.95	103.50	-64.55	QP
6	4.3376	15.24	20.25	35.49	103.50	-68.01	QP

Remark: Measured at antenna position 0 degree and 90 degree, recorded worst case at 0 degree.
 Margin= Reading level + Factor - Limit

Temperature	24.2°C	Humidity	53.1%
Test Engineer	Kay Hu	Configurations	Transmit

Below 1GHz*Horizontal*

Site 966 chamber #1

Polarization: **Horizontal**

Temperature: 24.2 (C)


Limit: FCC Part18 RE 30-1000MHz

Power: AC 120V/60Hz

Humidity: 53.1 %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.0667	42.91	-7.66	35.25	40.00	-4.75	QP
2	84.4054	46.02	-10.76	35.26	40.00	-4.74	QP
3	249.4250	37.63	-6.02	31.61	46.00	-14.39	QP
4	382.5879	38.17	-3.36	34.81	46.00	-11.19	QP
5	446.4141	42.01	-2.59	39.42	46.00	-6.58	QP
6	497.6765	38.47	-2.12	36.35	46.00	-9.65	QP

Vertical



Site 966 chamber #1

Polarization: **Vertical**

Temperature: 24.2 (C)

Limit: FCC Part18 RE_30-1000MHz

Power: AC 120V/60Hz

Humidity: 53.1 %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	33.7986	41.69	-7.60	34.09	40.00	-5.91	QP
2	55.2207	40.96	-6.25	34.71	40.00	-5.29	QP
3	72.8466	46.84	-10.59	36.25	40.00	-3.75	QP
4	96.0986	40.89	-8.14	32.75	43.50	-10.75	QP
5	378.5843	33.72	-3.45	30.27	46.00	-15.73	QP
6	506.4791	37.95	-1.92	36.03	46.00	-9.97	QP

Note: Margin= Reading level + Factor - Limit

8. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files for Test Setup Photos of the EUT.

9. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

10. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----