

FCC REPORT

Applicant: Dongguan KAKA Electronic Technology Co., Ltd.

Address of Applicant: No.395, Huanshi East Road, Shitanpu, Tangxia Town, Dongguan, Guangdong, China.

Equipment Under Test (EUT)

Product Name: TOOTHBRUSH

Model No.: GF-7

FCC ID: 2AV4E-GF-7

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 11 Dec., 2019

Date of Test: 12 Dec., to 07 Jan., 2020

Date of report issued: 08 Jan., 2020

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	08 Jan., 2020	Original

Tested by:

Mike Ou

Test Engineer

Date:

08 Jan., 2020

Reviewed by:

Winner Zhang

Project Engineer

Date:

08 Jan., 2020

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY	5
5.5 DESCRIPTION OF SUPPORT UNITS	6
5.6 RELATED SUBMITTAL(S) / GRANT (S).....	6
5.7 DESCRIPTION OF CABLE USED	6
5.8 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD	6
5.9 LABORATORY FACILITY	6
5.10 LABORATORY LOCATION.....	6
5.11 TEST INSTRUMENTS LIST	7
6 TEST RESULTS AND MEASUREMENT DATA	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION	13
7 TEST SETUP PHOTO	27
8 EUT CONSTRUCTIONAL DETAILS	32

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: The EUT not applicable of the test item.		
Test Method:	ANSI C63.4:2014	

5 General Information

5.1 Client Information

Applicant:	Dongguan KAKA Electronic Technology Co., Ltd.
Address:	No.395, Huanshi East Road, Shitanpu, Tangxia Town, Dongguan, Guangdong, China.
Manufacturer/Factory:	Dongguan KAKA Electronic Technology Co., Ltd.
Address:	No.395, Huanshi East Road, Shitanpu, Tangxia Town, Dongguan, Guangdong, China

5.2 General Description of E.U.T.

Product Name:	TOOTHBRUSH
Model No.:	GF-7
Power supply:	Rechargeable Li-ion polymer Battery DC3.7V/320mAh
Wireless charger:	Wall hanging: Input: 5V, 0.5A Output: 5V, 0.5A Charging box: Input: 5V, 0.5A Output: 5V, 0.5A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test Mode

Operating mode	Detail description
Charging + Wall hanging mode	Keep the EUT in Charging(by Wall hanging) mode
Charging + Charging box mode	Keep the EUT in Charging(by Charging box) mode
Working mode	Keep the EUT in Working mode
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.38 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.36 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
Xiaomi Inc.	Adapter	MDY-03-EB	N/A	N/A

5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

5.7 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	UnShielding	1.0m	EUT	Adapter

5.8 Additions to, deviations, or exclusions from the method

No

5.9 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.10 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>


5.11 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-18-2019	03-17-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2018	11-20-2019
				11-21-2019	11-20-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-18-2019	03-17-2020
Pre-amplifier	CD	PAP-1G18	11804	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2018	11-20-2019
				11-21-2019	11-20-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2019	03-17-2020
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2019	03-17-2020
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2019	03-17-2020
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2019	03-17-2020

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-18-2019	03-17-2020
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-18-2019	03-17-2020
LISN	CHASE	MN2050D	1447	03-18-2019	03-17-2020
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2021
Cable	HP	10503A	N/A	03-18-2019	03-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and Measurement Data


6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dBμV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4(latest version) on conducted measurement.		
Test Instruments:	Refer to section 5.11 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass(When EUT working, EUT can't Charg)		

Measurement data:

Wall hanging:

Product name:	TOOTHBRUSH	Product model:	GF-7
Test by:	Mike	Test mode:	Charging + Wall hanging
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%




	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.459	33.15	-0.38	-0.06	10.74	43.45	56.71	-13.26	QP
2	0.914	30.04	-0.38	0.24	10.84	40.74	46.00	-5.26	Average
3	0.918	37.11	-0.38	0.24	10.84	47.81	56.00	-8.19	QP
4	1.374	38.10	-0.39	0.10	10.91	48.72	56.00	-7.28	QP
5	1.374	29.85	-0.39	0.10	10.91	40.47	46.00	-5.53	Average
6	1.829	31.71	-0.41	-0.22	10.95	42.03	56.00	-13.97	QP
7	1.829	24.87	-0.41	-0.22	10.95	35.19	46.00	-10.81	Average
8	2.750	29.60	-0.43	-0.23	10.93	39.87	56.00	-16.13	QP
9	2.750	21.22	-0.43	-0.23	10.93	31.49	46.00	-14.51	Average
10	3.207	27.15	-0.45	-0.17	10.91	37.44	56.00	-18.56	QP
11	3.207	20.59	-0.45	-0.17	10.91	30.88	46.00	-15.12	Average
12	4.574	17.27	-0.47	0.03	10.87	27.70	46.00	-18.30	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	TOOTHBRUSH	Product model:	GF-7
Test by:	Mike	Test mode:	Charging + Wall hanging
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%



Trace: 3


	Freq	Read	LISN	Aux	Cable	Level	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.459	35.20	-0.65	0.00	10.74	45.29	56.71	-11.42	QP
2	0.459	28.39	-0.65	0.00	10.74	38.48	46.71	-8.23	Average
3	0.918	38.89	-0.63	0.07	10.84	49.17	56.00	-6.83	QP
4	0.918	32.21	-0.63	0.07	10.84	42.49	46.00	-3.51	Average
5	1.374	37.98	-0.65	0.12	10.91	48.36	56.00	-7.64	QP
6	1.374	30.59	-0.65	0.12	10.91	40.97	46.00	-5.03	Average
7	1.839	31.87	-0.67	0.16	10.95	42.31	56.00	-13.69	QP
8	1.839	25.87	-0.67	0.16	10.95	36.31	46.00	-9.69	Average
9	2.750	28.40	-0.67	0.28	10.93	38.94	56.00	-17.06	QP
10	2.750	22.92	-0.67	0.28	10.93	33.46	46.00	-12.54	Average
11	3.207	30.39	-0.68	0.36	10.91	40.98	56.00	-15.02	QP
12	3.207	22.09	-0.68	0.36	10.91	32.68	46.00	-13.32	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Charging box:

Product name:	TOOTHBRUSH	Product model:	GF-7
Test by:	Mike	Test mode:	Charging + Charging box
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%




Trace: 7

	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.454	35.91	-0.38	-0.01	10.74	46.26	56.80	-10.54	QP
2	0.454	27.52	-0.38	-0.01	10.74	37.87	46.80	-8.93	Average
3	0.614	31.41	-0.38	-0.38	10.77	41.42	56.00	-14.58	QP
4	0.909	37.99	-0.38	0.23	10.84	48.68	56.00	-7.32	QP
5	0.909	31.02	-0.38	0.23	10.84	41.71	46.00	-4.29	Average
6	1.367	37.24	-0.39	0.11	10.91	47.87	56.00	-8.13	QP
7	1.367	29.21	-0.39	0.11	10.91	39.84	46.00	-6.16	Average
8	1.819	30.28	-0.41	-0.21	10.95	40.61	56.00	-15.39	QP
9	1.819	23.51	-0.41	-0.21	10.95	33.84	46.00	-12.16	Average
10	2.721	29.42	-0.43	-0.24	10.93	39.68	56.00	-16.32	QP
11	2.721	22.83	-0.43	-0.24	10.93	33.09	46.00	-12.91	Average
12	4.092	16.50	-0.46	-0.04	10.89	26.89	46.00	-19.11	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	TOOTHBRUSH	Product model:	GF-7
Test by:	Mike	Test mode:	Charging + Charging box
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%



Trace: 5

	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.454	36.73	-0.65	-0.01	10.74	46.81	56.80	-9.99	QP
2	0.454	30.09	-0.65	-0.01	10.74	40.17	46.80	-6.63	Average
3	0.555	33.90	-0.65	0.03	10.76	44.04	56.00	-11.96	QP
4	0.904	38.84	-0.63	0.07	10.84	49.12	56.00	-6.88	QP
5	0.904	32.39	-0.63	0.07	10.84	42.67	46.00	-3.33	Average
6	1.359	38.98	-0.65	0.12	10.91	49.36	56.00	-6.64	QP
7	1.359	32.11	-0.65	0.12	10.91	42.49	46.00	-3.51	Average
8	1.810	33.37	-0.66	0.16	10.95	43.82	56.00	-12.18	QP
9	1.810	25.56	-0.66	0.16	10.95	36.01	46.00	-9.99	Average
10	2.707	31.46	-0.67	0.27	10.93	41.99	56.00	-14.01	QP
11	2.707	24.59	-0.67	0.27	10.93	35.12	46.00	-10.88	Average
12	3.156	19.00	-0.67	0.34	10.91	29.58	46.00	-16.42	Average



Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Note:

Cannot charge when EUT is working mode

6.2 Radiated Emission

Test Requirement:	FCC Part 15 B Section 15.109				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
RMS		1MHz	3MHz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
74.0			Peak Value		
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.				


	4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.11 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	All of the observed value above 6GHz ware the niose floor , which were no recorded

Measurement Data:

Wall hanging:

Below 1GHz:

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Wall hanging
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	53.131	46.62	11.78	1.32	29.81	29.91	40.00	-10.09	QP
2	59.025	45.38	11.44	1.38	29.78	28.42	40.00	-11.58	QP
3	100.229	48.55	12.50	1.94	29.53	33.46	43.50	-10.04	QP
4	141.330	46.61	9.42	2.42	29.27	29.18	43.50	-14.32	QP
5	175.037	45.58	9.81	2.69	29.01	29.07	43.50	-14.43	QP
6	332.519	37.89	14.28	3.04	28.52	26.69	46.00	-19.31	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Wall hanging
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable Preamp	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Level
	MHz	dBuV	dB/m	dB	dB	dBuV/m
	MHz	dBuV	dB/m	dB	dB	dBuV/m
1	55.805	37.50	11.56	1.36	29.80	20.62
2	166.068	38.75	9.49	2.63	29.08	21.79
3	175.652	38.92	9.84	2.70	29.01	22.45
4	245.090	37.87	12.50	2.82	28.57	24.62
5	258.326	36.11	12.87	2.83	28.52	23.29
6	848.056	28.14	22.60	4.20	28.01	26.93

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Wall hanging
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3819.945	47.08	29.72	6.08	41.79	43.29	74.00	-30.71	Peak
2	3819.945	37.35	29.72	6.08	41.79	33.56	54.00	-20.44	Average
3	4830.532	47.90	31.08	6.82	41.82	46.44	74.00	-27.56	Peak
4	4830.532	36.36	31.08	6.82	41.82	34.90	54.00	-19.10	Average
5	5861.858	47.80	32.67	7.90	42.03	49.10	74.00	-24.90	Peak
6	5861.858	36.04	32.67	7.90	42.03	37.34	54.00	-16.66	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Wall hanging
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3980.656	47.29	30.24	6.11	41.81	44.03	74.00	-29.97	Peak
2	3980.656	36.01	30.24	6.11	41.81	32.75	54.00	-21.25	Average
3	5015.753	49.52	31.44	6.95	41.89	48.52	74.00	-25.48	Peak
4	5015.753	37.51	31.44	6.95	41.89	36.51	54.00	-17.49	Average
5	5819.996	48.02	32.66	7.89	42.02	49.30	74.00	-24.70	Peak
6	5819.996	37.63	32.66	7.89	42.02	38.91	54.00	-15.09	Average


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Charging box:

Below 1GHz:

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Charging box
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	102.001	40.73	12.35	1.96	29.51	25.53	43.50	-17.97	QP
2	117.773	45.47	11.04	2.14	29.40	29.25	43.50	-14.25	QP
3	152.664	46.86	9.00	2.53	29.20	29.19	43.50	-14.31	QP
4	203.523	43.47	10.76	2.87	28.81	28.29	43.50	-15.21	QP
5	273.234	39.16	13.14	2.87	28.50	26.67	46.00	-19.33	QP
6	327.887	42.13	14.17	3.03	28.51	30.82	46.00	-15.18	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Charging box
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	31.180	45.46	10.75	0.78	29.97	27.02	40.00	-12.98 QP
2	100.581	39.52	12.46	1.94	29.52	24.40	43.50	-19.10 QP
3	126.329	40.84	10.44	2.24	29.35	24.17	43.50	-19.33 QP
4	188.413	39.09	10.26	2.79	28.91	23.23	43.50	-20.27 QP
5	212.270	40.43	11.15	2.86	28.75	25.69	43.50	-17.81 QP
6	830.400	32.59	22.21	4.25	28.08	30.97	46.00	-15.03 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Charging box
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3847.421	48.21	29.79	6.09	41.79	44.50	74.00	-29.50	Peak
2	3847.421	37.44	29.79	6.09	41.79	33.73	54.00	-20.27	Average
3	4770.324	48.30	30.97	6.81	41.85	46.66	74.00	-27.34	Peak
4	4770.324	37.33	30.97	6.81	41.85	35.69	54.00	-18.31	Average
5	5615.128	47.98	32.62	7.35	41.81	48.83	74.00	-25.17	Peak
6	5615.128	36.26	32.62	7.35	41.81	37.11	54.00	-16.89	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Charging + Charging box
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3980.656	47.87	30.24	6.11	41.81	44.61	74.00	-29.39	Peak
2	3980.656	36.84	30.24	6.11	41.81	33.58	54.00	-20.42	Average
3	4874.002	48.44	31.16	6.85	41.84	47.08	74.00	-26.92	Peak
4	4874.002	37.09	31.16	6.85	41.84	35.73	54.00	-18.27	Average
5	5685.998	49.10	32.64	7.55	41.89	50.10	74.00	-23.90	Peak
6	5685.998	37.34	32.64	7.55	41.89	38.34	54.00	-15.66	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Below 1GHz:

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Working mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable Preamp	Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	345.595	41.67	14.52	3.08	28.55	30.72	46.00	-15.28 QP
2	362.985	41.49	14.80	3.09	28.62	30.76	46.00	-15.24 QP
3	451.135	43.33	16.50	3.21	28.87	34.17	46.00	-11.83 QP
4	506.479	48.90	18.23	3.65	28.97	41.81	46.00	-4.19 QP
5	524.554	47.20	18.30	3.75	29.03	40.22	46.00	-5.78 QP
6	925.756	39.39	22.61	3.96	27.80	38.16	46.00	-7.84 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Working mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	dBuV/m	dBuV/m	Limit	
		dBuV	dB/m	dB	dB			dB	
1	133.151	32.78	9.95	2.32	29.31	15.74	43.50	-27.76	QP
2	153.200	34.42	9.02	2.54	29.19	16.79	43.50	-26.71	QP
3	185.138	34.41	10.13	2.77	28.93	18.38	43.50	-25.12	QP
4	246.815	33.69	12.58	2.81	28.56	20.52	46.00	-25.48	QP
5	348.027	37.88	14.57	3.09	28.56	26.98	46.00	-19.02	QP
6	857.025	29.35	22.59	4.12	27.99	28.07	46.00	-17.93	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Working mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3916.979	47.85	30.01	6.10	41.80	44.36	74.00	-29.64	Peak
2	3916.979	36.51	30.01	6.10	41.80	33.02	54.00	-20.98	Average
3	4830.532	49.86	31.08	6.82	41.82	48.40	74.00	-25.60	Peak
4	4830.532	37.22	31.08	6.82	41.82	35.76	54.00	-18.24	Average
5	5799.177	47.97	32.66	7.89	42.02	49.25	74.00	-24.75	Peak
6	5799.177	36.73	32.66	7.89	42.02	38.01	54.00	-15.99	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	TOOTHBRUSH	Product Model:	GF-7
Test By:	Mike	Test mode:	Working mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3987.794	47.57	30.26	6.11	41.81	44.33	74.00	-29.67	Peak
2	3987.794	37.21	30.26	6.11	41.81	33.97	54.00	-20.03	Average
3	4685.613	48.79	30.78	6.86	42.01	46.83	74.00	-27.17	Peak
4	4685.613	37.27	30.78	6.86	42.01	35.31	54.00	-18.69	Average
5	5605.076	48.07	32.62	7.30	41.79	48.89	74.00	-25.11	Peak
6	5605.076	37.45	32.62	7.30	41.79	38.27	54.00	-15.73	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 EUT Constructional Details

Reference to the test report No.: CCISE191206001

-----End of report-----