

# RF EVALUATION TEST REPORT

Applicant..... : ZHONGSHAN YONGWEI ELECTRICAL APPLIANCE CO.,LTD

Address..... : Building F, NO 21 Defu Street, Tiancheng Road, Dongsheng Town, Zhongshan  
City Guangdong Province, China

Manufacturer..... : ZHONGSHAN YONGWEI ELECTRICAL APPLIANCE CO.,LTD

Address..... : Building F, NO 21 Defu Street, Tiancheng Road, Dongsheng Town, Zhongshan  
City Guangdong Province, China

Factory ..... : ZHONGSHAN YONGWEI ELECTRICAL APPLIANCE CO.,LTD

Address ..... : Building F, NO 21 Defu Street, Tiancheng Road, Dongsheng Town, Zhongshan  
City Guangdong Province, China

Product Name..... : NAGA 60 Soundbar, NAGA 80 Soundbar

Brand Name..... :  YW, MAJORITY

Model No. ..... : YW-S35, YW-S35A, Naga 60, Naga 80 (For model difference refer to section 2.)

FCC ID..... : 2AV4H-NAGA60-NAGA80


Measurement Standard..... : 47 CFR PART 2, Section 2.1091

Receipt Date of Samples.... : November 21, 2023

Date of Tested..... : November 25, 2023 to December 05, 2023

Date of Report..... : December 15, 2023

This report shows that above equipment is technically compliant with the requirements of the standards above.  
All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore  
Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Julie Xiao / Project Engineer



## Table of Contents

1. General Description of EUT .....	4
2. Test Facility and Location .....	6
3. Applicable Standards and References.....	7
4. Maximum Permissible Exposure Limit.....	8
5. RF Exposure Evaluation Results .....	11

## Revision History

## 1. General Description of EUT

Product Information	
Product name:	NAGA 60 Soundbar, NAGA 80 Soundbar
Main Model Name:	Naga 80
Additional Model Name:	Naga 60, YW-S35, YW-S35A
Model Difference:	These models have the same circuit schematic, structure, PCB Layout and critical components. The differences are model number, brand name, power supply, output power and length due to trading purpose. Model YW-S35 and YW-S35A are the same except for model number, length, output power and power supply. Model YW-S35 and Naga 60 are the same except for model number and brand name. Model YW-S35A and Naga 80 are the same except for model number and brand name.
S/N:	2311-5725 for model Naga 80 2311-5726 for model Naga 60
Brand Name:	 <b>MAJORITY</b>
Hardware version:	VER00
Software version:	V03
Rating:	For model YW-S35, Naga 60: DC 20V 60W For model YW-S35A, Naga 80: DC 24V 80W
Typical Arrangement:	Table-top
I/O Port:	Refer to the user manual
Accessories Information	
Adapter 1:	Model: GM42-240170-1A Input: AC 100-240V, 50/60Hz, 1.5A Output: DC 24V, 1.7A
Adapter 2:	Model: GM39-200170-1A Input: AC 100-240V, 50/60Hz, 1.5A Output: DC 20V, 1.7A
Cable:	Power cord(adapter): 1.45m, unshielded, undetachable HDMI cable: 1.43m, shielded, detachable Audio cable: 1.13m, unshielded, detachable
Other:	N/A

**Additional Information**

Note:	According to these model differences and manufacturer's requirements, all tests were performed on model Naga 80 and it was performed with adapter 1.
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

**Technical Specification**

Bluetooth Version:	V5.0
Frequency Range:	2402-2480MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channel:	79 (refer to following channel list for details)
Channel Space:	1MHz
Antenna Type:	PCB antenna
Number of Antenna	1
Antenna Gain:	-0.68 dBi (Declared by the manufacturer)
The EUT does not support Bluetooth Low Energy feature in accordance with the manufacturer declaration.	

## 2. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	<p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01</p> <p>Listed by CNAS, August 13, 2018</p> <p>The Certificate Registration Number is L5795.</p> <p>The Certificate is valid until August 13, 2024</p> <p>The Laboratory has been assessed and proved to be in compliance with ISO17025</p> <p>Listed by A2LA, November 01, 2017</p> <p>The Certificate Registration Number is 4429.01</p> <p>Listed by FCC, November 06, 2017</p> <p>Test Firm Registration Number: 907417</p> <p>Listed by Industry Canada, June 08, 2017</p> <p>The Certificate Registration Number. Is 46405-9743A</p>
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China

### **3. Applicable Standards and References**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

**Test Standards:**

47 CFR Part 1, 1.1307

47 CFR Part 2, 2.1091

KDB 447498 D04 v01

#### 4. Maximum Permissible Exposure Limit

According to 47 CFR Part 1, 1.1307, for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if: 47 CFR Part 1, 1.1307

(A) The available maximum time- averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time- averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where,

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

And,

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the minimum separation distance (cm) in any direction from any part of the device antenna(s) or radiating structure(s) to the body of the device user.

For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time- averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where,

$a$  = number of fixed, mobile, or portable RF sources claiming exemption using para-graph (b)(3)(i)(B) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

$b$  = number of fixed, mobile, or portable RF sources claiming exemption using para-graph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

$c$  = number of existing fixed, mobile, or port-able RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) ac-cording to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

---

*Evaluated<sub>k</sub>*= the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

*Exposure Limit<sub>k</sub>*= either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

## 5. RF Exposure Evaluation Results

Single RF Source								
Mode	Frequency (MHz)	Max. Conducted Power (dBm)	Antenna Gain (dBi)	Max. EIRP (dBm)	Max. ERP (dBm)	Max. ERP (mW)	Separation Distance (cm)	Part 1.1307 Option (B) $P_{th}$ (mW)
GFSK	2402	-2.61	-0.68	-3.29	-5.44	0.29	20	3060
	2441	-4.19	-0.68	-4.87	-7.02	0.20	20	3060
	2480	-4.58	-0.68	-5.26	-7.41	0.18	20	3060
π4/-DQP SK	2402	-0.31	-0.68	-0.99	-3.14	0.49	20	3060
	2441	-1.85	-0.68	-2.53	-4.68	0.34	20	3060
	2480	-2.01	-0.68	-2.69	-4.84	0.33	20	3060
8DPSK	2402	-0.47	-0.68	-1.15	-3.3	0.47	20	3060
	2441	-1.54	-0.68	-2.22	-4.37	0.37	20	3060
	2480	-1.61	-0.68	-2.29	-4.44	0.36	20	3060

### Conclusion:

According to 47 CFR §1.1307 (b)(3)(i)(B), the RF exposure analysis concludes that the product is compliant with the FCC RF exposure requirements in mobile exposure condition.

---End---