

FCC ID: 2AV5CZP-100

According to KDB 447498 D01 General RF Exposure Guidance v06.

At 100 MHz to 6 GHz and for test separation distances \leq 50 mm, the SAR test exclusion threshold is determined according to the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0$$

1. SAR test exclusion threshold

Frequency: 2 480 MHz (min. separation distances = 0 mm)

SAR test exclusion thresholds(5 mm) = $3 \times 5 / (\sqrt{2.480}) = 9.525 \text{ mW}$

Max. tune-up tolerance (mW)	SAR Test Exclusion Thresholds (5 mm) (mW)
0.25	9.525

Calculation value: $0.25 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 0.079$

So, Calculation value \leq 3.0

Remark:

- Max. conducted power (mW): maximum tolerance power of EUT (-6 dBm)
- Max. conducted power 0.251 (mW), so 0.25 (mW) was calculated.
- When the minimum test separation distance is $< 5 \text{ mm}$, a distance of 5 mm is applied to determine SAR test exclusion.

2. Conclusion: SAR is not required.