

**1 Cover Page****RF Exposure Evaluation Report**

**Application No.:** SHEM2004002596CR  
**FCC ID:** 2AV5TMINGJIMINI  
**Applicant:** Beijing Kuangshi Technology Co., Ltd.  
**Address of Applicant:** 313, Tower A, No.2 Kexueyuan South Road, Beijing  
**Manufacturer:** Beijing Kuangshi Technology Co., Ltd.  
**Address of Manufacturer:** 313, Tower A, No.2 Kexueyuan South Road, Beijing  
**Factory:** Megvii(Beijing) Technology Co., Ltd.  
**Address of Factory:** Rm 316-319, Tower A, RayCom info Center, No.2 Kexueyuan South Rd, Beijing

**Equipment Under Test (EUT):**  
**EUT Name:** AI Temperature Measurement Unit  
**Model No.:** MegBox-B2R-411-CW,  
MegBox-B2R-411-XXXXXXXXXXXXXX (where X may be 0-9, A-Z, a-z, symbol or blank)  
 Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

**Trade mark:**

**Standard(s) :** FCC Rules 47 CFR §2.1091  
KDB447498 D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2020-04-10  
**Date of Test:** 2020-05-01 to 2020-05-08  
**Date of Issue:** 2020-05-12

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards specified above.

Parlam Zhan  
E&E Section Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /Inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Revision Record			
Version	Description	Date	Remark
00	Original	2020-05-12	/

Authorized for issue by:			
		 _____ <b>Micheal Niu /Project Engineer</b>	
		 _____ <b>Parlam Zhan /Reviewer</b>	

## **2 Contents**

	Page
<b>1 COVER PAGE</b>	<b>1</b>
<b>2 CONTENTS</b>	<b>3</b>
<b>3 GENERAL INFORMATION</b>	<b>4</b>
3.1 GENERAL DESCRIPTION OF E.U.T.	4
3.2 TECHNICAL SPECIFICATIONS	4
3.3 TEST LOCATION	5
3.4 TEST FACILITY	5
<b>4 TEST STANDARDS AND LIMITS</b>	<b>6</b>
4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
<b>5 MEASUREMENT AND CALCULATION</b>	<b>7</b>
5.1 MAXIMUM TRANSMIT POWER	7
5.2 MPE CALCULATION	8

### 3 General Information

#### 3.1 General Description of E.U.T.

Power supply:	DC 12V/5A by adapter Adapter model: KPL-060F INPUT: AC100~240V 50/60Hz OUTPUT: DC 12V/5A
---------------	---

#### 3.2 Technical Specifications

##### 2.4G WiFi

Antenna Gain	1.86dBi
Antenna Type	Whip Antenna
Channel Spacing	5MHz
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz

##### BT

Antenna Gain:	1.86dBi
Antenna Type:	Whip Antenna
Bluetooth Version:	V4.2 Classic
Channel Spacing:	1MHz
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels:	79
Operation Frequency:	2402MHz to 2480MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)

### **3.3 Test Location**

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

All measurement facilities used to collect the measurement data are located at

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

No tests were sub-contracted.

### **3.4 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L4354)**

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017

General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01

Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- FCC –Designation Number: CN1172**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory.

Designation Number: CN1172. Test Firm Registration Number: 995260.

- Industry Canada (IC) – IC Assigned Code: 2324E**

The 10m and 3m Semi-anechoic chamber of Compliance Certification Services (Kunshan) Inc. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 2324E-1 for 10m chamber, 2324E-2 for 3m chamber.

- VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

## 4 Test Standards and Limits

### 4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 2.4GHz is 1.0 mW/cm<sup>2</sup>

## 5 Measurement and Calculation

### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200400259601, SHEM200400259602

BT

Test Mode	Test Frequency (MHz)	Output Power (dBm)	Reading Power (mW)
GFSK	2402	6.16	4.13
	2441	5.98	3.96
	2480	4.26	2.67
Pi/4DQPSK	2402	-0.86	0.82
	2441	-1.27	0.75
	2480	2.22	1.67
8DPSK	2402	-0.28	0.94
	2441	-0.76	0.84
	2480	2.81	1.91

2.4G WiFi

Test Mode	Test Channel	Ant	Power [dBm]	Power [mW]
11B	2412	Ant1	16.00	39.81
11B	2437	Ant1	16.71	46.88
11B	2462	Ant1	17.02	50.35
11G	2412	Ant1	18.58	72.11
11G	2437	Ant1	19.51	89.33
11G	2462	Ant1	19.73	93.97
11N20SISO	2412	Ant1	18.34	68.23
11N20SISO	2437	Ant1	19.26	84.33
11N20SISO	2462	Ant1	19.47	88.51

## 5.2 MPE Calculation

For WiFi:

According to the formula  $S=P/4\pi R^2$ , we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm<sup>2</sup>

For WIFI

The max. antenna gain is 1.86 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
93.97	1.535	20	0.02869	1	Pass

For BT

The max. antenna gain is 1.86 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
4.13	1.535	20	0.00126	1	Pass

The BT and the DTS modules can simultaneous transmitting at frequency 2.4GHz band. But the maximum rate of MPE is  $0.029/1.0+0.001/1.0=0.03<=1.0$ . according to the KDB447498 section 7.2 determine the device is exclusion from SAR test.

**--End of the Report--**