



Test Report – FCC Part 15B Unintentional Radiator

Applicant: STORMQUANT

Signature:

A handwritten signature of Tim Royer is placed over a horizontal line.

Sr. EMC Engineer
EMC-003838-NE



Name & Title:

Tim Royer, Lab Manager

Date of Signature

12/17/2024

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.

Table of Contents

1. APPLICANT INFORMATION.....	3
1.1 TEST RESULT SUMMARY.....	3
2. LOCATION OF TESTING.....	4
2.1 TEST LABORATORY	4
3. TEST SAMPLE(S) (EUT/DUT).....	4
3.1 DESCRIPTION OF THE EUT.....	5
3.2 CONFIGURATION OF EUT.....	6
3.3 TEST SETUP OF EUT.....	6
4. TEST METHODS & APPLICABLE REGULATORY LIMITS.....	7
4.1 TEST METHODS/STANDARDS/GUIDANCE	7
5. MEASUREMENT UNCERTAINTY.....	7
6. ENVIRONMENTAL CONDITIONS	7
7. LIST OF TEST EQUIPMENT AND TEST FACILITY.....	8
8. TEST RESULTS.....	9
8.1 RADIATED EMISSIONS.....	10
8.1.1 Radiated Tabular Data	11
8.2 CONDUCTED EMISSIONS.....	12
8.2.1 Line 1 Plot	13
8.2.2 Line 2 Plot	14
9. ANNEX-B – TEST SETUP PHOTOGRAPHS.....	15
10. HISTORY OF TEST REPORT CHANGES.....	15

1. Applicant Information

Applicant: STORMQUANT
Address: 1431 Chaffee Drive suite 1
Titusville FL 32780

1.1 Test Result Summary

The following test procedure was used ANSI C63.4-2014. Full test results are available in this report.

No additions to the test methods were needed. There were no deviations, or exclusions from the test methods. No test results are from external providers or from the customer. The test results relate only to the items tested. IIA Lab Services LLC does not offer opinions and interpretations, only a pass/fail statement.

Clauses	Description of the Requirements	Result (Pass, Fail or N/A)
Applicable Clauses from FCC 15 B		
15.107	Conducted Emission Limits	Pass
15.109	Radiated Emission Limits	Pass

2. Location of Testing

2.1 Test Laboratory

IIA Lab Services LLC. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86th Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01

3. Test Sample(s) (EUT/DUT)

The test sample was received: 11/13/2024

Dates of Testing: 11/13/2024 – 11/22/2024

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
Brief Description	Weather Radar
Model(s) #	200AA
Firmware version	BRD108-0002; FPGA-0011; TMS-0004
Software version	4.0.0
Serial Number	24-28-000
FCC ID	2AV9O-BATV1

Technical Characteristics	
Antenna Type	Waveguide
Voltage Rating (AC or Batt.)	110V AC

Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

3.2 Configuration of EUT

Band (MHz)	Mode	Number of Ant.
n/a	Transmit	1

Operating conditions during Testing:

No modifications of the device under test (including firmware, specific software settings, and input/output signal levels to the EUT).

Peripherals used during Testing:

No peripherals used.

3.3 Test Setup of EUT

Equipment, antenna, and cable arrangement. The setup of the equipment and cable or wire placement on the test site that produces the highest radiated and the highest ac power-line conducted emissions shall be shown clearly and described. Information on the orientation of portable equipment during testing shall be included. Drawings or photographs may be used for this purpose.

Test Setups are included in the test report.

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance

The measurement was performed as per ANSI 63.4. Full test results are available in this report.

Limits and Regulatory Limits:

- 1) FCC 15.109 (2015)

5. Measurement Uncertainty

Parameter	Uncertainty (dB)
Conducted Emissions	± 3.14 dB
Radiated Emissions (9kHz – 30 MHz)	± 3.08 dB
Radiated Emissions (30 – 200 MHz)	± 2.16 dB
Radiated Emissions (200 – 1000 MHz)	± 2.15 dB
Radiated Emissions (1 GHz – 18 GHz)	± 2.14 dB
Radiated Emissions (18 GHz – 40 GHz)	± 2.31 dB

Note: The uncertainties provided in this table represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of K=2.

6. Environmental Conditions

Temperature & Humidity

Measurements performed at the test site did not exceed the following:

Parameter	Measurement
Temperature	23 C +/- 5%
Humidity	55% +/- 5%
Barometric Pressure	30.05 in Hg

Note: Specific environmental conditions that are applicable to a specific test are available in the test result section.

7. List of Test Equipment and Test Facility

The test equipment used identified by type, manufacturer, serial number, or other identification and the date on which the next calibration or service check is due.

Description of the firmware or software used to operate EUT for testing purposes.

A complete list of all test equipment used shall be included with the test report. The manufacturer's model and serial numbers, and date of last calibration, and calibration interval shall be included. Measurement cable loss, measuring instrument bandwidth and detector function, video bandwidth, if appropriate, and antenna factors shall also be included where applicable.

List of Test Equipment

Test Equipment						
Type	Device	Manufacturer	Model	SN#	Current Cal	Cal Due
Antenna	Biconical 1057	Eaton	94455-1	1057	9/1/2024	9/1/2027
Antenna, NSA	Log-Periodic 1243	Eaton	96005	1243	9/1/2024	9/1/2027
Antenna	Double-Ridged Horn/ETS Horn 1	ETS-Lindgren	3117	00035923	5/31/23	5/30/2026
CHAMBER	CHAMBER	Panashield	3M	N/A	12/29/23	12/18/2025
Pre-amp	Pre-amp	RF-LAMBDA	RLNA00M45GA	NA	2/27/22	7/26/2025
Receiver	EMI Test Receiver R&S ESW44	Rohde & Schwarz	ESW44	103049	10/13/22	10/12/2025

8. Test Results

The results of the test are usually indicated in the form of tables, spectrum analyzer plots, charts, sample calculations, as appropriate for each test procedure.

A description and/or a block diagram of the test setup is usually provided.

The measurement results, along with the appropriate limits for comparison, may be presented in tabular or graphical form. In addition, any variation in the measurement environment may be reported if applicable (e.g., a significant change of temperature that could affect the cable loss and amplifier response).

Units of measurement

Unless noted otherwise in the referenced standard, the measurements of ac power-line conducted emissions and conducted power output will be reported in units of dB μ V. Unless noted otherwise in the referenced standard, the measurements of radiated emissions will be reported in units of decibels, referenced to one microvolt per meter (dB μ V/m) for electric fields, or to one ampere per meter (dBA/m) for magnetic fields, at the distance specified in the appropriate standards or requirements. The measurements of antenna-conducted power for receivers may be reported in units of dB μ V if the impedance of the measuring instrument is also reported. Otherwise, antenna-conducted power will be reported in units of decibels referenced to one milliwatt (dBm). All formulas for data conversions and conversion factors, if used, will be included in this measurement report.

Example:


Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB μ V	+ 10.36 dB/m	+0.40 dB	=30.36 dB μ V/m @ 3m

$$\text{EIRP} = \text{Pcond (dBm)} + \text{dBi}$$


8.1 Radiated Emissions

Limits from FCC 15.109 and test procedure from ANSI C63.4-2014, Class A limits applied

Radiated Test Setup, 30 – 1000 MHz



Radiated Test Setup, Above 1000 MHz



8.1.1 Radiated Tabular Data


Emission Frequency (MHz)	15.205 Restricted Band	15.247(d) Detector	Meter Reading (dB μ V)	Antenna Polarity	Coax Loss (dB)	Duty Cycle Correction (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
42.80		PK	12.63	H	0.73	0.00	12.76	3.00	26.12	40	13.88
50.30		PK	22.43	V	0.82	0.00	10.91	3.00	34.16	40	5.84
142.24		PK	14.96	H	1.35	0.00	15.85	3.00	32.16	43.5	11.34
157.40		PK	4.85	V	1.44	0.00	17.00	3.00	23.29	43.5	20.21
294.87		PK	5.97	V	2.08	0.00	13.84	3.00	21.89	46	24.11
396.16		PK	5.45	H	2.28	0.00	15.86	3.00	23.59	46	22.41
706.40		PK	5.30	V	3.12	0.00	21.44	3.00	29.86	46	16.14
797.40		PK	3.03	H	3.33	0.00	21.34	3.00	27.71	46	18.29
1435.00	X	PK	15.65	V	4.32	0.00	27.95	3.00	47.92	53.98	6.06
1471.10	X	PK	15.83	H	4.41	0.00	27.79	3.00	48.03	53.98	5.95
7326.90	X	PK	10.36	V	9.59	0.00	36.41	3.00	56.35	53.98	-2.37
2233.90	X	PK	17.13	H	5.41	0.00	31.71	3.00	54.25	53.98	-0.27
15403.00	X	PK	10.81	V	14.13	0.00	41.31	3.00	66.24	53.98	-12.26
15283.00		PK	10.88	H	13.95	0.00	40.91	3.00	65.74	53.98	-11.76

Class A limits applied


8.2 Conducted Emissions

Limits from FCC 15.107 and test procedure from ANSI C63.4-2014.


Conducted Test Setup



8.2.1 Line 1 Plot



8.2.2 Line 2 Plot



9. ANNEX-B – Test Setup Photographs

Test setup photographs are located in a separate document.

10. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_17263-24_FCC 15B_1	1	Initial release	12/17/2024
	2	Changes in Page 11	07/24/2025



13146 NW 86th Drive, Suite 400, Alachua, Florida 32615
(352) 472-5500 / testing@industrial-ia.com

END OF TEST REPORT
