



Appendix D

RF Test Data for 5.2G WLAN (Conducted Measurement)

Product Name: Formuler Z10 Pro

Trade Mark: FORMULER

Test Model: Z10 Pro

Environmental Conditions

Temperature:	23.7° C
Relative Humidity:	51.6%
ATM Pressure:	100.0 kPa
Test Engineer:	Jay Li
Supervised by:	Li Huan


D.1 Duty Cycle

ANT0


Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5200	96.92	0.14	0.01
11N20 SISO	5200	96.72	0.14	0.01
11N40 SISO	5190	93.75	0.28	0.01
11AC20 SISO	5200	96.83	0.14	0.01
11AC40 SISO	5190	93.65	0.28	0.01
11AC80 SISO	5210	87.89	0.56	0.01




On Time and Duty Cycle




IEEE 802.11a




IEEE 802.11n HT20




IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11 AC40





IEEE 802.11AC80




ANT1

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5200	96.92	0.14	0.01
11N20 SISO	5200	96.72	0.14	0.01
11N40 SISO	5190	93.57	0.29	0.01
11AC20 SISO	5200	96.92	0.14	0.01
11AC40 SISO	5190	93.82	0.28	0.01
11AC80 SISO	5210	87.89	0.56	0.01







IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11 AC40



IEEE 802.11AC80

**D.2 Maximum Conduct Output Power****ANT0**

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Limit (dBm)	Verdict
11A	36	5180	12.39	24	Pass
	40	5200	12.7		Pass
	48	5240	12.93		Pass
11N20 SISO	36	5180	12.03	24	Pass
	40	5200	12.39		Pass
	48	5240	12.66		Pass
11N40 SISO	38	5190	12.41	24	Pass
	46	5230	12.65		Pass
11AC20 SISO	36	5180	11.94	24	Pass
	40	5200	12.3		Pass
	48	5240	12.58		Pass
11AC40 SISO	38	5190	12.36	24	Pass
	46	5230	12.7		Pass
11AC80 SISO	42	5210	12.52	24	Pass

ANT1

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Limit (dBm)	Verdict
11A	36	5180	12.75	24	Pass
	40	5200	13.01		Pass
	48	5240	13.04		Pass
11N20 SISO	36	5180	11.98	24	Pass
	40	5200	12.38		Pass
	48	5240	12.65		Pass
11N40 SISO	38	5190	12.4	24	Pass
	46	5230	12.78		Pass
11AC20 SISO	36	5180	12.4	24	Pass
	40	5200	12.66		Pass
	48	5240	13.07		Pass
11AC40 SISO	38	5190	12.28	24	Pass
	46	5230	12.64		Pass
11AC80 SISO	42	5210	12.49	24	Pass


MIMO


Test Mode	Channel	Frequency (MHz)	ANT 0 AVG Conducted Power (dBm)	ANT 1 AVG Conducted Power (dBm)	MIMO AVG Conducted Power (dBm)	Limit (dBm)	Verdict
11N20	36	5180	12.03	11.98	15.02	24	Pass
	40	5200	12.39	12.38	15.40		Pass
	48	5240	12.66	12.65	15.67		Pass
11N40	38	5190	12.41	12.4	15.42	24	Pass
	46	5230	12.65	12.78	15.73		Pass
11AC20	36	5180	11.94	12.4	15.19	24	Pass
	40	5200	12.3	12.66	15.34		Pass
	48	5240	12.58	13.07	15.75		Pass
11AC40	38	5190	12.36	12.28	15.48	24	Pass
	46	5230	12.7	12.64	15.53		Pass
11AC80	42	5210	12.52	12.49	15.65	24	Pass

**D.3 Power Spectral Density**


ANT0

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Cycle Factor (dB)	Report Power Density (dBm/MHz)	Limit (dBm/MHz)	Verdict
11A	36	5180	2.88	0.14	3.02	11	Pass
	40	5200	3.04	0.14	3.18		Pass
	48	5240	2.92	0.14	3.06		Pass
11N20 SISO	36	5180	1.95	0.14	2.10	11	Pass
	40	5200	2.12	0.14	2.26		Pass
	48	5240	2.92	0.28	3.07		Pass
11N40 SISO	38	5190	-0.26	0.28	0.02	11	Pass
	46	5230	1.07	0.28	1.36		Pass
11AC20 SISO	36	5180	1.97	0.14	2.11	11	Pass
	40	5200	2.27	0.14	2.41		Pass
	48	5240	2.49	0.14	2.63		Pass
11AC40 SISO	38	5190	-0.33	0.28	-0.05	11	Pass
	46	5230	0.14	0.28	0.42		Pass
11AC80 SISO	42	5210	-2.92	0.56	-2.36	11	Pass







IEEE 802.11na / Channel 40 / 5200MHz





IEEE 802.11na / Channel 48 / 5240MHz






IEEE 802.11n20 / Channel 48 / 5240MHz







IEEE 802.11ac20 / Channel 36 / 5180MHz




IEEE 802.11ac20 / Channel 40 / 5200MHz




IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz





IEEE 802.11ac80 / Channel 42 / 5210MHz




ANT1

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Cycle Factor (dB)	Report Power Density (dBm/MHz)	Limit (dBm/MHz)	Verdict
11A	36	5180	3.07	0.14	3.21	11	Pass
	40	5200	3.48	0.14	3.62		Pass
	48	5240	3.10	0.14	3.24		Pass
11N20 SISO	36	5180	2.13	0.14	2.27	11	Pass
	40	5200	2.31	0.14	2.45		Pass
	48	5240	3.31	0.14	3.46		Pass
11N40 SISO	38	5190	-0.19	0.29	0.10	11	Pass
	46	5230	-0.23	0.29	0.07		Pass
11AC20 SISO	36	5180	2.72	0.14	2.86	11	Pass
	40	5200	3.39	0.14	3.53		Pass
	48	5240	3.51	0.14	3.65		Pass
11AC40 SISO	38	5190	-0.13	0.28	0.15	11	Pass
	46	5230	-0.05	0.28	0.23		Pass
11AC80 SISO	42	5210	-3.30	0.56	-2.74	11	Pass






IEEE 802.11na / Channel 40 / 5200MHz




IEEE 802.11na / Channel 48 / 5240MHz




Power Spectral Density




IEEE 802.11n20 / Channel 36 / 5180MHz




IEEE 802.11n20 / Channel 40 / 5200MHz




IEEE 802.11n20 / Channel 48 / 5240MHz







IEEE 802.11ac20 / Channel 36 / 5180MHz




IEEE 802.11ac20 / Channel 40 / 5200MHz




IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz



IEEE 802.11ac80 / Channel 42 / 5210MHz




MIMO


Test Mode	Channel	Frequency (MHz)	ANT 0 Power Density (dBm/MHz)	ANT 1 Power Density (dBm/MHz)	MIMO Power Density (dBm/MHz)	Limit (dBm/MHz)	Verdict
11N20	36	5180	2.10	2.27	5.20	11	Pass
	40	5200	2.26	2.45	5.37		Pass
	48	5240	3.07	3.46	6.28		Pass
11N40	38	5190	0.02	0.10	3.07	11	Pass
	46	5230	1.36	0.07	3.77		Pass
11AC20	36	5180	2.11	2.86	5.51	11	Pass
	40	5200	2.41	3.53	6.02		Pass
	48	5240	2.63	3.65	6.18		Pass
11AC40	38	5190	-0.05	0.15	3.06	11	Pass
	46	5230	0.42	0.23	3.34		Pass
11AC80	42	5210	-2.36	-2.74	0.46	11	Pass

**D.4 Emission Bandwidth**


ANT0

Test Mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	36	5180	20.88	No Limit	Pass
	40	5200	20.92		Pass
	48	5240	20.84		Pass
11N20 SISO	36	5180	21.37	No Limit	Pass
	40	5200	21.54		Pass
	48	5240	21.36		Pass
11N40 SISO	38	5190	40.08	No Limit	Pass
	46	5230	39.59		Pass
11AC20 SISO	36	5180	21.32	No Limi	Pass
	40	5200	21.74		Pass
	48	5240	21.44		Pass
11AC40 SISO	38	5190	39.49	No Limi	Pass
	46	5230	39.98		Pass
11AC80 SISO	42	5210	80.53	No Limi	Pass







IEEE 802.11a / Channel 40 / 5200MHz



IEEE 802.11a / Channel 48 / 5240MHz







IEEE 802.11n20 / Channel 48 / 5240MHz




26dB Bandwidth




IEEE 802.11n40 / Channel 38 / 5190MHz




IEEE 802.11n40 / Channel 46 / 5230MHz




IEEE 802.11ac20 / Channel 36 / 5180MHz




IEEE 802.11ac20 / Channel 40 / 5200MHz




IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz





IEEE 802.11ac80 / Channel 42 / 5210MHz




ANT1

Test Mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	36	5180	20.77	No Limit	Pass
	40	5200	20.89		Pass
	48	5240	20.97		Pass
11N20 SISO	36	5180	21.58	No Limit	Pass
	40	5200	21.68		Pass
	48	5240	21.27		Pass
11N40 SISO	38	5190	39.85	No Limit	Pass
	46	5230	39.67		Pass
11AC20 SISO	36	5180	21.09	No Limi	Pass
	40	5200	21.05		Pass
	48	5240	21.03		Pass
11AC40 SISO	38	5190	39.69	No Limi	Pass
	46	5230	39.72		Pass
11AC80 SISO	42	5210	80.55	No Limi	Pass







IEEE 802.11a / Channel 40 / 5200MHz



IEEE 802.11a / Channel 48 / 5240MHz







IEEE 802.11n20 / Channel 48 / 5240MHz




26dB Bandwidth




IEEE 802.11n40 / Channel 38 / 5190MHz




IEEE 802.11n40 / Channel 46 / 5230MHz




IEEE 802.11ac20 / Channel 36 / 5180MHz




IEEE 802.11ac20 / Channel 40 / 5200MHz




IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz





IEEE 802.11ac80 / Channel 42 / 5210MHz

**D.5 Undesirable Emissions Measurement**

ANT0


Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
11A	36	4500.0	-49.83	2.00	0	47.40	Peak	68.20	Pass
		4500.0	-59.78	2.00	0	37.45	Average	54.00	Pass
		5150.0	-37.53	2.00	0	59.70	Peak	68.20	Pass
		5150.0	-54.65	2.00	0	42.58	Average	54.00	Pass
	48	5350.0	-49.95	2.00	0	47.28	Peak	68.20	Pass
		5350.0	-59.44	2.00	0	37.79	Average	54.00	Pass
		5460.0	-48.52	2.00	0	48.71	Peak	68.20	Pass
		5460.0	-59.66	2.00	0	37.57	Average	54.00	Pass
11N2 0 SISO	36	4500.0	-49.92	2.00	0	47.31	Peak	68.20	Pass
		4500.0	-59.77	2.00	0	37.46	Average	54.00	Pass
		5150.0	-41.31	2.00	0	55.92	Peak	68.20	Pass
		5150.0	-54.81	2.00	0	42.42	Average	54.00	Pass
	48	5350.0	-48.90	2.00	0	48.33	Peak	68.20	Pass
		5350.0	-59.42	2.00	0	37.81	Average	54.00	Pass
		5460.0	-49.53	2.00	0	47.70	Peak	68.20	Pass
		5460.0	-59.66	2.00	0	37.57	Average	54.00	Pass
11N4 0 SISO	38	4500.0	-49.89	2.00	0	47.34	Peak	68.20	Pass
		4500.0	-59.77	2.00	0	37.46	Average	54.00	Pass
		5150.0	-41.31	2.00	0	55.92	Peak	68.20	Pass
		5150.0	-52.67	2.00	0	44.56	Average	54.00	Pass
	46	5350.0	-48.50	2.00	0	48.73	Peak	68.20	Pass
		5350.0	-58.59	2.00	0	38.64	Average	54.00	Pass
		5460.0	-49.18	2.00	0	48.05	Peak	68.20	Pass
		5460.0	-59.32	2.00	0	37.91	Average	54.00	Pass
11A C20 SISO	36	4500.0	-50.20	2.00	0	47.03	Peak	68.20	Pass
		4500.0	-59.80	2.00	0	37.43	Average	54.00	Pass
		5150.0	-42.08	2.00	0	55.15	Peak	68.20	Pass
		5150.0	-54.95	2.00	0	42.28	Average	54.00	Pass
	48	4500.0	-50.20	2.00	0	47.03	Peak	68.20	Pass
		4500.0	-59.80	2.00	0	37.43	Average	54.00	Pass
		5150.0	-42.08	2.00	0	55.15	Peak	68.20	Pass
		5150.0	-54.95	2.00	0	42.28	Average	54.00	Pass
11A C40 SISO	38	4500.0	-50.62	2.00	0	46.61	Peak	68.20	Pass
		4500.0	-59.80	2.00	0	37.43	Average	54.00	Pass
		5150.0	-42.02	2.00	0	55.21	Peak	68.20	Pass
		5150.0	-53.00	2.00	0	44.23	Average	54.00	Pass
	46	5350.0	-48.43	2.00	0	48.80	Peak	68.20	Pass
		5350.0	-58.62	2.00	0	38.61	Average	54.00	Pass
		5460.0	-48.69	2.00	0	48.54	Peak	68.20	Pass
		5460.0	-59.27	2.00	0	37.96	Average	54.00	Pass
11A C80 SISO	42	4500.0	-46.67	2.00	0	50.56	Peak	68.20	Pass
		4500.0	-57.06	2.00	0	40.17	Average	54.00	Pass
		5150.0	-48.40	2.00	0	48.83	Peak	68.20	Pass
		5150.0	-58.64	2.00	0	38.59	Average	54.00	Pass
		5350.0	-46.67	2.00	0	50.56	Peak	68.20	Pass
		5350.0	-57.06	2.00	0	40.17	Average	54.00	Pass
		5460.0	-48.40	2.00	0	48.83	Peak	68.20	Pass
		5460.0	-58.64	2.00	0	38.59	Average	54.00	Pass









Undesirable Emissions Measurement



IEEE 802.11n20 / Channel 36 / 5180MHz / Peak




IEEE 802.11n20 / Channel 36 / 5180MHz / Average






Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 38 / 5190MHz / Peak




IEEE 802.11n40 / Channel 38 / 5190MHz / Average




Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 46 / 5230MHz / Peak




IEEE 802.11n40 / Channel 46 / 5230MHz / Average




IEEE 802.11ac20 / Channel 36 / 5180MHz / Peak




IEEE 802.11ac20 / Channel 36 / 5180MHz / Average




IEEE 802.11ac20 / Channel 48 / 5240MHz / Peak




IEEE 802.11ac20 / Channel 48 / 5240MHz / Average




IEEE 802.11ac40 / Channel 38/ 5190MHz / Peak




IEEE 802.11ac40 / Channel 38 / 5190MHz / Average




IEEE 802.11ac40 / Channel 46/ 5230MHz / Peak



IEEE 802.11ac40 / Channel 46 / 5230MHz / Average



IEEE 802.11ac80 / Channel 42 / 5210MHz / Peak



IEEE 802.11ac80 / Channel 42 / 5210MHz / Average




ANT1


Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
11A	36	4500.0	-49.55	2.00	0	47.68	Peak	68.20	Pass
		4500.0	-59.77	2.00	0	37.46	Average	54.00	Pass
		5150.0	-37.27	2.00	0	59.96	Peak	68.20	Pass
		5150.0	-54.64	2.00	0	42.59	Average	54.00	Pass
	48	5350.0	-49.15	2.00	0	48.08	Peak	68.20	Pass
		5350.0	-59.41	2.00	0	37.82	Average	54.00	Pass
		5460.0	-49.79	2.00	0	47.44	Peak	68.20	Pass
		5460.0	-59.64	2.00	0	37.59	Average	54.00	Pass
11N2 O SISO	36	4500.0	-49.47	2.00	0	47.76	Peak	68.20	Pass
		4500.0	-59.81	2.00	0	37.42	Average	54.00	Pass
		5150.0	-39.45	2.00	0	57.78	Peak	68.20	Pass
		5150.0	-54.85	2.00	0	42.38	Average	54.00	Pass
	48	5350.0	-49.15	2.00	0	48.08	Peak	68.20	Pass
		5350.0	-59.43	2.00	0	37.80	Average	54.00	Pass
		5460.0	-48.93	2.00	0	48.30	Peak	68.20	Pass
		5460.0	-59.61	2.00	0	37.62	Average	54.00	Pass
11N4 O SISO	38	4500.0	-49.51	2.00	0	47.72	Peak	68.20	Pass
		4500.0	-59.75	2.00	0	37.48	Average	54.00	Pass
		5150.0	-40.84	2.00	0	56.39	Peak	68.20	Pass
		5150.0	-52.62	2.00	0	44.61	Average	54.00	Pass
	46	5350.0	-48.84	2.00	0	48.39	Peak	68.20	Pass
		5350.0	-58.58	2.00	0	38.65	Average	54.00	Pass
		5460.0	-48.49	2.00	0	48.74	Peak	68.20	Pass
		5460.0	-59.30	2.00	0	37.93	Average	54.00	Pass
11A C20 SIS O	36	4500.0	-50.34	2.00	0	46.89	Peak	68.20	Pass
		4500.0	-59.74	2.00	0	37.49	Average	54.00	Pass
		5150.0	-37.17	2.00	0	60.06	Peak	68.20	Pass
		5150.0	-54.56	2.00	0	42.67	Average	54.00	Pass
	48	4500.0	-50.34	2.00	0	46.89	Peak	68.20	Pass
		4500.0	-59.74	2.00	0	37.49	Average	54.00	Pass
		5150.0	-37.17	2.00	0	60.06	Peak	68.20	Pass
		5150.0	-54.56	2.00	0	42.67	Average	54.00	Pass
11A C40 SIS O	38	4500.0	-50.23	2.00	0	47.00	Peak	68.20	Pass
		4500.0	-59.76	2.00	0	37.47	Average	54.00	Pass
		5150.0	-41.18	2.00	0	56.05	Peak	68.20	Pass
		5150.0	-52.68	2.00	0	44.55	Average	54.00	Pass
	46	5350.0	-47.32	2.00	0	49.91	Peak	68.20	Pass
		5350.0	-58.64	2.00	0	38.59	Average	54.00	Pass
		5460.0	-48.66	2.00	0	48.57	Peak	68.20	Pass
		5460.0	-59.28	2.00	0	37.95	Average	54.00	Pass
11A C80 SIS O	42	4500.0	-47.49	2.00	0	49.74	Peak	68.20	Pass
		4500.0	-57.06	2.00	0	40.17	Average	54.00	Pass
		5150.0	-49.74	2.00	0	47.49	Peak	68.20	Pass
		5150.0	-58.67	2.00	0	38.56	Average	54.00	Pass
		5350.0	-47.49	2.00	0	49.74	Peak	68.20	Pass
		5350.0	-57.06	2.00	0	40.17	Average	54.00	Pass
		5460.0	-49.74	2.00	0	47.49	Peak	68.20	Pass
		5460.0	-58.67	2.00	0	38.56	Average	54.00	Pass



Undesirable Emissions Measurement




IEEE 802.11a / Channel 36 / 5180MHz / Peak




IEEE 802.11a / Channel 36 / 5180MHz / Average



Undesirable Emissions Measurement




IEEE 802.11a / Channel 48 / 5240MHz / Peak




IEEE 802.11a / Channel 48 / 5240MHz / Average




Undesirable Emissions Measurement





IEEE 802.11n20 / Channel 36 / 5180MHz / Peak




IEEE 802.11n20 / Channel 36 / 5180MHz / Average












IEEE 802.11ac20 / Channel 36 / 5180MHz / Peak




IEEE 802.11ac20 / Channel 36 / 5180MHz / Average




IEEE 802.11ac20 / Channel 48 / 5240MHz / Peak




IEEE 802.11ac20 / Channel 48 / 5240MHz / Average




IEEE 802.11ac40 / Channel 38/ 5190MHz / Peak




IEEE 802.11ac40 / Channel 38 / 5190MHz / Average




IEEE 802.11ac40 / Channel 46/ 5230MHz / Peak



IEEE 802.11ac40 / Channel 46 / 5230MHz / Average



IEEE 802.11ac80 / Channel 42 / 5210MHz / Peak



IEEE 802.11ac80 / Channel 42 / 5210MHz / Average

**MIMO**

Test Mode	Channel	Frequency (MHz)	ANT 0 Conducted Power (dBm)	ANT 1 Conducted Power (dBm)	MIMO Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
11N20	36	4500.0	-49.92	-49.47	-46.68	5.01	0	50.55	Peak	68.20	Pass
		4500.0	-59.77	-59.81	-56.78	5.01	0	40.45	Average	54.00	Pass
		5150.0	-41.31	-39.45	-37.27	5.01	0	59.96	Peak	68.20	Pass
		5150.0	-54.81	-54.85	-51.82	5.01	0	45.41	Average	54.00	Pass
	48	5350.0	-48.90	-49.15	-46.01	5.01	0	51.22	Peak	68.20	Pass
		5350.0	-59.42	-59.43	-56.41	5.01	0	40.82	Average	54.00	Pass
		5460.0	-49.53	-48.93	-46.21	5.01	0	51.02	Peak	68.20	Pass
		5460.0	-59.66	-59.61	-56.62	5.01	0	40.61	Average	54.00	Pass
11N40	38	4500.0	-49.89	-49.51	-46.69	5.01	0	50.54	Peak	68.20	Pass
		4500.0	-59.77	-59.75	-56.75	5.01	0	40.48	Average	54.00	Pass
		5150.0	-41.31	-40.84	-38.06	5.01	0	59.17	Peak	68.20	Pass
		5150.0	-52.67	-52.62	-49.63	5.01	0	47.60	Average	54.00	Pass
	46	5350.0	-48.50	-48.84	-45.66	5.01	0	51.57	Peak	68.20	Pass
		5350.0	-58.59	-58.58	-55.57	5.01	0	41.66	Average	54.00	Pass
		5460.0	-49.18	-48.49	-45.81	5.01	0	51.42	Peak	68.20	Pass
		5460.0	-59.32	-59.30	-56.30	5.01	0	40.93	Average	54.00	Pass
11AC20	36	4500.0	-50.20	-50.34	-47.26	5.01	0	49.97	Peak	68.20	Pass
		4500.0	-59.80	-59.74	-56.76	5.01	0	40.47	Average	54.00	Pass
		5150.0	-42.08	-37.17	-35.95	5.01	0	61.28	Peak	68.20	Pass
		5150.0	-54.95	-54.56	-51.74	5.01	0	45.49	Average	54.00	Pass
	48	4500.0	-50.20	-50.34	-47.26	5.01	0	49.97	Peak	68.20	Pass
		4500.0	-59.80	-59.74	-56.76	5.01	0	40.47	Average	54.00	Pass
		5150.0	-42.08	-37.17	-35.95	5.01	0	61.28	Peak	68.20	Pass
		5150.0	-54.95	-54.56	-51.74	5.01	0	45.49	Average	54.00	Pass
11AC40	38	4500.0	-50.62	-50.23	-47.41	5.01	0	49.82	Peak	68.20	Pass
		4500.0	-59.80	-59.76	-56.77	5.01	0	40.46	Average	54.00	Pass
		5150.0	-42.02	-41.18	-38.57	5.01	0	58.66	Peak	68.20	Pass
		5150.0	-53.00	-52.68	-49.83	5.01	0	47.40	Average	54.00	Pass
	46	5350.0	-48.43	-47.32	-44.83	5.01	0	52.40	Peak	68.20	Pass
		5350.0	-58.62	-58.64	-55.62	5.01	0	41.61	Average	54.00	Pass
		5460.0	-48.69	-48.66	-45.66	5.01	0	51.57	Peak	68.20	Pass
		5460.0	-59.27	-59.28	-56.26	5.01	0	40.97	Average	54.00	Pass
11AC80	42	4500.0	-46.67	-47.49	-44.05	5.01	0	53.18	Peak	68.20	Pass
		5150.0	-57.06	-57.06	-54.05	5.01	0	43.18	Average	54.00	Pass
		4500.0	-48.40	-49.74	-46.01	5.01	0	51.22	Peak	68.20	Pass
		5150.0	-58.64	-58.67	-55.64	5.01	0	41.59	Average	54.00	Pass
		5350.0	-46.67	-47.49	-44.05	5.01	0	53.18	Peak	68.20	Pass
		5460.0	-57.06	-57.06	-54.05	5.01	0	43.18	Average	54.00	Pass
		5350.0	-48.40	-49.74	-46.01	5.01	0	51.22	Peak	68.20	Pass
		5460.0	-58.64	-58.67	-55.64	5.01	0	41.59	Average	54.00	Pass

E [dBuV/m]= Power [dBm] + Gain + Ground Factor + 95.23

The upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands or 2 dBi, whichever is greater