



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No. :** CQASZ20191201277E-02

**Applicant:** KEYFORT PTE.LTD.

**Address of Applicant:** 300 Beach Road.#34-06, The Concourse Singapore (199555)

**Equipment Under Test (EUT):**

**EUT Name:** KeyFort Wallet

**Mode No.:** K300, K300-S

**Test Model No.:** K300

**Brand Name:** KeyFort

**FCC ID:** 2AVA7-K300X

**Standards:** 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

**Date of Receipt:** 2019-12-09

**Date of Test:** 2019-12-09 to 2019-12-12

**Date of Issue:** 2019-12-12

**Test Result :** PASS\*

\* In the configuration tested, the EUT complied with the standards specified above.

**Tested By:**

Tom Chen.

(Tom Chen)

**Reviewed By:**

Aaron Ma

(Aaron Ma)

**Approved By:**

Jack Ai

( Jack Ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20191201277E-02	Rev.01	Initial report	2019-12-12

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits .....	5
4.1.3 EUT RF Exposure.....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	KEYFORT PTE.LTD.
Address of Applicant:	300 Beach Road.#34-06, The Concourse Singapore (199555)
Manufacturer:	KEYFORT PTE.LTD.
Address of Manufacturer:	300 Beach Road.#34-06, The Concourse Singapore (199555)

#### 3.2 General Description of EUT

Product Name:	KeyFort Wallet
Model No.:	K300, K300-S
Test Model No.:	K300
Trade Mark:	KeyFort
Hardware Version:	V1.3
Software Version:	V1.0.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.1
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	RF test(manufacturer declare )
Antenna Type:	PCB antenna
Antenna Gain:	1.0dBi
EUT Power Supply:	lithium battery:DC3.7V, USB by DC5.0V

Model No.: K300, K300-S

Only the model K300 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 4.1.3 EUT RF Exposure

For BLE

#### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)		(dBm)
Lowest(2402MHz)	-1.63	-2.5±1	-1.5	0.708
Middle(2440MHz)	-1.53	-2.5±1	-1.5	0.708
Highest(2480MHz)	-1.77	-2.5±1	-1.5	0.708

#### Worst case: GFSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-1.63	-2.5±1	-1.5	0.708	0.219	3.0
Middle (2440MHz)	-1.53	-2.5±1	-1.5	0.708	0.221	
Highest (2480MHz)	-1.77	-2.5±1	-1.5	0.708	0.223	

Conclusion: the calculated value ≤3.0, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20191201277E-01.