

FCC Radio Test Report

FCC ID: 2AVAA-XN002

Original Grant

Report No. : TB-FCC170184
Applicant : Shenzhen Double New Technology Co.,Ltd

Equipment Under Test (EUT)

EUT Name : Micro laser engraving machine
Model No. : XN002
Series Model No. : XN003,XN004,XN005,XN006,XN007,XN008

Brand Name : ----

Receipt Date : 2019-10-30

Test Date : 2019-10-30 to 2019-11-25

Issue Date : 2019-12-03

Standards : FCC Part 15, Subpart C(15.247 :2019)

Test Method : ANSI C63.10: 2013

Conclusions : **PASS**

Test/Witness Engineer : In the configuration tested, the EUT complied with the standards specified above,

Garen

Ivan Su

Ray Lai

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	5
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test)	5
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units	7
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting	8
1.7 Measurement Uncertainty	8
1.8 Test Facility.....	9
2. TEST SUMMARY	10
3. TEST EQUIPMENT.....	11
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	12
4.2 Test Setup.....	12
4.3 Test Procedure.....	12
4.4 EUT Operating Mode	13
4.5 Test Data.....	13
5. RADIATED EMISSION TEST	14
5.1 Test Standard and Limit.....	14
5.2 Test Setup.....	15
5.3 Test Procedure.....	16
5.4 EUT Operating Condition	16
5.5 Test Data.....	16
6. RESTRICTED BANDS REQUIREMENT	17
6.1 Test Standard and Limit.....	17
6.2 Test Setup.....	17
6.3 Test Procedure.....	17
6.4 EUT Operating Condition	18
6.5 Test Data.....	18
7. NUMBER OF HOPPING CHANNEL	19
7.1 Test Standard and Limit.....	19
7.2 Test Setup.....	19
7.3 Test Procedure.....	19
7.4 EUT Operating Condition	19
7.5 Test Data.....	19
8. AVERAGE TIME OF OCCUPANCY.....	20
8.1 Test Standard and Limit.....	20
8.2 Test Setup.....	20

8.3 Test Procedure.....	20
8.4 EUT Operating Condition	20
8.5 Test Data.....	21
9. CHANNEL SEPARATION AND BANDWIDTH TEST	22
9.1 Test Standard and Limit.....	22
9.2 Test Setup.....	22
9.3 Test Procedure.....	22
9.4 EUT Operating Condition	22
9.5 Test Data.....	23
10. PEAK OUTPUT POWER TEST.....	24
10.1 Test Standard and Limit	24
10.2 Test Setup.....	24
10.3 Test Procedure.....	24
10.4 EUT Operating Condition	24
10.5 Test Data.....	24
11. ANTENNA REQUIREMENT.....	25
11.1 Standard Requirement.....	25
11.2 Antenna Connected Construction	25
11.3 Result.....	25
ATTACHMENT A-- CONDUCTED EMISSION TEST DATA	26
ATTACHMENT B-- RADIATED EMISSION TEST DATA	28
ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT TEST DATA	48
ATTACHMENT D-- NUMBER OF HOPPING CHANNEL TEST DATA	66
ATTACHMENT E-- AVERAGE TIME OF OCCUPANCY TEST DATA.....	69
ATTACHMENT F-- CHANNEL SEPARATION AND BANDWIDTH TEST DATA.....	75
ATTACHMENT G-- PEAK OUTPUT POWER TEST DATA	87

Revision History

1. General Information about EUT

1.1 Client Information

Applicant	:	Shenzhen Double New Technology Co.,Ltd
Address	:	301B, No.13, phase I, zone 3, Xinhe community, Fuhai street, Bao'an District, Shenzhen, China
Manufacturer	:	Shenzhen Double New Technology Co.,Ltd
Address	:	301B, No.13, phase I, zone 3, Xinhe community, Fuhai street, Bao'an District, Shenzhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Micro laser engraving machine
Models No.	:	XN002,XN003,XN004,XN005,XN006,XN007,XN008
Model Difference	:	All these models are in the same PCB, layout and electrical circuit, the only difference is color.
Product Description	Operation Frequency:	Bluetooth V4.1: 2402~2480 MHz
	Number of Channel:	Bluetooth: 79 Channels <small>See Note 2</small>
	Max Peak Output Power:	Bluetooth: -0.648dBm(8-DPSK)
	Antenna Gain:	1.5dBi PCB Antenna
	Modulation Type:	GFSK (1 Mbps) Pi/4-DQPSK (2 Mbps) 8-DPSK (3 Mbps)
Power Supply	:	DC Voltage Supply from AC/DC Adapter.
Power Rating	:	AC/DC Adapter 1: GQ12-050200-ZU Input: 100~240V/50~60Hz 0.4A Output: 5V 2A AC/DC Adapter 2:GQ24-120200-AU Input: 100~240V/50~60Hz 1.0A Output: 12V 2.0A
Software Version	:	V1.0
Hardware Version	:	V1.8
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark	:	The antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.

Note:

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


(2) Channel List:

Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

(3) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

TX Mode



1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Note
Notebook	161301-CN	----	Xiaomi	Provided by the test lab

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Adapter 2 + TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	Adapter 2 + TX GFSK Mode
Mode 2	Adapter 2 + TX Mode(GFSK) Channel 00/39/78
Mode 3	Adapter 2 + TX Mode(Pi/4-DQPSK) Channel 00/39/78
Mode 4	Adapter 2 + TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Adapter 2 + Hopping Mode(GFSK)
Mode 6	Adapter 2 + Hopping Mode(Pi/4-DQPSK)
Mode 7	Adapter 2 + Hopping Mode(8-DPSK)

Both adapters were tested, and the report shows only the worst pattern: adapter 2

Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test modes above.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

- TX Mode: GFSK (1 Mbps)
- TX Mode:Pi/4-DQPSK (2 Mbps)
- TX Mode: 8-DPSK (3Mbps)

(2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis,

X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	FCC Test Tool		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
Pi/4-DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(c)& 15.209	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	N/A

Note: (1)"/" for no requirement for this test item.
 (2)N/A is an abbreviation for Not Applicable.
 (3)All tests were conducted using the adapter and antenna gain provided by the applicant, The laboratory tests only according to the information provided by the applicant.

Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
RF Conducted Measurement	MTS-8310	MWRFtest	V2.0.0.0

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 13, 2019	Jul. 12, 2020
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 13, 2019	Jul. 12, 2020
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 13, 2019	Jul. 12, 2020
LISN	Rohde & Schwarz	ENV216	101131	Jul. 13, 2019	Jul. 12, 2020
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 13, 2019	Jul. 12, 2020
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 13, 2019	Jul. 12, 2020
Spectrum Analyzer	Rohde & Schwarz	FSVR	1311.006K40-10094 5-DH	Feb. 10, 2019	Feb. 09, 2020
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Jan. 27, 2019	Jan. 26, 2020
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Jan. 27, 2019	Jan. 26, 2020
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.03, 2019	Mar. 02, 2020
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.03, 2019	Mar. 02, 2020
Horn Antenna	ETS-LINDGREN	BBHA 9170	BBHA9170582	Mar.03, 2019	Mar. 02, 2020
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 13, 2019	Jul. 12, 2020
Pre-amplifier	Sonoma	310N	185903	Mar.04, 2019	Mar. 03, 2020
Pre-amplifier	HP	8449B	3008A00849	Mar.03, 2019	Mar. 02, 2020
Pre-amplifier	EMCI	EMC02325	980217	Mar.03, 2019	Mar. 02, 2020
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.03, 2019	Mar. 02, 2020
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 13, 2019	Jul. 12, 2020
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 13, 2019	Jul. 12, 2020
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 16, 2019	Sep. 15, 2020
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 16, 2019	Sep. 15, 2020
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 16, 2019	Sep. 15, 2020
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 16, 2019	Sep. 15, 2020

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC Part 15.207

4.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please refer to the Attachment A.

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3



Radiated Emission Limit (Above 1000MHz)


Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)

5.2 Test Setup





Above 1GHz Test Setup

5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

6. Restricted Bands Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.209


FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

Note: All restriction bands have been tested, only the worst case is reported.

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with AVG Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

Please refer to the Attachment C.


7. Number of Hopping Channel

7.1 Test Standard and Limit

- 6.1.1 Test Standard
FCC Part 15.247 (a)(1)
- 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

7.2 Test Setup



7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=300 KHz, Sweep time= Auto.

7.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

7.5 Test Data

Please refer to the Attachment D.


8. Average Time of Occupancy

8.1 Test Standard and Limit

- 8.1.1 Test Standard
FCC Part 15.247 (a)(1)
- 8.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of Occupancy	0.4 sec

8.2 Test Setup



8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=3MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

8.4 EUT Operating Condition

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / X) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$
$$\{\text{Period}\} = 0.4s * \{\text{Number of Hopping Frequency}\}$$

Note: X=2 or 4 or 6 (1DH1=2, 1DH3=4, 1DH5=6. 2DH1=2, 2DH3=4, 2DH5=6. 3DH1=2, 3DH3=4, 3DH5=6)

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

The EUT was set to the Hopping Mode by the Customer.

8.5 Test Data

Please refer to the Attachment E.

9. Channel Separation and Bandwidth Test

9.1 Test Standard and Limit


9.1.1 Test Standard

FCC Part 15.247

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	<=1 MHz (20dB bandwidth)	2400~2483.5
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Channel Separation: RBW=100 kHz, VBW=300 kHz.
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

9.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

9.5 Test Data

Please refer to the Attachment F.

10. Peak Output Power Test

10.1 Test Standard and Limit


10.1.1 Test Standard

FCC Part 15.247 (b) (1)

10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

10.2 Test Setup



10.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.
RBW=3 MHz, VBW=8 MHz for bandwidth more than 1MHz.

10.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

10.5 Test Data

Please refer to the Attachment G.

11. Antenna Requirement

11.1 Standard Requirement

11.1.1 Standard

FCC Part 15.203

11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

11.2 Antenna Connected Construction


The directional gains of the antenna used for transmitting is 1.5dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

11.3 Result

The EUT antenna is a PCB Antenna. It complies with the standard requirement.


Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

Attachment A-- Conducted Emission Test Data

Temperature:	25°C	Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz							
Terminal:	Line							
Test Mode:	Adapter 2 + TX Mode							
Remark:	Only worse case is reported							
								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1		0.1700	30.59	9.79	40.38	64.96	-24.58	QP
2		0.1700	12.16	9.79	21.95	54.96	-33.01	Avg
3		0.1980	23.67	9.78	33.45	63.69	-30.24	QP
4		0.1980	10.44	9.78	20.22	53.69	-33.47	Avg
5		0.5540	16.66	9.96	26.62	56.00	-29.38	QP
6		0.5540	10.75	9.96	20.71	46.00	-25.29	Avg
7		1.0420	12.18	9.66	21.84	56.00	-34.16	QP
8		1.0420	6.93	9.66	16.59	46.00	-29.41	Avg
9		21.8180	24.80	9.51	34.31	60.00	-25.69	QP
10	*	21.8180	19.68	9.51	29.19	50.00	-20.81	Avg
11		26.6298	24.75	9.24	33.99	60.00	-26.01	QP
12		26.6298	19.55	9.24	28.79	50.00	-21.21	Avg

Emission Level= Read Level+ Correct Factor

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Neutral		
Test Mode:	Adapter 2 + TX Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV	dBuV	dB
1		0.1539	35.12	9.60	44.72	65.78	-21.06 QP
2		0.1539	15.00	9.60	24.60	55.78	-31.18 AVG
3		0.2700	18.17	9.69	27.86	61.12	-33.26 QP
4		0.2700	8.33	9.69	18.02	51.12	-33.10 AVG
5		0.5780	21.73	9.79	31.52	56.00	-24.48 QP
6		0.5780	15.48	9.79	25.27	46.00	-20.73 AVG
7		1.0180	15.77	9.62	25.39	56.00	-30.61 QP
8		1.0180	8.79	9.62	18.41	46.00	-27.59 AVG
9		21.8060	24.62	9.67	34.29	60.00	-25.71 QP
10		21.8060	18.94	9.67	28.61	50.00	-21.39 AVG
11		26.3580	24.87	9.72	34.59	60.00	-25.41 QP
12 *		26.3580	19.83	9.72	29.55	50.00	-20.45 AVG

Emission Level= Read Level+ Correct Factor


Attachment B-- Radiated Emission Test Data

9KHz~30MHz


From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz



Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	Adapter 2 + TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	*	30.2111	46.64	-13.16	33.48	40.00	-6.52 QP
2		55.2207	49.46	-23.92	25.54	40.00	-14.46 QP
3		74.1351	53.74	-23.15	30.59	40.00	-9.41 QP
4		168.4138	50.22	-20.55	29.67	43.50	-13.83 QP
5		437.1199	40.94	-11.86	29.08	46.00	-16.92 QP
6		574.6258	37.84	-8.50	29.34	46.00	-16.66 QP

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Above 1GHz(Only worse case is reported)

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Horizontal						
Test Mode:	TX GFSK Mode 2402MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4804.192	33.32	14.56	47.88	54.00	-6.12 AVG
2		4804.328	47.38	14.56	61.94	74.00	-12.06 peak
Emission Level= Read Level+ Correct Factor							

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Vertical						
Test Mode:	TX GFSK Mode 2402MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4804.152	33.38	14.56	47.94	54.00	-6.06 AVG
2		4804.366	47.02	14.56	61.58	74.00	-12.42 peak
Emission Level= Read Level+ Correct Factor							

Temperature:	25°C		Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz								
Ant. Pol.	Horizontal								
Test Mode:	TX GFSK Mode 2441MHz								
Remark:	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		4881.056	48.08	15.16	63.24	74.00	-10.76		
2	*	4881.344	33.85	15.16	49.01	54.00	-4.99		
							peak		
							AVG		
<hr/>									
Emission Level= Read Level+ Correct Factor									

Temperature:	25°C		Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz								
Ant. Pol.	Vertical								
Test Mode:	TX GFSK Mode 2441MHz								
Remark:	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dB	Detector		
1		4882.036	47.99	15.16	63.15	74.00	-10.85 peak		
2	*	4882.596	33.86	15.16	49.02	54.00	-4.98 AVG		
Emission Level= Read Level+ Correct Factor									

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Horizontal						
Test Mode:	TX GFSK Mode 2480MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4960.660	47.93	15.76	63.69	74.00	-10.31 peak
2	*	4961.000	33.94	15.76	49.70	54.00	-4.30 AVG
Emission Level= Read Level+ Correct Factor							

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Vertical						
Test Mode:	TX GFSK Mode 2480MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4959.550	48.12	15.76	63.88	74.00	-10.12 peak
2	*	4960.252	33.92	15.76	49.68	54.00	-4.32 AVG
Emission Level= Read Level+ Correct Factor							

Temperature:	25°C		Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz								
Ant. Pol.	Horizontal								
Test Mode:	TXPi/4-DQPSK Mode 2402MHz								
Remark:	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dB	Detector		
1		4803.440	47.17	14.56	61.73	74.00	-12.27 peak		
2	*	4804.170	33.34	14.56	47.90	54.00	-6.10 AVG		
Emission Level= Read Level+ Correct Factor									

Temperature:	25°C		Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz								
Ant. Pol.	Vertical								
Test Mode:	TXPi/4-DQPSK Mode 2402MHz								
Remark:	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dB	Detector		
1		4803.076	47.06	14.55	61.61	74.00	-12.39 peak		
2	*	4804.192	33.37	14.56	47.93	54.00	-6.07 AVG		
Emission Level= Read Level+ Correct Factor									

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Horizontal						
Test Mode:	TXPi/4-DQPSK Mode 2441MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	*	4882.736	33.86	15.16	49.02	54.00	-4.98
2		4882.884	47.61	15.16	62.77	74.00	-11.23
							Detector
Emission Level= Read Level+ Correct Factor							AVG
							peak

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Vertical						
Test Mode:	TXPi/4-DQPSK Mode 2441MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4882.454	33.88	15.16	49.04	54.00	-4.96 AVG
2		4882.510	48.28	15.16	63.44	74.00	-10.56 peak
Emission Level= Read Level+ Correct Factor							

Temperature:	25°C		Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz								
Ant. Pol.	Horizontal								
Test Mode:	TXPi/4-DQPSK Mode 2480MHz								
Remark:	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dB	Detector		
1		4960.392	47.63	15.76	63.39	74.00	-10.61 peak		
2	*	4960.798	33.93	15.76	49.69	54.00	-4.31 AVG		
Emission Level= Read Level+ Correct Factor									

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Vertical						
Test Mode:	TXPi/4-DQPSK Mode 2480MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	*	4959.202	33.91	15.76	49.67	54.00	-4.33
2		4959.704	48.51	15.76	64.27	74.00	-9.73
							Detector
Emission Level= Read Level+ Correct Factor							AVG
							peak

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	*	4804.414	33.33	14.56	47.89	54.00	-6.11 AVG
2		4804.714	47.02	14.56	61.58	74.00	-12.42 peak

Emission Level= Read Level+ Correct Factor

Temperature:	25°C		Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz								
Ant. Pol.	Vertical								
Test Mode:	TX 8-DPSK Mode 2402MHz								
Remark:	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		4804.418	47.75	14.56	62.31	74.00	-11.69		
2	*	4804.616	33.32	14.56	47.88	54.00	-6.12		
							peak		
							AVG		
<hr/>									
Emission Level= Read Level+ Correct Factor									

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Horizontal						
Test Mode:	TX 8-DPSK Mode 2441MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		4882.560	47.93	15.16	63.09	74.00	-10.91
2	*	4882.658	33.85	15.16	49.01	54.00	-4.99
							Detector
Emission Level= Read Level+ Correct Factor							AVG

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Vertical						
Test Mode:	TX 8-DPSK Mode 2441MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		4881.970	47.58	15.16	62.74	74.00	-11.26 peak
2	*	4882.616	33.87	15.16	49.03	54.00	-4.97 AVG
Emission Level= Read Level+ Correct Factor							


Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Horizontal						
Test Mode:	TX 8-DPSK Mode 2480MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	*	4959.930	34.82	15.76	50.58	54.00	-3.42
2		4959.966	48.53	15.76	64.29	74.00	-9.71
Emission Level= Read Level+ Correct Factor							

Temperature:	25°C		Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz								
Ant. Pol.	Vertical								
Test Mode:	TX 8-DPSK Mode 2480MHz								
Remark:	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dB	Detector		
1		4959.784	49.61	15.76	65.37	74.00	-8.63 peak		
2	*	4960.050	34.83	15.76	50.59	54.00	-3.41 AVG		
Emission Level= Read Level+ Correct Factor									

Attachment C-- Restricted Bands Requirement Test Data


(1) Radiation Test


Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		2390.000	45.11	0.97	46.08	74.00	-27.92 peak
2		2390.000	32.69	0.97	33.66	54.00	-20.34 AVG
3	*	2402.200	73.86	1.03	74.89	Fundamental Frequency	AVG
4	X	2402.300	84.32	1.03	85.35	Fundamental Frequency	peak

Emission Level= Read Level+ Correct Factor






Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	Only worse case is reported		





No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
1	X	2479.900	93.92	1.38	95.30	Fundamental Frequency	peak
2	*	2480.100	83.44	1.38	84.82	Fundamental Frequency	AVG
3		2483.500	55.97	1.40	57.37	74.00	-16.63 peak
4		2483.500	44.47	1.40	45.87	54.00	-8.13 AVG


Emission Level= Read Level+ Correct Factor


Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Horizontal						
Test Mode:	TXPi/4-DQPSK Mode 2402MHz						
Remark:	Only worse case is reported						
100.0 dBuV/m							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		2390.000	43.98	0.97	44.95	74.00	-29.05
2		2390.000	32.69	0.97	33.66	54.00	-20.34
3	X	2402.000	81.46	1.03	82.49	Fundamental Frequency	peak
4	*	2402.000	69.23	1.03	70.26	Fundamental Frequency	AVG






















(2) Conducted Test

















Attachment D-- Number of Hopping Channel Test Data

Temperature:	25°C	Relative Humidity:	55%																																																																																																									
Test Voltage:	AC 120V/60 Hz																																																																																																											
Test Mode:	Hopping Mode																																																																																																											
Frequency Range	Test Mode	Quantity of Hopping Channel	Limit																																																																																																									
2402MHz~2480MHz	GFSK	79	>15																																																																																																									
	Pi/4-DQPSK	79																																																																																																										
	8-DPSK	79																																																																																																										
GFSK Mode																																																																																																												
 <p>Start 2.40000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 2.48350 GHz Sweep 8.000 ms (1001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.401 837 0 GHz</td> <td>-1.536 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.479 993 0 GHz</td> <td>-1.843 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>7</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>8</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>9</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>11</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.401 837 0 GHz	-1.536 dBm				2	N	1	f	2.479 993 0 GHz	-1.843 dBm				3									4									5									6									7									8									9									10									11								
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																				
1	N	1	f	2.401 837 0 GHz	-1.536 dBm																																																																																																							
2	N	1	f	2.479 993 0 GHz	-1.843 dBm																																																																																																							
3																																																																																																												
4																																																																																																												
5																																																																																																												
6																																																																																																												
7																																																																																																												
8																																																																																																												
9																																																																																																												
10																																																																																																												
11																																																																																																												
Pi/4-DQPSK Mode																																																																																																												





Attachment E-- Average Time of Occupancy Test Data

Temperature:	25°C	Relative Humidity:	55%			
Test Voltage:	AC 120V/60 Hz					
Test Mode:	Hopping Mode (GFSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1DH1	2441	0.3715	118.88	31.60	400	PASS
1DH3	2441	1.628	260.48	31.60	400	PASS
1DH5	2441	2.876	306.77	31.60	400	PASS


1DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79


1DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79

1DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79

GFSK Hopping Mode 1DH1

2441 MHz






Temperature:	25°C		Relative Humidity:	55%		
Test Voltage:	AC 120V/60 Hz					
Test Mode:	Hopping Mode (Pi/4-DQPSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2DH1	2441	0.379	121.28	31.60	400	PASS
2DH3	2441	1.631	260.96	31.60	400	PASS
2DH5	2441	2.879	307.09	31.60	400	PASS


2DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79
2DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79
2DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79



Pi/4-DQPSK Hopping Mode 2DH1
2441 MHz



The screenshot shows a Keysight Spectrum Analyzer (Swept SA) interface. The main display shows a signal at 2441 MHz with markers X2 and Y2. The top status bar indicates: Center Freq 2.441000000 GHz, Trig Delay-1.000 ms, Avg Type: Log-Pwr, PNO: Fast, Trig: Video, IFGain:Low, Atten: 30 dB. The bottom status bar indicates: Center 2.44100000 GHz, Res BW 1.0 MHz, #VBW 3.0 MHz, Span 0 Hz, Sweep 5.000 ms (10001 pts). A table below the plot lists markers 1 and 2 with their respective values: X2 (379.0 us, -3.44 dB) and Y2 (998.5 us, -12.25 dBm).


MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	A2	1	t (A)	379.0 us (Δ)	-3.44 dB			
2	F	1	t	998.5 us	-12.25 dBm			
3								
4								
5								
6								
7								
8								
9								
10								
11								



Temperature:	25°C		Relative Humidity:	55%																																																																																																														
Test Voltage:	AC 120V/60 Hz																																																																																																																	
Test Mode:	Hopping Mode (8-DPSK)																																																																																																																	
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result																																																																																																												
3DH1	2441	0.3795	121.44	31.60	400	PASS																																																																																																												
3DH3	2441	1.630	260.80	31.60	400	PASS																																																																																																												
3DH5	2441	2.881	307.31	31.60	400	PASS																																																																																																												
1DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79																																																																																																																		
1DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79																																																																																																																		
1DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79																																																																																																																		
8-DPSK Hopping Mode 3DH1																																																																																																																		
2441 MHz																																																																																																																		
 <table border="1" data-bbox="377 1365 1270 1594"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Δ2</td> <td>1</td> <td>t</td> <td>(Δ)</td> <td>379.5 us</td> <td>(Δ)</td> <td>-3.45 dB</td> <td></td> </tr> <tr> <td>2</td> <td>F</td> <td>1</td> <td>t</td> <td></td> <td>999.0 us</td> <td></td> <td>-8.94 dBm</td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>7</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>8</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>9</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>11</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	Δ2	1	t	(Δ)	379.5 us	(Δ)	-3.45 dB		2	F	1	t		999.0 us		-8.94 dBm		3									4									5									6									7									8									9									10									11								
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																										
1	Δ2	1	t	(Δ)	379.5 us	(Δ)	-3.45 dB																																																																																																											
2	F	1	t		999.0 us		-8.94 dBm																																																																																																											
3																																																																																																																		
4																																																																																																																		
5																																																																																																																		
6																																																																																																																		
7																																																																																																																		
8																																																																																																																		
9																																																																																																																		
10																																																																																																																		
11																																																																																																																		
Temperature:	25°C		Relative Humidity:	55%																																																																																																														
Test Voltage:	AC 120V/60 Hz																																																																																																																	
Test Mode:	Hopping Mode (8-DPSK)																																																																																																																	
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result																																																																																																												
3DH1	2441	0.3795	121.44	31.60	400	PASS																																																																																																												
3DH3	2441	1.630	260.80	31.60	400	PASS																																																																																																												
3DH5	2441	2.881	307.31	31.60	400	PASS																																																																																																												
1DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79																																																																																																																		
1DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79																																																																																																																		
1DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79																																																																																																																		
8-DPSK Hopping Mode 3DH1																																																																																																																		
2441 MHz																																																																																																																		
 <table border="1" data-bbox="377 1365 1270 1594"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Δ2</td> <td>1</td> <td>t</td> <td>(Δ)</td> <td>379.5 us</td> <td>(Δ)</td> <td>-3.45 dB</td> <td></td> </tr> <tr> <td>2</td> <td>F</td> <td>1</td> <td>t</td> <td></td> <td>999.0 us</td> <td></td> <td>-8.94 dBm</td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>7</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>8</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>9</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>11</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	Δ2	1	t	(Δ)	379.5 us	(Δ)	-3.45 dB		2	F	1	t		999.0 us		-8.94 dBm		3									4									5									6									7									8									9									10									11								
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																										
1	Δ2	1	t	(Δ)	379.5 us	(Δ)	-3.45 dB																																																																																																											
2	F	1	t		999.0 us		-8.94 dBm																																																																																																											
3																																																																																																																		
4																																																																																																																		
5																																																																																																																		
6																																																																																																																		
7																																																																																																																		
8																																																																																																																		
9																																																																																																																		
10																																																																																																																		
11																																																																																																																		


8-DPSK Hopping Mode 3DH3

2441 MHz




8-DPSK Hopping Mode 3DH5

2441 MHz




Attachment F-- Channel Separation and Bandwidth Test Data

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	TX Mode (GFSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	846.56	927.6	
2441	841.44	885.7	
2480	843.49	919.9	
GFSK TX Mode			
2402 MHz			
			

GFSK TX Mode


2441 MHz





GFSK TX Mode


2480 MHz




Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	TX Mode (Pi/4-DQPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1157.5	1250	833.33
2441	1157.8	1252	834.67
2480	1159.5	1248	832.00
Pi/4-DQPSK TX Mode			
2402 MHz			
			



Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	TX Mode (8-DPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1156.3	1256	837.33
2441	1155.9	1261	840.67
2480	1158.7	1262	841.33
8-DPSK TX Mode			
2402 MHz			
			



Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	Hopping Mode (GFSK)		
Channel frequency (MHz)		Separation Read Value (kHz)	Separation Limit (kHz)
2402		990	618.40
2441		1000	590.47
2480		990	613.27
GFSK Hopping Mode			
2402 MHz			
			

GFSK Hopping Mode

2441 MHz




GFSK Hopping Mode

2480 MHz




Temperature:	25°C	Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz							
Test Mode:	Hopping Mode (Pi/4-DQPSK)							
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)						
2402	980	833.33						
2441	960	834.67						
2480	1010	832.00						
Pi/4-DQPSK Hopping Mode								
2402 MHz								
								
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ2	1	f	(Δ)	980 kHz (Δ)	-0.085 dB		
2	F	1	f		2.401 837 GHz	-2.279 dBm		
3								
4								
5								
6								
7								
8								
9								
10								
11								



Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	Hopping Mode (8-DPSK)		
Channel frequency (MHz)		Separation Read Value (kHz)	Separation Limit (kHz)
2402		1220	837.33
2441		1200	840.67
2480		1020	841.33
8-DPSK Hopping Mode			
2402 MHz			
			

8-DPSK Hopping Mode

2441 MHz





8-DPSK Hopping Mode


2480 MHz



Attachment G-- Peak Output Power Test Data


Temperature:	25°C	Relative Humidity:	55%		
Test Voltage:	AC 120V/60 Hz				
Test Mode:	TX Mode (GFSK)				
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)			
2402	-0.796	30			
2441	-0.650				
2480	-1.001				
GFSK TX Mode					
2402 MHz					
					



Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Test Mode:	TX Mode (Pi/4-DQPSK)						
Channel frequency (MHz)	Test Result (dBm)		Limit (dBm)				
2402	-1.286		21				
2441	-1.016						
2480	-1.372						
Pi/4-DQPSK TX Mode							
2402 MHz							
							


Pi/4-DQPSK TX Mode


2441 MHz



Pi/4-DQPSK TX Mode


2480 MHz



Temperature:	25°C	Relative Humidity:	55%		
Test Voltage:	AC 120V/60 Hz				
Test Mode:	TX Mode (8-DPSK)				
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)			
2402	-0.948	21			
2441	-0.648				
2480	-1.026				
8-DPSK TX Mode					
2402 MHz					
					


8-DPSK TX Mode

2441 MHz



8-DPSK TX Mode

2480 MHz



-----END OF REPORT-----