

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 1 of 50

Applicant : Shanghai Goodview Electronics Technology Co., Ltd.
Address of Applicant : Room 866, NO.888, West Huanhu 2 Road,
NanhuiXincheng Town, Pudong, Shanghai, China

Product Name : LCD DIGITAL DISPLAY/Digital Sign Board
Model No. : M*****,
(* = A to Z, 0 to 9, blank, just different in appearance color,
sales area customer code, and software version)

Sample No. : E19100015-01#01
E19100015-01#02

FCC ID : 2AVB8MSA

Standards : FCC CFR47 Part 15, Subpart C

Date of Receipt : 2019-10-24
Date of Test : 2019-10-24 ~ 2019-11-22
Date of Issue : 2019-12-10

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by: Jennifer Zhou
(Jennifer Zhou)

Reviewed by: Adrian Shi
(Adrian Shi)

Approved by: Guoyou Chi
(Authorized signatory: Guoyou Chi)

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 2 of 50

Revision Record			
Version	Date	Revisions	Revised By
1.0	2019-12-10	Original	--

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 3 of 50

Contents

1	GENERAL INFORMATION	4
1.1	TESTING LABORATORY	4
1.2	DETAILS OF APPLICATION	4
1.3	DETAILS OF EUT	4
1.4	TEST METHODOLOGY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	6
3	TEST SET-UP AND OPERATION MODES	7
3.1	DETAILS OF TEST MODE	7
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	7
3.3	SUPPORT SOFTWARE	7
3.4	TEST SETUP DIAGRAM	8
4	TEST RESULTS	10
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	10
4.1.1	<i>Antenna Requirement</i>	<i>10</i>
4.1.2	<i>Maximum Conducted Output Power</i>	<i>11</i>
4.1.3	<i>20dB Bandwidth and 99% Bandwidth</i>	<i>17</i>
4.1.4	<i>Conducted Spurious Emission & Authorized-band band-edge</i>	<i>21</i>
4.1.5	<i>Spurious Emission</i>	<i>35</i>
4.1.6	<i>Band Edge (Restricted-band band-edge)</i>	<i>36</i>
4.1.7	<i>Hopping Frequency Separation</i>	<i>37</i>
4.1.8	<i>Number of Hopping Frequency</i>	<i>39</i>
4.1.9	<i>Time of Occupancy</i>	<i>41</i>
4.2	MAINS EMISSIONS	45
4.2.1	<i>Conducted Emission on AC Mains</i>	<i>45</i>
4	APPENDIXES	48
4.1	PHOTOGRAPHS OF THE SAMPLE	48
4.2	SET-UP FOR CONDUCTED EMISSIONS	49
4.3	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	49
4.4	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHZ	50
4.5	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHZ	50

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 4 of 50

1 General Information

1.1 Testing Laboratory

Company Name	ICAS Testing Technology Services (Shanghai) Co., Ltd.
Address	155 Pingbei Rd, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

1.2 Details of Application

Company Name	Shanghai Goodview Electronics Technology Co., Ltd.
Address	Room 866, NO.888, West Huanhu 2 Road, NanhuiXincheng Town, Pudong, Shanghai, China
Contact Person	Hongyue Xu
Telephone	15618060409
Email	xuhongyue@goodview.com

1.3 Details of EUT

Product Name	LCD DIGITAL DISPLAY/Digital Sign Board
Brand Name	GOODVIEW
Model No.	M****, (*=A to Z, 0 to 9, blank, just different in appearance color, sales area customer code, and software version)
FCC ID	2AVB8MSA
Mode of Operation	Bluetooth BR/EDR
Frequency Range	2400MHz ~ 2483.5MHz
Number of Channels	79 (at intervals of 1 MHz)
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type	External Antenna
Antenna Gain	3 dBi
Extreme Temperature Range	10°C ~ +40°C
Test Voltage	AC 220V

Note(s):

All applicable tests as described in test case and measurement sections were performed on model M43SAQ.

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 5 of 50

1.4 Test Methodology

47 CFR Part 15, Subpart C (10-1-16 Edition)	Miscellaneous Wireless Communications Services
KDB Publication 558074 D01 v05r02	15.247 Meas Guidance.
KDB Publication 662911 D01 v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 6 of 50

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	18-25
Humidity (%RH)	40-65
Barometric Pressure (mbar)	960-1060

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Due Date
Spectrum Analyzer	Keysight	N9020B	MY59260184	2020-07-28
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2020-06-24
EMI Test Receiver	Rohde & Schwarz	ESPI3	100173	2020-06-19
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2020-06-19
V-network	SCHWARZBECK	NSLK 8127	8127-902	2020-02-20
Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	100687	2020-08-22
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2020-06-06
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2020-06-06
Loop Antenna	SCHWARZBECK	FMZB 1513	N/A	2021-03-19
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2020-07-26
EMC chamber 9*6*6 (L*W*H)	CHANGNING	966	N/A	2020-06-26
Shielded Enclosure 8*5*4 (L*W*H)	CHANGNING	854	N/A	2020-08-28
Test Software	BL	BL410_E	N/A	N/A

2.3 Measurement Uncertainty

Parameter	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	± 1.5 dB
	> 1GHz	± 1.5 dB
Radiated Emission	30 MHz – 1 GHz	± 3 dB
	> 1GHz	± 3 dB

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 7 of 50

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software was control EUT work in continuous transmitter and receiver mode. Select test channel as below:

Channel	Frequency
The lowest channel(CH0)	2402MHz
The middle channel(CH39)	2441MHz
The Highest channel(CH78)	2480MHz

The basic operation modes are:

- A. On
 - 1. BR/EDR mode
 - a. Transmitting
 - i. Low Channel
 - ii. Middle Channel
 - iii. High Channel
 - iv. Hopping mode
 - b. Receiving
 - 2. Normal working with Bluetooth on
- B. Standby
- C. Off

3.2 Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	TP00083A	N/A

3.3 Support Software

Description	Manufacturer	Software Name
Software	/	RF Test Tool

TEST REPORT


Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 8 of 50


3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Conduction Measurement




TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 9 of 50

Diagram of Measurement Equipment Configuration for Transmitter Measurement



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 10 of 50

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT:

PASS

Test standard	:	FCC Part 15.247(b)(4), Part 15.203
Requirement	:	The use of approved antennas only with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3 dBi. The antenna is an External antenna with no possibility of replacement with a non-approved antenna by the end-user.

Therefore, the EUT is considered to comply with this provision.

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 11 of 50

4.1.2 Maximum Conducted Output Power

RESULT:

PASS

Test standard : FCC Part 15.247(b)(1)
Requirement : ANSI C63.10-2013
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 25°C
Relative humidity : 52%

Table 1: Maximum Conducted Output Power

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(mW)	
GFSK	2402	5.67	3.69	< 1
	2441	5.46	3.52	
	2480	5.01	3.17	
$\pi/4$ -DQPSK	2402	2.92	1.96	< 0.125
	2441	2.57	1.81	
	2480	2.02	1.59	
8-DPSK	2402	2.94	1.97	< 0.125
	2441	2.60	1.82	
	2480	2.04	1.60	

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 12 of 50

Figure 1: Maximum Conducted Output Power, 2402MHz, GFSK



Figure 2: Maximum Conducted Output Power, 2441MHz, GFSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 13 of 50

Figure 3: Maximum Conducted Output Power, 2480MHz, GFSK



Figure 4: Maximum Conducted Output Power, 2402MHz, $\pi/4$ -DQPSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 14 of 50

Figure 5: Maximum Conducted Output Power, 2441MHz, $\pi/4$ -DQPSK



Figure 6: Maximum Conducted Output Power, 2480MHz, $\pi/4$ -DQPSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 15 of 50

Figure 7: Maximum Conducted Output Power, 2402MHz, 8-DPSK



Figure 8: Maximum Conducted Output Power, 2441MHz, 8-DPSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 16 of 50

Figure 9: Maximum Conducted Output Power, 2480MHz, 8-DPSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 17 of 50

4.1.3 20dB Bandwidth and 99% Bandwidth

RESULT:

PASS

Test standard : FCC Part 15.247(a)(1)
Requirement : ANSI C63.10-2013
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 25°C
Relative humidity : 52%

Table 2: 20dB Bandwidth and 99% Bandwidth

Test Mode	Test Channel (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
GFSK	2402	0.824	0.925
	2441	0.825	0.924
	2480	0.824	0.921
8-DPSK	2402	1.163	1.117
	2441	1.164	1.117
	2480	1.162	1.116

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 18 of 50

Figure 10: 20dB Bandwidth and 99% Bandwidth, 2402MHz, GFSK



Figure 11: 20dB Bandwidth and 99% Bandwidth, 2441MHz, GFSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 19 of 50

Figure 12: 20dB Bandwidth and 99% Bandwidth, 2480MHz, GFSK



Figure 13: 20dB Bandwidth and 99% Bandwidth, 2402MHz, 8-DPSK



TEST REPORT

Report No.: SHE19100015-01BE


Date: 2019-12-10

Page 20 of 50

Figure 14: 20dB Bandwidth and 99% Bandwidth, 2441MHz, 8-DPSK



Figure 15: 20dB Bandwidth and 99% Bandwidth, 2480MHz, 8-DPSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 21 of 50

4.1.4 Conducted Spurious Emission & Authorized-band band-edge

RESULT:

PASS

Test standard	: FCC Part 15.247(d)
Requirement	: ANSI C63.10-2013
Kind of test site	: Shielded room

Test setup

Test Channel	: Low/Middle/High for spurious, Low/High for Band Edge
Operation Mode	: A.1.a
Ambient temperature	: 25°C
Relative humidity	: 52%

For details refer to following test plot.

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 22 of 50

Figure 16: Conducted Spurious Emission & Authorized-band band-edge, 2402MHz, GFSK Carrier Level



Band Edge




TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 23 of 50



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 24 of 50

Conducted spurious emissions 30MHz-25GHz



Figure 17: Conducted Spurious Emission & Authorized-band band-edge, 2441MHz, GFSK Carrier Level



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 25 of 50

Conducted spurious emissions 30MHz-25GHz



Figure 18: Conducted Spurious Emission & Authorized-band band-edge, 2480MHz, GFSK Carrier Level



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 26 of 50

Band Edge



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 27 of 50

Figure 19: Conducted Spurious Emission & Authorized-band band-edge, 2402MHz, 8-DPSK Carrier Level



Band Edge



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 28 of 50

Conducted spurious emissions 30MHz-25GHz



Figure 20: Conducted Spurious Emission & Authorized-band band-edge, 2441MHz, 8-DPSK Carrier Level



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 29 of 50

Conducted spurious emissions 30MHz-25GHz



Figure 21: Conducted Spurious Emission & Authorized-band band-edge, 2480MHz, 8-DPSK Carrier Level



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 30 of 50

Band Edge



Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 31 of 50

Figure 22: Conducted Spurious Emission & Authorized-band band-edge, Hopping Mode, GFSK Carrier Level



Band Edge(Low)



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 32 of 50

Band Edge(High)



Conducted spurious emissions 30MHz-25GHz




TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 33 of 50

Figure 23: Conducted Spurious Emission & Authorized-band band-edge, Hopping Mode, 8-DPSK Carrier Level



Band Edge(Low)



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 34 of 50

Band Edge(High)



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 35 of 50

4.1.5 Spurious Emission

RESULT:

PASS

Test standard	: FCC Part 15.247(d), 15.205, 15.209 RSS-247 5.5
Requirement	: ANSI C63.10-2013
Kind of test site	: 3m Semi-Anechoic Chamber

Test setup

Test Channel	: Low/Middle/High
Operation Mode	: A
Ambient temperature	: 25°C
Relative humidity	: 52%

Notes:

1. Test plots please refer to the annex document "EXHIBIT A of SHE19100015-01BE".
2. For 9 kHz ~ 30 MHz, the amplitude of spurious emissions that are attenuated by more than 20dB below the permissible. The value has no need to be reported.
3. The spurious above 18GHz is noise only and 20dB below the limit. The value has no need to be reported.
4. The EUT is working in the Normal link mode below 1 GHz.

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 36 of 50

4.1.6 Band Edge (Restricted-band band-edge)

RESULT:

PASS

Test standard	: FCC Part 15.247(d), 15.205, 15.209 RSS-247 5.5
Requirement	: ANSI C63.10-2013
Kind of test site	: 3m Semi-Anechoic Chamber

Test setup

Test Channel	: Low/Middle/High
Operation Mode	: A.1
Ambient temperature	: 25°C
Relative humidity	: 52%

Note:

1. Test plots please refer to the annex document "EXHIBIT A of SHE19100015-01BE".

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 37 of 50

4.1.7 Hopping Frequency Separation

RESULT:

PASS

Test standard : FCC Part 15.247(a)(1)
RSS-247 5.1(2)
Requirement : ANSI C63.10-2013
Kind of test site : Shielded room

Test setup

Test Channel : Hopping
Operation Mode : A.1.a.iv
Ambient temperature : 25°C
Relative humidity : 52%

Table 3: Hopping Frequency Separation

Mode	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
GFSK	2441	0.999	≥ 25kHz or two-thirds of 20dB bandwidth
8-DPSK	2441	0.999	

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 38 of 50

Figure 24: Hopping Frequency Separation, Hopping Mode, GFSK



Figure 25: Hopping Frequency Separation, Hopping Mode, 8DPSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 39 of 50

4.1.8 Number of Hopping Frequency

RESULT:

PASS

Test standard : FCC Part 15.247(a)(1)(iii)
RSS-247 5.1(4)
Requirement : ANSI C63.10-2013
Kind of test site : Shielded room

Test setup

Test Channel : Hopping
Operation Mode : A.1.a.iv
Ambient temperature : 25°C
Relative humidity : 52%

Table 4: Number of Hopping Frequency

Mode	Frequency Range	Measured Quantity of Hopping Channel	Limit
GFSK	2400 – 2483.5	79	≥15
8-DPSK	2400 – 2483.5	79	≥15

TEST REPORT

Report No.: SHE19100015-01BE


Date: 2019-12-10

Page 40 of 50

Figure 26: Number of Hopping Frequency, Hopping Mode, GFSK



Figure 27: Number of Hopping Frequency, Hopping Mode, 8-DPSK



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 41 of 50

4.1.9 Time of Occupancy

RESULT:

PASS

Test standard : FCC Part 15.247(a)(1)(iii)
RSS-247 5.1(4)
Requirement : ANSI C63.10-2013
Kind of test site : Shielded room

Test setup

Test Channel : Middle
Operation Mode : A.1.a
Ambient temperature : 25°C
Relative humidity : 52%

Table 5: Time of Occupancy

Mode	Packet Type	Pulse Time (ms)	Total of Dwell (ms)	Limit (s)
GFSK	DH1	0.386	123.520	0.4
	DH3	1.644	263.040	0.4
	DH5	2.896	308.907	0.4
8-DPSK	DH1	0.392	125.440	0.4
	DH3	1.647	263.520	0.4
	DH5	2.900	309.333	0.4

Note:

For DH1 package type:

Total of Dwell = Pulse Time*(1600/2)/Number of Hopping Frequency*Period

Period = 0.4* Number of Hopping Frequency

For DH3 package type:

Total of Dwell = Pulse Time*(1600/4)/Number of Hopping Frequency*Period

Period = 0.4* Number of Hopping Frequency

For DH5 package type:

Total of Dwell = Pulse Time*(1600/6)/Number of Hopping Frequency*Period

Period = 0.4* Number of Hopping Frequency

TEST REPORT

Report No.: SHE19100015-01BE


Date: 2019-12-10

Page 42 of 50

Figure 28: Time of Occupancy, 2441MHz, GFSK DH1



Figure 29: Time of Occupancy, 2441MHz, GFSK DH3



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 43 of 50

Figure 30: Time of Occupancy, 2441MHz, GFSK DH5



Figure 31: Time of Occupancy, 2441MHz, 8-DPSK DH1



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 44 of 50

Figure 32: Time of Occupancy, 2441MHz, 8-DPSK DH3





Figure 33: Time of Occupancy, 2441MHz, 8-DPSK DH5



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 45 of 50

4.2 Mains Emissions

4.2.1 Conducted Emission on AC Mains

RESULT:

PASS

Test standard	:	FCC Part 15.207(a) RSS-Gen 8.8
Requirement	:	ANSI C63.10-2013
Kind of test site	:	Shielded room

Test setup

Input Voltage	:	AC 120V, 60Hz; AC 240V, 50Hz
Operation Mode	:	A.1.a
Earthing	:	Not Connected
Ambient temperature	:	25°C
Relative humidity	:	52%

For details refer to following test plot.

TEST REPORT

Report No.: SHE19100015-01BE


Date: 2019-12-10

Page 46 of 50

Note:

The all configurations were tested respectively, but only the worst configuration shown here.

Figure 34: Conducted Emission on AC Mains, L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.166	57.87	10.15	65.16	-7.29	Peak	L	Pass
1**	0.166	43.53	10.15	55.16	-11.63	AV	L	Pass
2	0.178	57.81	10.15	64.58	-6.77	Peak	L	Pass
2*	0.178	52.46	10.15	64.58	-12.12	QP	L	Pass
2**	0.178	45.64	10.15	54.58	-8.94	AV	L	Pass
3	0.364	43.53	10.14	58.64	-15.11	Peak	L	Pass
3**	0.364	35.84	10.14	48.64	-12.80	AV	L	Pass
4	0.500	41.09	10.15	56.00	-14.91	Peak	L	Pass
4**	0.500	33.21	10.15	46.00	-12.79	AV	L	Pass
5	10.290	45.65	10.41	60.00	-14.35	Peak	L	Pass
5**	10.290	38.38	10.41	50.00	-11.62	AV	L	Pass
6	15.004	46.30	10.49	60.00	-13.70	Peak	L	Pass
6**	15.004	32.59	10.49	50.00	-17.41	AV	L	Pass


TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 47 of 50

Figure 35: Conducted Emission on AC Mains, N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.160	56.06	10.15	65.46	-9.40	Peak	N	Pass
1**	0.160	41.11	10.15	55.46	-14.35	AV	N	Pass
2	0.182	55.83	10.15	64.39	-8.56	Peak	N	Pass
2*	0.182	50.90	10.15	64.39	-13.49	QP	N	Pass
2**	0.182	47.83	10.15	54.39	-6.56	AV	N	Pass
3	0.506	43.15	10.15	56.00	-12.85	Peak	N	Pass
3**	0.506	32.36	10.15	46.00	-13.64	AV	N	Pass
4	2.714	33.74	10.20	56.00	-22.26	Peak	N	Pass
4**	2.714	14.73	10.20	46.00	-31.27	AV	N	Pass
5	10.292	45.87	10.41	60.00	-14.13	Peak	N	Pass
5**	10.292	38.54	10.41	50.00	-11.46	AV	N	Pass
6	16.218	42.85	10.44	60.00	-17.15	Peak	N	Pass
6**	16.218	28.21	10.44	50.00	-21.79	AV	N	Pass

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 48 of 50

4 Appendixes

4.1 Photographs of the Sample



Front of the sample



Rear of the sample

TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 49 of 50

4.2 Set-up for Conducted Emissions



4.3 Set-up for Conducted RF test at Antenna Port



TEST REPORT

Report No.: SHE19100015-01BE

Date: 2019-12-10

Page 50 of 50

4.4 Set-up for Spurious Emissions below 1GHz



4.5 Set-up for Spurious Emissions above 1GHz



End of the report