

FCC RF Test Report

For

Shenzhen CYX Industrial Co., Ltd.

Test Standards:	<u>Part 15C Subpart C §15.247</u>
Product Description:	<u>TV BOX</u>
Tested Model:	<u>A95X F3 Air</u> <u>A95X F3 Slim, A95X F3, A95X D1, A95X D2,</u> <u>A95X F4, A95X F4 Air, A95X F4 Slim, A95X F5 Air,</u> <u>A95X F5 Slim, A95X F6 Air, A95X F6 Slim,</u> <u>A95X F7 Air, A95X F7 Slim, A95X F8 Air,</u> <u>A95X F8 Slim, A95X F5, A95X F6, A95X F7, A95X F8</u>
Additional Model No.	
FCC ID:	<u>2AVBM-A95XF3AIR</u>
Classification	Digital Spread Spectrum (DSS)
Report No.:	<u>EC2001001RF02</u>
Tested Date:	<u>2019-12-03 to 2020-01-08</u>
Issued Date:	<u>2020-01-08</u>
Prepared By:	<u>Jerry Wang</u> Jerry Wang / Engineer
Approved By:	<u>Bacon Wu</u> Bacon Wu / RF Manager
Hunan Eccloud Testing Technology Co., Ltd.	
Building A1, Changsha E Center, No. 18 Xiangtai Avenue, Liuyang Economic and Technological Development Zone, Hunan, P.R.C	
Tel.: +86-731-89634887 Fax.: +86-731-89634887	
www.hn-ecloud.com	

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of
Hunan Eccloud Testing Technology Co., Ltd., the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	2020.01.08	Valid	Original Report

TABLE OF CONTENTS

1 TEST LABORATORY	5
1.1 Test facility	5
2 GENERAL DESCRIPTION.....	6
2.1 Applicant	6
2.2 Manufacturer.....	6
2.3 General Description Of EUT	6
2.4 Modification of EUT	7
2.5 Applicable Standards.....	7
3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
3.1 Descriptions of Test Mode	8
3.2 Test Mode	8
3.3 Support Equipment.....	10
3.4 Test Setup	10
3.5 Measurement Results Explanation Example.....	13
4 TEST RESULT	14
4.1 20dB and 99% Bandwidth Measurement	14
4.2 Peak Output Power Measurement	15
4.3 Carrier Frequency Separation Measurement	16
4.4 Time of Occupancy Measurement.....	17
4.5 Number of Hopping Channels Measurement	18
4.6 Conducted Band Edges Measurement	19
4.7 Conducted Spurious Emission Measurement	20
4.8 Radiated Band Edges and Spurious Emission Measurement	21
4.9 AC Conducted Emission Measurement.....	50
4.10 Antenna Requirements.....	53
5 LIST OF MEASURING EQUIPMENT.....	54
6 UNCERTAINTY OF EVALUATION.....	56
Appendix A: 20dB Emission Bandwidth	57
Appendix B: Occupied Channel Bandwidth	63
Appendix C: Maximum conducted output power	69
Appendix D: Carrier frequency separation	75
Appendix E: Time of occupancy	78
Appendix F: Number of hopping channels.....	106
Appendix G: Band edge measurements	109
Appendix H: Conducted Spurious Emission.....	116
Appendix I. Setup Photographs	131

Summary of Test Result

FCC Rule	Description	Limit	Result	Remark
15.247(a)(1)	20dB Bandwidth	NA	Pass	-
-	99% Bandwidth	-	Pass	-
15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
15.247(a)(1)	Number of Channels	≥ 15 Chs	Pass	-
15.247(a)(1)	Average Time of Occupancy	≤ 0.4 sec in 31.6 sec period	Pass	-
15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
15.247(d)	Conducted Band Edges	≤ 20 dBc	Pass	-
15.247(d)	Conducted Spurious Emission	≤ 20 dBc	Pass	-
15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.54 dB at 43.58 MHz
15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.71 dB at 0.491 MHz
15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 Test Laboratory

1.1 Test facility

CNAS (accreditation number:L11138)

Hunan Ecloud Testing Technology Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number:CN1244 , Test Firm Registration

Number:793308)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

ISED(CAB identifier: CN0012, ISED# :24347)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the Wireless Device Testing Laboratories list of innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

A2LA (Certificate Number:4895.01)

Hunan Ecloud Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

2 General Description

2.1 Applicant

Shenzhen CYX Industrial Co., Ltd.

5/F, one buildings, xiaza industrial zone, zaohe road, Longhua District, Shenzhen, China

2.2 Manufacturer

Shenzhen CYX Industrial Co., Ltd.

5/F, one buildings, xiaza industrial zone, zaohe road, Longhua District, Shenzhen, China

2.3 General Description Of EUT

Product	TV BOX
Model No.	A95X F3 Air
Additional NO.	A95X F3 Slim, A95X F3, A95X D1, A95X D2, A95X F4, A95X F4 Air, A95X F4 Slim, A95X F5 Air, A95X F5 Slim, A95X F6 Air, A95X F6 Slim, A95X F7 Air, A95X F7 Slim, A95X F8 Air, A95X F8 Slim, A95X F5, A95X F6, A95X F7, A95X F8
Difference Description	Only the model name is different
FCC ID	2AVBM-A95XF3AIR
Power Supply	120Vac
Modulation Technology	FHSS
Modulation Type	GFSK, 8DPSK, $\pi/4$ DQPSK
Operating Frequency	2402MHz~2480MHz
Number Of Channel	79
Max. Output Power	Bluetooth BR(1Mbps) : 6.19 dBm (0.0042W) Bluetooth BR(2Mbps) : 8.10 dBm (0.0065W) Bluetooth BR(3Mbps) : 8.36 dBm (0.0069W)
Antenna Type	PCB Antenna type with 2dBi gain
HW Version	A95XF3_V81
SW Version	A95X_F3_AIR_M_9.0.0
I/O Ports	Refer to user's manual
Cable Supplied	N/A

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. The EUT was powered by the following adapters:

MODEL:	TSL-1681
INPUT:	110-240V~50/60Hz 0.3A
OUTPUT:	5V DC 2A
DC LINE:	1.0 m
Note: Add a magnetic ring at both ends of the power cord for testing	

4. The EUT matched the following HDMI cable:

Model:	A95X F3 Air
Signal Line:	0.8 Meter/Shielded

5. The EUT matched the following Remote controller:

Model:	A95X F3 Air
--------	-------------

2.4 Modification of EUT

No modifications are made to the EUT during all test items.

2.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 15.247 Meas Guidance v05r02

Remark:

1. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 Test Configuration of Equipment Under Test

3.1 Descriptions of Test Mode

The transmitter has a maximum peak conducted output power as follows:

Channel	Frequency	Mode	Bluetooth RF Output Power
Ch00	2402MHz	GFSK	6.09
		4π-DQPSK	7.94
		8PSK	8.27
Ch39	2441MHz	GFSK	6.19
		4π-DQPSK	8.1
		8PSK	8.36
Ch78	2480MHz	GFSK	5.03
		4π-DQPSK	6.8
		8PSK	7.18

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.

3.2 Test Mode

3.2.1 Antenna Port Conducted Measurement

Summary table of Test Cases				
Test Item	Data Rate / Modulation			
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π/4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK	
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz	

3.2.2 Radiated Emission Test (Below 1GHz)

Radiated Test Cases	Bluetooth EDR 3Mbps
	8-DPSK
	Mode 1: CH00_2441 MHz

Note : 1. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type. Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

2. Following channel(s) was (were) selected for the final test as listed above

3.2.3 Radiated Emission Test (Above 1GHz)

Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz
	Mode 2: CH39_2441 MHz
	Mode 3: CH78_2480 MHz

Note : 1. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

2. Following channel(s) was (were) selected for the final test as listed above

3. For frequency above 18GHz, the measured value is much lower than the limit, therefore, it is not reflected in the report.

3.2.4 Power Line Conducted Emission Test:

AC Conducted Emission	Mode 1 : Bluetooth Link + HDMI + TF Card Upload + USB playing + Ping
------------------------------	--

3.3 Support Equipment


Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	E470C	FCC DoC	N/A	shielded cable DC O/P 1.8 m unshielded AC I/P cable1.2 m

3.4 Test Setup

The EUT is continuously communicating to the Bluetooth tester during the tests.

EUT was set in the Hidden menu mode to enable BT communications.

The following picture is a screenshot of the test software






```

Administrator: C:\Windows\system32\cmd.exe - adb shell
ampere:/system/bin # boots -c dut
boots -c dut
[boots] User(?) <-> Socket<4> <-> server
  CMD: 03 0C 00
ampere:/system/bin # boots -c dut
boots -c dut
[boots] User(?) <-> Socket<4> <-> server
  CMD: 03 0C 00
  Event: 0E 04 01 03 0C 00 <HCI_RESET>
  CMD: 1A 0C 01 03
  Event: 0E 04 01 1A 0C 00
  CMD: 05 0C 03 02 00 02
  Event: 0E 04 01 05 0C 00
  CMD: 03 18 00
  Event: 0E 04 01 03 18 00
ampere:/system/bin # boots -c rft -p 04 -c 78 -t 04
boots -c rft -p 04 -c 78 -t 04
[boots] User(?) <-> Socket<4> <-> server
  CMD: 0D FC 17 00 00 04 00 4E 4E 00 02 04 1B 00 02 00 01...
[boots_pkt:W] Receive unknown type 00
Unknown 00: 32 00 E2 94 2A BF EF 44 55 00
[boots_btif:E] boots_btif_read: Invalid argument<22> !!!
[boots_srv:E] main: Read data from chip failed !!!
[boots_srv] Service STOP!
ampere:/system/bin #


```

Setup diagram for Conducted Test




Setup diagram for Raidation(9KHz~30MHz) Test

Setup diagram for Raidation(Below 1G) Test


Setup diagram for Raidation(Above1G) Test



Setup diagram for AC Conducted Emission Test



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 5 + 10 = 15 \text{ (dB)}$$

For all radiated test items:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Over Limit (dB μ V/m) = Level(dB μ V/m) - Limit Level (dB μ V/m)

4 Test Result

4.1 20dB and 99% Bandwidth Measurement

4.1.1 Limit of 20dB and 99% Bandwidth

None; for reporting purposes only.

4.1.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
4. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW \geq 1% of the 99% bandwidth; VBW \geq RBW; Sweep = auto; Detector function = sample;
Trace = max hold.

4.1.3 Test Result of 20dB Bandwidth

Refer to Appendix A of this test report.

4.1.4 Test Result of 99% Bandwidth

Refer to Appendix B of this test report.

4.2 Peak Output Power Measurement

4.2.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

4.2.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

4.2.3 Test Result of Peak Output Power

Refer to Appendix C of this test report.

4.3 Carrier Frequency Separation Measurement

4.3.1 Limit of Hopping Channel Separation

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

4.3.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

4.3.3 Test Result of Hopping Channel Separation

Refer to Appendix D of this test report.

4.4 Time of Occupancy Measurement

4.4.1 Limit of Average Time of Occupancy

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.
4. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as below:

DH1 time slot= Burst Width (ms)*(1600/ (2*79))*31.6

DH3 time slot= Burst Width (ms)*(1600/ (4*79))*31.6

DH5 time slot= Burst Width (ms)*(1600/ (6*79))*31.6

4.4.3 Test Result of Dwell Time

Refer to Appendix E of this test report.

4.5 Number of Hopping Channels Measurement

4.5.1 Limits of Number of Hopping Channels

FCC § 15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

4.5.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.

4.5.3 Test Result of Number of Hopping Channels

Refer to Appendix F of this test report.

4.6 Conducted Band Edges Measurement

4.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

4.6.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 1~3.

4.6.3 Test Result of Conducted Band Edges

Refer to Appendix G of this test report.

4.7 Conducted Spurious Emission Measurement

4.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

4.7.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

4.7.3 Test Result of Conducted Spurious Emission

Refer to Appendix H of this test report.

4.8 Radiated Band Edges and Spurious Emission Measurement

4.8.1 Limit of Radiated Band Edges and Spurious Emission


In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The frequency range from 9KHz to 10th harmonic (25GHz) are checked, and no any emissions were found from 18GHz to 25GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.8.2 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The measurement distance is 3 meter.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW = RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement:
VBW = 10 Hz, when duty cycle is no less than 98 percent.
 $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.8.3 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

4.8.4 Test Result of Radiated Spurious at Band Edges



Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.410GHz	Polarization :	Horizontal


Data: 124



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.78	26.91	3.48	35.43	23.74	54.00	-30.26	Average
2390.000	29.56	27.11	3.53	35.55	24.65	54.00	-29.35	Average
2402.000	91.44	27.15	3.54	35.56	86.57	54.00	32.57	Average

Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.410GHz	Polarization :	Vertical


Data: 126



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Limit level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	46.75	26.91	3.48	35.43	41.71	74.00	-32.29	Peak
2390.000	45.78	27.11	3.53	35.55	40.87	74.00	-33.13	Peak
2402.080	99.10	27.15	3.54	35.56	94.23	74.00	20.23	Peak


Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.410GHz	Polarization :	Vertical

Data: 127



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	32.49	26.91	3.48	35.43	27.45	54.00	-26.55	Average
2390.000	32.78	27.11	3.53	35.55	27.87	54.00	-26.13	Average
2402.080	92.53	27.15	3.54	35.56	87.66	54.00	33.66	Average


Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	2.47GHz~2.51GHz	Polarization :	Horizontal

Data: 139


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	109.58	27.35	3.59	35.67	104.85	74.00	30.85	Peak
2483.500	52.17	27.36	3.59	35.68	47.44	74.00	-26.56	Peak
2500.000	45.81	27.40	3.60	35.70	41.11	74.00	-32.89	Peak

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	2.47GHz~2.51GHz	Polarization :	Horizontal


Data: 142



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.040	94.49	27.35	3.59	35.67	89.76	74.00	15.76	Peak
2483.500	48.37	27.36	3.59	35.68	43.64	74.00	-30.36	Peak
2500.000	46.96	27.40	3.60	35.70	42.26	74.00	-31.74	Peak


Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	2.47GHz~2.51GHz	Polarization :	Vertical

Data: 143




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	89.67	27.35	3.59	35.67	84.94	54.00	30.94	Average
2483.500	33.60	27.36	3.59	35.68	28.87	54.00	-25.13	Average
2500.000	33.09	27.40	3.60	35.70	28.39	54.00	-25.61	Average

4.8.5 Test Result of Radiated Spurious Emission (1GHz ~ 10th Harmonic)




Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Data: 121



Data: 122




Freq MHz	Reading dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4810.000	43.70	31.24	5.57	34.85	45.66	54.00	-8.34	Average
4810.000	58.45	31.24	5.57	34.85	60.41	74.00	-13.59	Peak
7215.000	26.40	35.89	7.63	36.40	33.52	54.00	-20.48	Average
7215.000	38.95	35.89	7.63	36.40	46.07	74.00	-27.93	Peak
9620.000	28.35	37.82	10.33	36.40	40.10	54.00	-13.90	Average
9620.000	43.76	37.82	10.33	36.40	55.51	74.00	-18.49	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Data: 128




Freq MHz	Reading dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2402.000	96.15	27.15	3.54	35.56	91.28	74.00	17.28	Peak

Test Mode :	Bluetooth (3Mbps) CH00 (2402MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Data: 119




Data: 120


Freq MHz	Reading dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4810.000	33.08	31.24	5.57	34.85	35.04	54.00	-18.96	Average
4810.000	47.02	31.24	5.57	34.85	48.98	74.00	-25.02	Peak
7215.000	26.58	35.89	7.63	36.40	33.70	54.00	-20.30	Average
7215.000	39.20	35.89	7.63	36.40	46.32	74.00	-27.68	Peak
9620.000	28.42	37.82	10.33	36.40	40.17	54.00	-13.83	Average
9620.000	42.64	37.82	10.33	36.40	54.39	74.00	-19.61	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Data: 130




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Preamp level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2441.000	106.95	27.25	3.56	35.62	102.14	74.00	28.14	Peak

Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Data: 131




Data: 132


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Preamp level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	29.51	31.42	5.55	34.79	31.69	54.00	-22.31	Average
4882.000	54.36	31.42	5.55	34.79	56.54	74.00	-17.46	Peak
7323.000	26.61	36.14	7.52	36.40	33.87	54.00	-20.13	Average
7323.000	46.07	36.14	7.52	36.40	53.33	74.00	-20.67	Peak
9764.000	27.65	38.08	10.75	36.40	40.08	54.00	-13.92	Average
9764.000	43.71	38.08	10.75	36.40	56.14	74.00	-17.86	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Data: 129




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2441.000	91.23	27.25	3.56	35.62	86.42	74.00	12.42	Peak

Test Mode :	Bluetooth (3Mbps) CH39 (2441MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Data: 133




Data: 134


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Preamp level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	38.11	31.42	5.55	34.79	40.29	54.00	-13.71	Average
4882.000	45.86	31.42	5.55	34.79	48.04	74.00	-25.96	Peak
7323.000	26.41	36.14	7.52	36.40	33.67	54.00	-20.33	Average
7323.000	40.33	36.14	7.52	36.40	47.59	74.00	-26.41	Peak
9764.000	37.32	38.08	10.75	36.40	49.75	54.00	-4.25	Average
9764.000	40.70	38.08	10.75	36.40	53.13	74.00	-20.87	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Data: 141




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	93.36	27.35	3.59	35.67	88.63	74.00	14.63	Peak

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Data: 137

Data: 138




Freq MHz	Reading dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	38.12	31.60	5.52	34.73	40.51	54.00	-13.49	Average
4960.000	46.02	31.60	5.52	34.73	48.41	74.00	-25.59	Peak
7440.000	25.75	36.41	7.56	36.40	33.32	54.00	-20.68	Average
7440.000	38.28	36.41	7.56	36.40	45.85	74.00	-28.15	Peak
9920.000	32.57	38.36	11.17	36.40	45.70	54.00	-8.30	Average
9920.000	41.73	38.36	11.17	36.40	54.86	74.00	-19.14	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Data: 144




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	93.23	27.35	3.59	35.67	88.50	74.00	14.50	Peak

Test Mode :	Bluetooth (3Mbps) CH78 (2480MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Data: 135




Data: 136


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Limit level dBuV/m	Over limit dB	Remark
4960.000	38.33	31.60	5.52	34.73	40.72	54.00	-13.28 Average
4960.000	47.05	31.60	5.52	34.73	49.44	74.00	-24.56 Peak
7440.000	26.39	36.41	7.56	36.40	33.96	54.00	-20.04 Average
7440.000	38.28	36.41	7.56	36.40	45.85	74.00	-28.15 Peak
9920.000	28.57	38.36	11.17	36.40	41.70	54.00	-12.30 Average
9920.000	41.63	38.36	11.17	36.40	54.76	74.00	-19.24 Peak


Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

4.8.6 Test Result of Radiated Spurious Emission (30MHz ~ 1GHz)



Test Mode :	Bluetooth (3Mbps) CH00 (2441MHz)	Temperature :	21~23°C
Test Engineer :	Jerry Wang	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Vertical

Data: 236



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Preamp level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
43.580	54.75	12.70	1.54	32.53	36.46	40.00	-3.54	QP
106.630	56.10	9.60	1.97	32.60	35.07	43.50	-8.43	Peak
151.250	52.07	14.41	2.13	32.63	35.98	43.50	-7.52	Peak
250.190	45.85	13.10	2.54	32.68	28.81	46.00	-17.19	Peak
517.910	35.32	18.33	3.68	32.85	24.48	46.00	-21.52	Peak
792.420	33.81	22.37	4.64	32.02	28.80	46.00	-17.20	Peak

4.9 AC Conducted Emission Measurement

4.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.


Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


4.9.2 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

4.9.3 Test Result of AC Conducted Emission



Result Level= Reading Level + LISN Factor + Cable Loss



Result Level= Reading Level + LISN Factor + Cable Loss

4.10 Antenna Requirements

4.10.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded..

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

4.10.2 Antenna Connected Construction

An embedded-in antenna design is used.

4.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	Keysight	N9010A	MY56070788	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY56510025	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY57030005	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY56510018	2019-01-23	2020-01-22	Conducted
Power Sensor	Keysight	U2021XA	MY56480002	2019-01-23	2020-01-22	Conducted
Thermal Chamber	Sanmtest	SMC-408-CD	2435	2019-05-09	2020-05-08	Conducted
Base Station	R&S	CMW 270	101231	2019-01-23	2020-01-22	Conducted
Signal Generator (Blocker)	Keysight	N5171B	MY56200661	2019-04-19	2020-04-18	Conducted

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV 40	101433	2019-02-18	2020-02-17	Radiation
Amplifier	Sonoma	310	363917	2019-01-22	2020-01-21	Radiation
Amplifier	Schwarzbeck	BBV 9718	327	2019-01-22	2020-01-21	Radiation
Amplifier	Narda	TTA1840-35-HG	2034380	2019-05-15	2020-05-14	Radiation
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	2017-03-03	2020-03-02	Radiation
Broadband Antenna	Schwarzbeck	VULB 9168	9168-757	2017-03-03	2020-03-02	Radiation
Horn Antenna	Schwarzbeck	BBHA 9120 D	1677	2017-03-03	2020-03-02	Radiation
Horn Antenna	COM-POWER	AH-1840	101117	2018-06-20	2021-06-19	Radiation
Test Software	Auidx	E3	6.111221a	N/A	N/A	Radiation
Filter	Micro-Tronics	BRM 50702	G266	N/A	N/A	Radiation

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
LISN	R&S	ENV216	102125	2019-01-22	2020-01-21	Conducted
LISN	R&S	ENV432	101327	2019-01-22	2020-01-21	Conducted
EMI Test Receiver	R&S	ESR3	102143	2019-01-23	2020-01-22	Conducted
EMI Test Software	Audix	E3	N/A	N/A	N/A	Conducted

N/A: No Calibration Required

6 Uncertainty of Evaluation

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.60dB
Radiated emission	30MHz ~ 1GHz	5.05dB
	1GHz ~ 18GHz	5.06 dB
	18GHz ~ 40GHz	3.65dB

MEASUREMENT	UNCERTAINTY
Occupied Channel Bandwidth	±0.1%
RF output power, conducted	±1.2dB
Power density, conducted	±1.2dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Appendix A: 20dB Emission Bandwidth

Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.960	2401.526	2402.486	---	PASS
		2441	0.969	2440.520	2441.489	---	PASS
		2480	0.936	2479.538	2480.474	---	PASS
2DH5	Ant1	2402	1.317	2401.340	2402.657	---	PASS
		2441	1.326	2440.331	2441.657	---	PASS
		2480	1.314	2479.337	2480.651	---	PASS
3DH5	Ant1	2402	1.311	2401.346	2402.657	---	PASS
		2441	1.296	2440.337	2441.633	---	PASS
		2480	1.305	2479.349	2480.654	---	PASS

Test Graphs






2DH5_Ant1_2441



2DH5_Ant1_2480







Appendix B: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.86249	2401.563	2402.426	---	PASS
		2441	0.87405	2440.556	2441.430	---	PASS
		2480	0.87063	2479.555	2480.425	---	PASS
2DH5	Ant1	2402	1.1865	2401.403	2402.589	---	PASS
		2441	1.1786	2440.403	2441.581	---	PASS
		2480	1.1869	2479.402	2480.589	---	PASS
3DH5	Ant1	2402	1.1921	2401.395	2402.587	---	PASS
		2441	1.1933	2440.391	2441.585	---	PASS
		2480	1.1934	2479.393	2480.586	---	PASS

Test Graphs



DH5_Ant1_2480

2DH5_Ant1_2402









Appendix C: Maximum conducted output power

Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	6.09	<=20.97	PASS
		2441	6.19	<=20.97	PASS
		2480	5.03	<=20.97	PASS
2DH5	Ant1	2402	7.94	<=20.97	PASS
		2441	8.1	<=20.97	PASS
		2480	6.8	<=20.97	PASS
3DH5	Ant1	2402	8.27	<=20.97	PASS
		2441	8.36	<=20.97	PASS
		2480	7.18	<=20.97	PASS

Test Graphs



DH5_Ant1_2480



2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441






Appendix D: Carrier frequency separation

Test Result

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop_2441	1.004	>=0.646	PASS
2DH5	Ant1	Hop_2441	0.980	>=0.884	PASS
3DH5	Ant1	Hop_2441	1.012	>=0.874	PASS

Test Graphs





Appendix E: Time of occupancy

Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop_2402	0.37	180	0.067	<=0.4	PASS
		Hop_2441	0.37	140	0.052	<=0.4	PASS
		Hop_2480	0.37	140	0.052	<=0.4	PASS
DH3	Ant1	Hop_2402	1.63	160	0.261	<=0.4	PASS
		Hop_2441	1.63	140	0.228	<=0.4	PASS
		Hop_2480	1.63	120	0.195	<=0.4	PASS
DH5	Ant1	Hop_2402	2.88	50	0.144	<=0.4	PASS
		Hop_2441	2.88	120	0.345	<=0.4	PASS
		Hop_2480	2.87	70	0.201	<=0.4	PASS
2DH1	Ant1	Hop_2402	0.38	150	0.057	<=0.4	PASS
		Hop_2441	0.38	200	0.076	<=0.4	PASS
		Hop_2480	0.38	170	0.065	<=0.4	PASS
2DH3	Ant1	Hop_2402	1.63	160	0.261	<=0.4	PASS
		Hop_2441	1.63	150	0.245	<=0.4	PASS
		Hop_2480	1.63	190	0.31	<=0.4	PASS
2DH5	Ant1	Hop_2402	2.88	80	0.23	<=0.4	PASS
		Hop_2441	2.88	100	0.288	<=0.4	PASS
		Hop_2480	2.88	100	0.288	<=0.4	PASS
3DH1	Ant1	Hop_2402	0.38	170	0.065	<=0.4	PASS
		Hop_2441	0.38	170	0.065	<=0.4	PASS
		Hop_2480	0.38	180	0.068	<=0.4	PASS
3DH3	Ant1	Hop_2402	0.38	120	0.046	<=0.4	PASS
		Hop_2441	0.38	160	0.061	<=0.4	PASS
		Hop_2480	0.38	190	0.072	<=0.4	PASS
3DH5	Ant1	Hop_2402	2.88	90	0.259	<=0.4	PASS
		Hop_2441	2.88	120	0.346	<=0.4	PASS
		Hop_2480	2.88	90	0.259	<=0.4	PASS

Test Graphs

