



FCC RADIO TEST REPORT

FCC ID : 2AVC9-7448
Equipment : Digital Media Receiver
Model Name : V5S83A
Applicant : BROOKLYN EAST LLC
41 University Drive, Suite 400
Newtown, PA 18940
Standard : FCC Part 15 Subpart C §15.247

The product was received on Feb. 24, 2021 and testing was started from Mar. 01, 2021 and completed on Mar. 26, 2021. We, Sporton International (USA) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (USA) Inc., the test report shall not be reproduced except in full.

Approved by: Neil Kao

Sportun International (USA) Inc.
1175 Montague Expressway, Milpitas, CA 95035



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	5
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System.....	9
2.4 EUT Operation Test Setup	10
2.5 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 Number of Channel Measurement	11
3.2 Hopping Channel Separation Measurement	13
3.3 Dwell Time Measurement.....	17
3.4 20dB and 99% Bandwidth Measurement	19
3.5 Output Power Measurement.....	26
3.6 Conducted Band Edges Measurement.....	27
3.7 Conducted Spurious Emission Measurement	32
3.8 Radiated Band Edges and Spurious Emission Measurement	38
3.9 AC Conducted Emission Measurement.....	42
3.10 Antenna Requirements	44
4 List of Measuring Equipment	45
5 Uncertainty of Evaluation.....	47
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.247(a)(1)	Number of Channels	Pass
3.2	15.247(a)(1)	Hopping Channel Separation	Pass
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass
3.4	15.247(a)(1)	20dB Bandwidth	Pass
3.4	2.1049	99% Occupied Bandwidth	Reporting only
3.5	15.247(b)(1)	Peak Output Power	Pass
3.6	15.247(d)	Conducted Band Edges	Pass
3.7	15.247(d)	Conducted Spurious Emission	Pass
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass
3.9	15.207	AC Conducted Emission	Pass
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Digital Media Receiver
Model Name	V5S83A
FCC ID	2AVC9-7448
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE

Remark: The above EUT's information was declared by manufacturer.

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 13.21 dBm (0.0209 W) Bluetooth EDR (2Mbps) : 13.10 dBm (0.0204 W) Bluetooth EDR (3Mbps) : 13.18 dBm (0.0208 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.836MHz Bluetooth EDR (2Mbps) : 1.137MHz Bluetooth EDR (3Mbps) : 1.129MHz
Antenna Type / Gain	Dipole Antenna type with gain 2.8 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	Sportun International (USA) Inc
Test Site Location	1175 Montague Expressway, Milpitas, CA 95035 TEL : 408 9043300
Test Site No.	Sportun Site No.
	TH01-CA, CO01-CA, 03CH02-CA

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-



2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
Conducted Test Cases	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
AC Conducted Emission	Mode 1 : WLAN (2.4GHz) Tx + Bluetooth Tx + Dock (Charging from Adapter)		
	Remark: For Radiated Test Cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.		

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth Tx Mode>





2.4 EUT Operation Test Setup

The RF test items, utility “Compliance WiFi-BT-Zigbee V1.0.0.97” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300 kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.


3.1.4 Test Setup





3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.



3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300 kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.




<1Mbps>






<2Mbps>





<3Mbps>



3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

**Remark:**

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Use the following spectrum analyzer settings for 20 dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW \geq 1-5% of the 99% bandwidth; VBW \geq 3 * RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.




<1Mbps>






<2Mbps>






<3Mbps>



3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<2Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<3Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band:

1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set the maximum power setting and enable the EUT to transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2 and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup




3.6.5 Test Result of Conducted Band Edges

<1Mbps>




<2Mbps>






<3Mbps>




3.6.6 Test Result of Conducted Hopping Mode Band Edges

<1Mbps>




<2Mbps>





<3Mbps>





3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurious must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.7.4 Test Setup







3.7.5 Test Result of Conducted Spurious Emission


<1Mbps>






<2Mbps>








<3Mbps>







3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics / spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

See list of measuring equipment of this test report.



3.8.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz, RBW = 1 MHz for $f > 1$ GHz ; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
$$\text{On time} = N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
$$\text{Average Emission Level} = \text{Peak Emission Level} + 20 \cdot \log(\text{Duty cycle})$$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1 GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.8.7 Duty Cycle

Please refer to Appendix E.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	R&S	HFH2-Z2E	100840	9kHz~30MHz	Jun. 16, 2020	Mar. 04, 2021~Mar. 26, 2021	Jun. 15, 2021	Radiation (03CH02-CA)
Bilog Antenna	TESEQ	6111D	50392	30MHz~1GHz	Jul. 29, 2020	Mar. 04, 2021~Mar. 26, 2021	Jul. 28, 2021	Radiation (03CH02-CA)
Horn Antenna	SCHWARZBECK	BBHA 9120D	01895	1GHz~18GHz	Aug. 28, 2020	Mar. 04, 2021~Mar. 26, 2021	Aug. 27, 2021	Radiation (03CH02-CA)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00842	18GHz~40GHz	Jul. 27, 2020	Mar. 04, 2021~Mar. 26, 2021	Jul. 26, 2021	Radiation (03CH02-CA)
Amplifier	SONOMA	310N	372240	N/A	Aug. 12, 2020	Mar. 04, 2021~Mar. 26, 2021	Aug. 11, 2021	Radiation (03CH02-CA)
Preamplifier	Keysight	83017A	MY53270321	1GHz~26.5GHz	Jul. 28, 2020	Mar. 04, 2021~Mar. 26, 2021	Jul. 27, 2021	Radiation (03CH02-CA)
Preamplifier	EMEC	EMC18G40G	060725	18G-40G	Aug. 07, 2020	Mar. 04, 2021~Mar. 26, 2021	Aug. 06, 2021	Radiation (03CH02-CA)
Preamplifier	E-instrument	ERA-100M-18 G-56-01-A70	EC1900251	1GHz~18GHz	Nov. 26, 2019	Mar. 04, 2021~Mar. 26, 2021	Nov. 25, 2021	Radiation (03CH02-CA)
EMI Test Receiver	Rohde & Schwarz	ESR7	102177	9kHz~7GHz	Jul. 16, 2020	Mar. 04, 2021~Mar. 26, 2021	Jul. 15, 2021	Radiation (03CH02-CA)
Spectrum Analyzer	Keysight	N9010A	MY57420221	10Hz~44GHz	Sep. 11, 2020	Mar. 04, 2021~Mar. 26, 2021	Sep. 10, 2021	Radiation (03CH02-CA)
Filter	Wainwright	Whkx8-5872.5-6750-18000-40ST	SN8	6.75G Highpass	Jul. 24, 2020	Mar. 04, 2021~Mar. 26, 2021	Jul. 23, 2021	Radiation (03CH02-CA)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN10	3G Highpass	Jul. 24, 2020	Mar. 04, 2021~Mar. 26, 2021	Jul. 23, 2021	Radiation (03CH02-CA)
Filter	Wainwright	WLK12-1200-1272-11000-40SS	SN2	1.2G Low Pass	Jul. 24, 2020	Mar. 04, 2021~Mar. 26, 2021	Jul. 23, 2021	Radiation (03CH02-CA)
Hygrometer	TESEO	608-H1	45142602	N/A	Aug. 05, 2020	Mar. 04, 2021~Mar. 26, 2021	Aug. 04, 2021	Radiation (03CH02-CA)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Mar. 04, 2021~Mar. 26, 2021	N/A	Radiation (03CH02-CA)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 04, 2021~Mar. 26, 2021	N/A	Radiation (03CH02-CA)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 04, 2021~Mar. 26, 2021	N/A	Radiation (03CH02-CA)
Software	Audix	E3	N/A	N/A	N/A	Mar. 04, 2021~Mar. 26, 2021	N/A	Radiation (03CH02-CA)
LISN	TESEQ	NNB51	47407	N/A	Jul. 06, 2020	Mar. 12, 2021	Jul. 05, 2021	Conduction (CO01-CA)
EMI Test Receiver	R&S	ESR7	102177	9KHz~7GHz	Jul. 16, 2020	Mar. 12, 2021	Jul. 15, 2021	Conduction (CO01-CA)
Pulse limiter with 10dB attenuation	R&S	VTSD 9561-FN	9561-F-N00412	N/A	Jul. 08, 2020	Mar. 12, 2021	Jul. 07, 2021	Conduction (CO01-CA)
Test Software	R&S	EMC32 V10.30.0	N/A	N/A	N/A	Mar. 12, 2021	N/A	Conduction (CO01-CA)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	45142595	N/A	Aug. 05, 2020	Mar. 01, 2021~ Mar. 10, 2021	Aug. 04, 2021	Conducted (TH01-CA)
Power meter	Anritsu	ML2495A	1804004	N/A	Aug. 10, 2020	Mar. 01, 2021~ Mar. 10, 2021	Aug. 09, 2021	Conducted (TH01-CA)
Power Sensor	Anritsu	MA2411B	1726149	300MHz-40GHz	Aug. 10, 2020	Mar. 01, 2021~ Mar. 10, 2021	Aug. 09, 2021	Conducted (TH01-CA)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101089	10Hz-40GHz	Sep. 14, 2020	Mar. 01, 2021~ Mar. 10, 2021	Sep. 13, 2021	Conducted (TH01-CA)
Coupler	WOKEN	20dB 30W Coupler	CAT7AKW1A1	0.5-18GHz	Calibration from System	Mar. 01, 2021~ Mar. 10, 2021	Calibration from System	Conducted (TH01-CA)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.5
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	6.1
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	6.5
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Andy Kao/Kaying Xiong	Temperature:	17~22.2	°C
Test Date:	2021/3/1~2021/3/10	Relative Humidity:	31~47.5	%

<u>TEST RESULTS DATA</u> <u>20dB and 99% Occupied Bandwidth and Hopping Channel Separation</u>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.880	0.834	1.003	0.5866	Pass
DH	1Mbps	1	39	2441	0.880	0.836	1.003	0.5866	Pass
DH	1Mbps	1	78	2480	0.880	0.836	1.003	0.5866	Pass
2DH	2Mbps	1	0	2402	1.211	1.135	1.003	0.8075	Pass
2DH	2Mbps	1	39	2441	1.211	1.137	0.999	0.8075	Pass
2DH	2Mbps	1	78	2480	1.211	1.137	0.999	0.8075	Pass
3DH	3Mbps	1	0	2402	1.211	1.126	0.999	0.8075	Pass
3DH	3Mbps	1	39	2441	1.211	1.129	0.999	0.8075	Pass
3DH	3Mbps	1	78	2480	1.211	1.129	0.999	0.8075	Pass

<u>TEST RESULTS DATA</u> <u>Dwell Time</u>						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

<u>TEST RESULTS DATA</u> <u>Peak Power Table</u>					
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	13.21	30.00	Pass
	39	1	13.19	30.00	Pass
	78	1	12.40	30.00	Pass
2DH1	0	1	13.10	20.97	Pass
	39	1	13.09	20.97	Pass
	78	1	12.27	20.97	Pass
3DH1	0	1	13.18	20.97	Pass
	39	1	13.16	20.97	Pass
	78	1	12.38	20.97	Pass

<u>TEST RESULTS DATA</u> <u>Average Power Table</u> <u>(Reporting Only)</u>				
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	13.09	8.24
	39	1	13.07	8.24
	78	1	12.25	8.24
2DH1	0	1	11.62	8.13
	39	1	11.61	8.13
	78	1	10.80	8.13
3DH1	0	1	11.67	8.16
	39	1	11.66	8.16
	78	1	10.85	8.16

<u>TEST RESULTS DATA</u> <u>Number of Hopping Frequency</u>			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Appendix B. AC Conducted Emission Test Results


Test Engineer :	Janssen Wongso	Temperature :	18~21°C
		Relative Humidity :	40.6~44.8%

EUT Information

Site: CO01-CA

Power: 120Vac/60Hz
Model: Vesta
Mode: 1

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.197700	29.64	---	63.71	34.07	L1	OFF	20.0
0.197700	---	21.02	53.71	32.69	L1	OFF	20.0
0.240000	28.79	---	62.10	33.31	L1	OFF	20.0
0.240000	---	20.53	52.10	31.57	L1	OFF	20.0
0.904290	25.30	---	56.00	30.70	L1	OFF	20.0
0.904290	---	12.96	46.00	33.04	L1	OFF	20.0
4.933590	27.16	---	56.00	28.84	L1	OFF	20.1
4.933590	---	17.85	46.00	28.15	L1	OFF	20.1
6.859500	23.66	---	60.00	36.34	L1	OFF	20.1
6.859500	---	17.37	50.00	32.63	L1	OFF	20.1
26.133000	19.24	---	60.00	40.76	L1	OFF	20.6
26.133000	---	13.52	50.00	36.48	L1	OFF	20.6

EUT Information

Site: CO01-CA

Power: 120Vac/60Hz
Model: Vesta
Mode: 1

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.150203	---	26.37	55.99	29.62	N	OFF	20.0
0.150203	33.38	---	65.99	32.61	N	OFF	20.0
0.251250	---	19.09	51.72	32.63	N	OFF	20.0
0.251250	32.38	---	61.72	29.34	N	OFF	20.0
0.372750	---	18.69	48.44	29.75	N	OFF	20.0
0.372750	26.77	---	58.44	31.67	N	OFF	20.0
1.693860	---	11.32	46.00	34.68	N	OFF	20.0
1.693860	19.06	---	56.00	36.94	N	OFF	20.0
6.852210	---	17.68	50.00	32.32	N	OFF	20.1
6.852210	24.19	---	60.00	35.81	N	OFF	20.1
26.142000	---	15.07	50.00	34.93	N	OFF	20.6
26.142000	21.79	---	60.00	38.21	N	OFF	20.6



Appendix C. Radiated Spurious Emission

Test Engineer :	Calvin Wu and Michael Bui	Temperature :		19~24°C	
		Relative Humidity :		40~46%	

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2389.17	46.42	-27.58	74	42.74	27.63	7.42	31.37	218	354	P	H
		2389.17	21.63	-32.37	54	-	-	-	-	-	-	A	H
	*	2402	108.87	-	-	105.18	27.61	7.44	31.36	218	354	P	H
	*	2402	84.08	-	-	-	-	-	-	-	-	A	H
		2350.635	46.09	-27.91	74	42.33	27.81	7.36	31.41	102	245	P	V
		2350.635	21.3	-32.7	54	-	-	-	-	-	-	A	V
	*	2402	99.52	-	-	95.87	27.57	7.44	31.36	102	245	P	V
	*	2402	74.73	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2321.76	45.99	-28.01	74	42.26	27.84	7.31	31.42	237	349	P	H
		2321.76	21.2	-32.8	54	-	-	-	-	-	-	A	H
	*	2441	111.52	-	-	107.79	27.59	7.5	31.36	237	349	P	H
	*	2441	86.73	-	-	-	-	-	-	-	-	A	H
		2493.42	45.33	-28.67	74	41.53	27.56	7.58	31.34	237	349	P	H
		2493.42	20.54	-33.46	54	-	-	-	-	-	-	A	H
		2336.88	45.4	-28.6	74	41.66	27.82	7.34	31.42	400	275	P	V
		2336.88	20.61	-33.39	54	-	-	-	-	-	-	A	V
	*	2441	102.53	-	-	98.94	27.45	7.5	31.36	400	275	P	V
	*	2441	77.74	-	-	-	-	-	-	-	-	A	V
		2487.4	44.89	-29.11	74	41.27	27.39	7.58	31.35	400	275	P	V
		2487.4	20.1	-33.9	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz		*	2480	110.61	-	-	106.83	27.57	7.56	31.35	232	350	P	H
		*	2480	85.82	-	-	-	-	-	-	-	-	A	H
			2484.44	54.02	-19.98	74	50.24	27.56	7.57	31.35	232	350	P	H
			2484.44	29.23	-24.77	54	-	-	-	-	-	-	A	H
		*	2480	101.9	-	-	98.29	27.4	7.56	31.35	117	95	P	V
		*	2480	77.11	-	-	-	-	-	-	-	-	A	V
			2484.52	47.86	-26.14	74	44.25	27.39	7.57	31.35	117	95	P	V
			2484.52	23.07	-30.93	54	-	-	-	-	-	-	A	V
		Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		3603	56.98	-17.02	74	83.27	29.26	10.05	65.6	298	328	P	H
		3603	32.19	-21.81	54	-	-	-	-	-	-	A	H
		4804	46.39	-27.61	74	70.02	31.38	11.28	66.29	100	0	P	H
		4804	21.60	-32.40	54	-	-	-	-	-	-	A	H
		11760	55.81	-18.19	74	65.44	39.35	17.72	66.7	216	17	P	H
		11760	31.02	-22.98	54	-	-	-	-	-	-	A	H
		18000	62.76	-11.24	74	60.16	48.43	21.97	67.8	121	279	P	H
		18000	37.97	-16.03	54	-	-	-	-	-	-	A	H
		3603	51.31	-22.69	74	77.7	29.16	10.05	65.6	100	259	P	V
		3603	26.52	-27.48	54	-	-	-	-	-	-	A	V
		4804	43.38	-30.62	74	67	31.39	11.28	66.29	100	0	P	V
		4804	18.59	-35.41	54	-	-	-	-	-	-	A	V
		11760	55.59	-18.41	74	65.18	39.39	17.72	66.7	320	338	P	V
		11760	30.80	-23.20	54	-	-	-	-	-	-	A	V
		18000	62.57	-11.43	74	59.92	48.48	21.97	67.8	400	163	P	V
		18000	37.78	-16.22	54	-	-	-	-	-	-	A	V



BT CH 39 2441MHz	3660	51.55	-22.45	74	77.89	29.25	10.07	65.66	100	10	P	H
	3660	26.76	-27.24	54	-	-	-	-	-	-	A	H
	4882	46.68	-27.32	74	70.04	31.35	11.43	66.14	100	0	P	H
	4882	21.89	-32.11	54	-	-	-	-	-	-	A	H
	7323	48.06	-25.94	74	63.66	36.37	13.89	65.86	100	0	P	H
	7323	23.27	-30.73	54	-	-	-	-	-	-	A	H
	11760	57.25	-16.75	74	66.88	39.35	17.72	66.7	207	16	P	H
	11760	32.46	-21.54	54	-	-	-	-	-	-	A	H
	18000	62.63	-11.37	74	60.03	48.43	21.97	67.8	311	82	P	H
	18000	37.84	-16.16	54	-	-	-	-	-	-	A	H
	3660	41.41	-32.59	74	67.75	29.25	10.07	65.66	100	0	P	V
	3660	16.62	-37.38	54	-	-	-	-	-	-	A	V
	4882	44.58	-29.42	74	68.01	31.28	11.43	66.14	100	0	P	V
	4882	19.79	-34.21	54	-	-	-	-	-	-	A	V
	7323	46.33	-27.67	74	61.86	36.44	13.89	65.86	100	0	P	V
	7323	21.54	-32.46	54	-	-	-	-	-	-	A	V
	11760	54.83	-19.17	74	64.42	39.39	17.72	66.7	169	20	P	V
	11760	30.04	-23.96	54	-	-	-	-	-	-	A	V
	18000	62.40	-11.60	74	59.75	48.48	21.97	67.8	323	60	P	V
	18000	37.61	-16.39	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz		3720	44.41	-29.59	74	70.62	29.41	10.1	65.72	100	0	P	H
		3720	19.62	-34.38	54	-	-	-	-	-	-	A	H
		4960	41.79	-32.21	74	64.71	31.47	11.59	65.98	100	0	P	H
		4960	17	-37	54	-	-	-	-	-	-	A	H
		7440	45.44	-28.56	74	60.79	36.51	14.03	65.89	100	0	P	H
		7440	20.65	-33.35	54	-	-	-	-	-	-	A	H
		11760	57.19	-16.81	74	66.82	39.35	17.72	66.7	251	262	P	H
		11760	32.4	-21.6	54	-	-	-	-	-	-	A	H
		18000	62.66	-11.34	74	60.06	48.43	21.97	67.8	100	0	P	H
		18000	37.87	-16.13	54							A	H
		4960	42.89	-31.11	74	65.86	31.42	11.59	65.98	100	0	P	V
		4960	18.1	-35.9	54	-	-	-	-	-	-	A	V
		7440	45.5	-28.5	74	60.88	36.48	14.03	65.89	100	0	P	V
		7440	20.71	-33.29	54	-	-	-	-	-	-	A	V
		11760	56.31	-17.69	74	65.9	39.39	17.72	66.7	308	339	P	V
		11760	31.52	-22.48	54	-	-	-	-	-	-	A	V
		18000	62.48	-11.52	74	59.83	48.48	21.97	67.8	236	197	P	V
		18000	37.69	-16.31	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above 18GHz

2.4GHz BT (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT SHF		23572	39.42	-34.58	74	37.06	38.74	15.06	51.44	150	0	P	H
		24671	39.54	-34.46	74	36.19	39.13	15.73	51.51	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz BT LF		30.97	22.45	-17.55	40	29.28	24.71	0.9	32.44	-	-	P	H	
		97.9	30.47	-13.03	43.5	45.4	15.79	1.7	32.42	-	-	P	H	
		120.21	36.84	-6.66	43.5	49.92	17.6	1.73	32.41	100	0	P	H	
		167.74	36.65	-6.85	43.5	51.03	15.93	2.1	32.41	-	-	P	H	
		243.4	31.66	-14.34	46	43.78	17.74	2.55	32.41	-	-	P	H	
		645.95	35.57	-10.43	46	37.46	26.58	4.14	32.61	-	-	P	H	
		30.97	21.9	-18.1	40	28.73	24.71	0.9	32.44	-	-	P	V	
		120.21	33.12	-10.38	43.5	46.2	17.6	1.73	32.41	-	-	P	V	
		136.7	34.43	-9.07	43.5	47.32	17.6	1.92	32.41	100	0	P	V	
		146.4	32.24	-11.26	43.5	45.37	17.3	1.98	32.41	-	-	P	V	
		572.23	31.54	-14.46	46	34.31	25.96	3.9	32.63	-	-	P	V	
		859.35	32.98	-13.02	46	30.98	29.1	4.82	31.92	-	-	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB μ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB μ V) – 35.86 (dB)

= 55.45 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) – Limit Line(dB μ V/m)

= 55.45(dB μ V/m) – 74(dB μ V/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB μ V) – 35.86 (dB)

= 43.54 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) – Limit Line(dB μ V/m)

= 43.54(dB μ V/m) – 54(dB μ V/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.





Appendix D. Radiated Spurious Emission Plots


Test Engineer :	Calvin Wu and Michael Bui	Temperature :	19~24°C
		Relative Humidity :	40~46%


2.4GHz 2400~2483.5MHz


BT (Band Edge @ 3m)



















2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)










Emission above 18GHz


2.4GHz BT (SHF)






Emission below 1GHz

2.4GHz BT (LF)





Appendix E. Duty Cycle Plots



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. **DH5** has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100 \text{ ms} / 57.6 \text{ ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100 \text{ ms}) = -24.79 \text{ dB}$$

—————THE END—————