

# TEST REPORT

**Reference No.**..... : WTD19S12086161W002 V1  
**FCC ID** ..... : 2AVDQ-HBZRMLP4  
**Applicant**..... : Shenzhen Zonda Hobby Co.,Ltd  
**Address**..... : Rm 609, Block A, Dachong Business Center, #9678 Shennan Rd.  
Nanshan District, Shenzhen, China  
**Manufacturer** ..... : The same as above  
**Address**..... : The same as above  
**Product**..... : Remote Controller  
**Model(s)** ..... : HBZRMLP4  
**Brand Name**..... : Esky  
**Standards**..... : FCC CFR47 Part 15.247:2018  
**Date of Receipt sample** .... : 2019-12-11  
**Date of Test** ..... : 2019-12-12 to 2019-12-25  
**Date of Issue**..... : 2020-01-02  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Services (Shenzhen) Co., Ltd.**

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

*Ford Wang*

Ford Wang / Project Engineer

Approved by:



*Philip Zhong*

Philip Zhong / Manager

## 2 Contents

|                                                    | <b>Page</b> |
|----------------------------------------------------|-------------|
| <b>1 COVER PAGE.....</b>                           | <b>1</b>    |
| <b>2 CONTENTS .....</b>                            | <b>2</b>    |
| <b>3 REVISION HISTORY .....</b>                    | <b>4</b>    |
| <b>4 GENERAL INFORMATION.....</b>                  | <b>5</b>    |
| 4.1 GENERAL DESCRIPTION OF E.U.T. ....             | 5           |
| 4.2 DETAILS OF E.U.T. ....                         | 5           |
| 4.3 CHANNEL LIST.....                              | 6           |
| 4.4 TEST MODE .....                                | 6           |
| 4.5 TEST FACILITY.....                             | 6           |
| <b>5 TEST SUMMARY .....</b>                        | <b>7</b>    |
| <b>6 EQUIPMENT USED DURING TEST .....</b>          | <b>8</b>    |
| 6.1 EQUIPMENTS LIST .....                          | 8           |
| 6.2 DESCRIPTION OF SUPPORT UNITS .....             | 9           |
| 6.3 MEASUREMENT UNCERTAINTY .....                  | 9           |
| 6.4 TEST EQUIPMENT CALIBRATION .....               | 9           |
| <b>7 RADIATED SPURIOUS EMISSIONS.....</b>          | <b>10</b>   |
| 7.1 EUT OPERATION.....                             | 10          |
| 7.2 TEST SETUP .....                               | 11          |
| 7.3 SPECTRUM ANALYZER SETUP .....                  | 12          |
| 7.4 TEST PROCEDURE .....                           | 13          |
| 7.5 CORRECTED AMPLITUDE & MARGIN CALCULATION ..... | 13          |
| 7.6 SUMMARY OF TEST RESULTS .....                  | 14          |
| <b>8 CONDUCTED SPURIOUS EMISSIONS.....</b>         | <b>17</b>   |
| 8.1 TEST PROCEDURE .....                           | 17          |
| 8.2 TEST RESULT .....                              | 18          |
| <b>9 BAND EDGE MEASUREMENT .....</b>               | <b>21</b>   |
| 9.1 TEST PROCEDURE .....                           | 21          |
| 9.2 TEST RESULT .....                              | 22          |
| <b>10 20 DB BANDWIDTH MEASUREMENT .....</b>        | <b>24</b>   |
| 10.1 TEST PROCEDURE.....                           | 24          |
| 10.2 TEST RESULT .....                             | 24          |
| <b>11 MAXIMUM PEAK OUTPUT POWER .....</b>          | <b>27</b>   |
| 11.1 TEST PROCEDURE.....                           | 27          |
| 11.2 TEST RESULT .....                             | 28          |
| <b>12 HOPPING CHANNEL SEPARATION .....</b>         | <b>31</b>   |
| 12.1 TEST PROCEDURE.....                           | 31          |
| 12.2 TEST RESULT .....                             | 32          |
| <b>13 NUMBER OF HOPPING FREQUENCY.....</b>         | <b>35</b>   |
| 13.1 TEST PROCEDURE.....                           | 35          |
| 13.2 TEST RESULT .....                             | 36          |
| <b>14 DWELL TIME .....</b>                         | <b>37</b>   |
| 14.1 TEST PROCEDURE.....                           | 37          |
| 14.2 TEST RESULT .....                             | 37          |

15    **ANTENNA REQUIREMENT ..... 40**

16    **RF EXPOSURE..... 41**

17    **PHOTOGRAPHS OF TEST SETUP AND EUT..... 42**

### 3 Revision History

| Test report No.           | Date of Receipt sample | Date of Test                | Date of Issue | Purpose   | Comment | Approved |
|---------------------------|------------------------|-----------------------------|---------------|-----------|---------|----------|
| WTD19S12086<br>161W002    | 2019-12-11             | 2019-12-12<br>to 2019-12-25 | 2019-12-26    | original  | -       | Replaced |
| WTD19S12086<br>161W002 V1 | 2019-12-11             | 2019-12-12<br>to 2019-12-25 | 2020-01-02    | Version 1 | Updated | Valid    |

## **4 General Information**

### **4.1 General Description of E.U.T.**

|                    |                   |
|--------------------|-------------------|
| Product:           | Remote Controller |
| Model(s):          | HBZRMLP4          |
| Model Description: | N/A               |
| Hardware Version:  | VB                |
| Software Version:  | VG                |

### **4.2 Details of E.U.T.**

|                       |                    |
|-----------------------|--------------------|
| Operation Frequency:  | 2409~2472MHz       |
| Max. RF output power: | 10.85dBm           |
| Type of Modulation:   | GFSK               |
| Antenna installation: | Fixed antenna      |
| Antenna Gain:         | 2.0dBi             |
| Ratings:              | DC 6V from battery |

### 4.3 Channel List

Normal

| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
|-------------|-----------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| 0           | 2409            | 1           | 2410            | 2           | 2411            | 3           | 2412            |
| 4           | 2413            | 5           | 2414            | 6           | 2415            | 7           | 2416            |
| 8           | 2417            | 9           | 2418            | 10          | 2419            | 11          | 2420            |
| 12          | 2421            | 13          | 2422            | 14          | 2423            | 15          | 2424            |
| 16          | 2425            | 17          | 2426            | 18          | 2427            | 19          | 2428            |
| 20          | 2429            | 21          | 2430            | 22          | 2431            | 23          | 2432            |
| 24          | 2433            | 25          | 2434            | 26          | 2435            | 27          | 2436            |
| 28          | 2437            | 29          | 2438            | 30          | 2439            | 31          | 2440            |
| 32          | 2441            | 33          | 2442            | 34          | 2443            | 35          | 2444            |
| 36          | 2445            | 37          | 2446            | 38          | 2447            | 39          | 2448            |
| 40          | 2449            | 41          | 2450            | 42          | 2451            | 43          | 2452            |
| 44          | 2453            | 45          | 2454            | 46          | 2455            | 47          | 2456            |
| 48          | 2457            | 49          | 2458            | 50          | 2459            | 51          | 2460            |
| 52          | 2461            | 53          | 2462            | 54          | 2463            | 55          | 2464            |
| 56          | 2465            | 57          | 2466            | 58          | 2467            | 59          | 2468            |
| 60          | 2469            | 61          | 2470            | 62          | 2471            | 63          | 2472            |

### 4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests; the worst data were recorded and reported.

| Test mode    | Low channel | Middle channel | High channel |
|--------------|-------------|----------------|--------------|
| Transmitting | 2409MHz     | 2440MHz        | 2472MHz      |

### 4.5 Test Facility

The test facility has a test site registered with the following organizations:

**ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.**

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

**FCC Designation No.: CN1201. Test Firm Registration No.: 523476.**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

## 5 Test Summary

| Test Items                   | Test Requirement                 | Result   |
|------------------------------|----------------------------------|----------|
| Radiated Spurious Emissions  | 15.205(a)<br>15.209<br>15.247(d) | PASS     |
| Conducted Spurious emissions | 15.247(d)                        | PASS     |
| Band edge                    | 15.247(d)<br>15.205(a)           | PASS     |
| Conducted Emission           | 15.207                           | N/A      |
| 20dB Bandwidth               | 15.247(a)(1)                     | PASS     |
| Maximum Peak Output Power    | 15.247(b)(1)                     | PASS     |
| Frequency Separation         | 15.247(a)(1)                     | PASS     |
| Number of Hopping Frequency  | 15.247(a)(1)(iii)                | PASS     |
| Dwell time                   | 15.247(a)(1)(iii)                | PASS     |
| Antenna Requirement          | 15.203                           | Complies |

## 6 Equipment Used during Test

### 6.1 Equipments List

| Conducted Emissions Test Site 1#                              |                            |                                  |              |                 |                       |                      |
|---------------------------------------------------------------|----------------------------|----------------------------------|--------------|-----------------|-----------------------|----------------------|
| Item                                                          | Equipment                  | Manufacturer                     | Model No.    | Serial No.      | Last Calibration Date | Calibration Due Date |
| 1.                                                            | EMI Test Receiver          | R&S                              | ESCI         | 100947          | 2019-09-12            | 2020-09-11           |
| 2.                                                            | LISN                       | R&S                              | ENV216       | 101215          | 2019-09-12            | 2020-09-11           |
| 3.                                                            | Cable                      | Top                              | TYPE16(3.5M) | -               | 2019-09-12            | 2020-09-11           |
| Conducted Emissions Test Site 2#                              |                            |                                  |              |                 |                       |                      |
| Item                                                          | Equipment                  | Manufacturer                     | Model No.    | Serial No.      | Last Calibration Date | Calibration Due Date |
| 1.                                                            | EMI Test Receiver          | R&S                              | ESCI         | 101155          | 2019-09-12            | 2020-09-11           |
| 2.                                                            | LISN                       | SCHWARZBECK                      | NSLK 8128    | 8128-289        | 2019-09-12            | 2020-09-11           |
| 3.                                                            | Limiter                    | York                             | MTS-IMP-136  | 261115-001-0024 | 2019-09-12            | 2020-09-11           |
| 4.                                                            | Cable                      | LARGE                            | RF300        | -               | 2019-09-12            | 2020-09-11           |
| 3m Semi-anechoic Chamber for Radiation Emissions Test site 1# |                            |                                  |              |                 |                       |                      |
| Item                                                          | Equipment                  | Manufacturer                     | Model No.    | Serial No.      | Last Calibration Date | Calibration Due Date |
| 1                                                             | Spectrum Analyzer          | R&S                              | FSP          | 100091          | 2019-04-29            | 2020-04-28           |
| 2                                                             | Active Loop Antenna        | Beijing Dazhi                    | ZN30900A     | -               | 2019-04-09            | 2020-04-08           |
| 3                                                             | Trilog Broadband Antenna   | SCHWARZBECK                      | VULB9163     | 336             | 2019-04-09            | 2020-04-08           |
| 4                                                             | Coaxial Cable (below 1GHz) | Top                              | TYPE16(13M)  | -               | 2019-09-12            | 2020-09-11           |
| 5                                                             | Broad-band Horn Antenna    | SCHWARZBECK                      | BBHA 9120 D  | 667             | 2019-04-09            | 2020-04-08           |
| 6                                                             | Broad-band Horn Antenna    | SCHWARZBECK                      | BBHA 9170    | 335             | 2019-04-09            | 2020-04-08           |
| 7                                                             | Broadband Preamplifier     | COMPLIANCE DIRECTION             | PAP-1G18     | 2004            | 2019-04-13            | 2020-04-12           |
| 8                                                             | Coaxial Cable (above 1GHz) | Top                              | 1GHz-25GHz   | EW02014-7       | 2019-04-13            | 2020-04-12           |
| 3m Semi-anechoic Chamber for Radiation Emissions Test site 2# |                            |                                  |              |                 |                       |                      |
| Item                                                          | Equipment                  | Manufacturer                     | Model No.    | Serial No       | Last Calibration Date | Calibration Due Date |
| 1                                                             | Test Receiver              | R&S                              | ESCI         | 101296          | 2019-04-13            | 2020-04-12           |
| 2                                                             | Trilog Broadband Antenna   | SCHWARZBECK                      | VULB9160     | 9160-3325       | 2019-04-09            | 2020-04-08           |
| 3                                                             | Amplifier                  | Compliance pirection systems inc | PAP-0203     | 22024           | 2019-04-13            | 2020-04-12           |
| 4                                                             | Cable                      | HUBER+SUHNER                     | CBL2         | 525178          | 2019-04-13            | 2020-04-12           |



| RF Conducted Testing |                                 |              |           |            |                       |                      |
|----------------------|---------------------------------|--------------|-----------|------------|-----------------------|----------------------|
| Item                 | Equipment                       | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1.                   | EMC Analyzer<br>(9k~26.5GHz)    | Agilent      | E7405A    | MY45114943 | 2019-09-12            | 2020-09-11           |
| 2.                   | Spectrum Analyzer<br>(9k-6GHz)  | R&S          | FSL6      | 100959     | 2019-09-12            | 2020-09-11           |
| 3.                   | Signal Analyzer<br>(9k~26.5GHz) | Agilent      | N9010A    | MY50520207 | 2019-09-12            | 2020-09-11           |

## 6.2 Description of Support Units

| Equipment | Manufacturer | Model No. | Series No. |
|-----------|--------------|-----------|------------|
| /         | /            | /         | /          |

## 6.3 Measurement Uncertainty

| Parameter                                       | Uncertainty                             |
|-------------------------------------------------|-----------------------------------------|
| Conducted Emission                              | ± 3.64 dB(AC mains 150KHz~30MHz)        |
| Radiated Spurious Emissions                     | ± 5.08 dB (Bilog antenna 30M~1000MHz)   |
|                                                 | ± 4.99 dB (Horn antenna 1000M~25000MHz) |
| Radio Frequency                                 | ± 1 x 10 <sup>-7</sup> Hz               |
| RF Power                                        | ± 0.42 dB                               |
| Dwell time                                      | 1.0%                                    |
| Conducted Spurious Emissions                    | ± 2.76 dB (9kHz~26500MHz)               |
| Confidence interval: 95%. Confidence factor:k=2 |                                         |

## 6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

## 7 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.205 & 15.209 & 15.247

Test Method: ANSI C63.10: 2013

Test Result: PASS

Measurement Distance: 3m

Limit:

| Frequency<br>(MHz) | Field Strength |                 | Field Strength Limit at 3m Measurement Dist |                                |
|--------------------|----------------|-----------------|---------------------------------------------|--------------------------------|
|                    | uV/m           | Distance<br>(m) | uV/m                                        | dBuV/m                         |
| 0.009 ~ 0.490      | 2400/F(kHz)    | 300             | 10000 * 2400/F(kHz)                         | $20\log^{(2400/F(kHz))} + 80$  |
| 0.490 ~ 1.705      | 24000/F(kHz)   | 30              | 100 * 24000/F(kHz)                          | $20\log^{(24000/F(kHz))} + 40$ |
| 1.705 ~ 30         | 30             | 30              | 100 * 30                                    | $20\log^{(30)} + 40$           |
| 30 ~ 88            | 100            | 3               | 100                                         | $20\log^{(100)}$               |
| 88 ~ 216           | 150            | 3               | 150                                         | $20\log^{(150)}$               |
| 216 ~ 960          | 200            | 3               | 200                                         | $20\log^{(200)}$               |
| Above 960          | 500            | 3               | 500                                         | $20\log^{(500)}$               |

### 7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX Transmitting mode, the test data were shown in the report.


## 7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10: 2013.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



**7.3 Spectrum Analyzer Setup**

Below 30MHz

Sweep Speed ..... Auto  
IF Bandwidth.....10kHz  
Video Bandwidth.....10kHz  
Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed ..... Auto  
Detector .....PK  
Resolution Bandwidth.....100kHz  
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed ..... Auto  
Detector .....PK  
Resolution Bandwidth.....1MHz  
Video Bandwidth.....3MHz  
Detector .....Ave.  
Resolution Bandwidth.....1MHz  
Video Bandwidth.....10Hz

## 7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the Z position. So the data shown was the Z position only.

## 7.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

## 7.6 Summary of Test Results

### Test Frequency: 9KHz~30MHz

Remark: only the worst data (GFSK modulation Low channel mode) were reported

| Frequency | Measurement results dB $\mu$ V @3m | Detector PK/QP | Correct factor dB/m | Extrapolation factor dB | Measurement results (calculated) dB $\mu$ V/m @30m | Limits dB $\mu$ V/m @30m | Margin dB |
|-----------|------------------------------------|----------------|---------------------|-------------------------|----------------------------------------------------|--------------------------|-----------|
| (MHz)     | Measurement results                | Detector       | Correct factor      | Extrapolation factor    | Measurement results (calculated)                   | Limits                   | Margin    |
| 6.021     | 25.34                              | QP             | 21.84               | 40.00                   | 7.18                                               | 29.54                    | -22.36    |
| 15.730    | 25.36                              | QP             | 21.35               | 40.00                   | 6.71                                               | 29.54                    | -22.83    |
| 25.680    | 25.18                              | QP             | 20.67               | 40.00                   | 5.85                                               | 29.54                    | -23.69    |

### Test Frequency: 30MHz ~ 8GHz

Remark: only the worst data (GFSK modulation mode) were reported.

| Frequency        | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | Limit          | Margin |
|------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|----------------|--------|
|                  |                  |             |                  | Height     | Polar |                  |                     |                |        |
| (MHz)            | (dB $\mu$ V)     | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dB $\mu$ V/m)      | (dB $\mu$ V/m) | (dB)   |
| GFSK Low Channel |                  |             |                  |            |       |                  |                     |                |        |
| 268.32           | 36.89            | QP          | 342              | 1.5        | H     | -13.35           | 23.54               | 46.00          | -22.46 |
| 268.32           | 41.33            | QP          | 285              | 1.0        | V     | -13.35           | 27.98               | 46.00          | -18.02 |
| 4812.00          | 46.15            | PK          | 253              | 1.4        | V     | -1.06            | 45.09               | 74.00          | -28.91 |
| 4812.00          | 43.52            | Ave         | 253              | 1.4        | V     | -1.06            | 42.46               | 54.00          | -11.54 |
| 7218.00          | 40.62            | PK          | 142              | 1.1        | H     | 1.33             | 41.95               | 74.00          | -32.05 |
| 7218.00          | 35.37            | Ave         | 142              | 1.1        | H     | 1.33             | 36.70               | 54.00          | -17.30 |
| 2314.55          | 46.27            | PK          | 240              | 2.0        | V     | -13.19           | 33.08               | 74.00          | -40.92 |
| 2314.55          | 39.15            | Ave         | 240              | 2.0        | V     | -13.19           | 25.96               | 54.00          | -28.04 |
| 2361.82          | 42.14            | PK          | 343              | 1.5        | H     | -13.14           | 29.00               | 74.00          | -45.00 |
| 2361.82          | 37.68            | Ave         | 343              | 1.5        | H     | -13.14           | 24.54               | 54.00          | -29.46 |
| 2493.57          | 44.74            | PK          | 64               | 1.9        | V     | -13.08           | 31.66               | 74.00          | -42.34 |
| 2493.57          | 36.87            | Ave         | 64               | 1.9        | V     | -13.08           | 23.79               | 54.00          | -30.21 |

| Frequency           | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | Limit    | Margin |
|---------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|----------|--------|
|                     |                  |             |                  | Height     | Polar |                  |                     |          |        |
| (MHz)               | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m) | (dB)   |
| GFSK Middle Channel |                  |             |                  |            |       |                  |                     |          |        |
| 268.32              | 36.33            | QP          | 320              | 1.5        | H     | -13.35           | 22.98               | 46.00    | -23.02 |
| 268.32              | 41.83            | QP          | 325              | 1.2        | V     | -13.35           | 28.48               | 46.00    | -17.52 |
| 4882.00             | 45.13            | PK          | 105              | 1.8        | V     | -0.62            | 44.51               | 74.00    | -29.49 |
| 4882.00             | 44.66            | Ave         | 105              | 1.8        | V     | -0.62            | 44.04               | 54.00    | -9.96  |
| 7323.00             | 41.43            | PK          | 131              | 1.5        | H     | 2.21             | 43.64               | 74.00    | -30.36 |
| 7323.00             | 35.64            | Ave         | 131              | 1.5        | H     | 2.21             | 37.85               | 54.00    | -16.15 |
| 2339.33             | 46.49            | PK          | 117              | 1.1        | V     | -13.19           | 33.30               | 74.00    | -40.70 |
| 2339.33             | 37.30            | Ave         | 117              | 1.1        | V     | -13.19           | 24.11               | 54.00    | -29.89 |
| 2383.59             | 43.32            | PK          | 234              | 1.5        | H     | -13.14           | 30.18               | 74.00    | -43.82 |
| 2383.59             | 38.20            | Ave         | 234              | 1.5        | H     | -13.14           | 25.06               | 54.00    | -28.94 |
| 2494.07             | 43.64            | PK          | 283              | 1.2        | V     | -13.08           | 30.56               | 74.00    | -43.44 |
| 2494.07             | 37.17            | Ave         | 283              | 1.2        | V     | -13.08           | 24.09               | 54.00    | -29.91 |

| Frequency         | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | Limit    | Margin |
|-------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|----------|--------|
|                   |                  |             |                  | Height     | Polar |                  |                     |          |        |
| (MHz)             | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m) | (dB)   |
| GFSK High Channel |                  |             |                  |            |       |                  |                     |          |        |
| 268.32            | 36.85            | QP          | 289              | 1.2        | H     | -13.35           | 23.50               | 46.00    | -22.50 |
| 268.32            | 42.68            | QP          | 286              | 2.0        | V     | -13.35           | 29.33               | 46.00    | -16.67 |
| 4950.00           | 46.02            | PK          | 140              | 1.9        | V     | -0.24            | 45.78               | 74.00    | -28.22 |
| 4950.00           | 45.94            | Ave         | 140              | 1.9        | V     | -0.24            | 45.70               | 54.00    | -8.30  |
| 7425.00           | 42.15            | PK          | 357              | 1.1        | H     | 2.84             | 44.99               | 74.00    | -29.01 |
| 7425.00           | 37.10            | Ave         | 357              | 1.1        | H     | 2.84             | 39.94               | 54.00    | -14.06 |
| 2331.04           | 46.66            | PK          | 257              | 1.9        | V     | -13.19           | 33.47               | 74.00    | -40.53 |
| 2331.04           | 39.54            | Ave         | 257              | 1.9        | V     | -13.19           | 26.35               | 54.00    | -27.65 |
| 2387.06           | 44.25            | PK          | 151              | 1.3        | H     | -13.14           | 31.11               | 74.00    | -42.89 |
| 2387.06           | 37.64            | Ave         | 151              | 1.3        | H     | -13.14           | 24.50               | 54.00    | -29.50 |
| 2497.64           | 43.29            | PK          | 276              | 1.5        | V     | -13.08           | 30.21               | 74.00    | -43.79 |
| 2497.64           | 37.67            | Ave         | 276              | 1.5        | V     | -13.08           | 24.59               | 54.00    | -29.41 |

**Test Frequency: 8GHz~25GHz**

The measurements were more than 20 dB below the limit and not recorded



## 8 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;

2. Set the spectrum analyzer:

Below 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

Above 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto


Detector function = peak, Trace = max hold

8.2    Test Result


9KHz - 30MHz


GFSK

Low Channel




Middle Channel






30MHz – 25GHz  
GFSK Low Channel

Fundamental




## GFSK Middle Channel

Fundamental



## GFSK High Channel

Fundamental





## 9 Band Edge Measurement



|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Method:      | ANSI C63.10: 2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Limit:       | Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |
| Test Mode:        | Transmitting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

### 9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold

9.2 Test Result





## 10 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Mode: Test in fixing operating frequency at low, Middle, high channel.

### 10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz


### 10.2 Test Result

| Modulation | Test Channel | Bandwidth(MHz) |
|------------|--------------|----------------|
| GFSK       | Low          | 0.195          |
| GFSK       | Middle       | 0.211          |
| GFSK       | High         | 0.206          |





Test plots

GFSK Low Channel



GFSK Middle Channel





## 11 Maximum Peak Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Limit: Regulation 15.247 (a)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater 0.125 watts..

Test mode: Test in fixing frequency transmitting mode.

### 11.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer:
  - a) Use the following spectrum analyzer settings:
    - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
    - 2) RBW  $\geq$  20 dB bandwidth of the emission being measured.
    - 3) VBW  $\geq$  RBW.
    - 4) Sweep: Auto.
    - 5) Detector function: Peak.
    - 6) Trace: Max hold.
  - b) Allow trace to stabilize.
  - c) Use the marker-to-peak function to set the marker to the peak of the emission.
  - d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
  - e) A plot of the test results and setup description shall be included in the test report.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

## 11.2 Test Result


| Modulation | Test Channel | Output Power<br>(dBm) | Limit (dBm) |
|------------|--------------|-----------------------|-------------|
| GFSK       | Low          | 10.85                 | 30          |
| GFSK       | Middle       | 10.53                 | 30          |
| GFSK       | High         | 10.30                 | 30          |


Test plots

GFSK Low Channel



GFSK Middle Channel





## 12 Hopping Channel Separation

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Limit: Regulation 15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with power no greater than 0.125W.

Test Mode: Test in hopping transmitting operating mode.

### 12.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer:
  - a) Span: Wide enough to capture the peaks of two adjacent channels.
  - b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
  - c) Video (or average) bandwidth (VBW)  $\geq$  RBW.
  - d) Sweep: Auto.
  - e) Detector function: Peak.
  - f) Trace: Max hold.
  - g) Allow the trace to stabilize.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.


## 12.2 Test Result

| Modulation | Test Channel | Separation<br>(MHz) | Limit(MHz) | Result |
|------------|--------------|---------------------|------------|--------|
| GFSK       | Low          | 0.998               | 0.195      | PASS   |
| GFSK       | Middle       | 1.002               | 0.211      | PASS   |
| GFSK       | High         | 0.998               | 0.206      | PASS   |





Test plots

GFSK Low Channel



GFSK Middle Channel





## 13 Number of Hopping Frequency

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013


Test Limit: Regulation 15.247 (a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test Mode: Test in hopping transmitting operating mode.

### 13.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer:
  - a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
  - b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
  - c) VBW  $\geq$  RBW.
  - d) Sweep: Auto.
  - e) Detector function: Peak.
  - f) Trace: Max hold.
  - g) Allow the trace to stabilize..
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

13.2 Test Result



## 14 Dwell Time

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Limit: Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Mode: Test in hopping transmitting operating mode.

### 14.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. Centred on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).



### 14.2 Test Result

| Modulation | Channel | pulse time(ms) | Dwell Time(s) | Limits(s) |
|------------|---------|----------------|---------------|-----------|
| GFSK       | Low     | 22.500         | 0.122         | 0.4       |
|            | middle  | 22.500         | 0.122         | 0.4       |
|            | High    | 22.500         | 0.122         | 0.4       |

Remark: The manufacturer claims the device trasmitting every 37ms ,

Dwell Time =  $1000/37/64/2*0.4*64*(MkrDelta)/1000$






## 15 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT has one Fixed antenna, the gain is 2.0 dBi. meets the requirements of FCC 15.203.





## **16 RF Exposure**

Remark: refer to SAR report: WTD19S12086161W001

## **17 Photographs of test setup and EUT.**

Note: Please refer to appendix: Appendix-HBZRMLP4-Photos.

=====End of Report=====