



## CFR 47 FCC PART 15 SUBPART C

### TEST REPORT

*For*

**Séura Outdoor Entertainment**

**MODEL NUMBER: SHD2-75**

**FCC ID: 2AVE3SHD2-75A**

**PROJECT NUMBER: 4789257350**

**REPORT NUMBER: 4789257350-10**

**ISSUE DATE: Feb. 26, 2020**

*Prepared for*

**K-tronics (Su Zhou) Technology Co., LTD**

*Prepared by*

**UL-CCIC COMPANY LIMITED**

**No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China**

**Tel: +86 512 6808 6400**

**Fax: +86 512 6808 4099**

**Website: [www.ul.com](http://www.ul.com)**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	02/26/2020	Initial Issue	

Summary of Test Results			
Clause	Test Items	FCC/IC Rules	Test Results
1	6dB Bandwidth	FCC Part 15.247 (a) (2)	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3)	Pass
3	Power Spectral Density	FCC Part 15.247 (e)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d)	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205	Pass
6	Conducted Emission Test For AC Power Port	FCC Part 15.207	N/A
7	Antenna Requirement	FCC Part 15.203	Pass

Remark:  
The measurement result for the sample received is <Pass> according to < ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15C> when <Accuracy Method> decision rule is applied.

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>5</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>7</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> .....	7
4.2. <i>MEASUREMENT UNCERTAINTY</i> .....	7
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>8</b>
5.1. <i>DESCRIPTION OF EUT</i> .....	8
5.2. <i>MAXIMUM OUTPUT POWER</i> .....	8
5.3. <i>CHANNEL LIST</i> .....	8
5.4. <i>TEST CHANNEL CONFIGURATION</i> .....	8
5.5. <i>THE WORSE CASE CONFIGURATIONS</i> .....	9
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> .....	9
5.7. <i>THE WORSE CASE CONFIGURATIONS</i> .....	9
5.8. <i>DESCRIPTION OF TEST SETUP</i> .....	10
<b>6. MEASURING INSTRUMENT AND SOFTWARE USED .....</b>	<b>11</b>
<b>7. MEASUREMENT METHODS .....</b>	<b>12</b>
<b>8. ANTENNA PORT TEST RESULTS .....</b>	<b>13</b>
8.1. <i>ON TIME AND DUTY CYCLE</i> .....	13
8.2. <i>6 dB DTS BANDWIDTH</i> .....	15
8.3. <i>PEAK CONDUCTED OUTPUT POWER</i> .....	18
8.4. <i>POWER SPECTRAL DENSITY</i> .....	21
8.5. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS</i> .....	24
<b>9. RADIATED TEST RESULTS .....</b>	<b>39</b>
9.1. <i>RESTRICTED BANDEDGE</i> .....	45
9.2. <i>SPURIOUS EMISSIONS (1~18GHz)</i> .....	50
9.3. <i>SPURIOUS EMISSIONS (18~26GHz)</i> .....	56
9.4. <i>SPURIOUS EMISSIONS (0.03 ~ 1 GHz)</i> .....	58
9.5. <i>SPURIOUS EMISSIONS BELOW 30M</i> .....	60
<b>10. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>63</b>
<b>11. ANTENNA REQUIREMENTS .....</b>	<b>66</b>

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: K-tronics (Su Zhou) Technology Co., LTD  
Address: No.1088, Dajing Road, Economic and Technological Development Zone Wujiang District, Suzhou, Jiangsu, China

### Manufacturer Information

Company Name: K-tronics (Su Zhou) Technology Co., LTD  
Address: No.1088, Dajing Road, Economic and Technological Development Zone Wujiang District, Suzhou, Jiangsu, China

### EUT Description

EUT Name: Séura Outdoor Entertainment  
Model: SHD2-75  
Sample Status: Normal  
Sample Received Date: Dec. 25, 2019  
Date of Tested: Dec. 26, 2019 ~ Jan 14, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Tested By:

*Tom Tang*

---

Tom Tang  
Engineer Project Associate

Reviewed By:

*Chris Zhong*

---

Chris Zhong  
Senior Project Engineer

Authorized By:

*Scholl Zhang*

---

Scholl Zhang  
Laboratory Leader

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4829.01)</b> <b>UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA.</b></p> <p><b>FCC (FCC Designation No.: CN1247)</b> <b>UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</b></p> <p><b>IC (IC Designation No.: 25056)</b> <b>UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</b></p>
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.00dB
Radiation Emission test(include Fundamental emission) (9kHz-30MHz)	3.32dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	3.27dB
Radiation Emission test (1GHz to 26GHz)( include Fundamental emission)	3.80dB (1GHz-18Gz) 4.11dB (18GHz-26.5Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

Equipment	Séura Outdoor Entertainment				
Model Name	SHD2-75				
Product Description	Operation Frequency	2402 MHz ~ 2480 MHz			
	Modulation Type	Data Rate			
	GFSK	1Mbps			
Power Supply	AC 120V				
Bluetooth Version	LE				
Hardware Version	V1.0				

### 5.2. MAXIMUM OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Max Output Power(dBm)
BLE	2402-2480	0-39[40]	1.66

### 5.3. CHANNEL LIST

Channel	Frequency (MHz)						
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460		
8	2418	19	2440	30	2462		
9	2420	20	2442	31	2464		
10	2422	21	2444	32	2468		

### 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 0, CH 19, CH 39	2402MHz, 2440MHz, 2480MHz

## 5.5. THE WORSE CASE CONFIGURATIONS

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		Tera Term & QRCT		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH 00	CH 19	CH 39
GFSK	1	37	37	37

## 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2402-2480	Internal Antenna	2.99

Test Mode	Transmit and Receive Mode	Description
BLE	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

## 5.7. THE WORSE CASE CONFIGURATIONS

For the product, there is only one transmission antenna, so only the worst data for the antenna1 is recorded in the report.

Worst-case data rates as provided by the client were:

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BLE	DTS	GFSK	1Mbit/s

## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	Laptop	ThinkPad	E550c	N/A

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB to TTL	USB to TTL	USB	1	N/A


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	N/A	N/A	N/A	N/A

### TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

### SETUP DIAGRAM FOR TESTS





## 6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	126700	2018-12-13	2019-12-12	2020-12-11
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	126701	2018-12-13	2019-12-12	2020-12-11
<input checked="" type="checkbox"/>	Artificial Mains Networks	R&S	ENY81	126711	2018-12-13	2019-12-12	2020-12-11
Software							
Used	Description		Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance		R&S	EMC32	Ver. 9.25		
Radiated Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9010B	MY57110128	2018-05-30	2019-05-29	2020-05-28
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR26	1267603	2018-12-13	2019-12-12	2020-12-11
<input checked="" type="checkbox"/>	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	513-265	2018-06-17	2019-06-16	2020-06-15
<input checked="" type="checkbox"/>	Receiver Antenna (30MHz-1GHz)	SunAR RF Motion	JB1	126704	N/A	2019-01-28	2022-01-27
<input checked="" type="checkbox"/>	Receiver Antenna (1GHz-18GHz)	R&S	HF907	126705	2018-01-27	2019-01-26	2020-01-26
<input checked="" type="checkbox"/>	Receiver Antenna (18GHz-26.5GHz)	Schwarzbeck	BBHA9170	126706	2018-02-07	2019-02-06	2020-02-05
<input checked="" type="checkbox"/>	Receiver Antenna (26.5GHz-40GHz)	TOYO	HAP 26-40W	00000012	2018-07-25	2019-07-24	2020-07-23
<input checked="" type="checkbox"/>	Pre-amplification (To 1GHz)	R&S	SCU-03D	134666	2018-02-07	2019-02-06	2020-02-05
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	Compliance Direction System Inc.	PAP-1G18-50	14140-13467	N/A	2019-03-18	2020-03-17
<input checked="" type="checkbox"/>	Pre-amplification (To 26.5GHz)	R&S	SCU-26D	134668	2018-02-07	2019-02-06	2020-02-05
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	1	2018-05-30	2019-05-29	2020-05-28
<input checked="" type="checkbox"/>	Highpass Filter	Wainwright	WHKX10-2700-3000-18000-40SS	2	2018-05-30	2019-05-29	2020-05-28
Software							
Used	Description		Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance		Tonscend	JS32	V1.0		
Other instruments							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Next Cal.	
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9010B	MY57110128	2018-05-30	2019-05-29	2020-05-28
<input checked="" type="checkbox"/>	Power Sensor	Keysight	U2021XA	MY57110002	2018-06-13	2019-06-12	2020-06-11

## 7. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6dB Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Peak Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.1.3/8.3.2.3
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7

## 8. ANTENNA PORT TEST RESULTS

### 8.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	20°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (KHz)	Final setting For VBW (KHz)
BLE	0.379	0.625	0.6064	60.64%	2.17	2.64	3


Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.



## 8.2. 6 dB DTS BANDWIDTH

### LIMITS

FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(a)(2)	6dB Bandwidth	>= 500KHz	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Bandwidth :100K
VBW	For 6dB Bandwidth : $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP






### TEST ENVIRONMENT

Temperature	20°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

RESULTS

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
CH00	2402	0.7040	500	Pass
CH19	2440	0.7066	500	Pass
CH39	2480	0.7006	500	Pass





### 8.3. PEAK CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak Output Power	1 watt or 30dBm (See note1)	2400-2483.5

**Note:**


1. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.

Allow trace to fully stabilize and use peak marker function to determine the peak amplitude level.

#### TEST SETUP




#### TEST ENVIRONMENT



Temperature	20°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

## RESULTS

Test Channel	Frequency	Maximum Conducted Output Power(PK)	Result
	(MHz)	(dBm)	
CH00	2402	0.89	PASS
CH19	2440	1.66	PASS
CH39	2480	1.16	PASS

## Test Graphs:





## 8.4. POWER SPECTRAL DENSITY

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm/3 kHz (See note1)	2400-2483.5
<b>Note:</b> 1. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.			

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST SETUP





### TEST ENVIRONMENT

Temperature	20°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

**RESULTS**

Test Channel	Frequency	Power Spectral Density	Limit	Result
	(MHz)	(dBm/100kHz)	(dBm/3kHz)	
CH00	2402 MHz	-0.37	8	PASS
CH19	2440 MHz	0.40	8	PASS
CH39	2480 MHz	-0.05	8	PASS

**Test Graphs:**



## 8.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100K
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100K
VBW	$\geq 3 \times$ RBW
measurement points	$\geq$ span/RBW
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

TEST SETUPTEST ENVIRONMENT

Temperature	20°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

Part I: Conducted BandedgeRESULTS

Test Mode	Test Channel	Verdict																																																								
BLE	CH39	PASS																																																								
<table border="1"> <thead> <tr> <th>Mode</th> <th>Trace</th> <th>Scale</th> <th>X</th> <th>Y</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.479 990 0 GHz</td> <td>0.2340 dBm</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.483 500 0 GHz</td> <td>-44.46 dBm</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>f</td> <td>2.500 000 0 GHz</td> <td>-43.79 dBm</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.488 022 5 GHz</td> <td>-41.50 dBm</td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>			Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.479 990 0 GHz	0.2340 dBm			2	N	1	f	2.483 500 0 GHz	-44.46 dBm			3	N	1	f	2.500 000 0 GHz	-43.79 dBm			4	N	1	f	2.488 022 5 GHz	-41.50 dBm			5								6							
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																																																			
1	N	1	f	2.479 990 0 GHz	0.2340 dBm																																																					
2	N	1	f	2.483 500 0 GHz	-44.46 dBm																																																					
3	N	1	f	2.500 000 0 GHz	-43.79 dBm																																																					
4	N	1	f	2.488 022 5 GHz	-41.50 dBm																																																					
5																																																										
6																																																										

## Part II: Conducted Emission


### Test Plots

Test Mode	Channel	Verdict
BLE	CH00	PASS




## Puw test Plot


## LCH SPURIOUS EMISSION\_30MHz~3GHz




## LCH SPURIOUS EMISSION\_3GHz~5GHz



## LCH SPURIOUS EMISSION\_5GHz~10GHz




## LCH SPURIOUS EMISSION\_10GHz~15GHz



LCH SPURIOUS EMISSION\_15GHz~25GHz



Test Mode	Channel	Verdict
BLE	CH19	PASS




## MCH SPURIOUS EMISSION\_3GHz~5GHz




MCH SPURIOUS EMISSION\_5GHz~10GHz



MCH SPURIOUS EMISSION\_10GHz~15GHz




## MCH SPURIOUS EMISSION\_15GHz~25GHz



Test Mode	Channel	Verdict
BLE	CH39	PASS





Puw test Plot




## HCH SPURIOUS EMISSION\_3GHz~5GHz





## HCH SPURIOUS EMISSION\_15GHz~25GHz



## 9. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.



Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

FCC Restricted bands of operation:


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

## ABOVE 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 8.1.ON TIME AND DUTY CYCLE.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions:



Note: For all radiated test, EUT can only work in one axis(Z axis), so only this case (Z axis) data recorded in the report.


#### TEST ENVIRONMENT

Temperature	20°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

## 9.1. RESTRICTED BANDEDGE


Test Result Table

Test Mode	Channel	Puw(dBm)	Verdict
BLE	CH00	<Limit	PASS
	CH39	<Limit	PASS

**RESTRICTED BANDEDGE (CH00, HORIZONTAL)**


No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2363.8972	44.88	13.79	58.67	74.00	-15.33	peak
		29.47	13.79	43.26	54.00	-10.74	average
2	2390.0000	39.00	14.09	53.09	74.00	-20.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (CH00, VERTICAL)**


No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2370.4608	43.67	13.86	57.53	74.00	-16.47	peak
		29.39	13.86	43.25	54.00	-10.75	average
2	2390.0000	37.42	14.09	51.51	74.00	-22.49	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (CH39, HORIZONTAL)**

No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.5000	38.65	13.88	52.53	74.00	-21.47	peak
2	2509.6171	40.66	14.22	54.88	74.00	-19.12	peak
		27.40	14.22	41.62	54.00	-12.38	average

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (CH39, VERTICAL)**



No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.5000	38.04	13.88	51.92	74.00	-22.08	peak
2	2514.9415	40.14	14.22	54.36	74.00	-19.64	peak
		30.14	14.22	44.36	54.00	-9.64	average

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 9.2. SPURIOUS EMISSIONS (1~18GHz)

### HARMONICS AND SPURIOUS EMISSIONS (CH00, HORIZONTAL)




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
							(MHz) (dBuV/m) (dB) (dBuV/m) (dBuV/m) (dB)
1	1535.8170	55.49	-5.68	49.81	74.00	-24.19	peak
2	1834.8544	51.23	-3.89	47.34	74.00	-26.66	peak
3	2108.6386	50.30	-2.56	47.74	74.00	-26.26	peak
4	3191.2739	45.70	2.01	47.71	74.00	-26.29	peak
5	17184.2730	36.08	19.57	55.65	74.00	-18.35	peak
		26.16	19.57	45.73	54.00	-8.27	average
6	17518.0648	36.36	19.67	56.03	74.00	-17.97	peak
		26.50	19.67	46.17	54.00	-7.83	average

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. For below 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for BPF losses.
5. For above 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### HARMONICS AND SPURIOUS EMISSIONS (CH00, VERTICAL)




No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
							PK AV
1	1535.8170	56.40	-5.68	50.72	74.00	-23.28	peak
2	1842.3553	54.86	-3.85	51.01	74.00	-22.99	peak
3	3195.0244	46.88	1.95	48.83	74.00	-25.17	peak
4	13173.1466	38.75	14.24	52.99	74.00	-21.01	peak
5	17137.3922	37.01	19.30	56.31	74.00	-17.69	peak
		26.48	19.30	45.78	54.00	-8.22	average
6	17626.8284	38.72	19.09	57.81	74.00	-16.19	peak
		28.64	19.09	47.73	54.00	-6.27	average

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. For below 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for BPF losses.
5. For above 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### HARMONICS AND SPURIOUS EMISSIONS (CH19, HORIZONTAL)




No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
							PK AV
1	1535.8170	55.88	-5.68	50.20	74.00	-23.80	peak
2	2096.3870	50.49	-2.55	47.94	74.00	-26.06	peak
3	3847.6060	43.83	3.73	47.56	74.00	-26.44	peak
4	16122.8904	38.79	16.72	55.51	74.00	-18.49	peak
		28.29	16.72	45.01	54.00	-8.99	
5	16979.8725	35.61	20.65	56.26	74.00	-17.74	peak
		25.86	20.65	46.51	54.00	-7.49	average
6	17521.8152	35.50	19.65	55.15	74.00	-18.85	peak
		25.72	19.65	45.37	54.00	-8.63	average

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. For below 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for BPF losses.
5. For above 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### HARMONICS AND SPURIOUS EMISSIONS (CH19, VERTICAL)




No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
							PK AV
1	1535.8170	57.06	-5.68	51.38	74.00	-22.62	peak
2	2090.6363	50.33	-2.63	47.70	74.00	-26.30	peak
3	3191.2739	47.70	2.01	49.71	74.00	-24.29	peak
4	7601.8252	38.52	8.98	47.50	74.00	-26.50	peak
5	17034.2543	36.84	19.82	56.66	74.00	-17.34	peak
		26.99	19.82	46.81	54.00	-7.19	average
6	17604.3255	36.50	19.09	55.59	74.00	-18.41	peak
		26.81	19.09	45.90	54.00	-8.10	average

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. For below 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for BPF losses.
5. For above 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### HARMONICS AND SPURIOUS EMISSIONS (CH39, HORIZONTAL)




No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
							PK AV
1	1535.8170	55.64	-5.68	49.96	74.00	-24.04	peak
2	1849.1061	52.28	-3.67	48.61	74.00	-25.39	peak
3	3183.7730	45.16	2.14	47.30	74.00	-26.70	peak
4	14313.2892	37.72	15.69	53.41	74.00	-20.59	peak
5	17026.7533	37.28	20.20	57.48	74.00	-16.52	peak
		27.19	20.20	47.39	54.00	-6.61	average
6	17598.6998	37.40	19.51	56.91	74.00	-17.09	peak
		27.48	19.51	46.99	54.00	-7.01	average

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. For below 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for BPF losses.
5. For above 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### HARMONICS AND SPURIOUS EMISSIONS (CH39, VERTICAL)




No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
							PK AV
1	1535.8170	56.97	-5.68	51.29	74.00	-22.71	peak
2	1845.8557	55.53	-3.75	51.78	74.00	-22.22	peak
3	2099.3874	50.24	-2.51	47.73	74.00	-26.27	peak
4	4198.2748	44.04	4.45	48.49	74.00	-25.51	peak
5	17030.5038	35.18	20.18	55.36	74.00	-18.64	peak
		24.99	20.18	45.17	54.00	-8.83	average
6	17638.0798	38.92	19.40	58.32	74.00	-15.68	peak
		28.72	19.40	48.12	54.00	-5.88	average

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. For below 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for BPF losses.
5. For above 3GHz part, Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


### 9.3. SPURIOUS EMISSIONS (18~26GHz)

#### SPURIOUS EMISSIONS (CH19, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	18505.8006	47.51	-0.94	46.57	74.00	-27.43	peak
2	19599.8600	43.99	-0.69	43.30	74.00	-30.70	peak
3	21500.6501	41.88	-0.52	41.36	74.00	-32.64	peak
4	22616.8117	44.67	0.93	45.60	74.00	-28.40	peak
5	24653.6154	43.07	-0.37	42.70	74.00	-31.30	peak
6	25540.2540	43.04	0.92	43.96	74.00	-30.04	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

SPURIOUS EMISSIONS (CH19, WORST-CASE CONFIGURATION, VERTICAL)


No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19362.6863	44.15	-0.83	43.32	74.00	-30.68	peak
2	19814.9315	43.77	-0.62	43.15	74.00	-30.85	peak
3	21258.3758	41.97	-0.75	41.22	74.00	-32.78	peak
4	22726.4726	42.67	1.02	43.69	74.00	-30.31	peak
5	24602.6103	42.46	-0.44	42.02	74.00	-31.98	peak
6	25484.9985	41.02	0.82	41.84	74.00	-32.16	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All constructions and test modes have been tested, only the worst data record in the report


## 9.4. SPURIOUS EMISSIONS (0.03 ~ 1 GHz)

### SPURIOUS EMISSIONS (CH19, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.2611	7.86	26.35	34.21	40.00	-5.79	QP
2	39.3129	10.54	21.21	31.75	40.00	-8.25	QP
3	86.7507	17.16	14.35	31.51	40.00	-8.49	QP
4	191.9092	12.93	18.60	31.53	43.50	-11.97	QP
5	255.3535	19.16	19.00	38.16	46.00	-7.84	QP
6	514.4664	9.25	25.85	35.10	46.00	-10.90	QP

Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (CH19, WORST-CASE CONFIGURATION, VERTICAL)**


No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.4334	9.86	26.88	36.74	40.00	-3.26	QP
2	30.8761	9.81	26.59	36.40	40.00	-3.60	QP
3	68.8039	22.51	14.66	37.17	40.00	-2.83	Peak
4	145.9266	12.12	19.58	31.70	43.50	-11.80	Peak
5	211.1171	13.99	18.28	32.27	43.50	-11.23	Peak
6	631.6542	6.38	27.16	33.54	46.00	-12.46	Peak


Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Note: All constructions and test modes have been tested, only the worst data record in the report.

## 9.5. SPURIOUS EMISSIONS BELOW 30M

### SPURIOUS EMISSIONS (CH19, WORST-CASE CONFIGURATION, Face-on)


9kHz ~ 150kHz



No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0102	38.73	-61.25	-22.52	47.45	-69.97	peak
2	0.0252	29.94	-60.99	-31.05	39.57	-70.62	peak
3	0.0506	27.08	-61.17	-34.09	33.52	-67.61	peak
4	0.0759	24.55	-61.53	-36.98	30.00	-66.98	peak
5	0.1012	23.15	-60.87	-37.72	27.50	-65.22	peak
6	0.1270	21.62	-61.18	-39.56	25.53	-65.09	peak

Note:


1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report

150kHz ~ 490kHz


No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1873	31.58	-61.26	-29.68	22.15	-51.83	peak
2	0.2284	26.62	-61.05	-34.43	20.43	-54.86	peak
3	0.2503	26.58	-60.94	-34.36	19.63	-53.99	peak
4	0.2780	26.01	-60.92	-34.91	18.72	-53.63	peak
5	0.3770	32.44	-60.83	-28.39	16.08	-44.47	peak
6	0.4317	24.18	-60.78	-36.60	14.63	-51.23	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report

490kHz ~ 30MHz


No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5608	25.73	-20.75	4.98	32.63	-27.65	peak
2	1.3134	14.61	-20.44	-5.83	25.24	-31.07	peak
3	1.7974	10.15	-20.36	-10.21	29.54	-39.75	peak
4	4.7251	8.04	-20.32	-12.28	29.54	-41.82	peak
5	9.9932	8.52	-18.98	-10.46	29.54	-40.00	peak
6	19.9007	9.41	-17.47	-8.06	29.54	-37.60	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report

Note: All constructions and test modes and channels have been tested, only the worst data record in the report.


## 10. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

Please refer to CFR 47 FCC §15.207 (a)

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE



The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 7 and 13 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST ENVIRONMENT

Temperature	20°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V


## TEST RESULTS

### LINE N RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)



## Final Result

Frequency (MHz)	QuasiPeak (dB(iV))	Average (dB(iV))	Limit (dB(iV))	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
1.112663	---	27.31	46.00	18.70	1000.0	9.000	N	OFF	9.7
1.112663	48.91	---	56.00	7.09	1000.0	9.000	N	OFF	9.7
2.478300	46.32	---	56.00	9.68	1000.0	9.000	N	OFF	9.5
4.851375	45.82	---	56.00	10.18	1000.0	9.000	N	OFF	9.8
13.209375	50.79	---	60.00	9.21	1000.0	9.000	N	OFF	9.8
14.425763	---	36.37	50.00	13.63	1000.0	9.000	N	OFF	9.8
15.410813	---	38.69	50.00	11.31	1000.0	9.000	N	OFF	9.7
15.448125	---	38.91	50.00	11.09	1000.0	9.000	N	OFF	9.7
15.448125	53.17	---	60.00	6.83	1000.0	9.000	N	OFF	9.7
15.574988	---	38.39	50.00	11.61	1000.0	9.000	N	OFF	9.7
15.574988	52.91	---	60.00	7.09	1000.0	9.000	N	OFF	9.7
16.791375	---	38.06	50.00	11.94	1000.0	9.000	N	OFF	9.8

LINE L RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)**Final Result**

Frequency (MHz)	QuasiPeak (dBc/IV)	Average (dBc/IV)	Limit (dBc/IV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.866400	---	24.53	46.00	21.47	1000.0	9.000	L1	OFF	9.7
0.866400	48.35	---	56.00	7.65	1000.0	9.000	L1	OFF	9.7
0.896250	---	30.47	46.00	15.53	1000.0	9.000	L1	OFF	9.8
0.896250	48.70	---	56.00	7.30	1000.0	9.000	L1	OFF	9.8
0.955950	43.58	---	56.00	12.42	1000.0	9.000	L1	OFF	9.8
15.089925	48.85	---	60.00	11.15	1000.0	9.000	L1	OFF	9.8
15.246638	---	35.04	50.00	14.96	1000.0	9.000	L1	OFF	9.8
15.269025	---	35.03	50.00	14.97	1000.0	9.000	L1	OFF	9.8
15.291413	48.99	---	60.00	11.01	1000.0	9.000	L1	OFF	9.8
15.291413	---	35.38	50.00	14.62	1000.0	9.000	L1	OFF	9.8
16.463025	---	35.85	50.00	14.15	1000.0	9.000	L1	OFF	9.8
16.470488	48.94	---	60.00	11.06	1000.0	9.000	L1	OFF	9.8

Note: All the test modes have been tested, only the worst data record in the report.

## 11. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

**END OF REPORT**