

FCC RF Exposure Evaluation

1. Product Information

FCC ID:	2AVEM-H6PRO
Product name	Car intelligent Diagnosis
Model number	H6 PRO, H6 Pro Marster, H6D Pro, NITRO XT, NITRO GT
Power supply	DC 3.7V By lithium ion polymer battery(13000mAh) Recharged by DC 12V/3A adapter
Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2452MHz Bluetooth: 2402MHz-2480MHz 5.2GHz Band:5180~5240MHz 5.8GHz Band:5745~5825MHz
Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK,BPSK) GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V4.2 (DTS) IEEE 802.11a/n/ac: OFDM(64QAM, 16QAM, QPSK, BPSK)
Channel Number	11 Channels for 20MHz bandwidth(2412~2462MHz) 7 Channels for 40MHz bandwidth(2422~2452MHz) 79 Channels for Bluetooth V4.2(BDR/EDR) 40 channels for Bluetooth V4.2(BT LE) 4 channels for 20MHz bandwidth(5180MHz-5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz) 5 channels for 20MHz bandwidth(5745MHz-5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Antenna Type	PIFA Antenna
Antenna Gain	2.0dBi(Max.)
Hardware version	V1.03
Software version	PS80_V19.08
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Portable Device

2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ "

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f (\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

3. Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

4. Conducted Power Results

Mode	Channel	Frequency(MHz)	Average Conducted Output Power (dBm)
GFSK	0	2402	4.503
	39	2441	4.691
	78	2480	4.811
$\pi/4$ DQPSK	0	2402	1.156
	39	2441	1.086
	78	2480	1.077
8DPSK	0	2402	1.447
	39	2441	1.408
	78	2480	1.004

GFSK(BLE)	0	2402	3.542
	19	2440	3.569
	39	2480	2.592
IEEE 802.11b	1	2412	8.75
	6	2437	8.11
	11	2462	7.63
IEEE 802.11g	1	2412	8.54
	6	2437	7.96
	11	2462	7.55
IEEE 802.11n HT20	1	2412	5.46
	6	2437	6.92
	11	2462	7.44
IEEE 802.11n HT40	3	2422	5.94
	6	2437	7.22
	9	2452	6.32
IEEE 802.11a (5.2G)	36	5180	7.63
	40	5200	6.22
	48	5240	5.96
IEEE 802.11n20 (5.2G)	36	5180	6.44
	40	5200	7.13
	48	5240	6.28
IEEE 802.11n40 (5.2G)	38	5190	5.77
	46	5230	6.14
IEEE 802.11ac20 (5.2G)	36	5180	5.55
	40	5200	6.81
	48	5240	5.91
IEEE 802.11ac40 (5.2G)	38	5190	6.71
	46	5230	5.97
IEEE 802.11ac80 (5.2G)	42	5210	6.33
IEEE 802.11a (5.8G)	149	5745	6.71
	157	5785	5.95
	165	5825	6.71
IEEE 802.11n20 (5.8G)	149	5745	5.84
	157	5785	6.94
	165	5825	5.42
IEEE 802.11n40 (5.8G)	151	5755	4.76
	159	5795	5.31
IEEE 802.11ac20 (5.8G)	149	5745	6.84
	157	5785	6.49
	165	5825	5.11
IEEE 802.11ac40 (5.8G)	151	5755	5.94
	159	5795	4.11
IEEE 802.11ac80 (5.8G)	155	5775	5.36

5. Manufacturing tolerance

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
π /4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK (BT LE) (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	3.0	3.0	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	7.0	7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	5.0	6.0	7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	5.0	7.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11a(5.2G) (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	7.0	6.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11 N20 (5.2G) (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.0	7.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11 N40 (5.2G) (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	5.0	6.0	/

Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11 ac20 (5.2G) (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	5.0	6.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (5.2G) (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	6.0	5.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac80 (5.2G) (Average)			
Channel	Channel 42	/	/
Target (dBm)	6.0	/	/
Tolerance $\pm$ (dB)	1.0	/	/
IEEE 802.11a(5.8G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	5.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11 N20 (5.8G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	5.0	6.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11 N40 (5.8G) (Average)			
Channel	Channel 151	Channel 59	/
Target (dBm)	4.0	5.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11 ac20 (5.8G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (5.8G) (Average)			
Channel	Channel 151	Channel 59	/
Target (dBm)	5.0	4.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac80 (5.8G) (Average)			
Channel	Channel 155	/	/
Target (dBm)	5.0	/	/
Tolerance $\pm$ (dB)	1.0	/	/

6. Evaluation Results

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
GFSK	2.450	5	5.0	3.1623	0.9899 < 3.0	Yes
$\pi/4$ DQPSK	2.450	5	2.0	1.5849	0.4962 < 3.0	Yes
8DPSK	2.450	5	2.0	1.5849	0.4962 < 3.0	Yes
GFSK (BT LE)	2.450	5	4.0	2.5119	0.7863 < 3.0	Yes
IEEE 802.11b	2.450	5	9.0	7.9433	2.4866 < 3.0	Yes
IEEE 802.11g	2.450	5	9.0	7.9433	2.4866 < 3.0	Yes
IEEE 802.11n HT20	2.450	5	8.0	6.3096	1.9752 < 3.0	Yes
IEEE 802.11n HT40	2.450	5	8.0	6.3096	1.9752 < 3.0	Yes
IEEE 802.11a (5.2G)	5.250	5	8.0	6.3096	2.8914 < 3.0	Yes
IEEE 802.11n20 (5.2G)	5.250	5	8.0	6.3096	2.8914 < 3.0	Yes
IEEE 802.11n40 (5.2G)	5.250	5	7.0	5.0119	2.2967 < 3.0	Yes
IEEE 802.11ac20 (5.2G)	5.250	5	7.0	5.0119	2.2967 < 3.0	Yes
IEEE 802.11ac40 (5.2G)	5.250	5	7.0	5.0119	2.2967 < 3.0	Yes
IEEE 802.11ac80 (5.2G)	5.250	5	7.0	5.0119	2.2967 < 3.0	Yes
IEEE 802.11a (5.8G)	5.825	5	7.0	5.0119	2.4192 < 3.0	Yes
IEEE 802.11n20 (5.8G)	5.825	5	7.0	5.0119	2.4192 < 3.0	Yes
IEEE 802.11n40 (5.8G)	5.825	5	6.0	3.9811	1.9217 < 3.0	Yes
IEEE 802.11ac20 (5.8G)	5.825	5	7.0	5.0119	2.4192 < 3.0	Yes
IEEE 802.11ac40 (5.8G)	5.825	5	6.0	3.9811	1.9217 < 3.0	Yes
IEEE 802.11ac80 (5.8G)	5.825	5	6.0	3.9811	1.9217 < 3.0	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.
3. WLAN and BT share same modular and same antenna, no need consider simultaneous transmit.

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

.....THE END OF REPORT.....