

Annex 1: Measuring diagrams to
TEST REPORT
No.: 19-1-0117501T01a-C1

According to:
Title 47 CFR, Chapter I
FCC Regulations, Subchapter A
Part 15, Subpart C: §15.225

for

R&M USA Inc.

R&MinteliPhy Netscale 60 ports
RFID based network infrastructure monitoring system

FCC ID: 2AVF4R837014

Laboratory Accreditation and Listings
 Deutsche Akkreditierungsstelle D-PL-12047-01-01 D-PL-12047-01-03 D-PL-12047-01-04 Accredited EMC-Test Laboratory
accredited according to DIN EN ISO/IEC 17025:2018
CETECOM GmbH Laboratory Radio Communications & Electromagnetic Compatibility Im Teelbruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-0 • Fax: + 49 (0) 20 54 / 95 19-150 E-mail: contact@cetecom.com • Internet: www.cetecom.com

Table of contents

1. Measurement diagrams 3

 1.1. Conducted emissions on AC-Power lines 3

 1.2. Operating frequency ranges (99% OBW) 4

 1.3. H-Field requirements (§15.225 (a)(b)(c)) 5

 1.4. Transmitter spurious emissions 7

 1.5. Frequency tolerance of the carrier signal due temperature variations (§15.255(e)) 10

 1.6. Frequency tolerance of the carrier signal due voltage variations (§15.255(e)) 13

1. Measurement diagrams

1.1. Conducted emissions on AC-Power lines

1.01_S01_EMI_AC


Common Information

Test Description:	Conducted Voltage Measurement Class B
Test Site Location:	Conducted Emission, CETECOM GmbH Essen
Test Software:	R&S EMC32 v9.15
Test Standard:	FCC 15.207
Operating Mode:	NFC 13,56MHz
Measured on line:	N/L1
Diagram details:	Shows the peak values as a sum of measured ports in maxhold mode
Environmental Conditions::	Humidity : 40 % rH; Temperature: 21 °C
Operator:	Mah
Verdict:	Passed

EUT Information

PMT number:	19-1-01175S01
Product:	R&MinteliPhy Netscale Kit 60 ports
Model:	RFID based network infrastructure monitoring system
HW version:	Rev. A
SW version:	400C
Config:	NFC is switched on
Power Supply:	120 AC/60 Hz

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Marg in (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Corr. (dB)
0.523125	38.90	---	56.00	17.10	1000.	9.000	N	GN	0.1
0.523125	---	38.42	46.00	7.58	1000.	9.000	N	GN	0.1
0.538594	38.82	---	56.00	17.18	1000.	9.000	N	GN	0.1
0.538594	---	37.95	46.00	8.05	1000.	9.000	N	GN	0.1
0.862969	25.52	---	56.00	30.48	1000.	9.000	N	GN	0.2
0.862969	---	22.74	46.00	23.26	1000.	9.000	N	GN	0.2
1.401406	22.90	---	56.00	33.10	1000.	9.000	N	GN	0.3
1.401406	---	17.98	46.00	28.02	1000.	9.000	N	GN	0.3
13.562656	39.18	---	60.00	20.82	1000.	9.000	N	GN	0.6
13.562656	---	34.55	50.00	15.45	1000.	9.000	N	GN	0.6
20.326563	---	22.39	50.00	27.61	1000.	9.000	L1	GN	0.8
20.326563	26.44	---	60.00	33.56	1000.	9.000	L1	GN	0.8
27.121250	29.09	---	60.00	30.91	1000.	9.000	L1	GN	0.5
27.121250	---	25.05	50.00	24.95	1000.	9.000	L1	GN	0.5

1.3. H-Field requirements (§15.225 (a)(b)(c))




Diagram 2: EUT lying

Full Spectrum




Diagram 3: EUT standing

1.4. Transmitter spurious emissions

1.4.1. Frequency 9 kHz to 30 MHz (TX-Mode)




Diagram 4: TX spurious emissions up to 30 MHz

1.4.2. Frequency 30 MHz to 1000 MHz (TX Mode)




Diagram 5: E-Field measurements, EUT lying

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
68.956000	11.96	40.00	28.04	120.000	189.0	V	30.0	6.7
135.600000	29.50	43.50	14.00	120.000	203.0	H	295.0	9.8
162.724000	25.78	43.50	17.72	120.000	224.0	H	289.0	9.5

Full Spectrum





Diagram 6: E-Field measurements, EUT standing

Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)		Pol	Azimuth (deg)	Corr. (dB)
67.232000	8.18	40.00	31.82	120.000	170.0		V	352.0	6.9
81.004000	8.85	40.00	31.15	120.000	154.0		V	112.0	7.1
87.176000	9.37	40.00	30.63	120.000	225.0		V	175.0	8.0

1.5. Frequency tolerance of the carrier signal due temperature variations (§15.255(e))


1.5.1. T_{NOM} , V_{NOM}



Date: 3.DEC.2019 17:02:47

Diagram 7: Frequency error


1.5.2. $T = +40\text{ }^{\circ}\text{C}$, V_{NOM}



Date: 3.DEC.2019 20:08:51

Diagram 8: Frequency error at +40 °C, on start up


1.5.3. $T = +30^{\circ}\text{C}$, V_{NOM}



Date: 3.DEC.2019 19:28:48

Diagram 9: Frequency error at $+30^{\circ}\text{C}$, on start up


1.5.4. $T = +10^{\circ}\text{C}$, V_{NOM}



Date: 3.DEC.2019 18:50:27

Diagram 10: Frequency error at $+10^{\circ}\text{C}$, on start up


1.5.5. $T = 0\text{ }^{\circ}\text{C}$, V_{NOM}



Date: 3.DEC.2019 18:10:08


Diagram 11: Frequency error at 0 °C, on start up

1.6. Frequency tolerance of the carrier signal due voltage variations (§15.255(e))



Date: 3.DEC.2019 17:13:16

Diagram 12: Frequency error at $U_{MIN} = 12$ V



Date: 3.DEC.2019 17:04:12

Diagram 13: Frequency error at $U_{MAX} = 17$ V

End of the Annex