



TEST REPORT

Report No. : CHTEW1912017401 Report Verification: 

Project No..... : SHT1912016905EW

FCC ID..... : 2AVFS-GEO10

Applicant's name..... : Geotechvision Enterprises Limited

Address..... : 44 Cowper Drive, Kingston 20, Jamaica W.I. JMK0020

Manufacturer..... : DBETTER INTERNATIONAL LIMITED

Address..... : Room803 6F., Chevalier House, 45-51 Chatham Road South, Tsim Sha Tsui, Kowloon

Test item description : Tablet

Trade Mark : Geo

Model/Type reference..... : GEO10

Listed Model(s)..... : Geo10X

Standard : FCC CFR Title 47 Part 15 Subpart E Section 15.407

Date of receipt of test sample..... : Dec.12,2019

Date of testing..... : Dec.12,2019 ~ Dec.24,2019

Date of issue..... : Dec.25,2019

Result..... : PASS

Compiled by
(Position+Printed name+Signature): File administrator Yueming Li

Yueming Li

Supervised by
(Position+Printed name+Signature): Project Engineer Kiki Kong

Kiki Kong

Approved by
(Position+Printed name+Signature): RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

1.	TEST STANDARDS AND REPORT VERSION	3
1.1.	Test Standards	3
1.2.	Report version	3
2.	TEST DESCRIPTION	4
3.	SUMMARY	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
4.	TEST CONFIGURATION	7
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test mode	7
4.4.	Support unit used in test configuration and system	8
4.5.	Testing environmental condition	8
4.6.	Measurement uncertainty	8
4.7.	Equipment Used during the Test	9
5.	TEST CONDITIONS AND RESULTS	11
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Maximum Conducted Output Power	15
5.4.	Power Spectral Density	16
5.5.	26dB bandwidth and 99% Occupy bandwidth	18
5.6.	6dB Bandwidth	19
5.7.	Band edge	20
5.8.	Radiated Spurious Emissions	23
5.9.	Frequency stability	29
6.	TEST SETUP PHOTOS	30
7.	EXTERANAL AND INTERNAL PHOTOS	32
8.	APPENDIX REPORT	39

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC Rules Part 15.407](#): General technical requirements.
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB789033 D02 v02r01](#): GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-12-25	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247(c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	Maximum Conducted Output Power	15.407(a)	PASS
5.4	Maximum Power Spectral Density	15.407(a)	PASS
5.5	26dB Bandwidth and 99% Occupancy bandwidth	15.407(a)	PASS
5.6	6dB Bandwidth	15.407(a)	PASS
5.7	Band edge	15.407(b)	PASS
5.8	Radiated Spurious Emissions	15.209	PASS
5.9	Frequency Stability	15.407(g)	PASS

Note:

- The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	Geotechvision Enterprises Limited
Address:	44 Cowper Drive, Kingston 20, Jamaica W.I. JMK0020
Manufacturer:	DBETTER INTERNATIONAL LIMITED
Address:	Room803 6F., Chevalier House, 45-51 Chatham Road South, Tsim Sha Tsui, Kowloon

3.2. Product Description

Name of EUT:	Tablet
Trade Mark:	Geo
Model No.:	GEO10
Listed Model(s):	Geo10X
Power supply:	DC 3.7V
Adapter informations:	Model:BSY-F18Q Input:100-240Va.c.50/60Hz,0.5A Max Output:DC 5V/3A,7V,9V/2A,12V/1.5A,18W Max
Hardware version:	PC62_H_IPD
Software version:	andriid version 9

3.3. Radio Specification Description

Support type*1	☒ 802.11a	☒ 802.11n(HT20)	☒ 802.11n(HT40)
	☒ 802.11ac(HT20)	☒ 802.11ac(HT40)	☒ 802.11ac(HT80)
Function:	☐ Outdoor AP	☐ Indoor AP	☐ Fixed P2P
	☒ Client		
Modulation:	BPSK, QPSK, 16QAM, 64QAM		
Operation frequency:	☒ Band I: 5150MHz~5250MHz		
	☒ Band IV: 5725MHz~5850MHz		
Supported Bandwidth	20MHz: 802.11ac,802.11n, 802.11a		
	40MHz: 802.11ac,802.11n		
	80MHz: 802.11ac		
Antenna type:	FPCB Antenna		
Antenna gain:	1.56dBi		

Note:

*1: only show the RF function associated with this report.

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Qualifications	Type	Accreditation Number
	CNAS	L1225
	A2LA	3902.01
	FCC	762235
	Canada	5377A

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Band	Test Channel	20MHz		40MHz		80MHz	
		Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
I	CH _L	36	5180	38	5190	-	-
	CH _M	44	5220	-	-	42	5210
	CH _H	48	5240	46	5230	-	-
IV	CH _L	149	5745	151	5755	-	-
	CH _M	157	5785	-	-	155	5775
	CH _H	165	5825	159	5795	-	-

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates, final test modes are considering the modulation and worse data rates as below table.

Modulation	Data rate
802.11a	6Mbps
802.11n(HT20)/ 802.11ac(HT20)	MCS0
802.11n(HT40)/ 802.11ac(HT40)	MCS0
802.11ac(HT80)	MCS0

4.3. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?					
✓ No					
Item	Equipement	Trade Name	Model No.	FCC ID	Power cord
1					
2					

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.02 dB
Radiated Emission (30MHz~1000MHz)	4.90 dB
Radiated Emissions (1GHz~25GHz)	4.96 dB
Peak Output Power	0.51 dB
Power Spectral Density	0.51 dB
Conducted Spurious Emission	0.51 dB
6dB Bandwidth	70 Hz
Frequency error	70 Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.7. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX 142	EF-NM-BNCM-2M	2019/10/23	2020/10/22
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2019/10/26	2020/10/25
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2018/04/02	2021/04/01
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2019/11/14	2020/11/13
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2019/08/21	2020/08/20
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX 104	501184/4	2019/05/27	2020/05/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2017/04/01	2020/03/31
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	25841	2017/03/27	2020/03/26
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/10
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2019/11/14	2020/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2019/05/23	2020/05/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2019/10/26	2020/10/25
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2019/10/26	2020/10/25
●	Power Meter	Anritsu	ML249A	N/A	2019/10/26	2020/10/25
○	Radio communication tester	R&S	CMW500	137688-Lv	2019/10/26	2020/10/25

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a FPCB antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

Test Line:

L

**MEASUREMENT RESULT: "GM191218558_fin"**

12/18/2019 9:07PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.213000	49.10	10.2	63	14.0	QP	L1	GND
0.487500	41.90	10.0	56	14.3	QP	L1	GND
0.937500	33.50	9.9	56	22.5	QP	L1	GND
2.562000	32.20	10.0	56	23.8	QP	L1	GND
10.000500	40.10	10.2	60	19.9	QP	L1	GND
13.654500	31.80	10.2	60	28.2	QP	L1	GND


MEASUREMENT RESULT: "GM191218558_fin2"

12/18/2019 9:07PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154500	37.80	10.1	56	18.0	AV	L1	GND
0.514500	38.60	10.0	46	7.4	AV	L1	GND
1.356000	25.80	10.0	46	20.2	AV	L1	GND
2.116500	24.40	10.0	46	21.6	AV	L1	GND
8.974500	25.50	10.2	50	24.5	AV	L1	GND
19.432500	26.70	10.3	50	23.3	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM191218557_fin"**

12/18/2019 9:04PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.172500	54.80	10.1	65	10.0	QP	N	GND
0.492000	45.50	10.0	56	10.6	QP	N	GND
0.937500	33.90	9.9	56	22.1	QP	N	GND
3.138000	30.40	10.0	56	25.6	QP	N	GND
10.000500	41.40	10.2	60	18.6	QP	N	GND
13.510500	34.80	10.2	60	25.2	QP	N	GND

MEASUREMENT RESULT: "GM191218557_fin2"

12/18/2019 9:04PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.168000	37.30	10.1	55	17.8	AV	N	GND
0.487500	36.70	10.0	46	9.5	AV	N	GND
0.897000	22.30	9.9	46	23.7	AV	N	GND
3.471000	18.70	10.0	46	27.3	AV	N	GND
12.336000	29.60	10.2	50	20.4	AV	N	GND
12.543000	30.30	10.2	50	19.7	AV	N	GND

5.3. Maximum Conducted Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart E Section 15.407(a):


For the 5.15~5.25GHz band:

- Outdoor AP
The maximum conducted output power (P_{out}) shall not exceed the lesser of 1W (30dBm).
if $G_{TX} > 6\text{dBi}$, then $P_{out} = 30 - (G_{TX} - 6)$. e.i.r.p. at any elevation angle above 30 degrees $\leq 125\text{mW}$ (21dBm)
- Indoor AP
The maximum conducted output power (P_{out}) shall not exceed the lesser of 1W (30dBm).
if $G_{TX} > 6\text{dBi}$, then $P_{out} = 30 - (G_{TX} - 6)$.
- Point-to-point AP
The maximum conducted output power (P_{out}) shall not exceed the lesser of 1W (30dBm).
if $G_{TX} > 23\text{dBi}$, then $P_{out} = 30 - (G_{TX} - 23)$.
- Client devices
The maximum conducted output power (P_{out}) shall not exceed the lesser of 250W (24dBm).
if $G_{TX} > 6\text{dBi}$, then $P_{out} = 24 - (G_{TX} - 6)$.

For the 5.725~5.85GHz band:

- Point-to-multipoint systems (P2M)
The maximum conducted output power (P_{out}) shall not exceed the lesser of 1W (30dBm).
if $G_{TX} > 6\text{dBi}$, then $P_{out} = 30 - (G_{TX} - 6)$.
- Point-to-point systems (P2P)
The maximum conducted output power (P_{out}) shall not exceed the lesser of 1W (30dBm).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to KDB789033 Section E-3-b)
2. The maximum conducted output power may be measured using a broadband AVG RF power meter.
3. Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor.
4. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.
5. Record the measurement data.

6. TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix A on the appendix report

5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart E Section 15.407(a):


For the 5.15~5.25GHz band:

- Outdoor AP
The peak power spectral density (PSD) shall not exceed the lesser of 17dBm/MHz.
if $G_{TX} > 6\text{dBi}$, then $\text{PSD} = 17 - (G_{TX} - 6)$.
- Indoor AP
The peak power spectral density (PSD) shall not exceed the lesser of 17dBm/MHz.
if $G_{TX} > 6\text{dBi}$, then $\text{PSD} = 17 - (G_{TX} - 6)$.
- Point-to-point AP
The peak power spectral density (PSD) shall not exceed the lesser of 17dBm/MHz.
if $G_{TX} > 23\text{dBi}$, then $\text{PSD} = 17 - (G_{TX} - 23)$.
- Client devices
The peak power spectral density (PSD) shall not exceed the lesser of 11dBm/MHz.
if $G_{TX} > 6\text{dBi}$, then $\text{PSD} = 11 - (G_{TX} - 6)$.

For the 5.725~5.85GHz band:

- Point-to-multipoint systems (P2M)
The peak power spectral density (PSD) shall not exceed the lesser of 30dBm/500kHz.
if $G_{TX} > 6\text{dBi}$, then $\text{PSD} = 30 - (G_{TX} - 6)$.
- Point-to-point systems (P2P)
The peak power spectral density (PSD) shall not exceed the lesser of 30dBm/500kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. According KDB 789033 D02 – Section F
2. Analyzer was setting as follow:
Center frequency: test channel
Span was set to encompass the entire emission bandwidth of the signal
RBW=1MHz for devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz
RBW=500kHz for devices operating in the band 5.725-5.85 GHz
VBW ≥ 3 RBW
Number of sweep points $> 2 \times (\text{span}/\text{RBW})$
Sweep time = auto
Detector = Peak
Trigger was set to free run for all modes, trace was averaged over 100 sweeps
3. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data


Please refer to appendix B on the appendix report

5.5. 26dB bandwidth and 99% Occupy bandwidth

LIMIT

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033 D02 , and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

TEST CONFIGURATION



TEST PROCEDURE

1. According KDB 789033 D02 – Section C
2. Connect the antenna port(s) to the spectrum analyzer input.
3. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = Channel center frequency
Span = 2 x emission bandwidth
RBW = 1% to 5% of the emission bandwidth
VBW > 3 x RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
5. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission, and use the 99 % power bandwidth function of the instrument

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix C and D on the appendix report


5.6. 6dB Bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart E Section 15.407(e)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = test channel center frequency
Span = 2 x emission bandwidth
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix E on the appendix report

5.7. Band edge

LIMIT


FCC CFR Title 47 Part 15 Subpart E Section 15.407(b)

Un-restricted band emissions above 1GHz			
Operating Band	Frequency	EIRP Limit	Value
5150-5250MHz	Above 1GHz	-27dBm/MHz(68.2dBuV/m)@3m	Peak
5250-5350MHz	Above 1GHz	-27dBm/MHz(68.2dBuV/m)@3m	Peak
5470-5725MHz	Above 1GHz	-27dBm/MHz(68.2dBuV/m)@3m	Peak
5725-5850 MHz	1GHz-5.65GHz	-27 dBm/MHz(68.2dBuV/m)@3m	Peak
	5.65GHz-5.7GHz	-27*dBm/MHz to 10dBm/MHz (68.2* dBuV/m to 105.6dBuV/m)	Peak
	5.7GHz-5.72GHz	10*dBm/MHz to 15.6dBm/MHz (105.6*dBuV/m to 110.8dBuV/m)	Peak
	5.72GHz-5.725GHz	15.6*dBm/MHz to 27dBm/MHz (110.8dBuV/m to * 122.2dBuV/m)	Peak
	5.85GHz-5.855GHz	27dBm/MHz to 15.6*dBm/MHz (122.2dBuV/m to 110.8* dBuV/m)	Peak
	5.855GHz-5.875GHz	15.6dBm/MHz to 10*dBm/MHz (110.8dBuV/m to 105.6* dBuV/m)	Peak
	5.875GHz-5.925GHz	10dBm/MHz to -27*dBm/MHz (105.6dBuV/m to 68.2* dBuV/m)	Peak
	Above 5.925GHz	-27 dBm/MHz(68.2dBuV/m)@3m	Peak

* Increase/Decreases with the linearly of the frequency.

For emission above 1GHz and in restricted band, according to FCC KDB 789033 D02 General UNII Test Procedure, all emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit. $E[dBuV/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz PEAK detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 4.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

TEST Data

Band: I		Worst mode: 802.11a			Test channel: CH _L		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
5150.00	18.81	27.70	54.00	26.30	8.89	Vertical	Average
5150.00	24.74	33.63	68.20	34.57	8.89	Vertical	Peak
5150.00	19.84	28.73	54.00	25.27	8.89	Horizontal	Average
5150.00	24.66	33.55	68.20	34.65	8.89	Horizontal	Peak

Band: I		Worst mode: 802.11a			Test channel: CH _H		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
5250.00	18.26	26.80	54.00	27.20	8.54	Vertical	Average
5250.00	24.51	33.05	68.20	35.15	8.54	Vertical	Peak
5250.00	18.70	27.24	54.00	26.76	8.54	Horizontal	Average
5250.00	25.37	33.91	68.20	34.29	8.54	Horizontal	Peak

Band: IV		Worst mode: 802.11a			Test channel: CH _L		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
5725.00	17.38	26.38	54.00	27.62	9.00	Vertical	Average
5725.00	25.41	34.41	68.20	33.79	9.00	Vertical	Peak
5725.00	18.86	27.86	54.00	26.14	9.00	Horizontal	Average
5725.00	23.97	32.97	68.20	35.23	9.00	Horizontal	Peak

Band: IV		Worst mode: 802.11a			Test channel: CH _H		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
5850.00	17.41	27.18	54.00	26.82	9.77	Vertical	Average
5850.00	25.76	35.53	68.20	32.67	9.77	Vertical	Peak
5850.00	18.55	28.32	54.00	25.68	9.77	Horizontal	Average
5850.00	24.81	34.58	68.20	33.62	9.77	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Test 802.11a, 802.11n, 802.11ac mode, all modulations have been tested, only worst case is reported

5.8. Radiated Spurious Emissions

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209 and Part 15 Subpart E Section 15.407

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Unwanted emissions below 1GHz and Restricted band emissions above 1GHz		
Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9KHz ~30MHz



- 30MHz ~ 1GHz



➤ Above 1GHz

**TEST PROCEDURE**

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable


TEST Data**TEST DATA FOR 9 kHz ~ 30 MHz**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

TEST DATA FOR 30MHz-1GHz

Polarization:

Horizontal


**MEASUREMENT RESULT: "GM1912186099_red"**

12/18/2019 10:44PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	18.70	-8.4	40.0	21.3	QP	300.0	73.00	HORIZONTAL
55.220000	19.50	-8.4	40.0	20.5	QP	300.0	98.00	HORIZONTAL
127.000000	21.80	-12.5	43.5	21.7	QP	100.0	116.00	HORIZONTAL
286.080000	22.50	-6.8	46.0	23.5	QP	300.0	316.00	HORIZONTAL
526.640000	27.50	-0.6	46.0	18.5	QP	300.0	252.00	HORIZONTAL
957.320000	36.10	8.3	46.0	9.9	QP	100.0	116.00	HORIZONTAL

Polarization:

Vertical

**MEASUREMENT RESULT: "GM1912186100_red"**

12/18/2019 10:46PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	25.90	-12.1	40.0	14.1	QP	100.0	78.00	VERTICAL
59.100000	21.50	-9.1	40.0	18.5	QP	100.0	360.00	VERTICAL
88.200000	24.20	-12.6	43.5	19.3	QP	100.0	294.00	VERTICAL
125.060000	33.50	-12.3	43.5	10.0	QP	100.0	192.00	VERTICAL
553.800000	27.10	0.2	46.0	18.9	QP	100.0	0.00	VERTICAL
941.800000	35.50	8.0	46.0	10.5	QP	100.0	216.00	VERTICAL

Remark:

Transd=Cable lose+ Antenna factor- Pre-amplifier; Margin=Limit -Level

TEST DATA FOR Above 1GHz

Band: I		Worst mode: 802.11a			Test channel: CH _L		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
1461.19	23.17	17.56	74.00	56.44	-5.61	Vertical	Peak
4812.88	27.36	34.43	74.00	39.57	7.07	Vertical	Peak
6062.78	27.34	37.96	74.00	36.04	10.62	Vertical	Peak
7154.06	28.25	42.98	74.00	31.02	14.73	Vertical	Peak
1311.38	22.25	16.68	74.00	57.32	-5.57	Horizontal	Peak
1843.06	25.14	19.33	74.00	54.67	-5.81	Horizontal	Peak
3054.78	30.01	30.13	74.00	43.87	0.12	Horizontal	Peak
4846.66	27.03	34.14	74.00	39.86	7.11	Horizontal	Peak

Band: I		Worst mode: 802.11a			Test channel: CH _M		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
1590.44	21.82	15.60	74.00	58.40	-6.22	Vertical	Peak
3977.16	28.03	30.97	74.00	43.03	2.94	Vertical	Peak
5222.66	27.75	36.61	74.00	37.39	8.86	Vertical	Peak
8039.72	28.70	44.95	74.00	29.05	16.25	Vertical	Peak
2088.34	23.84	19.75	74.00	54.25	-4.09	Horizontal	Peak
4749.72	28.05	34.76	74.00	39.24	6.71	Horizontal	Peak
5115.44	28.53	37.36	74.00	36.64	8.83	Horizontal	Peak
8126.38	28.88	45.13	74.00	28.87	16.25	Horizontal	Peak

Band: I		Worst mode: 802.11a			Test channel: CH _H		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
1681.50	21.82	15.69	74.00	58.31	-6.13	Vertical	Peak
4442.75	28.21	33.31	74.00	40.69	5.10	Vertical	Peak
6923.47	27.02	41.14	74.00	32.86	14.12	Vertical	Peak
7447.81	28.60	43.99	74.00	30.01	15.39	Vertical	Peak
1447.97	21.35	15.75	74.00	58.25	-5.60	Horizontal	Peak
2125.06	29.16	25.41	74.00	48.59	-3.75	Horizontal	Peak
3514.50	28.69	29.80	74.00	44.20	1.11	Horizontal	Peak
5447.38	28.57	37.44	74.00	36.56	8.87	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Measuring frequencies from 1 GHz to 40GHz.
4. Test 802.11a, 802.11n , 802.11ac mode, all modulations have been tested, only worst case is reported

Band: IV		Worst mode: 802.11a			Test channel: CH _L		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
2220.531	23.67	20.83	74.00	53.17	-2.84	Vertical	Peak
3056.25	29.08	29.21	74.00	44.79	0.13	Vertical	Peak
4646.906	28.77	34.83	74.00	39.17	6.06	Vertical	Peak
5128.656	28.00	36.85	74.00	37.15	8.85	Vertical	Peak
2274.875	23.15	20.66	74.00	53.34	-2.49	Horizontal	Peak
6318.344	27.45	38.50	74.00	35.50	11.05	Horizontal	Peak
7151.125	29.01	43.73	74.00	30.27	14.72	Horizontal	Peak
9828.656	29.47	46.71	74.00	27.29	17.24	Horizontal	Peak

Band: IV		Worst mode: 802.11a			Test channel: CH _M		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
1255.563	22.26	16.57	74.00	57.43	-5.69	Vertical	Peak
4191.594	28.39	32.16	74.00	41.84	3.77	Vertical	Peak
7117.344	28.71	43.24	74.00	30.76	14.53	Vertical	Peak
7481.594	28.69	44.09	74.00	29.91	15.40	Vertical	Peak
1518.469	21.38	15.63	74.00	58.37	-5.75	Horizontal	Peak
3699.563	29.68	31.27	74.00	42.73	1.59	Horizontal	Peak
6214.063	27.94	38.84	74.00	35.16	10.90	Horizontal	Peak
8047.063	29.63	45.89	74.00	28.11	16.26	Horizontal	Peak

Band: IV		Worst mode: 802.11a			Test channel: CH _H		
Frequency (MHz)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Factor (dB)	Test value	Polarization
2307.19	22.9	20.56	74.00	53.44	-2.34	Vertical	Peak
4047.66	27.36	30.49	74.00	43.51	3.13	Vertical	Peak
5691.19	28.32	37.14	74.00	36.86	8.82	Vertical	Peak
7986.84	29.13	45.34	74.00	28.66	16.21	Vertical	Peak
1540.50	23.13	17.24	74.00	56.76	-5.89	Horizontal	Peak
2791.88	22.59	24.56	74.00	49.44	1.97	Horizontal	Peak
3799.44	29.13	31.12	74.00	42.88	1.99	Horizontal	Peak
6253.72	27.64	38.58	74.00	35.42	10.94	Horizontal	Peak

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Measuring frequencies from 1 GHz to 40GHz.
4. Test 802.11a, 802.11n, 802.11ac mode, all modulations have been tested, only worst case is reported

5.9. Frequency stability

LIMIT

Within Operation Band

TEST CONFIGURATION



Note : Measurement setup for testing on Antenna connector

TEST PROCEDURE

1. The equipment under test was connected to an external power supply.
2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators.
3. The EUT was placed inside the temperature chamber.
4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency.
5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency.
6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached..

TEST MODE:

Please refer to the clause 4.3



TEST RESULT

☒ Passed ☐ Not Applicable

Please refer to appendix F on the appendix report

6. TEST SETUP PHOTOS

Radiated Emission







AC Conducted Emission








7. EXTERANAL AND INTERNAL PHOTOS

External Photo



















Internal Photo









8. APPENDIX REPORT

APPENDIX REPORT

Project No.	SHT1912016905EW	Radio Specification	WIFI 5G
Test sample No.	YPHT19120169004	Model No.	GEO10
Start test date	2019/12/24	Finish date	2019/12/24
Temperature	25°C	Humidity	50%
Test Engineer	Ximing Huang	Auditor	<i>William.wang</i>


Appendix clause	Test item	Result
A	Maximum Conducted Output Power	PASS
B	Maximum Power Spectral Density	PASS
C	26 dB Bandwidth	PASS
D	99% Occupy bandwidth	PASS
E	6 dB Bandwidth	PASS
F	Frequency stability	PASS


Appendix A: Maximum Conducted Output Power


Band	Bandwidth (MHz)	Type	Channel	Conducted Output Power (dBm)	Limit (dBm)	Result
I	20	802.11ac	CH _L	16.35	24.00	Pass
			CH _M	16.38		
			CH _H	16.15		
		802.11n	CH _L	16.32	24.00	Pass
			CH _M	16.32		
			CH _H	16.12		
		802.11a	CH _L	16.50	24.00	Pass
			CH _M	16.53		
			CH _H	16.35		
	40	802.11ac	CH _L	15.70	24.00	Pass
			CH _H	15.53		
		802.11n	CH _L	15.61	24.00	Pass
			CH _H	15.56		
	80	802.11ac	CH _M	15.19	24.00	Pass
IV	20	802.11ac	CH _L	15.88	30.00	Pass
			CH _M	14.97		
			CH _H	14.79		
		802.11n	CH _L	16.41	30.00	Pass
			CH _M	15.30		
			CH _H	14.79		
		802.11a	CH _L	16.70	30.00	Pass
			CH _M	15.34		
			CH _H	15.31		
	40	802.11ac	CH _L	15.00	30.00	Pass
			CH _H	14.00		
		802.11n	CH _L	15.26	30.00	Pass
			CH _H	14.10		
	80	802.11ac	CH _M	14.55	30.00	Pass


Appendix B: Maximum Power Spectral Density

Band	Bandwidth (MHz)	Type	Channel	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)	Result
I	20	802.11ac	CH _L	6.66	11.00	Pass
			CH _M	7.55		
			CH _H	7.38		
		802.11n	CH _L	6.34	11.00	Pass
			CH _M	7.83		
			CH _H	6.59		
		802.11a	CH _L	7.83	11.00	Pass
			CH _M	6.83		
			CH _H	7.04		
	40	802.11ac	CH _L	3.94	11.00	Pass
			CH _H	3.49		
		802.11n	CH _L	3.08	11.00	Pass
			CH _H	2.91		
	80	802.11ac	CH _M	-0.22	11.00	Pass
Band	Bandwidth (MHz)	Type	Channel	Power Spectral Density (dBm/500kHz)	Limit (dBm/500KHz)	Result
IV	20	802.11ac	CH _L	4.39	30.00	Pass
			CH _M	3.78		
			CH _H	2.81		
		802.11n	CH _L	4.87	30.00	Pass
			CH _M	3.78		
			CH _H	3.69		
		802.11a	CH _L	5.02	30.00	Pass
			CH _M	3.60		
			CH _H	3.74		
	40	802.11ac	CH _L	1.05	30.00	Pass
			CH _H	-0.14		
		802.11n	CH _L	1.14	30.00	Pass
			CH _H	-0.63		
	80	802.11ac	CH _M	-2.50	30.00	Pass












Band I


802.11n (HT40)


CH_LCH_H


Band I


802.11ac (HT80)


CH_M












Appendix C: 26dB bandwidth

Band	Bandwidth (MHz)	Type	Channel	26dB bandwidth (MHz)	Result
I	20	802.11ac	CH _L	20.43	Pass
			CH _M	20.43	
			CH _H	20.64	
		802.11n	CH _L	20.52	Pass
			CH _M	20.61	
			CH _H	20.64	
		802.11a	CH _L	20.19	Pass
			CH _M	20.16	
			CH _H	20.22	
	40	802.11ac	CH _L	40.62	Pass
			CH _H	40.68	
		802.11n	CH _L	40.86	Pass
			CH _H	41.04	
	80	802.11ac	CH _M	81.48	Pass

Band I

802.11ac (HT20)

CH_L

Date: 24.DEC.2019 12:03:21

CH_M


Date: 24.DEC.2019 12:04:19

CH_H


Date: 24.DEC.2019 12:05:20

Band I


802.11n (HT20)

CH_L

Date: 24.DEC.2019 11:45:58

CH_M


Date: 24.DEC.2019 11:46:57

CH_H

Date: 24.DEC.2019 11:47:55

Band I

802.11a

CH_L

Date: 24.DEC.2019 11:42:48

CH_M

Date: 24.DEC.2019 11:43:41

CH_H

Date: 24.DEC.2019 11:44:40

Band I

802.11ac (HT40)

CH_L

Ref Level 20.50 dBm Offset 1.00 dB = RBW 500 kHz
 ATT 30 dB SWT 1.01 ms = VBW 2 MHz Mode Auto Sweep Count 500/500

1 Frequency Sweep

CF 5.19 GHz 1001 pts 6.0 MHz/ Span 60.0 MHz

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		5.16978 GHz	-24.11 dBm		
M2	1		5.1927 GHz	-1.95 dBm		
D3	M1	1	40.62 MHz	-0.21 dB		

Date: 24.DEC.2019 12:06:30

CH_H

Ref Level 20.50 dBm Offset 1.00 dB = RBW 500 kHz
 ATT 30 dB SWT 1.01 ms = VBW 2 MHz Mode Auto Sweep Count 500/500

1 Frequency Sweep

CF 5.23 GHz 1001 pts 6.0 MHz/ Span 60.0 MHz

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		5.2096 GHz	-24.09 dBm		
M2	1		5.22586 GHz	-2.28 dBm		
D3	M1	1	40.68 MHz	-0.64 dB		

Date: 24.DEC.2019 12:07:31

Band I

802.11n (HT40)

CH_L

Date: 24.DEC.2019 12:00:46

CH_H

Date: 24.DEC.2019 12:02:04

Band I

802.11ac (HT80)

CH_M


Date: 24.DEC.2019 12:08:42

Appendix D: 99% Occupy bandwidth


Band	Bandwidth (MHz)	Type	Channel	99% Occupy bandwidth (MHz)	Result
I	20	802.11ac	CH _L	17.68	Pass
			CH _M	17.68	
			CH _H	17.65	
		802.11n	CH _L	17.68	Pass
			CH _M	17.68	
			CH _H	17.68	
		802.11a	CH _L	16.69	Pass
			CH _M	16.69	
			CH _H	16.63	
	40	802.11ac	CH _L	36.02	Pass
			CH _H	36.02	
		802.11n	CH _L	36.08	Pass
			CH _H	36.08	
	80	802.11ac	CH _M	74.93	Pass
IV	20	802.11ac	CH _L	17.71	Pass
			CH _M	17.68	
			CH _H	17.68	
		802.11n	CH _L	17.65	Pass
			CH _M	17.68	
			CH _H	17.68	
		802.11a	CH _L	16.69	Pass
			CH _M	16.66	
			CH _H	16.63	
	40	802.11ac	CH _L	36.02	Pass
			CH _H	36.14	
		802.11n	CH _L	36.12	Pass
			CH _H	36.12	
	80	802.11ac	CH _M	75.17	Pass

Band I


802.11ac (HT20)

CH_L

Date: 24.DEC.2019 12:03:12

CH_M

Date: 24.DEC.2019 12:04:10

CH_H

Date: 24.DEC.2019 12:05:11

Band I

802.11n (HT20)

CH_L

Ref Level 20.50 dBm Offset 1.00 dB RBW 300 kHz
Att 30 dB SWT 1.01 ms VBW 1 MHz Mode Auto Sweep Count 500/500
1 Occupied Bandwidth M1[1] 5.179131 GHz 3.52 dBm 5.1791310 GHz

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		5.179131 GHz	3.52 dBm		
T1	1		5.171158 GHz	-4.53 dBm	Occ. BW	17.682317682 MHz
T2	1		5.188412 GHz	-4.38 dBm		

Date: 24.DEC.2019 11:45:49

CH_M

Ref Level 20.50 dBm Offset 1.00 dB RBW 300 kHz
Att 30 dB SWT 1.01 ms VBW 1 MHz Mode Auto Sweep Count 500/500
1 Occupied Bandwidth M1[1] 5.218951 GHz 3.44 dBm 5.2189510 GHz

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		5.218951 GHz	3.44 dBm		
T1	1		5.211289 GHz	-4.87 dBm	Occ. BW	17.682317682 MHz
T2	1		5.228812 GHz	-4.53 dBm		

Date: 24.DEC.2019 11:46:47

CH_H


Ref Level 20.50 dBm Offset 1.00 dB RBW 300 kHz
Att 30 dB SWT 1.01 ms VBW 1 MHz Mode Auto Sweep Count 500/500
1 Occupied Bandwidth M1[1] 5.239041 GHz 2.98 dBm 5.2390410 GHz

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		5.239041 GHz	2.98 dBm		
T1	1		5.231129 GHz	-5.57 dBm	Occ. BW	17.682317682 MHz
T2	1		5.248812 GHz	-5.13 dBm		


Date: 24.DEC.2019 11:47:46

Band I


802.11a

CH_L


Date: 24.DEC.2019 11:42:38

CH_M

Date: 24.DEC.2019 11:43:32


CH_H

Date: 24.DEC.2019 11:44:31



Band I

802.11n (HT40)

CH_L

Date: 24.DEC.2019 12:00:36

CH_H

Date: 24.DEC.2019 12:01:56

Band I


802.11ac (HT80)

CH_M


Date: 24.DEC.2019 12:08:33

Band IV

802.11ac (HT20)

CH_L

Date: 24.DEC.2019 13:02:45

CH_M



Date: 24.DEC.2019 13:03:44


CH_H

Date: 24.DEC.2019 13:04:40

Band IV


802.11n (HT20)

CH_LCH_MCH_H




Band IV

802.11ac (HT40)

$$\text{CH}_L$$



Date: 24.DEC.2019 13:05:54

$$\text{CH}_H$$



Date: 24.DEC.2019 13:06:53

Band IV

802.11n (HT40)

CH_L

Date: 24.DEC.2019 13:00:24

CH_H

Date: 24.DEC.2019 13:01:20

Band IV

802.11ac (HT80)

CH_M

Date: 24.DEC.2019 13:08:15

Appendix E: 6dB Bandwidth

Band	Bandwidth (MHz)	Type	Channel	6dB bandwidth (MHz)	Result
IV	20	802.11ac	CH _L	15.18	Pass
			CH _M	15.18	
			CH _H	15.18	
		802.11n	CH _L	15.18	Pass
			CH _M	15.51	
			CH _H	15.21	
		802.11a	CH _L	15.21	Pass
			CH _M	15.21	
			CH _H	15.21	
	40	802.11ac	CH _L	35.22	Pass
			CH _H	35.22	
		802.11n	CH _L	35.30	Pass
			CH _H	35.30	
	80	802.11ac	CH _M	75.48	Pass

Test channel	802.11ac (HT20)
CH _L	Spectrum Ref Level 20.50 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.04 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1 Frequency Sweep

Test channel	802.11n (HT20)
CH _L	Spectrum Ref Level 20.50 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.04 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1 Frequency Sweep </

Test channel	802.11a
CH _L	Spectrum Ref Level 20.50 dBm Offset 1.00 dB = RBW 100 kHz Att 30 dB SWT 1.04 ms = VBW 300 kHz Mode Auto Sweep Count 500/500 1 Frequency Sweep

Test channel

802.11ac (HT40)

CH_L

Ref Level 20.50 dBm Offset 1.00 dB = RBW 100 kHz
ATT 30 dB SWT 1.07 ms = VBW 300 kHz Mode Auto Sweep Count 500/500

1 Frequency Sweep

CF 5.755 GHz 1001 pts 6.0 MHz/ Span 60.0 MHz

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		5.73736 GHz	-10.95 dBm		
M2	1		5.75248 GHz	-3.32 dBm		
D3	M1	1	35.22 MHz	-0.48 dB		

Date: 24 DEC 2019 13:08:03

CH_H

Ref Level 20.50 dBm Offset 1.00 dB = RBW 100 kHz
ATT 30 dB SWT 1.07 ms = VBW 300 kHz Mode Auto Sweep Count 500/500

1 Frequency Sweep

CF 5.795 GHz 1001 pts 6.0 MHz/ Span 60.0 MHz

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		5.77736 GHz	-12.41 dBm		
M2	1		5.77360 GHz	-4.72 dBm		
D3	M1	1	35.22 MHz	-0.05 dB		

Date: 24 DEC 2019 13:07:02

Test channel	802.11n (HT40)
CH _L	Spectrum Ref Level 20.50 dBm Offset 1.00 dB = RBW 100 kHz Att 30 dB SWI 1.07 ms = VBW 300 kHz Mode Auto Sweep Count 500/500 1 Frequency Sweep

Appendix F: Frequency stability

Voltage VS Frequency stability

Band: I			Test Frequency: 5180.00MHz	
Temperature (°C)	Voltage (V)	Frequency Deviation (Hz)	Frequency Deviation (ppm)	Result
T _N	V _L	-7000.00	-1.35135	PASS
T _N	V _N	-7000.00	-1.35135	PASS
T _N	V _H	-7000.00	-1.35135	PASS

Band: IV			Test Frequency: 5745.00MHz	
Temperature (°C)	Voltage (V)	Frequency Deviation (Hz)	Frequency Deviation (ppm)	Result
T _N	V _L	-18000.00	-3.13316	PASS
T _N	V _N	-18000.00	-3.13316	PASS
T _N	V _H	-18000.00	-3.13316	PASS

Temperature VS Frequency stability

Band: I			Test Frequency: 5180.00MHz	
Voltage (V)	Temperature (°C)	Frequency Deviation (Hz)	Frequency Deviation (ppm)	Result
V _N	-20	-8000.00	-1.54440	PASS
V _N	-10	-9000.00	-1.73745	PASS
V _N	0	-10000.00	-1.93050	PASS
V _N	10	-10000.00	-1.93050	PASS
V _N	20	-10000.00	-1.93050	PASS
V _N	30	-10000.00	-1.93050	PASS
V _N	40	-10000.00	-1.93050	PASS
V _N	50	-11000.00	-2.12355	PASS

Band: IV			Test Frequency: 5745.00MHz	
Voltage (V)	Temperature (°C)	Frequency Deviation (Hz)	Frequency Deviation (ppm)	Result
V _N	-20	-20000.00	-3.48129	PASS
V _N	-10	-21000.00	-3.65535	PASS
V _N	0	-21000.00	-3.65535	PASS
V _N	10	-22000.00	-3.82942	PASS
V _N	20	-22000.00	-3.82942	PASS
V _N	30	-23000.00	-4.00348	PASS
V _N	40	-23000.00	-4.00348	PASS
V _N	50	-23000.00	-4.00348	PASS

-----End of Report-----