

承 認 書

SPECIFICATION FOR APPROVAL

客 戶:
CUSTOMER:

客 戶 料 號:
CUST P/N:

淘 軟 料 號:
BESOFTP/N:

產 品 型 號:
DESC:

日 期:
DATE:

版 本:
Version:

Φ 20.5x40-11Ts-0.08x72P-10mm

2024/10/31

A.0

擬制 PREPARED BY	審核 CHECKED BY	批准 APPROVED BY	客戶承認 CUSTOMER APPROVE

Shenzhen Taoruan Electronics Co., Ltd

Factory Address: Room 702, Building 1, Shijia Old Village, Shijia Community, Matian Street,
Guangming District, Shenzhen


TEL: 138 2488 3512

Version Change History


[illegible]

SPECIFICATION

產品型號: DESC		Φ20.5x40-11Ts-0.08*72-10mm-CLB		版本 Rev: A 0	客戶 CUST: 淘软料号 Fine P/N: 客户料号 CUST P/N:
---------------	--	--------------------------------	--	----------------	--

一、尺寸 DIMENSION:(mm)		A	40.0±1.0
		B	20.5±0.5
		C	0.7±0.05
		D1	12±2
		D2	10±2
		E	3-5mm
		F	42.5±0.5
		G	8.0 ref
		H	2.0±0.2 Max
		I	5.0 ref
		Note: 1. The coil is attached with a magnetic piece, with a size of 42.5 ± 0.5mm, an inner hole of 5.0mm, and a thickness of 0.8 ± 0.1mm, Open L slot 2. Winding width of coil outlet position 6 mm ± 0.5 high-temperature adhesive paper. 3. The back of the magnetic sheet is attached with hand torn circular tape with a diameter of 42 mm (ref) and an inner hole of 7.0 mm (ref). It is a regular double-sided adhesive tape.	

18 * 1.0 small magnetic piece in the middle

二、原理图 SCHEMATIC DIAGRAM:				
				
三、绕线参数 Winding Specification:				

序号 NO	端子 TERMINAL		线径 WIRE	圈数 Turns	绕线方向 Winding Direction
1	S	F	Hot air line 0.08*72P	11Ts	CCW

四、电气特性 ELECTRICAL CHARACTERISTICS:					
温度 TEMPERATURE :25 ± 10 °C , 湿度 RELATIVE HUMIDITY :65 ±20%					
序号 NO	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND.	S-F	5.5uH ± 20% individual coil	100KHz/ 1.0V	LCZ METER 1062B
2	IND.	S-F	8.0uH ± 10% with magnetic plate	100KHz/ 1.0V	LCZ METER 1062B
3	Q 值	S-F	≤ 90.0 (ref) with magnetic plates added	100KHz/ 1.0V	LCZ METER 1062B
4	DCR	S-F	≤90m Ω		LCZ METER 502B

拟制/日期 PREPARED BY/DATE			审核/日期 CHECKED BY/DATE		
------------------------	--	--	-----------------------	--	--