



TESTING LABORATORY
CERTIFICATE # 4821.01



FCC PART 15.249


TEST REPORT

For

W S Trading Limited

1/F, HK SPINNERS BLDG PHASE I & II 800 CHEUNG SHA WAN RD, KOWLOON, Hong Kong

FCC ID: 2AVGAMU21002

Report Type: Original Report	Product Type: SLIM WIRELESS MOUSE
Report Number: <u>RSZ191122834-00</u>	
Report Date: <u>2019-12-12</u>	
Simon Wang 	
Reviewed By: Reviewed By: <u>RF Engineer</u>	
Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	
Prepared By: Prepared By: <u>Simon Wang</u>	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk **. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY.....	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE DESCRIPTIONS.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS.....	7
TEST EQUIPMENT LIST	8
FCC§15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC§15.205, §15.209 & §15.249(D) - RADIATED EMISSIONS.....	10
APPLICABLE STANDARD	10
TEST EQUIPMENT SETUP	10
EUT SETUP	11
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST RESULTS SUMMARY.....	12
TEST DATA	12
FCC§15.215(C) - 20DB EMISSION BANDWIDTH	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA	21

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	SLIM WIRELESS MOUSE
Tested Model	MU21002
Frequency Range	2405~2475MHz
Modulation Technique	GFSK
Antenna Specification	4.0 dBi
Voltage Range	DC 3 V
Date of Test	2019-12-07 to 2019-12-08
Sample serial number	RSZ191122834(Assigned by BACL, Shenzhen)
Received date	2019-11-22
Sample/EUT Status	Good condition

Objective

This type approval report is prepared on behalf of *W S Trading Limited* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

Submitted with part of a system with FCC ID: 2AVGAMU2.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	±5%	
RF Output Power with Power meter	±0.73dB	
RF conducted test with spectrum	±1.6dB	
AC Power Lines Conducted Emissions	±1.95dB	
Emissions, Radiated	Below 1GHz Above 1GHz	±4.75dB ±4.88dB
Temperature	±1°C	
Humidity	±6%	
Supply voltages	±0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing by manufacturer.

7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2405	4	2457
1	2411	5	2463
2	2417	6	2469
3	2451	7	2475

Channel 0, Channel 3 and Channel 7 were selected for testing.

EUT Exercise Software

No software was used.

Equipment Modifications

No modifications were made to the unit tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
N/A	N/A	N/A	N/A

Support Cable Descriptions

Cable Description	Length (m)	From/Port	To
N/A	N/A	N/A	N/A

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Not Applicable
15.205, §15.209, §15.249(d)	Radiated Emissions& Outside of Band Emission	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

Not Applicable: The EUT was powered by battery only.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017-12-22	2020-12-21
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2019-07-22	2020-07-21
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	pre-amplifier	PA-122	181919	2019-04-20	2020-04-20
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
R&S	EMI Test Receiver	ESR3	102455	2019-07-09	2020-07-08
Ducommun technologies	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2019-05-21	2019-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun technologies	Horn Antenna(18-26G)	ARH-4223-02	1007726-04	NCR	NCR
Heatsink Required	Amplifier	QLW-18405536-J0	15964001002	2018-08-01	2019-02-01
Sinoscite	Band Reject filter	BSF2402-2480MN-0898-001	N/A	2019-04-20	2020-04-20

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one PCB antenna which was permanently attached and the antenna gain is 4.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC§15.205, §15.209 & §15.249(d) - RADIATED EMISSIONS**Applicable Standard**

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

As per FCC§15.249 (d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Equipment Setup

The spectrum analyzer or receiver is set as:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average


Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.


All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane for below 1GHz or 1.5 meter for above 1GHz, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the EUT complied with the FCC Part 15.205, 15.209 & §15.249


Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Steve Lan on 2019-12-08 for below 1G and Alen He on 2019-12-07 for above 1G.

Test Mode: Transmitting

30MHz – 1 GHz:

Frequency (MHz)	Corrected Amplitude (dB μ V/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
492.811250	23.44	105.0	H	184.0	-5.6	46.00	22.56
958.775000	34.73	305.0	H	144.0	5.3	46.00	11.27
30.363750	19.70	305.0	H	214.0	-7.9	40.00	20.30
678.202500	28.85	305.0	H	259.0	-1.4	46.00	17.15
583.991250	27.01	390.0	H	84.0	-2.4	46.00	18.99
838.737500	32.95	105.0	V	353.0	2.8	46.00	13.05

Note: Test result PK satisfies the limit value of QP

1 GHz - 25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	FCC Part 15.249&15.209	
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2405MHz)									
2405.00	62.93	PK	315	2.4	H	31.87	94.80	114	19.2
2405.00	59.71	Ave.	315	2.4	H	31.87	91.58	94	2.42
2405.00	58.65	PK	289	1.3	V	31.87	90.52	114	23.48
2405.00	54.26	Ave.	289	1.3	V	31.87	86.13	94	7.87
2356.10	27.97	PK	74	1.9	H	31.77	59.74	74	14.26
2356.10	14.03	Ave.	74	1.9	H	31.77	45.80	54	8.2
2495.70	29.36	PK	143	2.3	H	32.13	61.49	74	12.51
2495.70	13.83	Ave.	143	2.3	H	32.13	45.96	54	8.04
4810.00	52.23	PK	295	2.2	H	5.40	57.63	74	16.37
4810.00	41.56	Ave.	295	2.2	H	5.40	46.96	54	7.04
7215.00	48.75	PK	185	1.7	H	12.02	60.77	74	13.23
7215.00	37.55	Ave.	185	1.7	H	12.02	49.57	54	4.43
Middle Channel (2451MHz)									
2451.00	64.72	PK	316	1.9	H	32.03	96.75	114	17.3
2451.00	61.67	Ave.	316	1.9	H	32.03	93.70	94	0.3
2451.00	62.01	PK	8	2.4	V	32.03	94.04	114	20.0
2451.00	58.86	Ave.	8	2.4	V	32.03	90.89	94	3.1
4902.00	52.05	PK	344	1.6	H	6.43	58.48	74	15.52
4902.00	41.01	Ave.	344	1.6	H	6.43	47.44	54	6.56
7353.00	48.91	PK	18	2.1	H	12.21	61.12	74	12.88
7353.00	37.65	Ave.	18	2.1	H	12.21	49.86	54	4.14

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	FCC Part 15.249&15.209	
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel (2475 MHz)									
2475.00	64.95	PK	250	1.9	H	32.13	97.08	114	16.9
2475.00	61.83	AV	250	1.9	H	32.13	93.96	94	0.04
2475.00	59.85	PK	213	2.3	V	32.13	91.98	114	22.0
2475.00	55.48	AV	213	2.3	V	32.13	87.61	94	6.4
2349.80	27.86	PK	215	2.1	H	31.64	59.50	74	14.50
2349.80	13.76	AV	215	2.1	H	31.64	45.40	54	8.60
2483.70	28.67	PK	337	1.4	H	32.13	60.80	74	13.20
2483.70	15.54	AV	337	1.4	H	32.13	47.67	54	6.33
4950.00	52.23	PK	224	1.7	H	6.95	59.18	74	14.82
4950.00	41.25	AV	224	1.7	H	6.95	48.20	54	5.80
7425.00	49.58	PK	21	2.1	H	12.31	61.89	74	12.11
7425.00	38.33	AV	21	2.1	H	12.31	50.64	54	3.36


Note:

Corrected Amplitude = Corrected Factor + Reading


Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor

Margin = Limit- Corr. Amplitude

The emission more than 20dB below the limit was not required to be recorded.


**Pre-scan with Low channel Peak
Horizontal**

Date: 7.DEC.2019 15:01:21




Date: 7.DEC.2019 16:01:16

Vertical




Date: 7.DEC.2019 15:18:23




Date: 7.DEC.2019 16:12:30


**Average value for the peak point at pre-scan
Horizontal**




Date: 7.DEC.2019 15:06:49





Date: 7.DEC.2019 16:06:47



Vertical





FCC§15.215(c) - 20dB EMISSION BANDWIDTH

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that indicated 20dB bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions



Temperature:	23 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa


The testing was performed by Alen He on 2019-12-07.

Test Mode: Transmitting

Please refer to the following table and plots.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2405	3.813
Middle	2451	2.562
High	2475	2.656

Low Channel**Middle Channel**

High Channel

***** END OF REPORT *****