

FCC RF Exposure Evaluation

1. Product Information

FCC ID	2AVGT-H6
Product name	Projector
Model number	H6, D5, D5+, D6, D6+, D7, D7+, D8, D8+, D9, E3, E5, E6, E7, E8, E9, S6, S6+, S7, S7+, S8, S8+, S9, S9+, H6+, H7, H7+, H8, H8+, H9
Model Declaration	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power supply	Input: 5V $\overline{\text{---}}$ 3A For AC Adapter Input:100-240V~, 50/60Hz , 0.6A Max Output: 5V $\overline{\text{---}}$ 3000mA
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.0 (DSS) GFSK for Bluetooth V4.0(DTS) IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM,QPSK,BPSK) IEEE 802.11a/n/ac: OFDM
Antenna Type	Internal Antenna
Antenna Gain	0dBi
Hardware version	EP.RK3128.V56.XQ6 V1.2//2018.12.21
Software version	1.0.0.58
FCC Operation frequency	2402MHz-2480MHz 2412MHz-2462MHz 5180MHz-5240MHz 5745MHz-5825MHz 5260MHz-5320MHz 5500MHz-5700MHz
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	mobile device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093: Radiofrequency radiation exposure evaluation](#): mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

Internal Antenna can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Note
Antenna	Internal Antenna	2402MHz-2480MHz 2412MHz-2462MHz 5180MHz - 5240MHz 5745MHz -5825MHz 5260MHz-5320MHz 5500MHz-5700MHz	0dBi	Bluetooth, 2.4G WLAN, 5G WLAN Antenna

6. Conducted Power

[BT Max Conducted Power]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	0.718
	39	2441	-0.729
	78	2480	-2.322
$\pi/4$ DQPSK	0	2402	3.088
	39	2441	1.526
	78	2480	-0.092
8DPSK	0	2402	3.525
	39	2441	2.137
	78	2480	0.451

[BLE Max Conducted Power]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BT LE	0	2402	0.697
	19	2440	-0.773
	39	2480	-2.488

[2.4G-WIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
11B	1	2412	12.41
	6	2437	12.63
	11	2462	13.21
11G	1	2412	13.44
	6	2437	14.07
	11	2462	14.42
11N20SISO	1	2412	13.62
	6	2437	14.51
	11	2462	14.37
11N40SISO	3	2422	13.06
	6	2437	13.72
	9	2452	14.32

[5.2G-WIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
11A Mode	36	5180	8.61
	40	5200	9.19
	48	5240	8.73
11N20 SISO Mode	36	5180	7.9
	40	5200	8.01
	48	5240	7.45
11N40 SISO Mode	38	5190	9.51
	46	5230	9.51
11AC20 SISO Mode	36	5180	9.54
	40	5200	9.61
	48	5240	9.58
11AC40 SISO Mode	38	5190	9.23
	46	5230	9.21
11AC80 SISO Mode	42	5210	9.31

[5.8G-WIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
11A Mode	149	5745	9.63
	157	5785	9.66
	165	5825	10.64
11N20 SISO Mode	149	5745	9.2
	157	5785	9.38
	165	5825	9.27
11N40 SISO Mode	151	5755	9.99
	159	5795	10.08
11AC20 SISO Mode	149	5745	9.54
	157	5785	9.61
	165	5825	9.58
11AC40 SISO Mode	151	5755	9.23
	159	5795	9.19
11AC80 SISO Mode	155	5775	10.16

[5.3G Max Conducted Power]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
11A Mode	52	5260	9.24
	56	5280	9.07
	64	5320	9.02
11N20 SISO Mode	52	5260	9.23
	56	5280	9.05
	64	5320	9.51
11N40 SISO Mode	54	5270	9.73
	62	5310	9.47
11AC20 SISO Mode	52	5260	9.76
	56	5280	9.56
	64	5320	9.41
11AC40 SISO Mode	54	5270	9.63
	62	5310	9.37
11AC80 SISO Mode	58	5290	9.79

[5.5G Max Conducted Power]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
11A Mode	100	5500	9.16
	120	5600	9.72
	140	5700	9.47
11N20 SISO Mode	100	5500	9.81
	120	5600	9.24
	140	5700	9.0
11N40 SISO Mode	149	5510	9.52
	157	5590	9.65
	165	5670	9.72
11AC20 SISO Mode	100	5500	9.28
	120	5600	9.35
	140	5700	9.03
11AC40 SISO Mode	149	5510	9.08
	157	5590	9.84
	165	5670	9.27
11AC80 SISO Mode	106	5530	9.36
	122	5610	9.95

7. Manufacturing Tolerance

<BT >

GFSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	-2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3.0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3.0	2.0	0.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

<BT LE >

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	-2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

<2.4GWLAN >

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20SISO (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40SISO (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

<5.2GWLAN >

11A (5.2G) (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	8.0	9.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 SISO (5.2G) (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	7.0	8.0	7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 SISO (5.2G) (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	9.0	9.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
11AC20 SISO (5.2G) (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 SISO (5.2G) (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	9.0	9.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
11AC80 SISO (5.2G) (Average)			
Channel	Channel 42	/	/
Target (dBm)	9.0	/	/
Tolerance $\pm$ (dB)	1.0	/	/

<5.8GWLAN>

11A (5.8G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	9.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 SISO (5.8G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 SISO (5.8G) (Average)			
Channel	Channel 151	Channel 59	/
Target (dBm)	9.0	10.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
11AC20 SISO (5.8G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 SISO (5.8G) (Average)			
Channel	Channel 151	Channel 59	/
Target (dBm)	9.0	9.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
11AC80 SISO (5.8G) (Average)			
Channel	Channel 155	/	/
Target (dBm)	10.0	/	/
Tolerance $\pm$ (dB)	1.0	/	/

<5.3GWLAN >

11A (5.3G) (Average)			
Channel	Channel 52	Channel 56	Channel 64
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 SISO (5.3G) (Average)			
Channel	Channel 52	Channel 56	Channel 64
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 SISO (5.3G) (Average)			
Channel	Channel 54	Channel 62	/
Target (dBm)	10.0	9.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
11AC20 SISO (5.3G) (Average)			
Channel	Channel 52	Channel 56	Channel 64
Target (dBm)	10.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 SISO (5.3G) (Average)			
Channel	Channel 54	Channel 62	/
Target (dBm)	10.0	9.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
11AC80 SISO (5.3G) (Average)			
Channel	Channel 58	/	/
Target (dBm)	10.0	/	/
Tolerance $\pm$ (dB)	1.0	/	/

<5.5GWLAN>

11A (5.5G) (Average)			
Channel	Channel 100	Channel 120	Channel 140
Target (dBm)	9.0	10.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 SISO (5.5G) (Average)			
Channel	Channel 100	Channel 120	Channel 140
Target (dBm)	10.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 SISO (5.5G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC20 SISO (5.5G) (Average)			
Channel	Channel 100	Channel 120	Channel 140
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 SISO (5.5G) (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	9.0	10.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC80 SISO (5.5G) (Average)			
Channel	Channel 106	Channel 122	/
Target (dBm)	9.0	10.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/

8. Measurement Results

8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[Antenna]

BT

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
GFSK	1.0	1.2589	0	0.0003	1.0000
$\pi/4$ DQPSK	4.0	2.5119	0	0.0005	1.0000
8DPSK	4.0	2.5119	0	0.0005	1.0000

BLE

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
BT LE	1.0	1.2589	0	0.0003	1.0000

2.4GWIFI

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
IEEE 802.11b	14.0	25.1189	0	0.0050	1.0000
IEEE 802.11g	15.0	31.6228	0	0.0063	1.0000
IEEE 802.11n HT20	15.0	31.6228	0	0.0063	1.0000
IEEE 802.11n HT40	15.0	31.6228	0	0.0063	1.0000

5.2GWIFI

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
IEEE 802.11a	10.0	10.0000	0	0.0020	1.0000
IEEE 802.11n20	9.0	7.9433	0	0.0016	1.0000
IEEE 802.11n40	10.0	10.0000	0	0.0020	1.0000
IEEE 802.11ac20	10.0	10.0000	0	0.0020	1.0000
IEEE 802.11ac40	10.0	10.0000	0	0.0020	1.0000
IEEE 802.11ac80	10.0	10.0000	0	0.0020	1.0000

5.8GWIFI

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
IEEE 802.11a	11.0	12.5893	0	0.0025	1.0000
IEEE 802.11n20	10.0	10.0000	0	0.0020	1.0000
IEEE 802.11n40	11.0	12.5893	0	0.0025	1.0000
IEEE 802.11ac20	10.0	10.0000	0	0.0020	1.0000
IEEE 802.11ac40	10.0	10.0000	0	0.0020	1.0000
IEEE 802.11ac80	11.0	12.5893	0	0.0025	1.0000

5.3GWLAN

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
IEEE 802.11a	10	10.0000	0	0.0020	1.0000
IEEE 802.11n20	10	10.0000	0	0.0020	1.0000
IEEE 802.11n40	11	12.5893	0	0.0025	1.0000
IEEE 802.11ac20	11	12.5893	0	0.0025	1.0000
IEEE 802.11ac40	11	12.5893	0	0.0025	1.0000
IEEE 802.11ac80	11	12.5893	0	0.0025	1.0000

5.5GWLAN

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
IEEE 802.11a	11	12.5893	0	0.0025	1.0000
IEEE 802.11n20	11	12.5893	0	0.0025	1.0000
IEEE 802.11n40	11	12.5893	0	0.0025	1.0000
IEEE 802.11ac20	10	10.0000	0	0.0020	1.0000
IEEE 802.11ac40	11	12.5893	0	0.0025	1.0000
IEEE 802.11ac80	11	12.5893	0	0.0025	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

8.2 Simultaneous Transmission MPE**9. Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....THE END OF REPORT.....