



FCC TEST REPORT

FCC ID: 2AVH8PB-LP15W

Product Name	:	Moblie Power Bank
Model Name	:	PB-LP15W
Additional model		PB-LP27W, PB-LP16, PB-LP20, PB-LP27
Brand Name	:	ALTIZURE
Report No.	:	PTC19110602602E-FC01
Prepared for		
Shenzhen Shenqing New Material Co. LTD.		
Room 2003,Building C2, Nanshan Zhiyuan, Nanshan District, Shenzhen		
Prepared by		
Dongguan Precise Testing & Certification Corp., Ltd.		
Building D, Baoding Technology Park, Guangming Road 2, Guangming Community, Dongcheng District, Dongguan, Guangdong, China		



1 TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Shenqing New Material Co. LTD.
Address : Room 2003,Building C2, Nanshan Zhiyuan, Nanshan District, Shenzhen
Manufacture's name : Shenzhen Shenqing New Material Co. LTD.
Address : Room 2003,Building C2, Nanshan Zhiyuan, Nanshan District, Shenzhen
Product name : Moblie Power Bank
Model name : ALTIZURE
Additional model : PB-LP15W, PB-LP27W, PB-LP16, PB-LP20, PB-LP27
Standards : FCC CFR47 Part 15C
Test procedure : ANSI C63.10:2013
Test Date : Dec 1, 2019 to Dec 4.2019
Date of Issue : Dec 4.2019
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Leo Yang".

Leo Yang / Engineer

Technical Manager:

A handwritten signature in black ink that appears to read "Chris Du".

Chris Du / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION.....	2
2 TEST SUMMARY.....	4
3 TEST FACILITY.....	5
4 GENERAL INFORMATION.....	6
4.1 GENERAL DESCRIPTION OF E.U.T.....	6
4.2 TEST MODE.....	7
5 EQUIPMENT DURING TEST.....	8
5.1 EQUIPMENTS LIST.....	8
5.2 MEASUREMENT UNCERTAINTY.....	8
5.3 DESCRIPTION OF SUPPORT UNITS.....	11
6 CONDUCTED EMISSION.....	12
6.1 E.U.T. OPERATION.....	12
6.2 EUT SETUP.....	12
6.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	13
6.4 MEASUREMENT PROCEDURE.....	13
6.5 CONDUCTED EMISSION LIMIT.....	13
6.6 MEASUREMENT DESCRIPTION.....	13
6.7 CONDUCTED EMISSION TEST RESULT.....	13
7 RADIATED SPURIOUS EMISSIONS.....	16
7.1 EUT OPERATION.....	16
7.2 TEST SETUP.....	17
7.3 SPECTRUM ANALYZER SETUP.....	18
7.4 TEST PROCEDURE.....	17
7.5 SUMMARY OF TEST RESULTS.....	20
8 ANTENNA REQUIREMENT.....	23
8.1 ANTENNA REQUIREMENT.....	23
8.2 RESULT.....	23
9 TEST PHOTOS.....	24
10 EUT PHOTOS.....	26



2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.209	PASS



Report No.: PTC19110602602E-FC01

3 TEST FACILITY

Dongguan Precise Testing & Certification Corp., Ltd.

Address: Building D, Baoding Technology Park, Guangming Road2, Dongcheng District, Dongguan,
Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1



4 General Information

4.1 General Description of E.U.T.

Product Name	:	Moblie Power Bank
Model Name	:	PB-LP15W
Additional models	:	PB-LP27W, PB-LP16, PB-LP20, PB-LP27
Operating frequency	:	110-205KHz
Numbers of Channel	:	20 Channels
Antenna Type	:	Inductive Loop Coil Antenna
Antenna Gain	:	0dBi
Type of Modulation	:	ASK
Power supply	:	DC 5V3A,



4.2 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode or test configuration mode mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH01
Mode 2	CH10
Mode 3	CH20
Mode 4	Keeping TX+Charging mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX+Charging mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH10
Mode 3	CH20

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	0.110	6	0.135	11	0.160	16	0.185
2	0.115	7	0.140	12	0.165	17	0.190
3	0.120	8	0.145	13	0.170	18	0.195
4	0.125	9	0.150	14	0.175	19	0.200
5	0.130	10	0.155	15	0.180	20	0.205



5 Equipment During Test

5.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-30GHz	Aug. 21, 2020
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug. 21, 2020
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug. 28, 2020
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug. 28, 2020

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug. 28, 2020
Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	Aug. 28, 2020
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Aug. 22, 2020
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Aug. 21, 2020
Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	Aug. 21, 2020
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-40GHz	Aug. 28, 2020
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Apr. 13, 2020
Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	Aug. 21, 2020
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	14GHz-40GHz	Apr. 13, 2020
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Aug. 21, 2020



Report No.: PTC19110602602E-FC01

Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Aug. 21, 2020
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug. 21, 2020

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug. 28, 2020
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Aug. 21, 2020
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Aug. 21, 2020



5.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	



Report No.: PTC19110602602E-FC01

5.3 Description of Support Units

Equipment	Model No.	Series No.
Adapter	Model: PS65B150Y3000S Input: AC120V, 60Hz, 1.5A Output: DC 5V, 3000mA	N/A
Mobile Phone	Samsung S9	N/A

6 Conducted Emission

Test Requirement:	: FCC CFR 47 Part 15 Section 15.207
Test Method:	: ANSI C63.10:2013
Test Result:	: PASS
Frequency Range:	: 150kHz to 30MHz
Class/Severity:	: Class B
Detector:	: Peak for pre-scan (9kHz Resolution Bandwidth)


6.1 E.U.T. Operation

Operating Environment :


Temperature:	: 25.5 °C
Humidity:	: 51 % RH
Atmospheric Pressure:	: 101.2kPa
Test Voltage	: AC 120V/60Hz

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10: 2013



6.3 Test SET-UP (Block Diagram of Configuration)



6.4 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.6 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.7 Conducted Emission Test Result

Pass.




Line -120V/60Hz:



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBμV	Emission Level dBμV	Limit dBμV	Over Limit dB	Remark
1.	0.198	0.28	9.59	30.13	40.00	53.71	-13.71	Average
2.	0.198	0.28	9.59	47.49	57.36	63.71	-6.35	QP
3.	0.289	0.36	9.60	19.12	29.08	50.54	-21.46	Average
4.	0.289	0.36	9.60	39.23	49.19	60.54	-11.35	QP
5.	0.389	0.40	9.60	14.67	24.67	48.08	-23.41	Average
6.	0.389	0.40	9.60	33.88	43.88	58.08	-14.20	QP
7.	1.276	0.46	9.61	9.71	19.78	46.00	-26.22	Average
8.	1.276	0.46	9.61	26.09	36.16	56.00	-19.84	QP
9.	2.750	0.47	9.63	10.63	20.73	46.00	-25.27	Average
10.	2.750	0.47	9.63	24.39	34.49	56.00	-21.51	QP
11.	4.224	0.48	9.66	12.33	22.47	46.00	-23.53	Average
12.	4.224	0.48	9.66	25.16	35.30	56.00	-20.70	QP



Neutral -120V/60Hz:



Trace: 7

No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBμV	Emission Level dBμV	Limit dBμV	Over Limit dB	Remark
1.	0.194	0.27	9.61	26.99	36.87	53.84	-16.97	Average
2.	0.194	0.27	9.61	43.85	53.73	63.84	-10.11	QP
3.	0.299	0.37	9.62	19.11	29.10	50.28	-21.18	Average
4.	0.299	0.37	9.62	37.09	47.08	60.28	-13.20	QP
5.	0.502	0.43	9.63	11.08	21.14	46.00	-24.86	Average
6.	0.502	0.43	9.63	31.82	41.88	56.00	-14.12	QP
7.	0.796	0.45	9.64	7.07	17.16	46.00	-28.84	Average
8.	0.796	0.45	9.64	27.74	37.83	56.00	-18.17	QP
9.	2.750	0.47	9.66	8.88	19.01	46.00	-26.99	Average
10.	2.750	0.47	9.66	20.34	30.47	56.00	-25.53	QP
11.	4.247	0.48	9.69	10.67	20.84	46.00	-25.16	Average
12.	4.247	0.48	9.69	22.76	32.93	56.00	-23.07	QP



7 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209
 Test Method : ANSI C63.10:2013
 Test Result : PASS
 Measurement Distance : 3m
 Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

7.1 EUT Operation


Operating Environment :

Temperature : 23.5 °C
 Humidity : 51.1 % RH
 Atmospheric Pressure : 101.2kPa


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP




7.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
8. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



7.5 Summary of Test Results

Test Frequency: 9kHz-30MHz




Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	degree (dge)
0.0355	59.92	19.30	2.53	0	81.75	136.50	-54.75	Peak	15
0.0355	57.11	19.30	2.53	0	78.94	116.50	-37.56	AV	15
0.1104	75.53	19.30	2.53	0	97.36	133.60	-36.24	Peak	33
0.1104	73.74	19.30	2.53	0	95.57	113.60	-18.03	AV	33
0.1216	70.68	19.29	2.54	0	92.51	126.08	-33.57	Peak	124
0.1216	68.69	19.29	2.54	0	90.52	106.08	-15.56	AV	124
0.1369	68.24	19.36	2.55	0	90.15	120.79	-30.64	Peak	101
0.1369	66.71	19.36	2.55	0	88.62	100.79	-12.17	AV	101
0.2220	53.85	19.63	2.59	0	76.07	117.21	-41.14	Peak	324
0.2220	51.67	19.63	2.59	0	73.89	97.21	-23.32	AV	324
0.5220	43.11	20.32	2.60	0	66.03	72.86	-6.83	QP	0

Remark: According to FCC Part 15.209(d), the emission limits for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emission limits in these three bans are based on measurements employing an average detector.




Test Frequency: 30MHz ~ 1GHz

Horizontal:



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamp Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	36.001	1.52	12.18	31.47	29.90	15.27	40.00	-24.73	QP
2.	61.346	2.43	11.51	44.39	29.94	28.39	40.00	-11.61	QP
3.	166.651	4.15	13.55	51.11	30.03	38.78	43.50	-4.72	QP
4.	239.147	4.77	12.20	50.23	30.16	37.04	46.00	-8.96	QP
5.	370.702	5.53	14.57	40.42	30.60	29.92	46.00	-16.08	QP
6.	483.910	5.98	16.73	30.92	30.87	22.76	46.00	-23.24	QP

Vertical:



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamplifier Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	61.346	2.43	11.51	44.63	29.94	28.63	40.00	-11.37	QP
2.	85.898	3.01	8.79	35.89	29.97	17.72	40.00	-22.28	QP
3.	166.068	4.14	13.59	46.62	30.03	34.32	43.50	-9.18	QP
4.	238.310	4.76	12.18	43.44	30.16	30.22	46.00	-15.78	QP
5.	379.914	5.57	14.65	36.51	30.63	26.10	46.00	-19.90	QP
6.	824.597	6.90	21.50	26.27	31.14	23.53	46.00	-22.47	QP



8 Antenna Requirement

8.1 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

8.2 Result


The antenna is inductive loop coil antenna which permanently attached, and meets the requirement.

9 TEST PHOTOS

Conducted Emissions




Radiated Spurious Emissions
Test Frequency From 9KHz-30MHz





Test frequency from 30MHz-1000MHz







10 EUT PHOTOS














*****THE END REPORT*****