



RADIO TEST REPORT

Report No:STS1912036W03

Issued for

Shanghai Meitu Comprehensive Health Management Limited
Company

Room 3114, No.26, Guoding Road, Yangpu District,
Shanghai, China

Product Name:	meitueve
Brand Name:	meitu
Model Name:	MS1902
Series Model:	N/A
FCC ID:	2AVIV-MS1902
Test Standard:	FCC Part 15.407

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's Name..... : Shanghai Meitu Comprehensive Health Management Limited Company
Address : Room 3114, No.26, Guoding Road, Yangpu District, Shanghai, China
Manufacture's Name..... : Kingtronics Corporation Of Elec.& Mech. Technology (Zhangzhou) Co., Ltd.
Address : No.20 Longchi Road, Longchi Industrial Park, Zhangzhou Taiwanese Investment Zone, Fujian, China

Product Description

Product Name..... : meitueve
Brand Name : meitu
Model Name : MS1902
Series Model..... : N/A

Test Standards : FCC Part15.407

Test Procedure..... ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date of receipt of test item : 10 Dec. 2019

Date (s) of performance of tests : 10 Dec. 2019 ~ 20 Dec. 2019

Date of Issue..... : 20 Dec. 2019

Test Result..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sunday Hu)

Authorized Signatory :

(Vita Li)





Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6#
1.1 TEST FACTORY	7#
1.2 MEASUREMENT UNCERTAINTY	7#
2 . GENERAL INFORMATION	8#
2.1 GENERAL DESCRIPTION OF THE EUT	8#
2.2 DESCRIPTION OF TEST MODES	11#
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12#
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	13#
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	14#
3 . EMC EMISSION TEST	15#
3.1 CONDUCTED EMISSION MEASUREMENT	15#
3.2 RADIATED EMISSION AND (BANDEDGE) MEASUREMENT	19#
4. CONDUCTED SPURIOUS EMISSIONS AND BANDEDGE	34#
4.1 LIMIT	34#
4.2 TEST PROCEDURE	34#
4.3 DEVIATION FROM STANDARD	34#
4.4 TEST SETUP	35#
4.5 EUT OPERATION CONDITIONS	35#
4.6 TEST RESULTS	35#
5. POWER SPECTRAL DENSITY TEST	36#
5.1 LIMIT	36#
5.2 TEST PROCEDURE	36#
5.3 DEVIATION FROM STANDARD	37#
5.4 TEST SETUP	37#
5.5 EUT OPERATION CONDITIONS	37#
5.6 TEST RESULTS	37#
6. BANDWIDTH MEASUREMENT	39#
6.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	39#
6.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	41#
6.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	43#
7. MAXIMUM CONDUCTED OUTPUT POWER	45#
7.1 LIMIT	45#
7.2 TEST PROCEDURE	45#
7.3 DEVIATION FROM STANDARD	45#



Table of Contents	Page
7.4 TEST SETUP	45#
7.5 EUT OPERATION CONDITIONS	45#
7.6 TEST RESULTS	46#
8. AUTOMATICALLY DISCONTINUE TRANSMISSION	50#
8.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	50#
8.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	50#
9. ANTENNA REQUIREMENT	51#
9.1 STANDARD REQUIREMENT	51#
9.2 EUT ANTENNA	51#
APPENDIX - PHOTOS OF TEST SETUP	52#



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	20 Dec. 2019	STS1912036W03	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

§ 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
§ 15.407 (2) (26 dB) / § 15.407 (e) (6 dB) / § 15.407 (a) (99%)	26dB/6dB & 99% Bandwidth	PASS
15.407(a) (1).(2).(3).(4).(5)	Maximum Conducted Output Power	PASS
15.407(b) & 15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(b)7	Conducted Emission And (bandedge Emissions) Measurement	PASS
15.407(a) (1).(2).(3).(4).(5)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203/15.204	Antenna Requirement	PASS

NOTE:

(1) 'N/A' denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 30-1GHz	$\pm 6.7\text{dB}$
4	All emissions, radiated 1G-6GHz	$\pm 5.5\text{dB}$
5	All emissions, radiated >6G	$\pm 5.8\text{dB}$
6	Conducted Emission (9KHz-150KHz)	$\pm 4.43\text{dB}$
7	Conducted Emission (150KHz-30MHz)	$\pm 5\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	meitueve	
Trade Name	meitu	
Model Name	MS1902	
Series Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a meitueve	
	Operation Frequency:	IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz
		IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.310GHz
		IEEE 802.11ac(VHT80): 5.210GHz
	Modulation Type:	IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz
		IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz
		IEEE 802.11ac(VHT80): 5.775GHz
	Antenna Designation:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM
		802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM
		802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM
	See Note 2	
	17.61 dBm	
	More details of EUT technical specification, please refer to the User's Manual.	
Test Channel	Please refer to the Note 2.	
Adapter	Input: AC 100-240V, 50/60Hz, 1.5A Output: DC 12V, 5A	
Hardware version number	N/A	
Software version number	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual.	

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



1. Operation Frequency of channel			
5.180GHz-5.240GHz		5.745GHz-5.825GHz	
Channel	Frequency	Channel	Frequency
36	5180	149	5745
38	5190	151	5755
40	5200	153	5765
42	5210	157	5785
44	5220	159	5795
46	5230	161	5805
48	5240	165	5825

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n(HT20) /ac (VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	149	5745
40	5200	157	5785
48	5240	165	5825

For 802.11n(HT40) /ac (VHT40)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	151	5755
46	5230	159	5795

For 802.11ac (VHT80)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	155	5775



2. KDB 662911 D01 Multiple Transmitter Output v02r01

2) Directional Gain Calculations for In-Band Measurements

a) Basic methodology with NANT transmit antennas, each with the same directional gain G_{ANT} dBi, being driven by NANT transmitter outputs of equal power. Directional gain is to be computed as follows:

(i) If any transmit signals are correlated with each other,


Directional gain = $G_{ANT} + 10 \log(NANT)$ dBi

(ii) If all transmit signals are completely uncorrelated with each other,

Directional gain = G_{ANT}

{ Directional gain}

Ant	Brand	Model Name	Ant Type	Connector	Gain (dBi)	NOTE
A	meitu	MS1902	Ant. A: Internal Antennal, Ant. B: Internal Antennal,	N/A	Antenna number: 2Antenna A gain : -2dBiAntenna B gain : -2dBiMIMO technology Directional gain=1.01dBi	WLAN Ant





2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 3	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 4	TX IEEE 802.11ac VHT20 CH36&CH40&CH48	NSS1 MCS0
Mode 5	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 6	TX IEEE 802.11ac VHT20 CH149&CH157&CH165	NSS1 MCS0
Mode 7	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 8	TX IEEE 802.11ac VHT40 CH38&CH46	NSS1 MCS0
Mode 9	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 10	TX IEEE 802.11ac VHT40 CH151&CH159	NSS1 MCS0
Mode 11	TX IEEE 802.11ac VHT80 CH42	NSS1 MCS0
Mode 12	TX IEEE 802.11ac VHT80 CH155	NSS1 MCS0


- Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.

AC Conducted Emission


Test Case	
AC Conducted Emission	Mode 13: Keeping TX + WLAN Link

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test





2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-3	Adapter	N/A	N/A	N/A	N/A
C-2	DC Cable	N/A	110cm	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Notebook	DELL	VOSTRO.3800	N/A	N/A
C-1	USB Cable	N/A	100cm	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESCI	101427	2019.7.29	2020.7.28
Signal Analyzer	Agilent	N9020A	MY51110105	2019.03.02	2020.03.01
Active loop Antenna	ZHINAN	ZN30900C	16035	2018.03.11	2021.03.10
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2020.11.1
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-1343	2018.10.19	2021.10.18
Horn Antenna (18-40GHz)	A-INFO	LB-180400-KF	J211020657	2018.03.11	2021.03.10
Pre-mpifier (18G-40G)	SKET	LNPA_1840-50	SK2018101801	2019.10.22	2020.10.21
Spectrum Analyzer	R&S	FSV40-N	101823	2019.06.05	2020.06.04
Pre-Amplifier(0.1 M-3GHz)	EM	EM330	060665	2019.10.9	2020.10.8
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-4 5	SK2018080901	2019.10.12	2020.10.11
Temperature & Humidity	HH660	Mieo	N/A	2019.10.12	2020.10.11
Trn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Test SW	BULUN	BL410-E/18.905			

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2019.7.29	2020.7.28
LISN	R&S	ENV216	101242	2019.10.9	2020.10.8
LISN	EMCO	3810/2NM	23625	2019.10.9	2020.10.8
Temperature & Humidity	HH660	Mieo	N/A	2019.10.12	2020.10.11
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 CE)			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2019.10.9	2020.10.8
Signal Analyzer	Agilent	N9020A	MY49100060	2019.10.9	2020.10.8
Temperature & Humidity	HH660	Mieo	N/A	2019.10.12	2020.10.11
Test SW	FARAD	LZ-RF /LzRf-3A3			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS


Temperature:	26.3(C)	Relative Humidity:	52%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode :	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1660	29.02	20.54	49.56	65.16	-15.60	QP
2	0.1660	7.73	20.54	28.27	55.16	-26.89	AVG
3	0.5340	16.59	20.01	36.60	56.00	-19.40	QP
4	0.5340	7.30	20.01	27.31	46.00	-18.69	AVG
5	1.2060	14.45	19.52	33.97	56.00	-22.03	QP
6	1.2060	4.81	19.52	24.33	46.00	-21.67	AVG
7	2.8580	12.96	20.14	33.10	56.00	-22.90	QP
8	2.8580	2.07	20.14	22.21	46.00	-23.79	AVG
9	9.8580	11.15	20.55	31.70	60.00	-28.30	QP
10	9.8580	1.82	20.55	22.37	50.00	-27.63	AVG
11	26.1420	12.58	21.66	34.24	60.00	-25.76	QP
12	26.1420	7.69	21.66	29.35	50.00	-20.65	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit

100.0 dBuV






Temperature:	26.3(C)	Relative Humidity:	52%RH
Test Voltage	AC 120V/60Hz	Phase:	N
Test Mode	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1532	28.01	20.54	48.55	65.82	-17.27	QP
2	0.1532	12.04	20.54	32.58	55.82	-23.24	AVG
3	0.4516	18.17	20.16	38.33	56.85	-18.52	QP
4	0.4516	8.58	20.16	28.74	46.85	-18.11	AVG
5	1.3740	13.49	19.61	33.10	56.00	-22.90	QP
6	1.3740	5.26	19.61	24.87	46.00	-21.13	AVG
7	3.4940	13.01	20.23	33.24	56.00	-22.76	QP
8	3.4940	2.83	20.23	23.06	46.00	-22.94	AVG
9	7.1420	12.33	20.35	32.68	60.00	-27.32	QP
10	7.1420	2.70	20.35	23.05	50.00	-26.95	AVG
11	19.5220	10.56	21.37	31.93	60.00	-28.07	QP
12	19.5220	6.21	21.37	27.58	50.00	-22.42	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit





3.2 RADIATED EMISSION AND (BANDEDGE) MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7& 15.205/209(a), then the (a); limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	68.2	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed test to three orthogonal axis. The worst case emissions were reported

3.2.2 DEVIATION FROM TEST STANDARD


No deviation

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	23.7(C)	Relative Humidity:	57%RH
Test Voltage:	AC 120V/60Hz	Polarization :	--
Test Mode:	TX Mode		


Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.




**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature	23.7(C)	Relative Humidity:	57%RH
Test Voltage	AC 120V/60Hz	Polarization:	Horizontal
Test Mode	Mode 1~12(Mode 4 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	132.8200	51.15	-18.17	32.98	43.50	-10.52	QP
2	197.8100	60.59	-21.12	39.47	43.50	-4.03	QP
3	399.5700	52.70	-11.16	41.54	46.00	-4.46	QP
4	597.4500	46.88	-5.85	41.03	46.00	-4.97	QP
5	797.2700	40.75	-2.03	38.72	46.00	-7.28	QP
6	996.1200	42.23	2.04	44.27	54.00	-9.73	QP

Remark:

1. Margin = Result (Result = Reading + Factor)-Limit






Temperature	23.7(C)	Relative Humidity:	57%RH
Test Voltage	AC 120V/60Hz	Polarization:	Vertical
Test Mode	Mode 1~12(Mode 4 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34.8500	50.30	-15.34	34.96	40.00	-5.04	QP
2	263.7700	49.15	-14.75	34.40	46.00	-11.60	QP
3	398.6000	49.79	-11.20	38.59	46.00	-7.41	QP
4	600.3600	47.36	-5.84	41.52	46.00	-4.48	QP
5	800.1800	40.57	-2.05	38.52	46.00	-7.48	QP
6	1000.0000	43.26	2.04	45.30	54.00	-8.70	QP

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit





3.2.8 TEST RESULTS (Above 1000 MHz)

Band I 5150-5250MHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Corrected Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11n20/ 5180 MHz)										
3247.73	44.08	44.70	6.70	28.20	-9.80	34.28	68.20	-33.92	Pk	Vertical
3247.73	40.86	44.70	6.70	28.20	-9.80	31.06	54.00	-22.94	AV	Vertical
3252.93	44.63	44.70	6.70	28.20	-9.80	34.83	68.20	-33.37	Pk	Horizontal
3252.93	40.97	44.70	6.70	28.20	-9.80	31.17	54.00	-22.83	AV	Horizontal
3994.74	39.64	44.20	7.90	29.70	-6.60	33.04	68.20	-35.16	Pk	Vertical
3994.74	37.09	44.20	7.90	29.70	-6.60	30.49	54.00	-23.51	AV	Vertical
3985.38	39.41	44.20	7.90	29.70	-6.60	32.81	68.20	-35.39	Pk	Horizontal
3985.38	36.91	44.20	7.90	29.70	-6.60	30.31	54.00	-23.69	AV	Horizontal
7228.87	37.85	43.50	11.40	35.50	3.40	41.25	68.20	-26.95	Pk	Vertical
7228.87	34.73	43.50	11.40	35.50	3.40	38.13	54.00	-15.87	AV	Vertical
7221.17	36.79	43.50	11.40	35.50	3.40	40.19	68.20	-28.01	Pk	Horizontal
7221.17	34.05	43.50	11.40	35.50	3.40	37.45	54.00	-16.55	AV	Horizontal
10360.40	40.05	44.50	13.80	38.80	8.10	48.15	68.20	-20.05	Pk	Vertical
10360.40	35.91	44.50	13.80	38.80	8.10	44.01	54.00	-9.99	AV	Vertical
10359.98	39.57	44.50	13.80	38.80	8.10	47.67	68.20	-20.53	Pk	Horizontal
10359.98	36.27	44.50	13.80	38.80	8.10	44.37	54.00	-9.63	AV	Horizontal
11017.42	33.55	43.60	14.30	39.50	10.20	43.75	68.20	-24.45	Pk	Vertical
11017.42	31.16	43.60	14.30	39.50	10.20	41.36	54.00	-12.64	AV	Vertical
11032.98	33.16	43.60	14.30	39.50	10.20	43.36	68.20	-24.84	Pk	Horizontal
11032.98	29.79	43.60	14.30	39.50	10.20	39.99	54.00	-14.01	AV	Horizontal
13289.09	32.35	42.60	15.90	38.90	12.20	44.55	68.20	-23.65	Pk	Vertical
13289.09	29.77	42.60	15.90	38.90	12.20	41.97	54.00	-12.03	AV	Vertical
13297.44	32.64	42.60	15.90	38.90	12.20	44.84	68.20	-23.36	Pk	Horizontal
13297.44	29.86	42.60	15.90	38.90	12.20	42.06	54.00	-11.94	AV	Horizontal



Mid Channel (802.11n20/ 5200 MHz)										
3253.35	44.08	44.70	6.70	28.20	-9.80	34.28	68.20	-33.92	Pk	Vertical
3253.35	41.29	44.70	6.70	28.20	-9.80	31.49	54.00	-22.51	AV	Vertical
3261.59	44.02	44.70	6.70	28.20	-9.80	34.22	68.20	-33.98	Pk	Horizontal
3261.59	41.10	44.70	6.70	28.20	-9.80	31.30	54.00	-22.70	AV	Horizontal
3998.03	40.06	44.20	7.90	29.70	-6.60	33.46	68.20	-34.74	Pk	Vertical
3998.03	35.99	44.20	7.90	29.70	-6.60	29.39	54.00	-24.61	AV	Vertical
3989.07	38.88	44.20	7.90	29.70	-6.60	32.28	68.20	-35.92	Pk	Horizontal
3989.07	35.88	44.20	7.90	29.70	-6.60	29.28	54.00	-24.72	AV	Horizontal
7216.53	36.66	43.50	11.40	35.50	3.40	40.06	68.20	-28.14	Pk	Vertical
7216.53	34.36	43.50	11.40	35.50	3.40	37.76	54.00	-16.24	AV	Vertical
7234.51	37.71	43.50	11.40	35.50	3.40	41.11	68.20	-27.09	Pk	Horizontal
7234.51	34.18	43.50	11.40	35.50	3.40	37.58	54.00	-16.42	AV	Horizontal
10399.95	39.50	44.50	13.80	38.80	8.10	47.60	68.20	-20.60	Pk	Vertical
10399.95	36.65	44.50	13.80	38.80	8.10	44.75	54.00	-9.25	AV	Vertical
10400.10	39.24	44.50	13.80	38.80	8.10	47.34	68.20	-20.86	Pk	Horizontal
10400.10	36.81	44.50	13.80	38.80	8.10	44.91	54.00	-9.09	AV	Horizontal
11031.11	33.99	43.60	14.30	39.50	10.20	44.19	68.20	-24.01	Pk	Vertical
11031.11	30.55	43.60	14.30	39.50	10.20	40.75	54.00	-13.25	AV	Vertical
11025.79	33.06	43.60	14.30	39.50	10.20	43.26	68.20	-24.94	Pk	Horizontal
11025.79	30.73	43.60	14.30	39.50	10.20	40.93	54.00	-13.07	AV	Horizontal
13291.30	31.78	42.60	15.90	38.90	12.20	43.98	68.20	-24.22	Pk	Vertical
13291.30	29.52	42.60	15.90	38.90	12.20	41.72	54.00	-12.28	AV	Vertical
13298.00	32.58	42.60	15.90	38.90	12.20	44.78	68.20	-23.42	Pk	Horizontal
13298.00	29.65	42.60	15.90	38.90	12.20	41.85	54.00	-12.15	AV	Horizontal



High Channel (802.11n20/ 5240 MHz)										
3254.03	45.17	44.70	6.70	28.20	-9.80	35.37	68.20	-32.83	Pk	Vertical
3254.03	40.96	44.70	6.70	28.20	-9.80	31.16	54.00	-22.84	AV	Vertical
3257.41	44.98	44.70	6.70	28.20	-9.80	35.18	68.20	-33.02	Pk	Horizontal
3257.41	41.69	44.70	6.70	28.20	-9.80	31.89	54.00	-22.11	AV	Horizontal
3987.60	38.87	44.20	7.90	29.70	-6.60	32.27	68.20	-35.93	Pk	Vertical
3987.60	35.75	44.20	7.90	29.70	-6.60	29.15	54.00	-24.85	AV	Vertical
3981.48	39.76	44.20	7.90	29.70	-6.60	33.16	68.20	-35.04	Pk	Horizontal
3981.48	35.70	44.20	7.90	29.70	-6.60	29.10	54.00	-24.90	AV	Horizontal
7217.82	36.56	43.50	11.40	35.50	3.40	39.96	68.20	-28.24	Pk	Vertical
7217.82	34.90	43.50	11.40	35.50	3.40	38.30	54.00	-15.70	AV	Vertical
7217.06	36.47	43.50	11.40	35.50	3.40	39.87	68.20	-28.33	Pk	Horizontal
7217.06	33.56	43.50	11.40	35.50	3.40	36.96	54.00	-17.04	AV	Horizontal
10480.09	39.13	44.50	13.80	38.80	8.10	47.23	68.20	-20.97	Pk	Vertical
10480.09	35.72	44.50	13.80	38.80	8.10	43.82	54.00	-10.18	AV	Vertical
10480.22	40.16	44.50	13.80	38.80	8.10	48.26	68.20	-19.94	Pk	Horizontal
10480.22	36.87	44.50	13.80	38.80	8.10	44.97	54.00	-9.03	AV	Horizontal
11029.35	32.97	43.60	14.30	39.50	10.20	43.17	68.20	-25.03	Pk	Vertical
11029.35	30.41	43.60	14.30	39.50	10.20	40.61	54.00	-13.39	AV	Vertical
11017.42	34.02	43.60	14.30	39.50	10.20	44.22	68.20	-23.98	Pk	Horizontal
11017.42	30.83	43.60	14.30	39.50	10.20	41.03	54.00	-12.97	AV	Horizontal
13280.50	32.96	42.60	15.90	38.90	12.20	45.16	68.20	-23.04	Pk	Vertical
13280.50	29.03	42.60	15.90	38.90	12.20	41.23	54.00	-12.77	AV	Vertical
13286.74	32.92	42.60	15.90	38.90	12.20	45.12	68.20	-23.08	Pk	Horizontal
13286.74	28.80	42.60	15.90	38.90	12.20	41.00	54.00	-13.00	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (VHT-20), 802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11n (HT-20).
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.
4. Pre-scan both the SISO and MIMO mode, only the worst-case results were reported.

**Band IV(5.725-5.850) GHz**

Frequency (MHz)	Reading	Amplifier	Loss	Antenna Factor	Orrected Factor	Emission Level	Limit (dBuV/m)	Margin	Detector	Comment
	(dBuV)	(dB)	(dB)	(dB/m)	(dB)	(dBuV/m)		(dB)		
Low Channel (802.11n20/ 5180 MHz)										
3259.95	44.78	44.70	6.70	28.20	-9.80	34.98	68.20	-33.22	Pk	Vertical
3259.95	40.77	44.70	6.70	28.20	-9.80	30.97	54.00	-23.03	AV	Vertical
3255.26	45.01	44.70	6.70	28.20	-9.80	35.21	68.20	-32.99	Pk	Horizontal
3255.26	41.05	44.70	6.70	28.20	-9.80	31.25	54.00	-22.75	AV	Horizontal
3984.58	39.91	44.20	7.90	29.70	-6.60	33.31	68.20	-34.89	Pk	Vertical
3984.58	36.21	44.20	7.90	29.70	-6.60	29.61	54.00	-24.39	AV	Vertical
3982.64	39.99	44.20	7.90	29.70	-6.60	33.39	68.20	-34.81	Pk	Horizontal
3982.64	35.69	44.20	7.90	29.70	-6.60	29.09	54.00	-24.91	AV	Horizontal
7229.13	36.69	43.50	11.40	35.50	3.40	40.09	68.20	-28.11	Pk	Vertical
7229.13	34.09	43.50	11.40	35.50	3.40	37.49	54.00	-16.51	AV	Vertical
7227.03	37.92	43.50	11.40	35.50	3.40	41.32	68.20	-26.88	Pk	Horizontal
7227.03	33.62	43.50	11.40	35.50	3.40	37.02	54.00	-16.98	AV	Horizontal
10359.97	38.88	44.50	13.80	38.80	8.10	46.98	68.20	-21.22	Pk	Vertical
10359.97	37.11	44.50	13.80	38.80	8.10	45.21	54.00	-8.79	AV	Vertical
10359.99	38.79	44.50	13.80	38.80	8.10	46.89	68.20	-21.31	Pk	Horizontal
10359.99	36.39	44.50	13.80	38.80	8.10	44.49	54.00	-9.51	AV	Horizontal
11033.90	33.02	43.60	14.30	39.50	10.20	43.22	68.20	-24.98	Pk	Vertical
11033.90	30.50	43.60	14.30	39.50	10.20	40.70	54.00	-13.30	AV	Vertical
11017.29	32.87	43.60	14.30	39.50	10.20	43.07	68.20	-25.13	Pk	Horizontal
11017.29	30.64	43.60	14.30	39.50	10.20	40.84	54.00	-13.16	AV	Horizontal
13288.21	32.66	42.60	15.90	38.90	12.20	44.86	68.20	-23.34	Pk	Vertical
13288.21	28.84	42.60	15.90	38.90	12.20	41.04	54.00	-12.96	AV	Vertical
13285.32	32.60	42.60	15.90	38.90	12.20	44.80	68.20	-23.40	Pk	Horizontal
13285.32	29.19	42.60	15.90	38.90	12.20	41.39	54.00	-12.61	AV	Horizontal



Mid Channel (802.11n20/ 5200 MHz)										
3255.34	45.24	44.70	6.70	28.20	-9.80	35.44	68.20	-32.76	Pk	Vertical
3255.34	41.72	44.70	6.70	28.20	-9.80	31.92	54.00	-22.08	AV	Vertical
3260.81	44.37	44.70	6.70	28.20	-9.80	34.57	68.20	-33.63	Pk	Horizontal
3260.81	41.90	44.70	6.70	28.20	-9.80	32.10	54.00	-21.90	AV	Horizontal
3988.68	39.34	44.20	7.90	29.70	-6.60	32.74	68.20	-35.46	Pk	Vertical
3988.68	36.16	44.20	7.90	29.70	-6.60	29.56	54.00	-24.44	AV	Vertical
3996.82	39.08	44.20	7.90	29.70	-6.60	32.48	68.20	-35.72	Pk	Horizontal
3996.82	35.90	44.20	7.90	29.70	-6.60	29.30	54.00	-24.70	AV	Horizontal
7226.17	36.51	43.50	11.40	35.50	3.40	39.91	68.20	-28.29	Pk	Vertical
7226.17	34.43	43.50	11.40	35.50	3.40	37.83	54.00	-16.17	AV	Vertical
7229.90	37.65	43.50	11.40	35.50	3.40	41.05	68.20	-27.15	Pk	Horizontal
7229.90	34.40	43.50	11.40	35.50	3.40	37.80	54.00	-16.20	AV	Horizontal
10400.18	39.09	44.50	13.80	38.80	8.10	47.19	68.20	-21.01	Pk	Vertical
10400.18	36.76	44.50	13.80	38.80	8.10	44.86	54.00	-9.14	AV	Vertical
10400.30	39.74	44.50	13.80	38.80	8.10	47.84	68.20	-20.36	Pk	Horizontal
10400.30	37.16	44.50	13.80	38.80	8.10	45.26	54.00	-8.74	AV	Horizontal
11018.94	33.21	43.60	14.30	39.50	10.20	43.41	68.20	-24.79	Pk	Vertical
11018.94	30.03	43.60	14.30	39.50	10.20	40.23	54.00	-13.77	AV	Vertical
11022.01	34.17	43.60	14.30	39.50	10.20	44.37	68.20	-23.83	Pk	Horizontal
11022.01	30.79	43.60	14.30	39.50	10.20	40.99	54.00	-13.01	AV	Horizontal
13292.07	31.63	42.60	15.90	38.90	12.20	43.83	68.20	-24.37	Pk	Vertical
13292.07	29.49	42.60	15.90	38.90	12.20	41.69	54.00	-12.31	AV	Vertical
13294.07	32.80	42.60	15.90	38.90	12.20	45.00	68.20	-23.20	Pk	Horizontal
13294.07	29.15	42.60	15.90	38.90	12.20	41.35	54.00	-12.65	AV	Horizontal



High Channel (802.11n20/ 5240 MHz)										
3247.05	44.50	44.70	6.70	28.20	-9.80	34.70	68.20	-33.50	Pk	Vertical
3247.05	42.13	44.70	6.70	28.20	-9.80	32.33	54.00	-21.67	AV	Vertical
3264.09	44.27	44.70	6.70	28.20	-9.80	34.47	68.20	-33.73	Pk	Horizontal
3264.09	41.45	44.70	6.70	28.20	-9.80	31.65	54.00	-22.35	AV	Horizontal
4000.20	39.82	44.20	7.90	29.70	-6.60	33.22	68.20	-34.98	Pk	Vertical
4000.20	35.73	44.20	7.90	29.70	-6.60	29.13	54.00	-24.87	AV	Vertical
3984.17	39.87	44.20	7.90	29.70	-6.60	33.27	68.20	-34.93	Pk	Horizontal
3984.17	36.93	44.20	7.90	29.70	-6.60	30.33	54.00	-23.67	AV	Horizontal
7221.38	36.43	43.50	11.40	35.50	3.40	39.83	68.20	-28.37	Pk	Vertical
7221.38	34.50	43.50	11.40	35.50	3.40	37.90	54.00	-16.10	AV	Vertical
7220.57	37.24	43.50	11.40	35.50	3.40	40.64	68.20	-27.56	Pk	Horizontal
7220.57	34.92	43.50	11.40	35.50	3.40	38.32	54.00	-15.68	AV	Horizontal
10480.09	39.78	44.50	13.80	38.80	8.10	47.88	68.20	-20.32	Pk	Vertical
10480.09	36.55	44.50	13.80	38.80	8.10	44.65	54.00	-9.35	AV	Vertical
10480.26	39.61	44.50	13.80	38.80	8.10	47.71	68.20	-20.49	Pk	Horizontal
10480.26	35.72	44.50	13.80	38.80	8.10	43.82	54.00	-10.18	AV	Horizontal
11028.93	33.79	43.60	14.30	39.50	10.20	43.99	68.20	-24.21	Pk	Vertical
11028.93	29.71	43.60	14.30	39.50	10.20	39.91	54.00	-14.09	AV	Vertical
11033.11	33.69	43.60	14.30	39.50	10.20	43.89	68.20	-24.31	Pk	Horizontal
11033.11	30.32	43.60	14.30	39.50	10.20	40.52	54.00	-13.48	AV	Horizontal
13295.68	33.00	42.60	15.90	38.90	12.20	45.20	68.20	-23.00	Pk	Vertical
13295.68	29.07	42.60	15.90	38.90	12.20	41.27	54.00	-12.73	AV	Vertical
13293.61	31.88	42.60	15.90	38.90	12.20	44.08	68.20	-24.12	Pk	Horizontal
13293.61	29.88	42.60	15.90	38.90	12.20	42.08	54.00	-11.92	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (VHT-20), 802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11n (HT-20).
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.
4. Pre-scan both the SISO and MIMO mode, only the worst-case results were reported.




3.2.9 Band Edge

Note: Antenna A Power > Antenna B Power, Both antenna A and B have been test, Only show the worst data of Antenna A.

Band I 5150-5250MHz


802.11n20 Low

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4797.585	55.31	-7.22	48.09	74.00	-25.91	peak
2	5150.000	53.81	-5.73	48.08	74.00	-25.92	peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4789.935	52.65	-7.23	45.42	74.00	-28.58	peak
2	5150.000	58.68	-5.73	52.95	74.00	-21.05	peak

**802.11n20 High**
Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	52.03	-5.23	46.80	74.00	-27.20	peak
2	5568.650	53.28	-4.80	48.48	74.00	-25.52	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.02	-5.23	44.79	74.00	-29.21	peak
2	5760.410	53.28	-4.45	48.83	74.00	-25.17	peak

Note: 1.802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) all has been tested, the worst case is 802.11n (HT-20),only shown the worst case.

2. Pre-scan both the SISO and MIMO mode, only the worst-case results were reported.

Band IV(5.725-5.85 GHz)

Note: The main frequency is too far away from the restricted band and does not require testing.



4. CONDUCTED SPURIOUS EMISSIONS AND BANDEDGE

4.1 LIMIT

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	1000 KHz/3000 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 5700 to 5725 MHz Upper Band Edge: 5850 to 5870 MHz
RB / VB (emission in restricted band)	1000 KHz/3000 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1000 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

Data See Attachment A.





5. POWER SPECTRAL DENSITY TEST

5.1 LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2 TEST PROCEDURE

1. The setting follows Method SA-1 of FCC KDB D02 General UNII Test Procedures New Rules v01r03.

For devices operating in the band, the rules specify a measurement bandwidth of 500 kHz.

Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used.

The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (*i.e.*, 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHZ}$ is available on nearly all spectrum analyzers.



5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

5150-5250MHz									
Frequency	Ant_A Power Density(dBm)	Ant_B Power Density(dBm)	Ant_A Duty cycle factor	Ant_B Duty cycle factor	Ant_A Power Density(dBm)	Ant_B Power Density(dBm)	Power Density Total(dBm)	Limit	Result
802.11a									
5180	5.586	4.682	0.21	0.21	5.797	4.893	--	11	PASS
5200	5.378	4.596	0.21	0.21	5.589	4.807	--	11	PASS
5240	5.147	4.268	0.21	0.21	5.358	4.479	--	11	PASS
802.11n20									
5180	7.233	5.678	0.28	0.28	7.509	5.954	9.811	11	PASS
5200	6.441	5.719	0.28	0.28	6.717	5.995	9.381	11	PASS
5240	6.691	6.075	0.28	0.28	6.967	6.351	9.680	11	PASS
802.11n40									
5190	3.713	2.974	0.43	0.43	4.145	3.406	6.801	11	PASS
5230	3.544	2.788	0.43	0.43	3.976	3.220	6.625	11	PASS
802.11ac20									
5180	7.450	6.174	0.24	0.24	7.694	6.418	10.113	11	PASS
5200	7.242	5.764	0.24	0.24	7.486	6.008	9.820	11	PASS
5240	7.262	5.783	0.24	0.24	7.506	6.027	9.840	11	PASS



802.11ac40									
5190	3.790	2.512	0.41	0.41	4.200	2.922	6.618	11	PASS
5230	4.157	3.233	0.41	0.41	4.567	3.643	7.140	11	PASS
802.11ac80									
5210	-0.325	-0.771	0.97	0.97	0.647	0.201	3.440	11	PASS

5725-5850MHz									
Frequen cy	Ant_A Power Density(dB m)	Ant_B Power Density(dB m)	Ant_A Duty cycl e facto r	Ant_B Duty cycl e facto r	Ant_A Power Density(dB m)	Ant_B Power Density(dB m)	Power Density Total(dB m)	Lim it	Resu lt
802.11a									
5745	10.731	10.049	0.20	0.20	10.929	10.247	--	30	PAS S
5785	10.822	9.759	0.20	0.20	11.020	9.957	--	30	PAS S
5825	10.343	9.079	0.20	0.20	10.541	9.277	--	30	PAS S
802.11n20									
5745	11.381	10.502	0.23	0.23	11.614	10.735	14.207	30	PAS S
5785	11.418	9.859	0.23	0.23	11.651	10.092	13.951	30	PAS S
5825	10.959	9.732	0.23	0.23	11.192	9.965	13.632	30	PAS S
802.11n40									
5755	7.167	6.588	0.45	0.45	7.620	7.041	10.351	30	PAS S
5795	6.664	6.352	0.45	0.45	7.117	6.805	9.974	30	PAS S
802.11ac20									
5745	10.878	9.831	0.22	0.22	11.098	10.051	13.616	30	PAS S
5785	10.759	9.793	0.22	0.22	10.979	10.013	13.533	30	PAS S
5825	10.550	9.487	0.22	0.22	10.770	9.707	13.281	30	PAS S
802.11ac40									
5755	6.782	6.605	0.44	0.44	7.224	7.047	10.147	30	PAS S
5795	6.665	6.146	0.44	0.44	7.107	6.588	9.866	30	PAS S
802.11ac80									
5775	4.953	3.089	0.90	0.90	5.851	3.987	8.029	30	PAS S

Test plots see Attachment B

6. BANDWIDTH MEASUREMENT

6.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

See list of measuring instruments of this test report.

6.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.5 TEST RESULTS

Note: Antenna A Power > Antenna B Power, Both antenna A and B have been test, Only show the worst data of Antenna A.

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5180	22.16	Pass
5200	22.29	Pass
5240	23.26	Pass
802.11n(HT20)		
5180	22.80	Pass
5200	23.36	Pass
5240	23.29	Pass
802.11n(HT40)		
5190	40.92	Pass
5230	40.43	Pass
802.11ac(VHT20)		
5180	22.78	Pass
5200	22.81	Pass
5240	22.86	Pass
802.11ac(VHT40)		
5190	40.79	Pass
5230	41.03	Pass
802.11ac(VHT80)		
5210	82.88	Pass

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	23.68	Pass
5785	23.76	Pass
5825	23.97	Pass
802.11n(HT20)		
5745	22.98	Pass
5785	23.88	Pass
5825	23.92	Pass
802.11n(HT40)		
5755	40.79	Pass
5795	40.85	Pass
802.11ac(VHT20)		
5745	23.31	Pass
5785	23.37	Pass
5825	23.96	Pass
802.11ac(VHT40)		
5755	41.14	Pass
5795	40.98	Pass
802.11ac(VHT80)		
5775	82.60	Pass

Test plots see Attachment C



6.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth:

6.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.


The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.2.2 DEVIATION FROM STANDARD

No deviation.

6.2.3 TEST SETUP



6.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.2.5 TEST RESULTS

Note: Antenna A Power > Antenna B Power, Both antenna A and B have been test, Only show the worst data of Antenna A.

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5180	16.52	Pass
5200	16.53	Pass
5240	16.54	Pass
802.11n(HT20)		
5180	17.74	Pass
5200	17.75	Pass
5240	17.74	Pass
802.11n(HT40)		
5190	36.19	Pass
5230	36.18	Pass
802.11ac(VHT20)		
5180	17.75	Pass
5200	17.73	Pass
5240	17.72	Pass
802.11ac(VHT40)		
5190	36.21	Pass
5230	36.17	Pass
802.11ac(VHT80)		
5210	75.83	Pass

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5745	16.57	Pass
5785	16.58	Pass
5825	16.59	Pass
802.11n(HT20)		
5745	17.76	Pass
5785	17.78	Pass
5825	17.78	Pass
802.11n(HT40)		
5755	36.18	Pass
5795	36.15	Pass
802.11ac(VHT20)		
5745	17.78	Pass
5785	17.76	Pass
5825	17.76	Pass
802.11ac(VHT40)		
5755	36.18	Pass
5795	36.21	Pass
802.11ac(VHT80)		
5775	75.86	Pass

Test plots See Attachment C

6.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

6.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3.2 DEVIATION FROM STANDARD

No deviation.

6.3.3 TEST SETUP



6.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.3.5 TEST RESULTS

Note: Antenna A Power > Antenna B Power, Both antenna A and B have been test, Only show the worst data of Antenna A.

Frequency (MHz)	6dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	15.66	Pass
5785	15.14	Pass
5825	15.13	Pass
802.11n(HT20)		
5745	15.50	Pass
5785	15.15	Pass
5825	15.12	Pass
802.11n(HT40)		
5755	35.75	Pass
5795	35.50	Pass
802.11ac(VHT20)		
5745	15.14	Pass
5785	15.14	Pass
5825	16.67	Pass
802.11ac(VHT40)		
5755	35.75	Pass
5795	35.76	Pass
802.11ac(VHT80)		
5775	75.41	Pass

Data see Attachment D

7. MAXIMUM CONDUCTED OUTPUT POWER

7.1 LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Peak Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or 11 dBm + 10 log (26 dB emission bandwidth)	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	


7.2 TEST PROCEDURE

The EUT was directly connected to the Power Sensor&PC

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULTS


Note:

1. For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 0.25 W.
2. For the band 5.745-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W.

Band I (5.15-5.25GHz)									
Test Channel	Frequency (MHz)	Ant_A AV Power (dBm)	Ant_B AV Power (dBm)	Ant_A Duty cycle factor(dB)	Ant_B Duty cycle factor(dB)	Ant_A AV Power (dBm)	Ant_B AV Power (dBm)	AV Power Total(dBm)	LIMIT (dBm)
802.11a									
36	5180	10.34	10.28	0.21	0.21	10.55	10.49	--	23.98
40	5200	10.19	10.09	0.21	0.21	10.40	10.30	--	23.98
48	5240	9.92	9.90	0.21	0.21	10.13	10.11	--	23.98
802.11n(HT20)									
36	5180	10.47	10.31	0.28	0.28	10.75	10.59	13.68	23.98
40	5200	10.02	9.96	0.28	0.28	10.30	10.24	13.28	23.98
48	5240	9.92	9.72	0.28	0.28	10.20	10.00	13.11	23.98
802.11n(HT40)									
38	5190	10.12	10.06	0.43	0.43	10.55	10.49	13.53	23.98
46	5230	10.28	10.13	0.43	0.43	10.71	10.56	13.65	23.98
802.11ac(VHT20)									
36	5180	10.27	10.19	0.24	0.24	10.51	10.43	13.48	23.98
40	5200	10.05	9.97	0.24	0.24	10.29	10.21	13.26	23.98
48	5240	9.91	9.85	0.24	0.24	10.15	10.09	13.13	23.98
802.11ac(VHT40)									
38	5190	10.12	10.05	0.41	0.41	10.53	10.46	13.51	23.98
46	5230	10.43	10.09	0.41	0.41	10.84	10.50	13.68	23.98
802.11ac(VHT80)									
42	5210	9.57	9.52	0.97	0.97	10.54	10.49	13.53	23.98



Band IV (5.725-5.85GHz)									
Test Channel	Frequency (MHz)	Ant_A AV Power (dBm)	Ant_B AV Power (dBm)	Ant_A Duty cycle factor(dB)	Ant_B Duty cycle factor(dB)	AV Power (dBm)	AV Power B(dBm)	AV Power Total(dBm)	LIMIT (dBm)
802.11a									
149	5745	14.53	14.39	0.20	0.20	14.73	14.59	--	30
157	5785	14.36	14.08	0.20	0.20	14.56	14.28	--	30
165	5825	13.93	13.76	0.20	0.20	14.13	13.96	--	30
802.11n(HT20)									
149	5745	14.49	14.24	0.23	0.23	14.72	14.47	17.610	30
157	5785	14.30	14.04	0.23	0.23	14.53	14.27	17.415	30
165	5825	13.96	13.86	0.23	0.23	14.19	14.09	17.153	30
802.11n(HT40)									
151	5755	12.03	12.01	0.45	0.45	12.48	12.46	15.484	30
159	5795	11.98	11.64	0.45	0.45	12.43	12.09	15.277	30
802.11ac(VHT20)									
149	5745	14.34	14.30	0.22	0.22	14.56	14.52	17.550	30
157	5785	14.22	14.03	0.22	0.22	14.44	14.25	17.356	30
165	5825	13.86	13.73	0.22	0.22	14.08	13.95	17.026	30
802.11ac(VHT40)									
151	5755	12.06	12.00	0.44	0.44	12.50	12.44	15.482	30
159	5795	12.02	11.58	0.44	0.44	12.46	12.02	15.258	30
802.11ac(VHT80)									
155	5775	14.07	13.04	0.90	0.90	14.97	13.94	17.494	30



5210MHz_Ant A



5775MHz_Ant A



5210MHz_Ant B



5775MHz_Ant B



BandI(5.15-5.25) GHz				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.444	1.516	95.25%	0.21
n20	1.220	1.300	93.85%	0.28
n40	0.612	0.676	90.53%	0.43
ac20	1.244	1.316	94.53%	0.24
ac40	0.626	0.688	90.99%	0.41
ac80	0.311	0.389	79.95%	0.97

BandIV(5.15-5.25) GHz				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.456	1.524	95.54%	0.20
n20	1.236	1.304	94.79%	0.23
n40	0.618	0.686	90.09%	0.45
ac20	1.232	1.296	95.06%	0.22
ac40	0.616	0.682	90.32%	0.44
ac80	0.309	0.380	81.32%	0.90






8. AUTOMATICALLY DISCONTINUE TRANSMISSION

8.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

8.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.





9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is Ant. A: Internal Antennal, Ant. B: Internal Antennal, Antenna. It comply with the standard requirement.



**APPENDIX - PHOTOS OF TEST SETUP**

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

XXXXXXXXEND OF THE REPORTXXXXXXXX

