

FCC RF Exposure

EUT Description: Robo Thruster Family

Model No.: I-MX-1100-20

FCC ID: 2AVJ9-I-MX-1100-20

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max power of channel, including tune - up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result = $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn - up power in mw

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

433.89MHz:

EIRP(dBm) = 68.34dBuV/m - 95.3 = -26.96(dBm)

Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
433.89	-26.96	-27 ± 1	-26/0.003	5	0.00033	3.0	Pass

Note:

PK Output power = conducted power.

Conducted power see the test report **HK2212065522-E**, antenna gain = 0dBi

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.00033 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results = $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

f(GHz) is the RF channel transmit frequency in GHz

Distance = 5mm