

## MPE Calculation

Regulation(s): Part 1.1310, Part 2.1091

Method: KDB447498 D01v06

RF feature	Frequency range (GHz)		Separation distance(cm)	Max. tune-up EIRP (dBm) <sup>Note1</sup>	Maximum EIRP (mW)	Maximum power density(mW/cm <sup>2</sup> )	Requirement (mW/cm <sup>2</sup> )
FMCW(Module 1)	79.0	~	81.0	20.8	120.227	0.024	1.000
FMCW(Module 2)	78.0	~	80.0	20.6	114.816	0.023	1.000
FMCW(Module 3)	79.0	~	81.0	20.8	120.227	0.024	1.000
		~					
		~					
		~					
		~					
		~					

Note1: Please refer to the tune-up procedure for tune-up max power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 \bullet S &= EIRP / (4 R^2 \pi) \\
 &= 120.227 / (4 \times R^2 \times \pi) \\
 &= 0.024 \text{ mW/cm}^2
 \end{aligned}$$

**- Note**  
 S= Maximum power density(mW/cm<sup>2</sup>)  
 EIRP= Equivalent Isotropic Radiated Power(mW)  
 R= Distance to the center of the radiation of the antenna

### ▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averageing time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC