



TESTING LABORATORY  
CERTIFICATE#4323.01



## FCC PART 15C

## TEST REPORT

For

### TARGA TELEMATICS SPA

VIA REGINATO, 87, TREVISO 31100, Italy

**FCC ID: 2AVLG-MTR2018**

|                                        |                                                                                                                                                                                                                            |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report | <b>Product Type:</b><br>RFID Reader                                                                                                                                                                                        |
| <b>Test Engineer:</b>                  | Winnie Yang <i>Winnie Yang</i>                                                                                                                                                                                             |
| <b>Report Number:</b>                  | RSHA191216001-00A                                                                                                                                                                                                          |
| <b>Report Date:</b>                    | 2020-01-16                                                                                                                                                                                                                 |
| <b>Reviewed By:</b>                    | Oscar Ye <i>Oscar Ye</i><br>EMC Manager                                                                                                                                                                                    |
| <b>Prepared By:</b>                    | Bay Area Compliance Laboratories Corp. (Kunshan)<br>No.248 Chenghu Road,Kunshan,Jiangsu province,China<br>Tel: +86-0512-86175000<br>Fax: +86-0512-88934268<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

|                                                                          |           |
|--------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                          | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                 | 3         |
| OBJECTIVE .....                                                          | 3         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                       | 3         |
| TEST METHODOLOGY .....                                                   | 3         |
| MEASUREMENT UNCERTAINTY .....                                            | 4         |
| TEST FACILITY .....                                                      | 4         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                    | <b>5</b>  |
| JUSTIFICATION .....                                                      | 5         |
| EUT EXERCISE SOFTWARE .....                                              | 5         |
| EQUIPMENT MODIFICATIONS .....                                            | 5         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                 | 5         |
| EXTERNAL I/O CABLE.....                                                  | 5         |
| BLOCK DIAGRAM OF TEST SETUP .....                                        | 5         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                     | <b>7</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                         | <b>8</b>  |
| <b>FCC§15.203 - ANTENNA REQUIREMENT.....</b>                             | <b>9</b>  |
| APPLICABLE STANDARD .....                                                | 9         |
| ANTENNA CONNECTED CONSTRUCTION .....                                     | 9         |
| <b>FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS .....</b>               | <b>10</b> |
| APPLICABLE STANDARD .....                                                | 10        |
| EUT SETUP .....                                                          | 10        |
| EMI TEST RECEIVER SETUP.....                                             | 10        |
| TEST PROCEDURE .....                                                     | 10        |
| FACTOR & OVER LIMIT CALCULATION.....                                     | 11        |
| TEST RESULTS SUMMARY .....                                               | 11        |
| TEST DATA .....                                                          | 11        |
| <b>FCC§15.225, §15.205 &amp; §15.209 - RADIATED EMISSIONS TEST .....</b> | <b>14</b> |
| APPLICABLE STANDARD .....                                                | 14        |
| EUT SETUP .....                                                          | 14        |
| EMI TEST RECEIVER SETUP.....                                             | 15        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                           | 15        |
| TEST RESULTS SUMMARY .....                                               | 15        |
| TEST DATA .....                                                          | 15        |
| <b>FCC§15.225(E) - FREQUENCY STABILITY.....</b>                          | <b>22</b> |
| APPLICABLE STANDARD .....                                                | 22        |
| TEST PROCEDURE .....                                                     | 22        |
| TEST DATA .....                                                          | 23        |
| <b>§15.215(C) - 20DB EMISSION BANDWIDTH TESTING .....</b>                | <b>24</b> |
| REQUIREMENT .....                                                        | 24        |
| TEST PROCEDURE .....                                                     | 24        |
| TEST DATA .....                                                          | 24        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                      |                                             |
|----------------------|---------------------------------------------|
| Applicant            | TARGA TELEMATICS SPA                        |
| Tested Model         | MTR2018                                     |
| Product Type         | RFID Reader                                 |
| Power Supply:        | DC 8V~32V                                   |
| Operation Frequency  | 125kHz,13.56MHz                             |
| RF Function          | SRD, RFID                                   |
| Modulation Type:     | GFSK                                        |
| Antenna Type:        | 125kHz: Coil Antenna, 13.56MHz: PCB Antenna |
| Maximum Antenna Gain | 0dBi                                        |

*\*All measurement and test data in this report was gathered from production sample serial number: 20191216001.  
(Assigned by the BACL. The EUT supplied by the applicant was received on 2019-12-16)*

### Objective

This Type approval report is prepared on behalf of *TARGA TELEMATICS SPA* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission's rules.

The objective is to determine the Compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209, 15.215 and 15.225.

### Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

| Item                               |            | Uncertainty |
|------------------------------------|------------|-------------|
| AC Power Lines Conducted Emissions |            | 3.19 dB     |
| RF conducted test with spectrum    |            | 0.9dB       |
| Radiated emission                  | 9kHz~30MHz | 6.07dB      |
|                                    | 30MHz~1GHz | 6.11dB      |
| Occupied Bandwidth                 |            | 0.5kHz      |
| Temperature                        |            | 1.0°C       |
| Humidity                           |            | 6%          |

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

## Justification

# EUT Exercise Software


## Equipment Modifications

## Support Equipment List and Details

| Manufacturer | Description | Model       | Serial Number |
|--------------|-------------|-------------|---------------|
| MCH          | DC Source   | MCH-303D-II | 14070562      |

| Cable Description | Length (m) | From/Port | To        |
|-------------------|------------|-----------|-----------|
| Power Cable       | 5.0        | EUT       | DC Source |

For Conducted Emissions:



Turntable  
2m Diameter

AC Source

DC Source

EUT

Non-Conductive Table  
80cm above Ground Plane

1.5 Meter

1.0 Meter

**SUMMARY OF TEST RESULTS**

| FCC Rules               | Description of Test             | Result    |
|-------------------------|---------------------------------|-----------|
| §15.203                 | Antenna Requirement             | Compliant |
| §15.207 (a)             | AC Line Conducted Emissions     | Compliant |
| §15.225 §15.209 §15.205 | Radiated Emission Test          | Compliant |
| §15.225(e)              | Frequency Stability             | Compliant |
| §15.215(c)              | 20dB Emission Bandwidth Testing | Compliant |

## TEST EQUIPMENT LIST

| Manufacturer                   | Description                    | Model    | Serial Number          | Calibration Date | Calibration Due Date |
|--------------------------------|--------------------------------|----------|------------------------|------------------|----------------------|
| <b>Radiated Emission Test</b>  |                                |          |                        |                  |                      |
| Rohde & Schwarz                | EMI Test Receiver              | ESCI     | 100195                 | 2019-11-30       | 2020-11-29           |
| Sunol Sciences                 | Broadband Antenna              | JB3      | A040914-2              | 2016-01-09       | 2022-01-08           |
| Sonoma Instrument              | Pre-amplifier                  | 310N     | 171205                 | 2019-08-15       | 2020-08-14           |
| ETS-LINDGREN                   | Loop Antenna                   | 6512     | 00108100               | 2019-04-25       | 2022-04-24           |
| Rohde & Schwarz                | Auto Test Software             | EMC32    | 100361                 | /                | /                    |
| MICRO-COAX                     | Coaxial Cable                  | Cable-8  | 008                    | 2019-08-15       | 2020-08-14           |
| MICRO-COAX                     | Coaxial Cable                  | Cable-9  | 009                    | 2019-08-15       | 2020-08-14           |
| MICRO-COAX                     | Coaxial Cable                  | Cable-10 | 010                    | 2019-08-15       | 2020-08-14           |
| BACL                           | Temperature & Humidity Chamber | BTH-150  | 30023                  | 2019-10-10       | 2020-10-09           |
| <b>Conducted Emission Test</b> |                                |          |                        |                  |                      |
| Rohde & Schwarz                | EMI Test Receiver              | ESR      | 1316.3003K03-101746-zn | 2019-07-11       | 2020-07-10           |
| Rohde & Schwarz                | LISN                           | ENV216   | 3560655016             | 2019-11-30       | 2020-11-29           |
| Audix                          | Test Software                  | e3       | V9                     | /                | /                    |
| Rohde & Schwarz                | Pulse limiter                  | ESH3-Z2  | 0357.8810.54           | 2019-08-10       | 2020-08-09           |
| MICRO-COAX                     | Coaxial Cable                  | Cable-15 | 015                    | 2019-08-15       | 2020-08-14           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connected Construction**

The EUT has two integral antenna arrangement, one for 13.56MHz, one for 125kHz and antenna gain are 0.0dBi, which was permanently attached, fulfill the requirement of this section, please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207(a)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the DC Source was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over Limit of 7 dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

## Test Data


### Environmental Conditions

|                    |          |
|--------------------|----------|
| Temperature:       | 23.2 °C  |
| Relative Humidity: | 50 %     |
| ATM Pressure:      | 101.3kPa |


*The testing was performed by Winnie Yang on 2020-01-16.*

*EUT operation mode: Transmitting*

## AC 120V/60 Hz, Line



|    |        | Read  |        |       | Limit | Over   |         |
|----|--------|-------|--------|-------|-------|--------|---------|
|    | Freq   | Level | Factor | Level | Line  | Limit  | Remark  |
|    | MHz    | dBuV  | dB     | dBuV  | dBuV  | dB     |         |
| 1  | 0.189  | -5.40 | 19.82  | 14.42 | 54.06 | -39.64 | Average |
| 2  | 0.189  | 0.70  | 19.82  | 20.52 | 64.06 | -43.54 | QP      |
| 3  | 0.294  | -6.00 | 19.83  | 13.83 | 50.41 | -36.58 | Average |
| 4  | 0.294  | 0.30  | 19.83  | 20.13 | 60.41 | -40.28 | QP      |
| 5  | 0.529  | -6.79 | 19.75  | 12.96 | 46.00 | -33.04 | Average |
| 6  | 0.529  | -2.79 | 19.75  | 16.96 | 56.00 | -39.04 | QP      |
| 7  | 0.755  | -7.10 | 19.72  | 12.62 | 46.00 | -33.38 | Average |
| 8  | 0.755  | -4.50 | 19.72  | 15.22 | 56.00 | -40.78 | QP      |
| 9  | 14.828 | 3.50  | 19.63  | 23.13 | 50.00 | -26.87 | Average |
| 10 | 14.828 | 9.40  | 19.63  | 29.03 | 60.00 | -30.97 | QP      |
| 11 | 22.063 | 5.80  | 19.84  | 25.64 | 50.00 | -24.36 | Average |
| 12 | 22.063 | 10.60 | 19.84  | 30.44 | 60.00 | -29.56 | QP      |

**AC 120V/60 Hz, Neutral**

|    | Freq   | Read Level | Factor | Level | Limit Line | Over Limit | Remark  |
|----|--------|------------|--------|-------|------------|------------|---------|
|    | MHz    | dBuV       | dB     | dBuV  | dBuV       | dB         |         |
| 1  | 0.186  | -5.19      | 19.82  | 14.63 | 54.20      | -39.57     | Average |
| 2  | 0.186  | 1.11       | 19.82  | 20.93 | 64.20      | -43.27     | QP      |
| 3  | 0.336  | -6.41      | 19.82  | 13.41 | 49.31      | -35.90     | Average |
| 4  | 0.336  | 0.39       | 19.82  | 20.21 | 59.31      | -39.10     | QP      |
| 5  | 0.471  | -6.69      | 19.75  | 13.06 | 46.49      | -33.43     | Average |
| 6  | 0.471  | -2.09      | 19.75  | 17.66 | 56.49      | -38.83     | QP      |
| 7  | 0.634  | -6.90      | 19.75  | 12.85 | 46.00      | -33.15     | Average |
| 8  | 0.634  | -4.20      | 19.75  | 15.55 | 56.00      | -40.45     | QP      |
| 9  | 15.146 | 4.80       | 19.64  | 24.44 | 50.00      | -25.56     | Average |
| 10 | 15.146 | 10.70      | 19.64  | 30.34 | 60.00      | -29.66     | QP      |
| 11 | 22.535 | 7.00       | 19.81  | 26.81 | 50.00      | -23.19     | Average |
| 12 | 22.535 | 11.60      | 19.81  | 31.41 | 60.00      | -28.59     | QP      |

**Note:**

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)  
 2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

## FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

### Applicable Standard

FCC Part 15.205, 15.209, 15.225


(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

### EUT Setup



The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Detector   |
|-------------------|---------|-----------|---------|------------|
| 9 kHz – 150 kHz   | 200 Hz  | 1 kHz     | /       | QP/Average |
| 150 kHz – 30 MHz  | 9 kHz   | 30 kHz    | /       | QP/Average |
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz   | 120 kHz | QP         |

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain

Corrected Amplitude = Meter Reading + Corrected Factor

The “**Margin**” column of the following data tables indicates the degree of Compliant with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209, 15.205, 15.225.

## Test Data


### Environmental Conditions

|                    |                 |
|--------------------|-----------------|
| Temperature:       | 24.2~25.1 °C    |
| Relative Humidity: | 48~50 %         |
| ATM Pressure:      | 101.1~101.3 kPa |

The testing was performed by Winnie Yang from 2019-12-22 to 2020-01-16.

Test mode: Transmitting

## 1) Spurious Emissions (9 kHz~150 kHz):



Date: 22.DEC.2019 16:19:26

| Indicated       |                                  | PK/QP/Ave. | Corrected Factor (dB/m) | FCC Part 15.225/15.209 |             |
|-----------------|----------------------------------|------------|-------------------------|------------------------|-------------|
| Frequency (kHz) | Corrected Amplitude (dBμV/m) @3m |            |                         | Limit (dBμV/m) @3m     | Margin (dB) |
| 35.21           | 72.43                            | PK         | 45.85                   | 116.67                 | 44.24       |
| 37.92           | 70.93                            | PK         | 45.14                   | 116.03                 | 45.10       |
| 73.40           | 81.65                            | PK         | 45.84                   | 110.29                 | 28.64       |
| 125.00          | 98.17                            | PK         | 50.55                   | 105.67                 | 7.50        |

Note:

1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

## 2) Spurious Emissions (150 kHz~30 MHz):




Date: 16.JAN.2020 14:16:47

| Frequency (MHz) | Corrected Amplitude (dBμV/m)@3m | Detector PK/QP/Ave. | Corrected Factor (dB/m) | FCC Part 15.225/15.209 |             |
|-----------------|---------------------------------|---------------------|-------------------------|------------------------|-------------|
|                 |                                 |                     |                         | Limit (dBμV/m)@3m      | Margin (dB) |
| 0.34135         | 72.91                           | PK                  | 27.46                   | 96.94                  | 24.03       |
| 0.48486         | 65.73                           | PK                  | 23.52                   | 93.89                  | 28.16       |
| 1.72861         | 60.78                           | PK                  | 15.25                   | 69.54                  | 8.76        |
| 13.56           | 84.27                           | PK                  | 6.12                    | 124.00                 | 39.73       |

Note:


1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

3) Spurious Emissions (13.11MHz~13.41 MHz):




Date: 22.DEC.2019 16:46:14

Spurious Emissions (13.41MHz~13.553 MHz):




Date: 22.DEC.2019 16:41:22

Spurious Emissions (13.567MHz~13.710 MHz):



Date: 22.DEC.2019 16:43:24


## Spurious Emissions (13.710MHz~14.010 MHz):



Date: 22.DEC.2019 16:48:02

| Frequency (MHz) | Corrected Amplitude (dBμV/m)@3m | Detector PK/QP/Ave. | Corrected Factor (dB/m) | FCC Part 15.225/15.209 |             |
|-----------------|---------------------------------|---------------------|-------------------------|------------------------|-------------|
|                 |                                 |                     |                         | Limit (dBμV/m)@3m      | Margin (dB) |
| 13.35           | 50.99                           | PK                  | 35.33                   | 80.51                  | 29.52       |
| 13.55           | 65.31                           | PK                  | 35.32                   | 90.47                  | 25.16       |
| 13.57           | 64.45                           | PK                  | 35.31                   | 90.47                  | 26.02       |
| 13.77           | 53.23                           | PK                  | 35.31                   | 80.51                  | 27.28       |

4) Spurious Emissions (30 MHz ~1 GHz):



| Frequency<br>(MHz) | Corrected<br>Amplitude | Rx Antenna     |                | Turntable<br>Degree | Corrected<br>Factor<br>(dB/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|------------------------|----------------|----------------|---------------------|-------------------------------|-------------------|----------------|
|                    | Quasi-peak<br>(dBμV/m) | Height<br>(cm) | Polar<br>(H/V) |                     |                               |                   |                |
| 40.71              | 27.93                  | 100            | V              | 61                  | -11.2                         | 40.00             | 12.07          |
| 68.43              | 7.68                   | 200            | V              | 67                  | -17.4                         | 40.00             | 32.32          |
| 95.16              | 10.84                  | 100            | V              | 330                 | -16.1                         | 43.50             | 32.66          |
| 149.80             | 10.64                  | 100            | V              | 200                 | -12.3                         | 43.50             | 32.86          |
| 231.29             | 17.36                  | 100            | H              | 218                 | -12.2                         | 46.00             | 28.64          |
| 257.08             | 12.72                  | 100            | H              | 0                   | -11.9                         | 46.00             | 33.28          |

---

**FCC§15.225(e) - FREQUENCY STABILITY**

---

**Applicable Standard**

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

**Test Procedure**

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.  
NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.

f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

g) Measure the frequency at each of frequencies specified in 5.6.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

i) Lower the chamber temperature by not more than  $10^{\circ}\text{C}$ , and allow the temperature inside the chamber to stabilize.

j) Repeat step f) through step i) down to the lowest specified temperature.

**Test Data****Environmental Conditions**

|                           |          |
|---------------------------|----------|
| <b>Temperature:</b>       | 24.5 °C  |
| <b>Relative Humidity:</b> | 50%      |
| <b>ATM Pressure:</b>      | 101.3kPa |

The testing was performed by Winnie Yang on 2019-12-25.

Test Mode: Transmitting.

Test Result: Compliant

| <b>F<sub>0</sub>=13.56MHz</b>       |                         |                                 |                            |                          |
|-------------------------------------|-------------------------|---------------------------------|----------------------------|--------------------------|
| <b>Power Supply(V<sub>DC</sub>)</b> | <b>Temperature (°C)</b> | <b>Measured Frequency (MHz)</b> | <b>Frequency Error (%)</b> | <b>Part 15.225 Limit</b> |
| 12.0                                | -20                     | 13.55953                        | -0.00347                   | ±0.01%                   |
|                                     | -10                     | 13.55949                        | -0.00376                   | ±0.01%                   |
|                                     | 0                       | 13.55967                        | -0.00243                   | ±0.01%                   |
|                                     | 10                      | 13.55972                        | -0.00206                   | ±0.01%                   |
|                                     | 20                      | 13.55967                        | -0.00243                   | ±0.01%                   |
|                                     | 30                      | 13.55945                        | -0.00406                   | ±0.01%                   |
|                                     | 40                      | 13.55977                        | -0.00170                   | ±0.01%                   |
|                                     | 50                      | 13.55948                        | -0.00383                   | ±0.01%                   |
| 10.2                                | 20                      | 13.55979                        | -0.00155                   | ±0.01%                   |
| 13.8                                | 20                      | 13.55969                        | -0.00229                   | ±0.01%                   |

| <b>F<sub>0</sub>=13.56MHz</b>       |                         |                                 |                            |                          |
|-------------------------------------|-------------------------|---------------------------------|----------------------------|--------------------------|
| <b>Power Supply(V<sub>DC</sub>)</b> | <b>Temperature (°C)</b> | <b>Measured Frequency (MHz)</b> | <b>Frequency Error (%)</b> | <b>Part 15.225 Limit</b> |
| 24.0                                | -20                     | 13.55961                        | -0.00288                   | ±0.01%                   |
|                                     | -10                     | 13.55955                        | -0.00332                   | ±0.01%                   |
|                                     | 0                       | 13.55973                        | -0.00199                   | ±0.01%                   |
|                                     | 10                      | 13.55974                        | -0.00192                   | ±0.01%                   |
|                                     | 20                      | 13.55971                        | -0.00214                   | ±0.01%                   |
|                                     | 30                      | 13.55956                        | -0.00324                   | ±0.01%                   |
|                                     | 40                      | 13.55974                        | -0.00192                   | ±0.01%                   |
|                                     | 50                      | 13.55951                        | -0.00361                   | ±0.01%                   |
| 20.4                                | 20                      | 13.55982                        | -0.00133                   | ±0.01%                   |
| 27.6                                | 20                      | 13.55974                        | -0.00192                   | ±0.01%                   |

## **§15.215(c) - 20dB EMISSION BANDWIDTH TESTING**

### **Requirement**

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### **Test Procedure**

With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer, plot the 20 dB bandwidth.

### **Test Data**

#### **Environmental Conditions**


|                           |                 |
|---------------------------|-----------------|
| <b>Temperature:</b>       | 23.2~24.7 °C    |
| <b>Relative Humidity:</b> | 48~50 %         |
| <b>ATM Pressure:</b>      | 102.3~102.5 kPa |

*The testing was performed by Winnie Yang from 2019-12-22 to 2019-12-24.*

*Test Mode: Transmitting*


*Test Result: Compliant*

| Frequency (MHz) | 20 dB Bandwidth (kHz) |
|-----------------|-----------------------|
| 0.125           | 1.079                 |
| 13.56           | 4.519                 |

**20 dB Emission Bandwidth-125kHz**

Date: 24.DEC.2019 17:25:08

### 20 dB Emission Bandwidth-13.56MHz



Date: 22.DEC.2019 17:11:21

\*\*\*\*\* END OF REPORT \*\*\*\*\*