



FCC PART 15B

TEST REPORT

For

Shenzhen Anysecu Technology Co., Ltd.

2B-2413, COFCO Xiangyun international, Longcheng street, Longgang, Shenzhen, Guangdong, China

FCC ID: 2AVLJ-WP67


Report Type: Original Report	Product Name: Amateur Radio
Report Number:	2407A50343E-EM-01
Report Date:	2025-01-25
Reviewed By:	Ash Lin 
Approved By:	Miles Chen
Prepared By:	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REPORT REVISION HISTORY	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST FACILITY	4
MEASUREMENT UNCERTAINTY.....	5
SYSTEM TEST CONFIGURATION.....	6
TEST MODE AND VOLTAGE.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §15.107 - CONDUCTED EMISSION	11
APPLICABLE STANDARD	11
TEST SYSTEM SETUP.....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
RESULT & MARGIN CALCULATION	12
TEST DATA	13
FCC §15.109 - RADIATED EMISSION IN FREQUENCY	21
APPLICABLE STANDARD	21
TEST SYSTEM SETUP.....	21
EMI TEST RECEIVER SETUP.....	22
TEST PROCEDURE	22
RESULT & MARGIN CALCULATION	22
TEST DATA	23
FCC §15.121(B) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS.....	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	40
EXHIBIT A - EUT PHOTOGRAPHS.....	41
EXHIBIT B – TEST SETUP PHOTOGRAPHS.....	42

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2407A50343E-EM-01	R1V1	2025-01-25	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:		Shenzhen Anysecu Technology Co., Ltd.
Product Name:		Amateur Radio
Tested Model:		WP67
Series Model(s):		W350, W360, W380, W385, W577, W660, W661, W662, K50
Trade mark:		
Power Supply:		DC 7.4V from Battery or DC 8.4V from Charger
Adapter information	Model:	DLD-12005-M
	Input:	AC 100-240V, 50/60Hz, 0.3A
	Output:	DC 12V, 0.5A
Charger Information	Model:	Unknown
	Input:	DC 12V, 0.5A
	Output:	DC 8.4V, 0.4A
★Highest Operating Frequency:		480 MHz
EUT Receive Status:		Good
<i>Note:</i> 1. The highest operating frequency is provided by the applicant. 2. The test model is identify with the series models except for the model name, please refer to declaration letter for more detail. 3. All measurement and test data in this report was gathered from production sample serial number: 2VN4-1 (Assigned by the BACL (Xiamen). The EUT was received on 2024-12-06).		

Objective

This report is prepared for *Shenzhen Anysecu Technology Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commission's rules.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the product as specified in CISPR 16-4-2. This uncertainty represents expanded uncertainty expressed at 95% confidence level using a coverage factor of k=2.

$$u_c(y) = \sqrt{\sum_i c_i^2 u^2(x_i)}$$

Item	Frequency Range	$U_{lab} = 2 u_c(y)$ (Confidence of 95%)
Conducted Emission	150kHz-30MHz	2.33dB
Radiated Emission	30MHz~200MHz	4.38dB
	200MHz~1GHz	4.50dB
	1GHz~6GHz	4.58dB
Humidity		5%
Temperature		1℃

SYSTEM TEST CONFIGURATION

Test Mode and Voltage

The system was configured for testing in a typical mode (as normally used by a typical user).	
Test mode:	Test Mode 1: Charging & Scanning Test Mode 2: Charging & Receiving
Test voltage:	DC 8.4V from charger(AC 120V/60Hz)

Description of Test Configuration

Operation Modes	Operation Frequency Range (MHz)	Test Frequency (MHz)
Scanning	400-480	400-480
UHF Receiving	400-480	400.0125, 440, 479.9875

EUT Exercise Software

No exercise software was used to test.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HP	RF Communications test set	8920A	3524A07202
Unknown	Antenna	Unknown	Unknown


External I/O Cable

Cable Description	Length (m)	From Port	To Port
Antenna Cable	3.0	8920A	Antenna


Block Diagram of Test Setup

Conducted Emission:

Test Mode 1:




Test Mode 2:




Radiated Emission:

Test Mode 1:



Test Mode 2:



SUMMARY OF TEST RESULTS

Rule Part	Description of Test	Results
FCC§15.107	Conducted Emission	Compliant
FCC§15.109	Radiated Emission	Compliant
FCC §15.121(b)	Scanning receivers and frequency converters used with scanning receivers	Compliant

TEST EQUIPMENT LIST

Test Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission					
EMI Test Receiver	Rohde & Schwarz	ESR	103105	2024/03/29	2025/03/28
LISN	Rohde & Schwarz	ENV216	100129	2024/03/29	2025/03/28
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	0357.8810.54	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC001	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emission 30 MHz to 1 GHz					
EMI Test Receiver	Rohde & Schwarz	ESR	103103	2024/03/29	2025/03/28
Antenna	Sunol Sciences	JB6	A122022-5	2023/07/27	2026/07/26
Amplifier	Sonoma	310B	120903	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC002	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH460B-N-2M	CC006	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH460B-N-12M	CC007	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emission Above 1 GHz					
Spectrum Analyzer	Rohde & Schwarz	FSU	100405	2025/02/20	2026/02/19
Horn Antenna	EMCO	3115	9002-3355	2024/11/19	2027/11/18
Preamplifier	A.H.Systems	PAM-0118P	489	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH800A-N-6M	CC003	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH800A-N-1M	CC005	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
Scanning Receiver					
Coaxial Cable	N/A	N/A	N/A	Each time	Each time
RF Communications test set	HP	8920A	3524A07202	2024/04/26	2025/04/25
Power Splitter	narda	4426LB-2	1661	N/A	N/A
Microwave Analog Signal Generator	Agilent	N5183A	MY47420335	2024/03/29	2025/03/28
Attenuator	Electronic Corporation	30-WA-FFN-30	1172435	2024/03/29	2025/03/28

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.107 - CONDUCTED EMISSION

Applicable Standard


FCC §15.107

(a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Test System Setup



The measurement procedure of test setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Result & Margin Calculation

The Result is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

$$\text{Result (dB}\mu\text{V)} = \text{Reading (dB}\mu\text{V)} + \text{Factor (dB)}$$


The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Result (dB}\mu\text{V)}$$

Test Data

Project No.: 2407A50343E-EM
Test Mode: Mode 1(400-480MHz)
EUT Model: WP67

Temp/Humi/ATM: 22.7°C/46%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 8.4V from charger
(AC 120V/60Hz)



Trace: 1

Condition: QP

RBW:9kHz

AV


RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.19	1.47	20.64	22.11	54.08	31.97	Line	Average
0.19	15.27	20.64	35.91	64.08	28.17	Line	QP
0.20	-6.63	20.57	13.94	53.52	39.58	Line	Average
0.20	9.36	20.57	29.93	63.52	33.59	Line	QP
0.40	1.68	20.35	22.03	47.77	25.74	Line	Average
0.40	16.96	20.35	37.31	57.77	20.46	Line	QP
0.42	0.10	20.34	20.44	47.50	27.06	Line	Average
0.42	15.75	20.34	36.09	57.50	21.41	Line	QP
0.45	0.35	20.32	20.67	46.87	26.20	Line	Average
0.45	17.59	20.32	37.91	56.87	18.96	Line	QP
0.50	1.19	20.29	21.48	46.01	24.53	Line	Average
0.50	16.99	20.29	37.28	56.01	18.73	Line	QP

Project No.: 2407A50343E-EM
 Test Mode: Mode 1(400-480MHz)
 EUT Model: WP67

Temp/Humi/ATM: 22.7°C/46%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)

Date: 2025-01-07



Trace: 1


Condition: QP RBW:9kHz
 AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	-3.82	20.73	16.91	55.96	39.05	Neutral	Average
0.15	11.84	20.73	32.57	65.96	33.39	Neutral	QP
0.19	-0.61	20.68	20.07	54.16	34.09	Neutral	Average
0.19	13.60	20.68	34.28	64.16	29.88	Neutral	QP
0.21	-7.03	20.65	13.62	53.17	39.55	Neutral	Average
0.21	8.67	20.65	29.32	63.17	33.85	Neutral	QP
0.23	-5.87	20.63	14.76	52.57	37.81	Neutral	Average
0.23	9.68	20.63	30.31	62.57	32.26	Neutral	QP
0.40	-1.58	20.45	18.87	47.78	28.91	Neutral	Average
0.40	12.76	20.45	33.21	57.78	24.57	Neutral	QP
0.45	-3.85	20.43	16.58	46.89	30.31	Neutral	Average
0.45	11.91	20.43	32.34	56.89	24.55	Neutral	QP

Project No.: 2407A50343E-EM
 Test Mode: Mode 2(400.0125MHz)
 EUT Model: WP67

Temp/Humi/ATM: 22.7°C/46%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)

Date: 2025-01-07



Trace: 1


Condition: QP RBW:9kHz
 AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.16	-1.21	20.88	19.67	55.70	36.03	Line	Average
0.16	15.00	20.88	35.88	65.70	29.82	Line	QP
0.16	-1.86	20.86	19.00	55.54	36.54	Line	Average
0.16	13.60	20.86	34.46	65.54	31.08	Line	QP
0.18	-2.79	20.71	17.92	54.55	36.63	Line	Average
0.18	11.95	20.71	32.66	64.55	31.89	Line	QP
0.19	2.99	20.62	23.61	53.96	30.35	Line	Average
0.19	16.45	20.62	37.07	63.96	26.89	Line	QP
0.20	-4.88	20.56	15.68	53.48	37.80	Line	Average
0.20	11.12	20.56	31.68	63.48	31.80	Line	QP
0.45	-0.07	20.32	20.25	46.89	26.64	Line	Average
0.45	17.12	20.32	37.44	56.89	19.45	Line	QP

Project No.: 2407A50343E-EM
 Test Mode: Mode 2(400.0125MHz)
 EUT Model: WP67

Temp/Humi/ATM: 22.7°C/46%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)

Date: 2025-01-07



Trace: 1


Condition: QP RBW:9kHz
 AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	-2.40	20.73	18.33	55.99	37.66	Neutral	Average
0.15	13.16	20.73	33.89	65.99	32.10	Neutral	QP
0.16	-4.54	20.71	16.17	55.35	39.18	Neutral	Average
0.16	11.09	20.71	31.80	65.35	33.55	Neutral	QP
0.20	-5.97	20.67	14.70	53.59	38.89	Neutral	Average
0.20	9.33	20.67	30.00	63.59	33.59	Neutral	QP
0.21	-6.49	20.65	14.16	53.02	38.86	Neutral	Average
0.21	9.04	20.65	29.69	63.02	33.33	Neutral	QP
0.42	-4.32	20.44	16.12	47.51	31.39	Neutral	Average
0.42	11.99	20.44	32.43	57.51	25.08	Neutral	QP
0.50	-3.29	20.39	17.10	46.03	28.93	Neutral	Average
0.50	11.86	20.39	32.25	56.03	23.78	Neutral	QP

Project No.: 2407A50343E-EM
 Test Mode: Mode 2(440MHz)
 EUT Model: WP67

Temp/Humi/ATM: 22.7°C/46%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)

Date: 2025-01-07



Trace: 1


Condition: QP RBW:9kHz
 AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.16	-5.81	20.83	15.02	55.36	40.34	Line	Average
0.16	9.81	20.83	30.64	65.36	34.72	Line	QP
0.19	0.66	20.63	21.29	54.01	32.72	Line	Average
0.19	14.68	20.63	35.31	64.01	28.70	Line	QP
0.20	-7.67	20.57	12.90	53.49	40.59	Line	Average
0.20	8.60	20.57	29.17	63.49	34.32	Line	QP
0.40	2.22	20.35	22.57	47.75	25.18	Line	Average
0.40	17.17	20.35	37.52	57.75	20.23	Line	QP
0.42	-0.13	20.34	20.21	47.49	27.28	Line	Average
0.42	16.13	20.34	36.47	57.49	21.02	Line	QP
0.45	0.29	20.33	20.62	46.89	26.27	Line	Average
0.45	17.97	20.33	38.30	56.89	18.59	Line	QP

Project No.: 2407A50343E-EM
Test Mode: Mode 2(440MHz)
EUT Model: WP67

Temp/Humi/ATM: 22.7°C/46%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2025-01-07



Trace: 1


Condition: QP RBW:9kHz
AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	-5.19	20.72	15.53	55.75	40.22	Neutral	Average
0.15	11.64	20.72	32.36	65.75	33.39	Neutral	QP
0.17	-7.31	20.70	13.39	54.84	41.45	Neutral	Average
0.17	8.64	20.70	29.34	64.84	35.50	Neutral	QP
0.19	-1.76	20.69	18.93	54.24	35.31	Neutral	Average
0.19	12.72	20.69	33.41	64.24	30.83	Neutral	QP
0.40	-2.48	20.45	17.97	47.80	29.83	Neutral	Average
0.40	12.53	20.45	32.98	57.80	24.82	Neutral	QP
0.45	-3.24	20.42	17.18	46.88	29.70	Neutral	Average
0.45	12.11	20.42	32.53	56.88	24.35	Neutral	QP
0.50	-1.73	20.39	18.66	46.03	27.37	Neutral	Average
0.50	12.99	20.39	33.38	56.03	22.65	Neutral	QP

Project No.: 2407A50343E-EM
 Test Mode: Mode 2(479.9875MHz)
 EUT Model: WP67

Temp/Humi/ATM: 22.7℃/46%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)

Date: 2025-01-07



Trace: 1


Condition: QP RBW:9kHz
 AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	-4.26	20.93	16.67	56.00	39.33	Line	Average
0.15	12.50	20.93	33.43	66.00	32.57	Line	QP
0.18	-5.35	20.71	15.36	54.55	39.19	Line	Average
0.18	10.09	20.71	30.80	64.55	33.75	Line	QP
0.19	0.50	20.63	21.13	54.06	32.93	Line	Average
0.19	14.68	20.63	35.31	64.06	28.75	Line	QP
0.42	0.57	20.34	20.91	47.51	26.60	Line	Average
0.42	16.19	20.34	36.53	57.51	20.98	Line	QP
0.45	0.21	20.33	20.54	46.89	26.35	Line	Average
0.45	17.97	20.33	38.30	56.89	18.59	Line	QP
0.50	1.15	20.29	21.44	46.06	24.62	Line	Average
0.50	17.73	20.29	38.02	56.06	18.04	Line	QP

Project No.: 2407A50343E-EM
 Test Mode: Mode 2(479.9875MHz)
 EUT Model: WP67

Temp/Humi/ATM: 22.7°C/46%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)

Date: 2025-01-07



Trace: 1

Condition: QP RBW:9kHz
 AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	-4.19	20.73	16.54	55.96	39.42	Neutral	Average
0.15	13.00	20.73	33.73	65.96	32.23	Neutral	QP
0.16	-6.39	20.72	14.33	55.52	41.19	Neutral	Average
0.16	10.46	20.72	31.18	65.52	34.34	Neutral	QP
0.18	-4.99	20.69	15.70	54.41	38.71	Neutral	Average
0.18	10.57	20.69	31.26	64.41	33.15	Neutral	QP
0.20	-6.96	20.68	13.72	53.77	40.05	Neutral	Average
0.20	9.05	20.68	29.73	63.77	34.04	Neutral	QP
0.40	-1.03	20.45	19.42	47.76	28.34	Neutral	Average
0.40	12.79	20.45	33.24	57.76	24.52	Neutral	QP
0.50	-1.75	20.39	18.64	46.03	27.39	Neutral	Average
0.50	13.03	20.39	33.42	56.03	22.61	Neutral	QP

FCC §15.109 - RADIATED EMISSION IN FREQUENCY

Applicable Standard


FCC§15.109

(a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:


Frequency of emission (MHz)	Field strength (microvolts/meter)
30–88	100
88–216	150
216–960	200
Above 960	500

Test System Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW	Measurement	Detector
30 MHz– 1000 MHz	100 kHz	300 kHz	PK	PK
	120 kHz	/	QP	QP
Above 1 GHz	1 MHz	3 MHz	PK	PK
	1 MHz	10 Hz	AV	PK

Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Result & Margin Calculation

The Result is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

Result (dBμV/m) = Reading (dBμV) + Factor (dB/m)

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Result (dBμV/m)


Test Data

Please refer to below plots:

1) 30MHz-1GHz:

Project No.: 2407A50343E-EM
Test Mode: Mode 1(400-480MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.00	24.88	-5.60	19.28	40.00	20.72	Horizontal	Peak
91.21	33.18	-17.04	16.14	43.50	27.36	Horizontal	Peak
145.72	29.54	-10.96	18.58	43.50	24.92	Horizontal	Peak
169.87	30.72	-11.85	18.87	43.50	24.63	Horizontal	Peak
202.37	30.83	-11.88	18.95	43.50	24.55	Horizontal	Peak
867.79	26.34	2.15	28.49	46.00	17.51	Horizontal	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 1(400-480MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
41.74	42.30	-12.90	29.40	40.00	10.60	Vertical	QP
49.30	49.68	-17.27	32.41	40.00	7.59	Vertical	QP
78.99	48.11	-16.99	31.12	40.00	8.88	Vertical	QP
90.43	48.80	-17.01	31.79	43.50	11.71	Vertical	Peak
129.13	40.05	-10.03	30.02	43.50	13.48	Vertical	Peak
174.82	39.15	-12.13	27.02	43.50	16.48	Vertical	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
32.91	26.14	-6.90	19.24	40.00	20.76	Horizontal	Peak
155.62	29.91	-11.34	18.57	43.50	24.93	Horizontal	Peak
213.82	32.25	-12.68	19.57	43.50	23.93	Horizontal	Peak
277.54	28.47	-9.47	19.00	46.00	27.00	Horizontal	Peak
337.01	28.09	-8.38	19.71	46.00	26.29	Horizontal	Peak
793.20	26.89	1.19	28.08	46.00	17.92	Horizontal	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
39.02	37.38	-10.87	26.51	40.00	13.49	Vertical	Peak
48.33	46.56	-16.98	29.58	40.00	10.42	Vertical	Peak
65.41	44.11	-17.28	26.83	40.00	13.17	Vertical	Peak
89.56	43.40	-17.06	26.34	43.50	17.16	Vertical	Peak
127.97	39.87	-9.92	29.95	43.50	13.55	Vertical	Peak
145.53	37.25	-10.97	26.28	43.50	17.22	Vertical	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(440MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.55	25.04	-6.16	18.88	40.00	21.12	Horizontal	Peak
75.40	32.15	-17.12	15.03	40.00	24.97	Horizontal	Peak
126.90	29.57	-10.02	19.55	43.50	23.95	Horizontal	Peak
168.52	29.29	-11.76	17.53	43.50	25.97	Horizontal	Peak
296.56	30.54	-9.26	21.28	46.00	24.72	Horizontal	Peak
336.71	30.07	-8.38	21.69	46.00	24.31	Horizontal	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(440MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
51.34	48.61	-17.59	31.02	40.00	8.98	Vertical	QP
84.32	46.03	-17.16	28.87	40.00	11.13	Vertical	QP
125.06	37.61	-9.94	27.67	43.50	15.83	Vertical	Peak
144.56	37.92	-10.97	26.95	43.50	16.55	Vertical	Peak
175.60	37.67	-12.11	25.56	43.50	17.94	Vertical	Peak
205.96	33.11	-12.18	20.93	43.50	22.57	Vertical	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.26	25.08	-6.00	19.08	40.00	20.92	Horizontal	Peak
51.15	33.09	-17.56	15.53	40.00	24.47	Horizontal	Peak
109.54	27.31	-12.04	15.27	43.50	28.23	Horizontal	Peak
147.27	30.73	-11.12	19.61	43.50	23.89	Horizontal	Peak
210.23	32.23	-12.63	19.60	43.50	23.90	Horizontal	Peak
988.65	24.01	3.86	27.87	54.00	26.13	Horizontal	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.8°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
38.54	37.22	-10.59	26.63	40.00	13.37	Vertical	Peak
47.27	46.79	-16.49	30.30	40.00	9.70	Vertical	QP
80.93	46.73	-17.06	29.67	40.00	10.33	Vertical	Peak
89.27	50.05	-17.13	32.92	43.50	10.58	Vertical	Peak
135.92	36.93	-10.33	26.60	43.50	16.90	Vertical	Peak
164.44	35.37	-11.61	23.76	43.50	19.74	Vertical	Peak

2) 1GHz ~ 5GHz

Project No.: 2407A50343E-EM
Test Mode: Mode 1(400-480MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.6°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2599.60	26.23	-2.69	23.54	54.00	30.46	horizontal	Average
2599.60	45.50	-2.69	42.81	74.00	31.19	horizontal	Peak
3004.80	26.41	-3.31	23.10	54.00	30.90	horizontal	Average
3004.80	47.03	-3.31	43.72	74.00	30.28	horizontal	Peak
3162.80	27.38	-2.25	25.13	54.00	28.87	horizontal	Average
3162.80	46.43	-2.25	44.18	74.00	29.82	horizontal	Peak
3367.20	26.34	-2.99	23.35	54.00	30.65	horizontal	Average
3367.20	46.92	-2.99	43.93	74.00	30.07	horizontal	Peak
3558.80	26.65	-3.69	22.96	54.00	31.04	horizontal	Average
3558.80	47.16	-3.69	43.47	74.00	30.53	horizontal	Peak
4920.80	26.73	-4.94	21.79	54.00	32.21	horizontal	Average
4920.80	47.05	-4.94	42.11	74.00	31.89	horizontal	Peak

Project No.: 2407A50343E-EM
 Test Mode: Mode 1(400-480MHz)
 EUT Model: WP67
 Test distance: 3m

Temp/Humi/ATM: 22.6°C/48%/100.1kPa
 Tested by: Lucas Lin
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2591.20	26.72	-2.72	24.00	54.00	30.00	vertical	Average
2591.20	45.65	-2.72	42.93	74.00	31.07	vertical	Peak
3072.80	25.54	-2.66	22.88	54.00	31.12	vertical	Average
3072.80	46.23	-2.66	43.57	74.00	30.43	vertical	Peak
3148.80	27.01	-2.25	24.76	54.00	29.24	vertical	Average
3148.80	46.06	-2.25	43.81	74.00	30.19	vertical	Peak
3236.80	25.33	-2.79	22.54	54.00	31.46	vertical	Average
3236.80	46.33	-2.79	43.54	74.00	30.46	vertical	Peak
3558.00	26.42	-3.69	22.73	54.00	31.27	vertical	Average
3558.00	47.12	-3.69	43.43	74.00	30.57	vertical	Peak
4988.40	27.63	-4.54	23.09	54.00	30.91	vertical	Average
4988.40	47.05	-4.54	42.51	74.00	31.49	vertical	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.6°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2571.60	27.73	-2.78	24.95	54.00	29.05	horizontal	Average
2571.60	46.33	-2.78	43.55	74.00	30.45	horizontal	Peak
2654.00	25.49	-2.85	22.64	54.00	31.36	horizontal	Average
2654.00	45.82	-2.85	42.97	74.00	31.03	horizontal	Peak
3089.60	27.15	-2.47	24.68	54.00	29.32	horizontal	Average
3089.60	46.40	-2.47	43.93	74.00	30.07	horizontal	Peak
3142.00	25.77	-2.27	23.50	54.00	30.50	horizontal	Average
3142.00	46.04	-2.27	43.77	74.00	30.23	horizontal	Peak
3454.00	26.84	-2.95	23.89	54.00	30.11	horizontal	Average
3454.00	46.33	-2.95	43.38	74.00	30.62	horizontal	Peak
4984.00	27.63	-4.56	23.07	54.00	30.93	horizontal	Average
4984.00	47.54	-4.56	42.98	74.00	31.02	horizontal	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.6°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
3075.60	25.74	-2.61	23.13	54.00	30.87	vertical	Average
3075.60	46.30	-2.61	43.69	74.00	30.31	vertical	Peak
3189.60	25.81	-2.24	23.57	54.00	30.43	vertical	Average
3189.60	46.42	-2.24	44.18	74.00	29.82	vertical	Peak
3325.60	27.48	-3.19	24.29	54.00	29.71	vertical	Average
3325.60	46.77	-3.19	43.58	74.00	30.42	vertical	Peak
3485.60	27.29	-3.24	24.05	54.00	29.95	vertical	Average
3485.60	46.55	-3.24	43.31	74.00	30.69	vertical	Peak
4453.60	27.33	-4.83	22.50	54.00	31.50	vertical	Average
4453.60	47.55	-4.83	42.72	74.00	31.28	vertical	Peak
4994.00	28.60	-4.52	24.08	54.00	29.92	vertical	Average
4994.00	47.27	-4.52	42.75	74.00	31.25	vertical	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(440MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.6°C /48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2605.20	26.15	-2.70	23.45	54.00	30.55	horizontal	Average
2605.20	45.86	-2.70	43.16	74.00	30.84	horizontal	Peak
3088.40	27.59	-2.49	25.10	54.00	28.90	horizontal	Average
3088.40	46.42	-2.49	43.93	74.00	30.07	horizontal	Peak
3231.60	26.14	-2.72	23.42	54.00	30.58	horizontal	Average
3231.60	46.94	-2.72	44.22	74.00	29.78	horizontal	Peak
3492.40	27.70	-3.28	24.42	54.00	29.58	horizontal	Average
3492.40	47.02	-3.28	43.74	74.00	30.26	horizontal	Peak
4005.20	26.62	-3.62	23.00	54.00	31.00	horizontal	Average
4005.20	46.09	-3.62	42.47	74.00	31.53	horizontal	Peak
4936.40	26.54	-4.82	21.72	54.00	32.28	horizontal	Average
4936.40	47.11	-4.82	42.29	74.00	31.71	horizontal	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(440MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.6°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2562.00	27.19	-2.82	24.37	54.00	29.63	vertical	Average
2562.00	46.54	-2.82	43.72	74.00	30.28	vertical	Peak
3174.40	25.86	-2.24	23.62	54.00	30.38	vertical	Average
3174.40	46.37	-2.24	44.13	74.00	29.87	vertical	Peak
3360.40	27.24	-3.02	24.22	54.00	29.78	vertical	Average
3360.40	46.64	-3.02	43.62	74.00	30.38	vertical	Peak
3421.20	27.67	-2.89	24.78	54.00	29.22	vertical	Average
3421.20	46.48	-2.89	43.59	74.00	30.41	vertical	Peak
4000.40	26.83	-3.65	23.18	54.00	30.82	vertical	Average
4000.40	46.33	-3.65	42.68	74.00	31.32	vertical	Peak
4927.60	27.45	-4.89	22.56	54.00	31.44	vertical	Average
4927.60	46.93	-4.89	42.04	74.00	31.96	vertical	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.6°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2607.20	26.46	-2.69	23.77	54.00	30.23	horizontal	Average
2607.20	45.48	-2.69	42.79	74.00	31.21	horizontal	Peak
3098.40	26.09	-2.38	23.71	54.00	30.29	horizontal	Average
3098.40	45.90	-2.38	43.52	74.00	30.48	horizontal	Peak
3176.80	26.94	-2.24	24.70	54.00	29.30	horizontal	Average
3176.80	46.27	-2.24	44.03	74.00	29.97	horizontal	Peak
3378.00	27.05	-2.95	24.10	54.00	29.90	horizontal	Average
3378.00	46.67	-2.95	43.72	74.00	30.28	horizontal	Peak
3963.20	27.57	-3.57	24.00	54.00	30.00	horizontal	Average
3963.20	46.87	-3.57	43.30	74.00	30.70	horizontal	Peak
4972.80	26.78	-4.61	22.17	54.00	31.83	horizontal	Average
4972.80	46.43	-4.61	41.82	74.00	32.18	horizontal	Peak

Project No.: 2407A50343E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: WP67
Test distance: 3m

Temp/Humi/ATM: 22.6°C/48%/100.1kPa
Tested by: Lucas Lin
Power Source: DC 8.4V from charger
(AC 120V/60Hz)

Date: 2024-12-10



Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2548.80	27.62	-2.88	24.74	54.00	29.26	vertical	Average
2548.80	46.94	-2.88	44.06	74.00	29.94	vertical	Peak
2600.40	26.74	-2.69	24.05	54.00	29.95	vertical	Average
2600.40	46.18	-2.69	43.49	74.00	30.51	vertical	Peak
3146.80	27.92	-2.26	25.66	54.00	28.34	vertical	Average
3146.80	46.35	-2.26	44.09	74.00	29.91	vertical	Peak
3428.00	27.19	-2.90	24.29	54.00	29.71	vertical	Average
3428.00	46.17	-2.90	43.27	74.00	30.73	vertical	Peak
3592.40	26.81	-3.70	23.11	54.00	30.89	vertical	Average
3592.40	46.18	-3.70	42.48	74.00	31.52	vertical	Peak
4973.20	27.58	-4.61	22.97	54.00	31.03	vertical	Average
4973.20	47.00	-4.61	42.39	74.00	31.61	vertical	Peak

FCC §15.121(b) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS


Applicable Standard

FCC §15.121(b).

(b) Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

Test Procedure

1. Connected the EUT as the below block diagram;



2. Apply a signal to the EUT antenna port at lowest, middle, highest channel frequencies of the operating band;
3. Adjust the audio output level of the EUT to it's rated value with the distortion less than 10%;
4. Adjust the 8920 output power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB; These output level of the 8920 at each channel frequency is the sensitivity of the EUT;
5. Select the lowest or worst case sensitivity level for all of the bands as the reference sensitivity;
6. Adjust the Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5 and its frequency to the frequency point in the Cellular Band;
7. Set the EUT squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level;
8. Set the EUT in a scanning mode and allow it to scan through it's complete receiving range;
9. If the EUT un-squelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38 dB;
10. Repeat above procedure at the frequencies 824, 836, 849 MHz for the mobile band, and 869, 881.5 and 894 MHz for the Cellular Base Band.

Test Data

Test Mode:	Scanning	Test Engineer:	Lucas Lin
Test Date:	2025-01-24	Test Result:	Pass

Environment Conditions:					
Temperature: (°C)	21.3	Relative Humidity: (%)	50	ATM Pressure: (kPa)	100.1

Scanning Frequency Range (MHz)	Test Frequency (MHz)	Measurement Result (Worst Case) (dB)	Limit (dB)
400-480	824, 836, 849, 869, 881.5, 895	48	>38

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2407A50343E-EM-EXP EUT EXTERNAL PHOTOGRAPHS and 2407A50343E-EM-INP EUT INTERNAL PHOTOGRAPHS

EXHIBIT B – TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2407A50343E-EM-TSP TEST SETUP PHOTOGRAPHS.

Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95 % confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

*******END OF REPORT*******