



802.11n 20 TEST RESULT AT CHAIN 0


TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL




TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL




802.11n 20 TEST RESULT AT CHAIN 1


TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL




TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL




802.11n 40 TEST RESULT AT CHAIN 0


TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL




TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL




802.11n 40 TEST RESULT AT CHAIN 1


TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL



11. RADIATED EMISSION


11.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.




11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,
the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT


RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.



RADIATED EMISSION BELOW 1GHZ

EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Horizontal




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1		57.4831	6.44	19.09	25.53	40.00	-14.47	peak
2		96.2831	10.55	15.63	26.18	43.50	-17.32	peak
3		314.5332	6.88	19.98	26.86	46.00	-19.14	peak
4	*	451.9499	13.44	24.02	37.46	46.00	-8.54	peak
5		493.9832	6.98	24.87	31.85	46.00	-14.15	peak
6		875.5167	4.17	31.38	35.55	46.00	-10.45	peak

RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Vertical



No.	Mk	Freq. MHz	Reading dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	41.3166	16.25	20.04	36.29	40.00	-3.71	peak
2	!	60.7167	15.92	18.74	34.66	40.00	-5.34	peak
3		99.5167	20.24	15.96	36.20	43.50	-7.30	peak
4		249.8667	11.37	18.49	29.86	46.00	-16.14	peak
5		314.5332	18.36	19.98	38.34	46.00	-7.66	peak
6		500.4499	9.35	25.00	34.35	46.00	-11.65	peak

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

3. Both antenna 0 and antenna 1 have been pre-tested, and all modes of each antenna are tested, Only the test data of antenna 0 in 802.11b at low channel is the worst case and recorded in the report.



RADIATED EMISSION ABOVE 1GHZ

EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4824.000	54.16	0.08	54.24	74	-19.76	peak
4824.000	45.31	0.08	45.39	54	-8.61	AVG
7236.000	48.28	2.21	50.49	74	-23.51	peak
7236.000	39.14	2.21	41.35	54	-12.65	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4824.000	53.29	0.08	53.37	74	-20.63	peak
4824.000	44.87	0.08	44.95	54	-9.05	AVG
7236.000	47.18	2.21	49.39	74	-24.61	peak
7236.000	38.12	2.21	40.33	54	-13.67	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2437MHz	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.000	56.94	0.14	57.08	74	-16.92	peak
4874.000	47.12	0.14	47.26	54	-6.74	AVG
7311.000	48.13	2.36	50.49	74	-23.51	peak
7311.000	39.57	2.36	41.93	54	-12.07	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2437MHz	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.000	54.16	0.14	54.3	74	-19.7	peak
4874.000	44.91	0.14	45.05	54	-8.95	AVG
7311.000	45.18	2.36	47.54	74	-26.46	peak
7311.000	36.27	2.36	38.63	54	-15.37	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4924.000	54.29	0.22	54.51	74	-19.49	peak
4924.000	45.37	0.22	45.59	54	-8.41	AVG
7386.000	46.12	2.64	48.76	74	-25.24	peak
7386.000	38.27	2.64	40.91	54	-13.09	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4924.000	53.18	0.22	53.4	74	-20.6	peak
4924.000	44.18	0.22	44.4	54	-9.6	AVG
7386.000	45.62	2.64	48.26	74	-25.74	peak
7386.000	36.54	2.64	39.18	54	-14.82	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: PASS

Note:

- Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report.
- Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.
The "Factor" value can be calculated automatically by software of measurement system.
- Both antenna 0 and antenna 1 have been pre-tested, and all modes of each antenna are tested, only the antenna 0 in 802.11b mode is the worst case and recorded in the report.



12. BAND EDGE EMISSION

12.1. MEASUREMENT PROCEDURE

Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

12.2. TEST SET-UP

same as 11.2

Note:


1. Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level
2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.
3. Both antenna 0 and antenna 1 have been pre-tested, and all modes of each antenna are tested,. The antenna 0 is the worst case and recorded in the report.



12.3. TEST RESULT

EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Horizontal

PK



AV




RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Vertical

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHz	Antenna	Horizontal

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHz	Antenna	Vertical

PK



AV




RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHz	Antenna	Horizontal

PK



AV




RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHz	Antenna	Vertical

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHz	Antenna	Horizontal

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHz	Antenna	Vertical

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHz	Antenna	Horizontal

PK



AV




RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHz	Antenna	Vertical

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHz	Antenna	Horizontal

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHz	Antenna	Vertical

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHz	Antenna	Horizontal

PK



AV



RESULT: PASS



EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHz	Antenna	Vertical

PK



AV



RESULT: PASS




EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40with data rate 13.5 2452MHz	Antenna	Horizontal

PK



AV



RESULT: PASS




EUT	AC3000 Tri-Band Mesh Router	Model Name	TT-ND001
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2452MHz	Antenna	Vertical

PK



AV



RESULT: PASS



13. FCC LINE CONDUCTED EMISSION TEST


13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

13.2. BLOCK DIAGRAM OF TEST SETUP




13.3. PROCEDURE OF LINE CONDUCTED EMISSION TEST

- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per ANSI C63.10.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- (4) The EUT received AC120V/60Hz power from a LISN.
- (5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (6) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- (7) During the above scans, the emissions were maximized by cable manipulation.
- (8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
- (9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.



13.4. TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION TEST-L1



MEASUREMENT RESULT: "agc_fin"

2020/6/15 13:05

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154000	43.10	9.3	66	22.7	QP	L1	FLO
0.178000	41.90	9.3	65	22.7	QP	L1	FLO
0.202000	38.90	9.3	64	24.6	QP	L1	FLO
0.582000	37.80	9.3	56	18.2	QP	L1	FLO
0.614000	37.60	9.3	56	18.4	QP	L1	FLO
0.618000	29.50	9.3	56	26.5	QP	L1	FLO
4.190000	32.60	9.4	56	23.4	QP	L1	FLO

MEASUREMENT RESULT: "agc_fin2"


2020/6/15 13:05

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154000	23.30	9.3	56	32.5	AV	L1	FLO
0.178000	24.70	9.3	55	29.9	AV	L1	FLO
0.202000	23.90	9.3	54	29.6	AV	L1	FLO
0.582000	30.90	9.3	46	15.1	AV	L1	FLO
4.194000	22.90	9.4	46	23.1	AV	L1	FLO

RESULT: PASS



LINE CONDUCTED EMISSION TEST-N



MEASUREMENT RESULT: "agc_fin"

2020/6/15 12:48

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.170000	46.00	9.3	65	19.0	QP	N	FLO
0.198000	42.10	9.3	64	21.6	QP	N	FLO
0.230000	38.10	9.3	62	24.3	QP	N	FLO
0.442000	34.30	9.3	57	22.7	QP	N	FLO
0.582000	37.10	9.3	56	18.9	QP	N	FLO
0.610000	38.00	9.3	56	18.0	QP	N	FLO

MEASUREMENT RESULT: "agc_fin2"


2020/6/15 12:48

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.170000	30.40	9.3	55	24.6	AV	N	FLO
0.198000	25.30	9.3	54	28.4	AV	N	FLO
0.230000	22.10	9.3	52	30.3	AV	N	FLO
0.422000	23.10	9.3	47	24.3	AV	N	FLO
0.582000	30.30	9.3	46	15.7	AV	N	FLO
0.610000	29.60	9.3	46	16.4	AV	N	FLO




APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP BELOW 1GHZ




FCC RADIATED EMISSION TEST SETUP ABOVE 1GHZ



FCC CONDUCTED EMISSION TEST SETUP



CONDUCTED TEST SETUP



APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC00210200519AP01

----END OF REPORT----

