



FCC PART 15.247

TEST REPORT

For

Colorlight (Shenzhen) Cloud Technology Co., Ltd.

Room 101, IC Industrial Park, No. 1089 Chaguang Road, Xili Street, Nanshan
District, Shenzhen, China

FCC ID: 2AVV2C100CLT

Report Type: Original Report	Product Type: Player
Report Number: RSZ200312810-00A	
Report Date: 2020-05-18	
Nancy Wang 	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “*”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	10
TEST EQUIPMENT LIST	11
FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	12
APPLICABLE STANDARD	12
RESULT	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP.....	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
CORRECTED FACTOR & MARGIN CALCULATION	15
TEST RESULTS SUMMARY	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST RESULTS SUMMARY	19
TEST DATA	20
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	36

APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	38
FCC §15.247(e) - POWER SPECTRAL DENSITY	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST DATA	42

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Player
Model	C1
Frequency Range	2.4G Wi-Fi: 2412~2462MHz
Maximum Conducted Peak Output Power	2.G Wi-Fi: 16.55dBm(802.11b), 20.24dBm(802.11g), 18.97dBm(802.11n20)
Modulation Technique	2.4G Wi-Fi: DSSS, OFDM
Antenna Specification	4.5dBi
Voltage Range	AC 120V 60Hz
Date of Test	2020-04-09 to 2020-05-07
Sample serial number	RSZ200312810-RF-S1 (Assigned by BACL, Shenzhen)
Received date	2020-03-12
Sample/EUT Status	Good condition

Objective

This report is prepared on behalf of *Colorlight (Shenzhen) Cloud Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.407 NII submissions with FCC ID: 2AVV2C100CLT.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2437	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


“rftesttool 54” software was used to test.

Mode	Data rate	Power level		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	Default	Default	Default
802.11g	6 Mbps	Default	Default	Default
802.11n-HT20	MCS0	Default	Default	Default

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.


Duty cycle

802.11b mode




Date: 9.APR.2020 13:01:03

802.11g mode



Date: 9.APR.2020 13:02:32

802.11n-HT20 Mode

Date: 9.APR.2020 13:03:38


Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	--	--	100
802.11g	--	--	100
802.11n-HT20	--	--	100

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HIKVISION	Router	DS-3WR03-E	10021642429
Unknown	Earphone	001	Unknown
BRL	USB Disk(*2)	866.275.8378	Unknown
Unknown	Display	Unknown	Unknown

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielded detachable AC cable	1.0	EUT	LISN
Un-shielded detachable RJ45 cable	8.0	Router	EUT

Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure(MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2019/7/9	2020/7/8
Rohde & Schwarz	LISN	ENV216	101613	2020/1/22	2021/1/21
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2019/11/29	2020/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2019/11/29	2020/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test (30M-1G)					
R&S	EMI Test Receiver	ESR3	102455	2019/7/9	2020/7/8
Sonoma instrument	Pre-amplifier	310 N	186238	2020/4/20	2021/4/19
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017/12/22	2020/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2019/11/29	2020/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2019/11/29	2020/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Radiated Emission Test (above 1G)					
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2019/7/22	2020/7/21
COM-POWER	Pre-amplifier	PA-122	181919	2019/11/29	2020/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2019/11/29	2020/11/28
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017/12/22	2020/12/21
Insulted Wire Inc.	RF Cable	SPS-2503-3150	02222010	2019/11/29	2020/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2019/11/29	2020/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2019/4/20	2020/4/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-02 1304	2017/12/6	2020/12/5
RF Conducted Test					
Agilent	USB Wideband Power Sensor	U2021XA	MY54250003	2019/7/10	2020/7/9
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2020/3/2	2021/3/1
WEINSCHL	10dB Attenuator	5324	AU3842	2019/11/29	2020/11/28
Unknown	RF Cable	Unknown	2301 276	2019/11/29	2020/11/28

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Max Tune Up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	4.5	2.82	20.5	112.2	20	0.063	1.0

Note:

(1) To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

(2) The equipment is not a simultaneous transmit system.

Result: compliance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one external antenna which used non-standard antenna connectors. The antenna gain is 4.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the EUT complied with the FCC Part 15.207,


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2020-05-07.

EUT operation mode: Wi-Fi Transmitting (Wi-Fi Low channel in 802.11g mode was the worst case)

AC 120V/60 Hz, Line

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.865070	34.2	19.8	56.0	21.8	QP
0.972370	35.9	19.9	56.0	20.1	QP
1.077930	33.0	19.9	56.0	23.0	QP
4.507250	38.6	19.9	56.0	17.4	QP
4.562230	39.1	19.9	56.0	16.9	QP
20.998970	44.3	20.5	60.0	15.7	QP
0.865070	26.6	19.8	46.0	19.4	Ave.
0.972370	29.5	19.9	46.0	16.5	Ave.
1.077930	27.3	19.9	46.0	18.7	Ave.
4.507250	30.0	19.9	46.0	16.0	Ave.
4.562230	28.5	19.9	46.0	17.5	Ave.
20.998970	37.0	20.5	50.0	13.0	Ave.

AC 120V/60 Hz, Neutral


Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.975510	34.5	19.8	56.0	21.5	QP
1.125110	35.4	19.8	56.0	20.6	QP
4.245650	36.0	19.9	56.0	20.0	QP
4.530170	37.1	19.9	56.0	18.9	QP
24.998970	46.6	20.3	60.0	13.4	QP
27.000970	45.5	20.2	60.0	14.5	QP
0.870000	28.5	19.7	46.0	17.5	Ave.
4.774000	31.1	19.9	46.0	14.9	Ave.
4.998000	30.1	19.9	46.0	15.9	Ave.
21.002000	33.6	20.4	50.0	16.4	Ave.
25.002000	38.7	20.3	50.0	11.3	Ave.
26.998000	37.4	20.2	50.0	12.6	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.


Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Hams He on 2020-05-07 for below 1G and Charlie Cha on 2020-04-16 for above 1G.

EUT operation mode: Transmitting

30 MHz~1 GHz (Wi-Fi Low channel in 802.11g mode was the worst case):



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
58.968625	31.88	103.0	V	220.0	-20.1	40.00	8.12
228.150250	29.33	119.0	H	286.0	-14.0	46.00	16.67
282.775875	31.05	102.0	H	157.0	-11.8	46.00	14.95
347.794000	35.21	109.0	H	348.0	-10.8	46.00	10.79
364.380875	36.12	102.0	H	336.0	-10.7	46.00	9.88
875.021125	35.04	104.0	V	223.0	3.6	46.00	10.96

1 GHz-25 GHz (Wi-Fi):**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2331.25	28.71	PK	21	1.0	H	31.64	60.35	74	13.65
2331.25	13.63	Ave.	21	1.0	H	31.64	45.27	54	8.73
2489.67	28.79	PK	212	1.5	H	32.13	60.92	74	13.08
2489.67	13.68	Ave.	212	1.5	H	32.13	45.81	54	8.19
4824.00	44.25	PK	234	1.5	H	5.40	49.65	74	24.35
4824.00	29.57	Ave.	234	1.5	H	5.40	34.97	54	19.03
Middle Channel (2437MHz)									
4874.00	44.42	PK	325	1.3	H	6.43	50.85	74	23.15
4874.00	29.33	Ave.	325	1.3	H	6.43	35.76	54	18.24
High Channel (2462 MHz)									
2323.34	28.78	PK	248	1.8	H	31.64	60.42	74	13.58
2323.34	13.68	Ave.	248	1.8	H	31.64	45.32	54	8.68
2491.77	28.89	PK	241	1.6	H	32.13	61.02	74	12.98
2491.77	13.84	Ave.	241	1.6	H	32.13	45.97	54	8.03
4924.00	44.19	PK	1	2.5	H	6.43	50.62	74	23.38
4924.00	29.13	Ave.	1	2.5	H	6.43	35.56	54	18.44

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2338.64	28.77	PK	124	2.0	H	31.64	60.41	74	13.59
2338.64	13.73	Ave.	124	2.0	H	31.64	45.37	54	8.63
2487.69	28.69	PK	240	2.3	H	32.13	60.82	74	13.18
2487.69	13.61	Ave.	240	2.3	H	32.13	45.74	54	8.26
4824.00	44.15	PK	160	1.3	H	5.40	49.55	74	24.45
4824.00	29.53	Ave.	160	1.3	H	5.40	34.93	54	19.07
Middle Channel (2437MHz)									
4874.00	44.35	PK	69	1.2	H	6.43	50.78	74	23.22
4874.00	29.23	Ave.	69	1.2	H	6.43	35.66	54	18.34
High Channel (2462 MHz)									
2365.58	28.79	PK	41	1.3	H	31.87	60.66	74	13.34
2365.58	13.63	Ave.	41	1.3	H	31.87	45.50	54	8.50
2487.51	28.89	PK	125	1.7	H	32.13	61.02	74	12.98
2487.51	13.78	Ave.	125	1.7	H	32.13	45.91	54	8.09
4924.00	44.15	PK	88	1.6	H	6.43	50.58	74	23.42
4924.00	29.11	Ave.	88	1.6	H	6.43	35.54	54	18.46

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2342.31	28.74	PK	48	2.1	H	31.64	60.38	74	13.62
2342.31	13.62	Ave.	48	2.1	H	31.64	45.26	54	8.74
2486.89	28.91	PK	327	1.4	H	32.13	61.04	74	12.96
2486.89	13.76	Ave.	327	1.4	H	32.13	45.89	54	8.11
4824.00	44.12	PK	254	1.2	H	5.40	49.52	74	24.48
4824.00	29.43	Ave.	254	1.2	H	5.40	34.83	54	19.17
Middle Channel (2437MHz)									
4874.00	44.28	PK	268	1.7	H	6.43	50.71	74	23.29
4874.00	29.01	Ave.	268	1.7	H	6.43	35.44	54	18.56
High Channel (2462 MHz)									
2361.37	28.81	PK	25	1.5	H	31.87	60.68	74	13.32
2361.37	13.68	Ave.	25	1.5	H	31.87	45.55	54	8.45
2495.74	28.85	PK	258	1.7	H	32.13	60.98	74	13.02
2495.74	13.72	Ave.	258	1.7	H	32.13	45.85	54	8.15
4924.00	43.98	PK	33	1.3	H	6.43	50.41	74	23.59
4924.00	29.05	Ave.	33	1.3	H	6.43	35.48	54	18.52

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude


The other spurious emission which is 20dB to the limit was not recorded.

And for the harmonic test, it is performed with the 2400-2483.5MHz band filter.

**Pre-scan with 802.11b Mode, Middle channel
Horizontal**




Date: 16.APR.2020 19:02:54




Date: 16.APR.2020 19:50:25

Vertical




Date: 16.APR.2020 19:11:19




Date: 16.APR.2020 19:56:41

Pre-scan for Average Horizontal




Date: 16.APR.2020 19:07:03




Date: 16.APR.2020 19:53:51

Vertical



Date: 16.APR.2020 19:15:37



Date: 16.APR.2020 19:59:20


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Chen on 2020-06-09.


Test Result: Pass.

Please refer to the following table and plots.

EUT operation mode: Transmitting


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b mode			
Low	2412	8.205	≥ 0.5
Middle	2437	8.141	≥ 0.5
High	2462	8.205	≥ 0.5
802.11g			
Low	2412	16.282	≥ 0.5
Middle	2437	16.090	≥ 0.5
High	2462	16.282	≥ 0.5
802.11n-HT20 mode			
Low	2412	16.538	≥ 0.5
Middle	2437	17.179	≥ 0.5
High	2462	17.564	≥ 0.5

802.11b Low Channel




Date: 9.JUN.2020 19:04:57

802.11b Middle Channel




Date: 9.JUN.2020 19:07:24

802.11b High Channel




Date: 9.JUN.2020 19:08:36

802.11g Low Channel




Date: 9.JUN.2020 21:31:16

802.11g Middle Channel




Date: 9.JUN.2020 21:32:11

802.11g High Channel




Date: 9.JUN.2020 21:33:29

802.11n-HT20 Low Channel




Date: 9.JUN.2020 21:35:53

802.11n-HT20 Middle Channel



Date: 9.JUN.2020 21:35:10

802.11n-HT20 High Channel



Date: 9.JUN.2020 21:34:21


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Chen on 2020-04-09.

EUT operation mode: Transmitting

Wi-Fi mode

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b				
Low	2412	16.05	13.33	30
Middle	2437	16.38	13.65	30
High	2462	16.55	13.94	30
802.11g				
Low	2412	20.24	13.83	30
Middle	2437	20.07	14.25	30
High	2462	20.07	14.06	30
802.11n HT20				
Low	2412	18.97	12.98	30
Middle	2437	18.75	12.59	30
High	2462	18.73	13.02	30


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Chen on 2020-04-09.

EUT operation mode: Transmitting

Test Result: Compliance


Please refer to the following plots.

802.11b: Band Edge, Left Side




Date: 9.APR.2020 12:39:12

802.11b: Band Edge, Right Side




Date: 9.APR.2020 12:40:36

802.11g: Band Edge, Left Side




Date: 9.APR.2020 12:36:59

802.11g: Band Edge, Right Side




Date: 9.APR.2020 12:35:38

802.11n-HT20: Band Edge, Left Side



Date: 9.APR.2020 12:42:16

802.11n-HT20: Band Edge, Right Side



Date: 9.APR.2020 12:44:33


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Chen on 2020-04-09.

EUT operation mode: Transmitting

Test Result: Pass


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-8.10	≤ 8
Middle	2437	-8.11	≤ 8
High	2462	-8.36	≤ 8
802.11g mode			
Low	2412	-11.86	≤ 8
Middle	2437	-12.06	≤ 8
High	2462	-11.57	≤ 8
802.11n-HT20 mode			
Low	2412	-13.80	≤ 8
Middle	2437	-12.46	≤ 8
High	2462	-13.03	≤ 8

Power Spectral Density, 802.11b Low Channel




Date: 9.APR.2020 12:55:43

Power Spectral Density, 802.11b Middle Channel




Date: 9.APR.2020 12:56:53

Power Spectral Density, 802.11b High Channel




Date: 9.APR.2020 12:58:07

Power Spectral Density, 802.11g Low Channel




Date: 9.APR.2020 12:51:12

Power Spectral Density, 802.11g Middle Channel




Date: 9.APR.2020 12:52:38

Power Spectral Density, 802.11g High Channel




Date: 9.APR.2020 12:53:28

Power Spectral Density, 802.11n-HT20 Low Channel




Date: 9.APR.2020 12:49:59

Power Spectral Density, 802.11n-HT20 Middle Channel



Date: 9.APR.2020 12:48:51

Power Spectral Density, 802.11n-HT20 High Channel



Date: 9.APR.2020 12:47:30

***** END OF REPORT *****