

## RF Exposure Evaluation

For

Liquipel Protection LLC

## 3 in 1 WIRELESS CHARGING STAND

Test Model: 827072


<b>RF Exposure Evaluation</b>	
<b>Report Reference No.</b> ..... : <b>LCSC08125004EB</b>	
Date of Issue ..... : September 03, 2025	
<b>Testing Laboratory Name</b> ..... : <b>Guangzhou LCS Compliance Testing Laboratory Ltd.</b>	
Address ..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China	
Testing Location/ Procedure ..... : Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>	
<b>Applicant's Name</b> ..... : <b>Liquipel Protection LLC</b>	
Address ..... : 19800 MacArthur Blvd. Suite 300, Irvine	
<b>Test Specification</b>	
Standard ..... : FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091 KDB447498 D01 General RF Exposure Guidance v06	
<b>Test Report Form No.</b> ..... : TRF-4-E-148 A/0	
TRF Originator ..... : Guangzhou LCS Compliance Testing Laboratory Ltd.	
Master TRF ..... : Dated 2011-03	
<b>Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.</b>	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
<b>EUT Description</b> ..... : <b>3 in 1 WIRELESS CHARGING STAND</b>	
Trade Mark ..... : Simple	
Test Model ..... : 827072	
Ratings ..... : Please Refer to Page 6	
Result ..... : <b>PASS</b>	

Compiled by:



Lifeng Le/ File administrators

Supervised by:



Justin Zhu/ Technique Director

Approved by:



Gavin Liang/ Manager

**FCC TEST REPORT**

<b>Test Report No. :</b>	<b>LCSC08125004EB</b>	<u>September 03, 2025</u>
		Date of issue

Test Model.....	: 827072
EUT.....	: 3 in 1 WIRELESS CHARGING STAND
<b>Applicant</b> .....	: <b>Liquipel Protection LLC</b>
Address.....	: 19800 MacArthur Blvd. Suite 300, Irvine
Telephone.....	: /
Fax.....	: /
<b>Manufacturer</b> .....	: <b>XYCOSMOS HOLDING CO.,Ltd.</b>
Address.....	: NO.12, Donghuan 2nd Road, Huangjiang Town, Dongguan City, Guangdong, China
Telephone.....	: /
Fax.....	: /
<b>Factory</b> .....	: <b>XYCOSMOS HOLDING CO.,Ltd.</b>
Address.....	: NO.12, Donghuan 2nd Road, Huangjiang Town, Dongguan City, Guangdong, China
Telephone.....	: /
Fax.....	: /

<b>Test Result</b>	<b>PASS</b>
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

Report Version	Issue Date	Revision Content	Revised By
000	September 03, 2025	Initial Issue	--

## TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION .....	6
2. EVALUATION METHOD .....	8
3. EVALUATION LIMIT .....	11
4. TEST SETUP DIAGRAM .....	12
5. TEST EQUIPMENT .....	12
6. MEASUREMENT PROCEDURE .....	12
7. EQUIPMENT APPROVAL CONSIDERATIONS .....	13
8. E AND H FIELD STRENGTH .....	14
9. CONCLUSION .....	21

## 1. GENERAL INFORMATION

### 1.1 Product Information

EUT	: 3 in 1 WIRELESS CHARGING STAND
Test Model	: 827072
Ratings	: INPUT 9V==3A PHONE OUTPUT 5W, 7.5W, 10W, 15W Max EARBUD OUTPUT 5W Max SMART WATCH OUTPUT 3W Max MAX OUTPUT 23W For Adapter: INPUT 100-240V~ 50/60Hz 0.8A Max OUTPUT 5V==3A, 9V==3A   PPS:3.3-11V==3A 15V==2A, 20V==1.5A   3.3-16V==2A (30W Max)
Hardware Version	: /
Software Version	: /
Wireless Charging	: [REDACTED]
Operating Frequency	: Airpods coil: 110.3~205.0kHz Mobile Phone coil: 110.3~205.0kHz Apple Watch coil: 327.7kHz
Modulation Type	: ASK
Antenna Type	: Coil Antenna

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

## 1.2 Description of Test Facility

### Site Description

EMC Lab. : CNAS Registration Number is L11555  
 EMC Lab. : A2LA Certificate Number: 5099.01  
 EMC Lab. : FCC Designation Number is CN1379  
 EMC Lab. : Test Firm Registration Number: 729882

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 1.3 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.4 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	3.10dB	(1)
	30MHz~200MHz	2.96dB	(1)
	200MHz~1000MHz	3.10dB	(1)
	1GHz~26.5GHz	3.80dB	(1)
	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	1.63dB	(1)
Power disturbance	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2. Evaluation Method

Per KDB 680106 D01 Section 3. RF Exposure Requirements;

- 1) Wireless power transfer devices must comply with RF exposure requirements for all design configurations in which they can operate. At a minimum, RF exposure must be evaluated for the worst-case scenario, typically when the transmitter, while delivering energy to a client device, is operating at maximum output power. RF exposure compliance for equipment authorization must be determined following the guidance of KDB447498, which includes consideration of the different test requirements for *Mobile Device* and *Portable Device* exposure categories, as defined in §§ 2.1091 and 2.1093 of the Rules.
- 2) The RF exposure limits, as set forth in § 1.1310, do not cover the frequency range below 100 kHz for Specific Absorption Rate (SAR) and below 300 kHz for Maximum Permitted Exposure (MPE). In addition, present limitations of RF exposure evaluation systems prevent an accurate evaluation of SAR below 4 MHz. For these reasons, a specific MPE-based RF Exposure compliance procedure for devices operating in the aforementioned low-frequency ranges has been set in place. This procedure is applicable to Equipment Authorization of all RF devices, thus including, but not limited to, Part 18 and WPT devices. Accordingly, for § 2.1091-*Mobile* devices, the MPE limits between 100 kHz to 300 kHz are to be considered the same as those at 300 kHz in Table 1 of § 1.1310, that is, 614 V/m and 1.63 A/m, for the electric field and magnetic field, respectively. For § 2.1093-*Portable* devices below 4 MHz and down to 100 kHz, the MPE limits in § 1.1310 (with the 300 kHz limit applicable all the way down to 100 kHz) can be used for the purpose of equipment authorization in lieu of SAR evaluations.

Furthermore, consistent with FCC's equipment authorization RF exposure guidance, any device (both portable and mobile) operating at frequencies below 100 kHz is considered compliant for the purpose of equipment authorization when the external (unperturbed) temporal peak field strengths do not exceed the following reference levels:

83 V/m for the electric field strength (*E*)


and 90 A/m for the magnetic field strength (*H*)

These data may be provided through measurements and/or numerical simulations, and for all the positions in space relevant for any possible body exposure.

- 3) "Large size" probes may prevent the measurement of E- and/or H-fields near the surface of the radiating structure (e.g., a WPT source coil), as in the example shown in Figure 1.

If the center of the probe sensing element is located more than 5 mm from the probe outer surface, the field strengths need to be estimated through modeling for those positions that are not reachable. The estimates may be done either via numerical calculation, or via analytic model: e.g., approximated formulas for circular coils, dipoles, etc., may be acceptable if it is shown that the model is applicable for the design parameters considered. A typical example is the use of a quasi-static approximation formula for a low-frequency magnetic field source. These estimates shall include points spaced no more than 2 cm from each other. Thus, in the example of


Figure 1, at least the estimates at 0 cm<sup>2</sup> and 2 cm are required, while only one point would not be sufficient. In addition, the model needs to be validated through the probe measurements for the two closest points to the device surface, and with 2-cm increments, as indicated in Figure 1. In that example, the same model must also be applied to the 4 cm and 6 cm positions, and then compared with the measured data, for validation purposes. The validation is considered sufficient if a 30% agreement between the model and the (E- and/or H-field) probe measurements is demonstrated. If such a level of agreement cannot be shown, a more accurate model (and/or a smaller probe) shall be used.




**Figure 1. Example of probe (in yellow) measurements in points close to the WPT device (in red/brown). The probe radius is 4 cm, thus the closest point to the device where the field can be measured is at 4 cm from the surface (this example assumes that the probe calibration refers to the center of the sensing element structure, in this case a sphere of 4 cm radius). Data at 0 cm and 2 cm must be estimated through a model, and then the same model must be validated via comparison with the actual measurements at 4 cm and 6 cm, where the probe center can be positioned and collect valid data.**

4) Part 18 Wireless Power Transfer up to One-Meter Distance. This section applies only to WPT transmitters that, by design, can provide power to a load located at a distance no greater than one meter. This distance shall be measured between the closest points between the transmitter and the receiver enclosure surfaces. For instance, two coils positioned as in Figure 2-a may be operated and considered under the provisions of this section, because both receivers are within one-meter distance from the transmitter. However, the case in Figure 2-b cannot be considered in the same way, and it is treated according to the prescription of Section 5.3.

For WPT designs with more than one radiating structure the distance to the load shall be considered as in Figure 3, thus measured between the receiver and the closest transmitting structure.




**a) Not considered as WPT  
“at-a-distance”**



**b) WPT “at-a-distance”  
because RX2 position**

**Figure 2-a)** For multiple-receiver systems (here shown with two receivers, indicated with RX1 and RX2) the one-meter distance limit must apply for all the receivers that are engaged in the charging process. **b)** The WPT system is considered “at-a-distance” because it can function when the RX2 is further away than one meter from the transmitter.



**Figure 3.** For multiple-coil transmitter systems, the one-meter distance limit is measured from the closest coil edge. A WPT within one meter operates with loads configured as those labeled in green font, if a load can be powered beyond one meter (in red), then it shall be considered “at-a-distance”

There might be situations where the WPT RF emissions are limited enough that even operations in a “crowded” environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an “Equipment Compliance Review” KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met:

- (1) The power transfer frequency is below 1 MHz.
- (2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.
- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
- (4) Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093 – Portable exposure conditions).
- (5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.
- 5) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be

powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested

### 3. Evaluation Limit

#### 3.1 Refer evaluation method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 680106 D01 Wireless Power Transfer v04](#): EQUIPMENT AUTHORIZATION OF WIRELESS POWER TRANSFER DEVICES

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

[FCC CFR 47 part 18.107](#): Indusial, Scientific, and Medical Equipment

#### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	/	/	f/300	6
1,500-100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	/	/	f/1500	30
1,500-100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density


According to FCC KDB 680106 D01 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 – Section1.310 as following (measured distance

shall be 15cm from the center of the probe to the edge of the device):

	E-Field	*/*	B-Field
Frequency	V/m	A/m	uT
0.3 MHz – 3.0 MHz	614	1.613	2.0
3.0 MHz – 30 MHz	824/f (=27.5 <sub>30MHz</sub> )	2.19/f (=0.073 <sub>30MHz</sub> )	--

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.

#### 4. Test Setup Diagram



#### 5. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Exposure Level Tester	Narda	ELT-400	N-0713	2024-11-11	2025-11-10
2	B-Field Probe	Narda	ELT-400	M-1154	2024-10-08	2025-10-07
3	Electric field probe	Narda	EP601	611WX70332	N/A	N/A

#### 6. Measurement Procedure

- The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- The measurement probe was placed at test distance (15cm and 20cm) which is between the edges of the charger and the geometric center of probe.
- The turn table was rotated 360d degree to search of highest strength.
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- The EUT were measured according to the dictates of KDB 680106D01v03.

## 7. Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01v04 as follows table;

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operates in the frequency range 110.3 KHz – 205.0 KHz and 327.7 KHz.
The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.	Yes	The device contains three transmitter coils, the maximum output power of coil is 15W.
A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)	Yes	Client device is placed directly in contact with the transmitter.
Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).	Yes	Mobile exposure condition only.
The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.	Yes	The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit
For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not	Yes	Only one radiating structure and tested at maximum Output Power

powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested		
--	--	--

There might be situations where the WPT RF emissions are limited enough that even operations in a "crowded" environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an "Equipment Compliance Review" KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met.

## 8. E and H field Strength

Test Modes		
Mode 1	AC/DC Adapter(9V/3A) + EUT + Phone + Apple Watch + AirPods (Battery Status: <1%)	Record
Mode 2	AC/DC Adapter (9V/3A)+ EUT + Phone + Apple Watch + AirPods (Battery Status: <50%)	Record
Mode 3	AC/DC Adapter (9V/3A) + EUT + Phone + Apple Watch + AirPods (Battery Status: 100%)	Record
Mode 4	AC/DC Adapter(9V/3A) + EUT + Phone (Battery Status: <1%)	Pre-tested
Mode 5	AC/DC Adapter (9V/3A)+ EUT + Phone (Battery Status: <50%)	Pre-tested
Mode 6	AC/DC Adapter (9V/3A) + EUT + Phone (Battery Status: 100%)	Pre-tested
Mode 7	AC/DC Adapter(9V/3A) + EUT + Apple Watch (Battery Status: <1%)	Pre-tested
Mode 8	AC/DC Adapter (9V/3A)+ EUT + Apple Watch (Battery Status: <50%)	Pre-tested
Mode 9	AC/DC Adapter (9V/3A) + EUT + Apple Watch (Battery Status: 100%)	Pre-tested
Mode 10	AC/DC Adapter(9V/3A) + EUT + AirPods (Battery Status: <1%)	Pre-tested
Mode 11	AC/DC Adapter (9V/3A)+ EUT + AirPods (Battery Status: <50%)	Pre-tested
Mode 12	AC/DC Adapter (9V/3A) + EUT + AirPods (Battery Status: 100%)	Pre-tested

Note: All test modes were pre-tested, but we only recorded the worst case in this report.

**For Phone**

Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values					50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
Mode 1	110.3~205.0	uT	0.128	0.137	0.144	0.132	0.148	--	--
Mode 1	110.3~205.0	A/m	0.102	0.109	0.115	0.105	0.118	0.815	1.63
Mode 1	110.3~205.0	V/m	38.368	41.085	43.345	39.578	44.460	307.0	614.0
Mode 2	110.3~205.0	uT	0.126	0.136	0.140	0.126	0.147	--	--
Mode 2	110.3~205.0	A/m	0.101	0.109	0.112	0.101	0.118	0.815	1.63
Mode 2	110.3~205.0	V/m	37.920	40.817	42.091	37.833	44.344	307.0	614.0
Mode 3	110.3~205.0	uT	0.123	0.133	0.139	0.124	0.146	--	--
Mode 3	110.3~205.0	A/m	0.098	0.107	0.111	0.100	0.117	0.815	1.63
Mode 3	110.3~205.0	V/m	36.853	40.053	41.864	37.405	43.834	307.0	614.0

**For Apple Watch**

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values					50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
Mode 1	327.7	uT	0.128	0.140	0.143	0.129	0.146	--	--
Mode 1	327.7	A/m	0.102	0.112	0.114	0.103	0.117	0.815	1.63
Mode 1	327.7	V/m	38.492	41.977	42.897	38.842	43.813	307	614
Mode 2	327.7	uT	0.127	0.137	0.138	0.128	0.144	--	--
Mode 2	327.7	A/m	0.102	0.109	0.110	0.103	0.115	0.815	1.63
Mode 2	327.7	V/m	38.148	41.065	41.471	38.626	43.373	307	614
Mode 3	327.7	uT	0.125	0.129	0.137	0.125	0.143	--	--
Mode 3	327.7	A/m	0.100	0.104	0.110	0.100	0.114	0.815	1.63
Mode 3	327.7	V/m	37.642	38.934	41.168	37.623	42.966	307	614

**For AirPods**

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values					50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
Mode 1	110.3~205.0	uT	0.126	0.140	0.145	0.134	0.145	--	--
Mode 1	110.3~205.0	A/m	0.101	0.112	0.116	0.107	0.116	0.815	1.63
Mode 1	110.3~205.0	V/m	37.846	42.077	43.504	40.293	43.507	307	614
Mode 2	110.3~205.0	uT	0.125	0.139	0.143	0.128	0.142	--	--
Mode 2	110.3~205.0	A/m	0.100	0.111	0.114	0.103	0.114	0.815	1.63
Mode 2	110.3~205.0	V/m	37.707	41.737	42.865	38.534	42.788	307	614
Mode 3	110.3~205.0	uT	0.121	0.137	0.140	0.125	0.141	--	--
Mode 3	110.3~205.0	A/m	0.097	0.110	0.112	0.100	0.113	0.815	1.63
Mode 3	110.3~205.0	V/m	36.395	41.278	41.959	37.561	42.295	307	614

Field Strength at 20 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT

**For Phone**

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values	50% Limits	Limits
			Test Position E		
Mode 1	110.3~205.0	uT	0.147	--	--
Mode 1	110.3~205.0	A/m	0.117	0.815	1.63
Mode 1	110.3~205.0	V/m	44.125	307	614
Mode 2	110.3~205.0	uT	0.143	--	--
Mode 2	110.3~205.0	A/m	0.115	0.815	1.63
Mode 2	110.3~205.0	V/m	43.056	307	614
Mode 3	110.3~205.0	uT	0.139	--	--
Mode 3	110.3~205.0	A/m	0.111	0.815	1.63
Mode 3	110.3~205.0	V/m	41.778	307	614

**For Apple Watch**

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values	50% Limits	Limits
			Test Position E		
Mode 1	327.7	uT	0.143	--	--
Mode 1	327.7	A/m	0.114	0.815	1.63
Mode 1	327.7	V/m	42.885	307	614
Mode 2	327.7	uT	0.142	--	--
Mode 2	327.7	A/m	0.114	0.815	1.63
Mode 2	327.7	V/m	42.828	307	614
Mode 3	327.7	uT	0.138	--	--
Mode 3	327.7	A/m	0.110	0.815	1.63
Mode 3	327.7	V/m	41.514	307	614

**For AirPods**


Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values	50% Limits	Limits
			Test Position E		
Mode 1	110.3~205.0	uT	0.146	--	--
Mode 1	110.3~205.0	A/m	0.117	0.815	1.63
Mode 1	110.3~205.0	V/m	43.796	307	614
Mode 2	110.3~205.0	uT	0.141	--	--
Mode 2	110.3~205.0	A/m	0.113	0.815	1.63
Mode 2	110.3~205.0	V/m	42.397	307	614
Mode 3	110.3~205.0	uT	0.140	--	--
Mode 3	110.3~205.0	A/m	0.112	0.815	1.63
Mode 3	110.3~205.0	V/m	42.031	307	614

Note: V/m =  $10(((20\lg(A/m \cdot 10^6) + 51.5) - 120)/20)$ 

Note: A/m = uT/1.


### Test Setup Photos

#### 9.1. Test Position A - Exposure photo from side edge surface-Rear







(TM1)

#### 9.2. Test Position B - Exposure photo from side edge surface-Left



(TM1)

**9.3. Test Position C - Exposure photo from side edge surface-Front****(TM1)****9.4. Test Position D - Exposure photo from side edge surface-Right****(TM1)**

**9.5. Test Position E - Exposure photo from top surface (20cm)****(TM1)****9.6. Test Position E- Exposure photo from top surface (15cm)****(TM1)**

## 9. Conclusion

A minimum safety distance of at 15 cm surrounding the device and 20 cm above the top surface of the device is required when the device is charging a smart phone. The detected emissions with a distance of 15 cm surrounding the device and 20 cm above the top surface of the device are below the limitations according to FCC KDB 680106 D01 Section 3. RF Exposure Requirement Clause 3.

.....END OF REPORT.....