



# FCC Part 15C

## Measurement and Test Report

For

**Ansell**

511 Westinghouse Rd, Pendleton, SC 29670, United States

**FCC ID: 2AVVF-ANSLMJL0619**

**FCC Rule(s):** FCC Part 15.247

**Product Description:** IntelliMove

**Tested Model:** ANSL0001

**Report No.:** WTX20X03008166W

**Sample Receipt Date:** Mar.09, 2020

**Tested Date:** Mar.09, 2020 to Mar.13, 2020

**Issued Date:** Mar.13, 2020

**Tested By:** Mike Shi / Engineer

*Mike Shi*

**Reviewed By:** Lion Cai / RF Manager

*Lion Cai*

**Approved & Authorized By:** Silin Chen / Manager

*Silin Chen*

**Prepared By:**

**Shenzhen SEM Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

## **TABLE OF CONTENTS**

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION.....</b>                          | <b>4</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 4         |
| 1.2 TEST STANDARDS.....                                     | 5         |
| 1.3 TEST METHODOLOGY .....                                  | 5         |
| 1.4 TEST FACILITY .....                                     | 5         |
| 1.5 EUT SETUP AND TEST MODE .....                           | 6         |
| 1.6 MEASUREMENT UNCERTAINTY .....                           | 7         |
| 1.7 TEST EQUIPMENT LIST AND DETAILS .....                   | 8         |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                     | <b>10</b> |
| <b>3. RF EXPOSURE .....</b>                                 | <b>11</b> |
| 3.1 STANDARD APPLICABLE.....                                | 11        |
| 3.2 TEST RESULT.....                                        | 11        |
| <b>4. ANTENNA REQUIREMENT .....</b>                         | <b>12</b> |
| 4.1 STANDARD APPLICABLE.....                                | 12        |
| 4.2 EVALUATION INFORMATION .....                            | 12        |
| <b>5. POWER SPECTRAL DENSITY .....</b>                      | <b>13</b> |
| 5.1 STANDARD APPLICABLE.....                                | 13        |
| 5.2 TEST PROCEDURE.....                                     | 13        |
| 5.3 SUMMARY OF TEST RESULTS/PLOTS .....                     | 13        |
| <b>6. DTS BANDWIDTH.....</b>                                | <b>15</b> |
| 6.1 STANDARD APPLICABLE.....                                | 15        |
| 6.2 TEST PROCEDURE.....                                     | 15        |
| 6.3 SUMMARY OF TEST RESULTS/PLOTS .....                     | 15        |
| <b>7. RF OUTPUT POWER .....</b>                             | <b>17</b> |
| 7.1 STANDARD APPLICABLE.....                                | 17        |
| 7.2 TEST PROCEDURE.....                                     | 17        |
| 7.3 SUMMARY OF TEST RESULTS/PLOTS .....                     | 17        |
| <b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS .....</b>        | <b>19</b> |
| 8.1 STANDARD APPLICABLE.....                                | 19        |
| 8.2 TEST PROCEDURE.....                                     | 19        |
| 8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....           | 20        |
| 8.4 SUMMARY OF TEST RESULTS/PLOTS .....                     | 20        |
| <b>9. OUT OF BAND EMISSIONS.....</b>                        | <b>28</b> |
| 9.1 STANDARD APPLICABLE.....                                | 28        |
| 9.2 TEST PROCEDURE.....                                     | 28        |
| 9.3 SUMMARY OF TEST RESULTS/PLOTS .....                     | 29        |
| <b>10. CONDUCTED EMISSIONS .....</b>                        | <b>35</b> |
| 10.1 TEST PROCEDURE.....                                    | 35        |
| 10.2 BASIC TEST SETUP BLOCK DIAGRAM.....                    | 35        |
| 10.3 TEST RECEIVER SETUP .....                              | 35        |
| 10.4 SUMMARY OF TEST RESULTS/PLOTS .....                    | 35        |

**Report version**

| Version No. | Date of issue | Description |
|-------------|---------------|-------------|
| Rev.00      | Mar.13, 2020  | Original    |
| /           | /             | /           |



## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Ansell  
 Address of applicant: 511 Westinghouse Rd, Pendleton, SC 29670, United States

Manufacturer: Ansell  
 Address of manufacturer: 511 Westinghouse Rd, Pendleton, SC 29670, United States

| General Description of EUT                                                              |                 |
|-----------------------------------------------------------------------------------------|-----------------|
| Product Name:                                                                           | IntelliMove     |
| Brand Name:                                                                             | Ansell          |
| Model No.:                                                                              | ANSL0001        |
| Adding Model(s):                                                                        | /               |
| Rated Voltage:                                                                          | Battery: DC3.7V |
| Battery Capacity                                                                        | 150mAh          |
| Power Adapter:                                                                          | /               |
| Firmware Version:                                                                       | FW1.0           |
| Hardware Version:                                                                       | ANSL0001        |
| Note: The test data is gathered from a production sample, provided by the manufacturer. |                 |

| Technical Characteristics of EUT |                      |
|----------------------------------|----------------------|
| Bluetooth Version:               | V5.0 (BLE mode)      |
| Frequency Range:                 | 2402-2480MHz         |
| RF Output Power:                 | -2.82dBm (Conducted) |
| Data Rate:                       | 1Mbps                |
| Modulation:                      | GFSK                 |
| Quantity of Channels:            | 40                   |
| Channel Separation:              | 2MHz                 |
| Type of Antenna:                 | Integral Antenna     |
| Antenna Gain:                    | 1.0dBi               |

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**558074 D01 15.247 Meas Guidance v05r02:** Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of The FCC Rules.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### Address of the test laboratory

Laboratory: Shenzhen SEM Test Technology Co., Ltd.

Address: 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

### FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing use the customer default power level, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List |             |         |
|----------------|-------------|---------|
| Test Mode      | Description | Remark  |
| TM1            | Low         | 2402MHz |
| TM2            | Middle      | 2440MHz |
| TM3            | High        | 2480MHz |

| Test Conditions    |           |
|--------------------|-----------|
| Temperature:       | 22~25 °C  |
| Relative Humidity: | 50~55 %.  |
| ATM Pressure:      | 1019 mbar |

| EUT Cable List and Details |            |                     |                        |
|----------------------------|------------|---------------------|------------------------|
| Cable Description          | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| Charging cable             | 0.9        | Unshielded          | Without Ferrite        |

| Special Cable List and Details |            |                     |                        |
|--------------------------------|------------|---------------------|------------------------|
| Cable Description              | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| /                              | /          | /                   | /                      |

| Auxiliary Equipment List and Details |                      |           |               |
|--------------------------------------|----------------------|-----------|---------------|
| Description                          | Manufacturer         | Model     | Serial Number |
| Programmer board                     | Dialog Semiconductor | SB_CIB_vD | 078-71-D      |

| EUT Software List    |              |       |         |
|----------------------|--------------|-------|---------|
| Description          | Manufacturer | Model | Version |
| SmartSnippets Studio | Dialog       | /     | 2.0.7   |

## 1.6 Measurement Uncertainty

| Measurement uncertainty        |            |                                |
|--------------------------------|------------|--------------------------------|
| Parameter                      | Conditions | Uncertainty                    |
| RF Output Power                | Conducted  | $\pm 0.42\text{dB}$            |
| Occupied Bandwidth             | Conducted  | $\pm 1.5\%$                    |
| Power Spectral Density         | Conducted  | $\pm 1.8\text{dB}$             |
| Conducted Spurious Emission    | Conducted  | $\pm 2.17\text{dB}$            |
| Conducted Emissions            | Conducted  | 9-150kHz $\pm 3.74\text{dB}$   |
|                                |            | 0.15-30MHz $\pm 3.34\text{dB}$ |
| Transmitter Spurious Emissions | Radiated   | 30-200MHz $\pm 4.52\text{dB}$  |
|                                |            | 0.2-1GHz $\pm 5.56\text{dB}$   |
|                                |            | 1-6GHz $\pm 3.84\text{dB}$     |
|                                |            | 6-18GHz $\pm 3.92\text{dB}$    |

## 1.7 Test Equipment List and Details

| No.       | Description       | Manufacturer           | Model                 | Serial No.  | Cal Date   | Due Date   |
|-----------|-------------------|------------------------|-----------------------|-------------|------------|------------|
| SEMT-1072 | Spectrum Analyzer | Agilent                | E4407B                | MY41440400  | 2019-04-30 | 2020-04-29 |
| SEMT-1031 | Spectrum Analyzer | Rohde & Schwarz        | FSP30                 | 836079/035  | 2019-04-30 | 2020-04-29 |
| SEMT-1007 | EMI Test Receiver | Rohde & Schwarz        | ESVB                  | 825471/005  | 2019-04-30 | 2020-04-29 |
| SEMT-1008 | Amplifier         | Agilent                | 8447F                 | 3113A06717  | 2019-04-30 | 2020-04-29 |
| SEMT-1043 | Amplifier         | C&D                    | PAP-1G18              | 2002        | 2019-04-30 | 2020-04-29 |
| SEMT-1011 | Broadband Antenna | Schwarz beck           | VULB9163              | 9163-333    | 2019-05-05 | 2021-05-04 |
| SEMT-1042 | Horn Antenna      | ETS                    | 3117                  | 00086197    | 2019-05-05 | 2021-05-04 |
| SEMT-1121 | Horn Antenna      | Schwarzbeck            | BBHA 9170             | BBHA9170582 | 2019-05-05 | 2021-05-04 |
| SEMT-1069 | Loop Antenna      | Schwarz beck           | FMZB 1516             | 9773        | 2019-05-05 | 2021-05-04 |
| SEMT-1001 | EMI Test Receiver | Rohde & Schwarz        | ESPI                  | 101611      | 2019-04-30 | 2020-04-29 |
| SEMT-1003 | L.I.S.N           | Schwarz beck           | NSLK8126              | 8126-224    | 2019-04-30 | 2020-04-29 |
| SEMT-1002 | Pulse Limiter     | Rohde & Schwarz        | ESH3-Z2               | 100911      | 2019-04-30 | 2020-04-29 |
| SEMT-1168 | Pre-amplifier     | Direction Systems Inc. | PAP-0126              | 14141-12838 | 2019-04-30 | 2020-04-29 |
| SEMT-1169 | Pre-amplifier     | Direction Systems Inc. | PAP-2640              | 14145-14153 | 2019-04-30 | 2020-04-29 |
| SEMT-1163 | Spectrum Analyzer | Rohde & Schwarz        | FSP40                 | 100612      | 2019-04-30 | 2020-04-29 |
| SEMT-1170 | DRG Horn Antenna  | A.H. SYSTEMS           | SAS-574               | 571         | 2019-05-05 | 2021-05-04 |
| SEMT-1166 | Power Limiter     | Agilent                | N9356B                | MY45450376  | 2019-04-30 | 2020-04-29 |
| SEMT-1048 | RF Limiter        | ATTEN                  | AT-BSF-2400~2500      | /           | 2019-04-30 | 2020-04-29 |
| SEMT-1076 | RF Switcher       | Top Precision          | RCS03-A2              | /           | 2019-04-30 | 2020-04-29 |
| SEMT-C001 | Cable             | Zheng DI               | LL142-07-07-10M(A)    | /           | 2019-03-18 | 2020-03-17 |
| SEMT-C002 | Cable             | Zheng DI               | ZT40-2.92J-2.92J-6M   | /           | 2019-03-18 | 2020-03-17 |
| SEMT-C003 | Cable             | Zheng DI               | ZT40-2.92J-2.92J-2.5M | /           | 2019-03-18 | 2020-03-17 |
| SEMT-C004 | Cable             | Zheng DI               | 2M0RFC                | /           | 2019-03-18 | 2020-03-17 |
| SEMT-C005 | Cable             | Zheng DI               | 1M0RFC                | /           | 2019-03-18 | 2020-03-17 |
| SEMT-C006 | Cable             | Zheng DI               | 1M0RFC                | /           | 2019-03-18 | 2020-03-17 |





| Software List                              |              |        |         |
|--------------------------------------------|--------------|--------|---------|
| Description                                | Manufacturer | Model  | Version |
| EMI Test Software<br>(Radiated Emission)*  | Farad        | EZ-EMC | RA-03A1 |
| EMI Test Software<br>(Conducted Emission)* | Farad        | EZ-EMC | RA-03A1 |

\*Remark: indicates software version used in the compliance certification testing



## 2. SUMMARY OF TEST RESULTS

| FCC Rules                 | Description of Test Item          | Result    |
|---------------------------|-----------------------------------|-----------|
| §2.1093                   | RF Exposure                       | Compliant |
| §15.203; §15.247(b)(4)(i) | Antenna Requirement               | Compliant |
| §15.205                   | Restricted Band of Operation      | Compliant |
| §15.207(a)                | Conducted Emission                | Compliant |
| §15.247(e)                | Power Spectral Density            | Compliant |
| §15.247(a)(2)             | DTS Bandwidth                     | Compliant |
| §15.247(b)(3)             | RF Output Power                   | Compliant |
| §15.209(a)                | Radiated Emission                 | Compliant |
| §15.247(d)                | Band Edge (Out of Band Emissions) | Compliant |

N/A: not applicable



### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to §1.1307 and §2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has an Integral antenna, fulfill the requirement of this section.

## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:


- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 5.3 Summary of Test Results/Plots

| Test Mode | Test Channel | Power Spectral Density<br>dBm/3kHz | Limit<br>dBm/3kHz |
|-----------|--------------|------------------------------------|-------------------|
| GFSK(BLE) | Low          | -17.71                             | 8                 |
|           | Middle       | -17.92                             | 8                 |
|           | High         | -17.21                             | 8                 |


Please refer to the following test plots:

Low




Date: 12.MAR.2020 14:53:31

Middle



Date: 12.MAR.2020 14:53:01

High



Date: 12.MAR.2020 14:52:17

## 6. DTS Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:


- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times \text{RBW}$ .
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Summary of Test Results/Plots

| Test Mode | Test Channel | 6 dB Bandwidth<br>KHz | Limit<br>kHz |
|-----------|--------------|-----------------------|--------------|
| GFSK(BLE) | Low          | 675                   | $\geq 500$   |
|           | Middle       | 672                   | $\geq 500$   |
|           | High         | 669                   | $\geq 500$   |


Please refer to the following test plots:

Low




Date: 12.MAR.2020 14:56:31

Middle



Date: 12.MAR.2020 14:56:57

High



Date: 12.MAR.2020 14:57:16



## 7. RF Output Power

### 7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure


According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Set span  $\geq 3 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

### 7.3 Summary of Test Results/Plots


| Test Mode | Test Channel | Reading<br>dBm | Output Power<br>mW | Limit<br>mW |
|-----------|--------------|----------------|--------------------|-------------|
| GFSK(BLE) | Low          | -3.17          | 0.48               | 1000        |
|           | Middle       | -3.23          | 0.48               | 1000        |
|           | High         | -2.82          | 0.52               | 1000        |

Low




Date: 12.MAR.2020 14:49:59

Middle



Date: 12.MAR.2020 14:50:38

High



Date: 12.MAR.2020 14:51:02

## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Summary of Test Results/Plots

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*


➤ Spurious Emissions Below 1GHz

|              |     |           |            |
|--------------|-----|-----------|------------|
| Test Channel | Low | Polarity: | Horizontal |
|--------------|-----|-----------|------------|




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 52.0251            | 27.71               | -11.59          | 16.12              | 40.00             | -23.88         | 89            | 100            | peak   |
| 2   | 90.8554            | 27.04               | -13.57          | 13.47              | 43.50             | -30.03         | 104           | 100            | peak   |
| 3   | 289.0021           | 26.15               | -8.56           | 17.59              | 46.00             | -28.41         | 84            | 100            | peak   |
| 4   | 492.4685           | 28.28               | -5.51           | 22.77              | 46.00             | -23.23         | 108           | 100            | peak   |
| 5   | 750.1083           | 28.12               | -1.98           | 26.14              | 46.00             | -19.86         | 210           | 100            | peak   |
| 6   | 872.1832           | 28.06               | 0.44            | 28.50              | 46.00             | -17.50         | 315           | 100            | peak   |

|              |     |           |          |
|--------------|-----|-----------|----------|
| Test Channel | Low | Polarity: | Vertical |
|--------------|-----|-----------|----------|




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 45.6948            | 27.13               | -11.85          | 15.28              | 40.00             | -24.72         | 166           | 100            | peak   |
| 2   | 92.7872            | 27.71               | -13.96          | 13.75              | 43.50             | -29.75         | 188           | 100            | peak   |
| 3   | 195.1365           | 29.34               | -13.74          | 15.60              | 43.50             | -27.90         | 70            | 100            | peak   |
| 4   | 348.0274           | 27.10               | -6.96           | 20.14              | 46.00             | -25.86         | 259           | 100            | peak   |
| 5   | 584.7895           | 27.44               | -3.55           | 23.89              | 46.00             | -22.11         | 171           | 100            | peak   |
| 6   | 903.3094           | 26.97               | 1.03            | 28.00              | 46.00             | -18.00         | 213           | 100            | peak   |

|              |        |           |            |
|--------------|--------|-----------|------------|
| Test Channel | Middle | Polarity: | Horizontal |
|--------------|--------|-----------|------------|



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 45.6948            | 27.44               | -11.85          | 15.59              | 40.00             | -24.41         | 269           | 100            | peak   |
| 2   | 103.4421           | 26.27               | -13.51          | 12.76              | 43.50             | -30.74         | 100           | 100            | peak   |
| 3   | 217.5443           | 26.70               | -12.46          | 14.24              | 46.00             | -31.76         | 228           | 100            | peak   |
| 4   | 296.1836           | 26.22               | -8.17           | 18.05              | 46.00             | -27.95         | 95            | 100            | peak   |
| 5   | 696.8567           | 27.69               | -1.84           | 25.85              | 46.00             | -20.15         | 146           | 100            | peak   |
| 6   | 929.0082           | 26.78               | 1.31            | 28.09              | 46.00             | -17.91         | 129           | 100            | peak   |


|              |        |           |          |
|--------------|--------|-----------|----------|
| Test Channel | Middle | Polarity: | Vertical |
|--------------|--------|-----------|----------|



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 47.3255            | 26.90               | -11.70          | 15.20              | 40.00             | -24.80         | 195           | 100            | peak   |
| 2   | 98.1419            | 27.38               | -14.02          | 13.36              | 43.50             | -30.14         | 216           | 100            | peak   |
| 3   | 242.5253           | 27.05               | -10.06          | 16.99              | 46.00             | -29.01         | 89            | 100            | peak   |
| 4   | 492.4685           | 27.86               | -5.51           | 22.35              | 46.00             | -23.65         | 282           | 100            | peak   |
| 5   | 731.9203           | 28.28               | -2.02           | 26.26              | 46.00             | -19.74         | 329           | 100            | peak   |
| 6   | 938.8326           | 27.40               | 1.40            | 28.80              | 46.00             | -17.20         | 238           | 100            | peak   |




|              |      |           |            |
|--------------|------|-----------|------------|
| Test Channel | High | Polarity: | Horizontal |
|--------------|------|-----------|------------|



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 49.8814            | 27.00               | -11.60          | 15.40              | 40.00             | -24.60         | 198           | 100            | peak   |
| 2   | 89.2764            | 27.18               | -13.96          | 13.22              | 43.50             | -30.28         | 133           | 100            | peak   |
| 3   | 246.8149           | 25.77               | -10.01          | 15.76              | 46.00             | -30.24         | 98            | 100            | peak   |
| 4   | 289.0021           | 26.35               | -8.56           | 17.79              | 46.00             | -28.21         | 99            | 100            | peak   |
| 5   | 647.3856           | 27.14               | -2.51           | 24.63              | 46.00             | -21.37         | 161           | 100            | peak   |
| 6   | 863.0562           | 27.26               | 0.19            | 27.45              | 46.00             | -18.55         | 255           | 100            | peak   |



|              |      |           |          |
|--------------|------|-----------|----------|
| Test Channel | High | Polarity: | Vertical |
|--------------|------|-----------|----------|



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 45.6948            | 26.76               | -11.85          | 14.91              | 40.00             | -25.09         | 130           | 100            | peak   |
| 2   | 99.5281            | 27.44               | -13.86          | 13.58              | 43.50             | -29.92         | 118           | 100            | peak   |
| 3   | 348.0274           | 27.89               | -6.96           | 20.93              | 46.00             | -25.07         | 89            | 100            | peak   |
| 4   | 629.4772           | 27.49               | -2.74           | 24.75              | 46.00             | -21.25         | 306           | 100            | peak   |
| 5   | 711.6734           | 26.95               | -1.86           | 25.09              | 46.00             | -20.91         | 196           | 100            | peak   |
| 6   | 979.1804           | 26.79               | 2.24            | 29.03              | 54.00             | -24.97         | 91            | 100            | peak   |



## ➤ Spurious Emissions Above 1GHz

| Frequency              | Reading  | Correct | Result   | Limit    | Margin | Polar | Detector |
|------------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz)                  | (dBuV/m) | dB      | (dBuV/m) | (dBuV/m) | (dB)   | H/V   |          |
| Low Channel-2402MHz    |          |         |          |          |        |       |          |
| 4804                   | 60.89    | -3.59   | 57.30    | 74       | -16.70 | H     | PK       |
| 4804                   | 43.90    | -3.59   | 40.31    | 54       | -13.69 | H     | AV       |
| 7206                   | 58.94    | -0.52   | 58.42    | 74       | -15.58 | H     | PK       |
| 7206                   | 36.09    | -0.52   | 33.57    | 54       | -18.43 | H     | AV       |
| 4804                   | 61.46    | -3.59   | 57.87    | 74       | -16.13 | V     | PK       |
| 4804                   | 40.17    | -3.59   | 36.58    | 54       | -17.42 | V     | AV       |
| 7206                   | 56.98    | -0.52   | 56.46    | 74       | -17.54 | V     | PK       |
| 7206                   | 41.45    | -0.52   | 40.93    | 54       | -13.07 | V     | AV       |
| Middle Channel-2440MHz |          |         |          |          |        |       |          |
| 4880                   | 59.44    | -3.49   | 55.95    | 74       | -18.05 | H     | PK       |
| 4880                   | 44.40    | -3.49   | 40.91    | 54       | -13.09 | H     | AV       |
| 7320                   | 63.28    | -0.47   | 62.81    | 74       | -11.19 | H     | PK       |
| 7320                   | 36.51    | -0.47   | 36.04    | 54       | -17.96 | H     | AV       |
| 4880                   | 61.31    | -3.49   | 57.82    | 74       | -16.18 | V     | PK       |
| 4880                   | 39.00    | -3.49   | 35.51    | 54       | -18.49 | V     | AV       |
| 7320                   | 58.07    | -0.47   | 57.60    | 74       | -16.40 | V     | PK       |
| 7320                   | 40.04    | -0.47   | 39.57    | 54       | -14.43 | V     | AV       |
| High Channel-2480MHz   |          |         |          |          |        |       |          |
| 4960                   | 60.32    | -3.41   | 56.91    | 74       | -17.09 | H     | PK       |
| 4960                   | 42.15    | -3.41   | 38.74    | 54       | -15.26 | H     | AV       |
| 7440                   | 60.65    | -0.42   | 60.23    | 74       | -13.77 | H     | PK       |
| 7440                   | 36.77    | -0.42   | 36.35    | 54       | -17.65 | H     | AV       |
| 4960                   | 61.06    | -3.41   | 57.65    | 74       | -16.35 | V     | PK       |
| 4960                   | 43.99    | -3.41   | 40.58    | 54       | -13.42 | V     | AV       |
| 7440                   | 57.54    | -0.42   | 57.12    | 74       | -16.88 | V     | PK       |
| 7440                   | 42.24    | -0.42   | 41.82    | 54       | -12.18 | V     | AV       |

*Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

**B. Antenna-port conducted measurements**

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b)  $VBW \geq [3 \times RBW]$ .
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

RBW as a function of frequency

| Frequency        | RBW              |
|------------------|------------------|
| 9kHz to 150kHz   | 200Hz to 300Hz   |
| 0.15MHz to 30MHz | 9kHz to 10kHz    |
| 30MHz to 1000MHz | 100kHz to 120kHz |
| >1000MHz         | 1MHz             |


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

**9.3 Summary of Test Results/Plots**


➤ Radiated test

|              |     |           |                         |
|--------------|-----|-----------|-------------------------|
| Test Channel | Low | Polarity: | Horizontal (worst case) |
|--------------|-----|-----------|-------------------------|



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>Factor(dB) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------------|--------------------|-------------------|----------------|------------------|
| 1   | 2310.000           | 40.93               | -9.66                 | 31.27              | 54.00             | -22.73         | Average Detector |
|     | 2310.000           | 52.42               | -9.66                 | 42.76              | 74.00             | -31.24         | Peak Detector    |
| 2   | 2390.000           | 40.61               | -9.50                 | 31.11              | 54.00             | -22.89         | Average Detector |
|     | 2390.000           | 52.74               | -9.50                 | 43.24              | 74.00             | -30.76         | Peak Detector    |
| 3   | 2402.000           | 78.95               | -9.47                 | 69.48              | /                 | /              | Average Detector |
|     | 2402.300           | 100.44              | -9.47                 | 90.97              | /                 | /              | Peak Detector    |


|              |      |           |                         |
|--------------|------|-----------|-------------------------|
| Test Channel | High | Polarity: | Horizontal (worst case) |
|--------------|------|-----------|-------------------------|




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2479.875           | 81.71               | -9.32           | 72.39              | /                 | /              | Average Detector |
|     | 2479.975           | 106.20              | -9.32           | 96.88              | /                 | /              | Peak Detector    |
| 2   | 2483.500           | 54.52               | -9.31           | 45.21              | 54.00             | -8.79          | Average Detector |
|     | 2483.500           | 68.24               | -9.31           | 58.93              | 74.00             | -15.07         | Peak Detector    |
| 3   | 2500.000           | 40.15               | -9.28           | 30.87              | 54.00             | -23.13         | Average Detector |
|     | 2500.000           | 54.22               | -9.28           | 44.94              | 74.00             | -29.06         | Peak Detector    |

➤ Conducted test

Low




Date: 12.MAR.2020 15:04:23




Date: 12.MAR.2020 15:04:47



Middle




Date: 12.MAR.2020 15:05:25




Date: 12.MAR.2020 15:06:04

High



Date: 12.MAR.2020 15:06:46



Date: 12.MAR.2020 15:07:24


## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram




### 10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz  
 Stop Frequency ..... 30 MHz  
 Sweep Speed ..... Auto  
 IF Bandwidth..... 10 kHz  
 Quasi-Peak Adapter Bandwidth ..... 9 kHz  
 Quasi-Peak Adapter Mode ..... Normal

### 10.4 Summary of Test Results/Plots


|           |               |             |           |         |
|-----------|---------------|-------------|-----------|---------|
| Test Mode | Communication | AC120V 60Hz | Polarity: | Neutral |
|-----------|---------------|-------------|-----------|---------|



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|----------------|---------------|--------------|-------------|----------|
| 1   | 0.1820          | 35.55          | 9.96           | 45.51         | 64.39        | -18.88      | QP       |
| 2*  | 0.4700          | 27.93          | 10.02          | 37.95         | 56.51        | -18.56      | QP       |
| 3   | 0.4700          | 16.89          | 10.02          | 26.91         | 46.51        | -19.60      | AVG      |
| 4   | 0.7780          | 14.89          | 10.15          | 25.04         | 46.00        | -20.96      | AVG      |
| 5   | 1.1180          | 12.25          | 10.38          | 22.63         | 46.00        | -23.37      | AVG      |
| 6   | 1.5980          | 22.28          | 10.37          | 32.65         | 56.00        | -23.35      | QP       |



|           |               |             |           |      |
|-----------|---------------|-------------|-----------|------|
| Test Mode | Communication | AC120V 60Hz | Polarity: | Line |
|-----------|---------------|-------------|-----------|------|



\*\*\*\*\* END OF REPORT \*\*\*\*\*