

FCC MPE TEST REPORT

FCC ID: 2AVVH-KCWSC

Product: WSC63

Trade Name: N/A

Model Name: WSC63

Serial Model: WSC48, WSC69, WSC80

Report No.: UNIA20030205FR-02

Prepared for

HAN PROMOTION LIMITED

Rm.18 & 20, Blk 1, 12/F, Golden Ind. Bldg., 16-26 Kwai Tak Street,
Kwai Chung, N.T. Hong Kong

Prepared by

Shenzhen United Testing Technology Co., Ltd.

2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang
Community, Xixiang Str, Bao'an District, Shenzhen, China

TEST RESULT CERTIFICATION

Applicant's name.....: HAN PROMOTION LIMITED

Address.....: Rm.18 & 20, Blk 1, 12/F, Golden Ind. Bldg., 16-26 Kwai Tak Street, Kwai Chung, N.T. Hong Kong

Manufacture's Name.....: HAN PROMOTION LIMITED

Address.....: Rm.18 & 20, Blk 1, 12/F, Golden Ind. Bldg., 16-26 Kwai Tak Street, Kwai Chung, N.T. Hong Kong

Product description

Product name.....: WSC63

Trade Mark.....: N/A

Model and/or type reference .. : WSC63, WSC48, WSC69, WSC80

Standards.....: FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v03

This device described above has been tested by Shenzhen United Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of UNI, this document may be altered or revised by Shenzhen United Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

Date of Test..... :

Date (s) of performance of tests.....: Mar. 03, 2020 ~Mar. 13, 2020

Date of Issue.....: Mar. 13, 2020

Test Result.....: Pass

Prepared by:

Bob liao

Bob liao/Editor

Reviewer:

Kahn yang

Kahn yang/Supervisor

Approved & Authorized Signer:

Liuze

Liuze/Manager

Note:For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

ChannelList			
Channel	Frequency(KHz)	Channel	Frequency(MHz)
01	127		

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.

1. SUMMARY OF TEST RESULTS

1.1 Test procedures according to the technical standards:

FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v03

FCC CFR 47			
Standard Section	Test Item	Judgment	Remark
FCC CFR 47 part 1, 1.1310 KDB680106 D01v03(3)(3)	Electric Field Strength (E) (V/m)	PASS	
	Magnetic Field Strength (H) (A/m)	PASS	

Note: 1: Charging frequency is less than 1 MHz;

Yes, The working frequency of the prototype is 127 KHz.

2: The output power of each primary coil is less than 15 watts;

Yes, The maximum output power of the prototype is 10 watts.

3: The energy transfer only includes the primary and secondary coils. Some charging systems contain multiple primary coils, which can detect multiple charged products. The coupling of energy is only between the paired primary and secondary coils.

Yes, the transfer system includes only single primary and secondary coils.

4: Client device is placed directly in contact with the transmitter.

Yes.

5: Mobile exposure conditions only (mobile exposure conditions are not covered by this exclusion).

Yes, the EUT is for mobile exposure conditions only.

6: The aggregate H-field strengths at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yes, the EUT h-field strengths levels are less than 50% of the MPE limit.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95%**.

No.	Item	Uncertainty
1	All emissions, radiated (<30M) (9KHz-30MHz)	$\pm 2.45\text{dB}$
2	Temperature	$\pm 0.5^\circ\text{C}$
3	Humidity	$\pm 2\%$

1.3 Test Instruments

Description	Brand	Model No.	Frequency Range	Calibrated Until
Broadband Field Meter	NARDA	NBM-550	—	Sep. 01, 2020
Magnetic Field Meter	NARDA	ELT-400	1–400kHz	Sep. 01, 2020
Magnetic Probe	NARDA	HF-3061	300kHz–30MHz	Sep. 01, 2020
Magnetic Probe	NARDA	HF-0191	27–1000MHz	Sep. 01, 2020
Broadband Field Meter	NARDA	NBM-550	—	Sep. 01, 2020
Electric Field Meter	COMBINOVA	EFM 200	5Hz–400kHz	Sep. 01, 2020
E-Field Probe	NARDA	EF-0391	100kHz–3GHz	Sep. 01, 2020
E-Field Probe	NARDA	EF-6091	100MHz–60GHz	Sep. 01, 2020

NOTE: The calibration interval of the above test instruments is 12 months.

2 MAXIMUM PERMISSIBLEEXPOSURE

2.1 MAXIMUM PERMISSIBLEEXPOSURE

Limit of Maximum PermissibleExposure

Limits for Occupational / Controlled Exposure				
FrequencyRange(M Hz)	ElectricFieldStrength (E)(V/m)	MagneticField Strength (H)(A/m)	Power Density(S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6
Limits for General Population / Uncontrolled Exposure				
FrequencyRange(M Hz)	ElectricFieldStrength (E)(V/m)	MagneticFieldStrength (H)(A/m)	Power Density(S)(mW/cm ²)	Averaging Time E ² , H ² or S(minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density.

2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03.


3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

3. TESTPROCEDURE


a. For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm.

E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair at the 15 cm surrounding the device and 20 cm above the top surface.

4.1 TESTSETUP



4.2 TESTPHOTO



4.3 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE

For Full load mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
0.127	1.20	1.08	1.13	1.15	1.26	307	614

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0.127	0.28	0.24	0.27	0.19	0.18	0.815	1.63

For Half Load mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
0.127	1.27	1.09	1.15	1.18	1.16	307	614

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0.127	0.19	0.22	0.21	0.20	0.19	0.815	1.63

For No load mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
0.127	1.20	1.14	1.18	1.17	1.20	307	614

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0.127	0.14	0.18	0.22	0.20	0.19	0.815	1.63

*****THE END*****