

FCC Radio Test Report

FCC ID: 2AVVT-CU413UCMPS1

Report No. : BTL-FCCP-6-2103T126
Equipment : iTraMS CCU
Model Name : CU-41-3U-CM-PS1
Brand Name : Bosch
Applicant : Robert Bosch Engineering and Business Solutions Private Limited
Address : RBEI/PAC, Ban 601, Post Box No 3000 Hosur Road, Adugodi, Bengaluru, Karnataka-560030, India.

Radio Function : Bluetooth EDR

FCC Rule Part(s) : FCC Part15, Subpart C (15.247)
Measurement Procedure(s) : ANSI C63.10-2013


Date of Receipt : 2021/4/6
Date of Test : 2021/4/6 ~ 2021/7/26
Issued Date : 2021/10/15

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by

: 
Jerry Chuang, Supervisor

Approved by

: 
Peter Chen, Vice Manager



BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299

Fax: +886-2-2657-3331

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

CONTENTS

REVISION HISTORY	5
1 SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
1.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	8
1.5 DUTY CYCLE	9
1.6 OTHER REQUIREMENTS FOR FREQUENCY HOPPING SYSTEM (FHSS)	
EQUIPMENT UNDER SECTION 15.247	10
2 GENERAL INFORMATION	12
2.1 DESCRIPTION OF EUT	12
2.2 TEST MODES	14
2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	15
2.4 SUPPORT UNITS	15
3 RADIATED EMISSIONS TEST	16
3.1 LIMIT	16
3.2 TEST PROCEDURE	17
3.3 DEVIATION FROM TEST STANDARD	17
3.4 TEST SETUP	17
3.5 EUT OPERATING CONDITIONS	18
3.6 TEST RESULT – BELOW 30 MHZ	19
3.7 TEST RESULT – 30 MHZ TO 1 GHZ	19
3.8 TEST RESULT – ABOVE 1 GHZ	19
4 NUMBER OF HOPPING CHANNEL	20
4.1 APPLIED PROCEDURES	20
4.2 TEST PROCEDURE	20
4.3 DEVIATION FROM STANDARD	20
4.4 TEST SETUP	20
4.5 EUT OPERATION CONDITIONS	20
4.6 TEST RESULTS	20
5 AVERAGE TIME OF OCCUPANCY	21
5.1 APPLIED PROCEDURES / LIMIT	21
5.2 TEST PROCEDURE	21
5.3 DEVIATION FROM STANDARD	21
5.4 TEST SETUP	21
5.5 EUT OPERATION CONDITIONS	21
5.6 TEST RESULTS	21
6 HOPPING CHANNEL SEPARATION MEASUREMENT	22
6.1 APPLIED PROCEDURES / LIMIT	22
6.2 TEST PROCEDURE	22
6.3 DEVIATION FROM STANDARD	22
6.4 TEST SETUP	22
6.5 TEST RESULTS	22
7 BANDWIDTH TEST	23
7.1 APPLIED PROCEDURES	23
7.2 TEST PROCEDURE	23
7.3 DEVIATION FROM STANDARD	23

7.4	TEST SETUP	23
7.5	EUT OPERATION CONDITIONS	23
7.6	TEST RESULTS	23
8	OUTPUT POWER TEST	24
8.1	APPLIED PROCEDURES / LIMIT	24
8.2	TEST PROCEDURE	24
8.3	DEVIATION FROM STANDARD	24
8.4	TEST SETUP	24
8.5	EUT OPERATION CONDITIONS	24
8.6	TEST RESULTS	24
9	ANTENNA CONDUCTED SPURIOUS EMISSION	25
9.1	APPLIED PROCEDURES / LIMIT	25
9.2	TEST PROCEDURE	25
9.3	DEVIATION FROM STANDARD	25
9.4	TEST SETUP	25
9.5	EUT OPERATION CONDITIONS	25
9.6	TEST RESULTS	25
10	LIST OF MEASURING EQUIPMENTS	26
11	EUT TEST PHOTO	28
12	EUT PHOTOS	28
APPENDIX A	RADIATED EMISSIONS - 30 MHZ TO 1 GHZ	29
APPENDIX B	RADIATED EMISSIONS - ABOVE 1 GHZ	32
APPENDIX C	NUMBER OF HOPPING CHANNEL	49
APPENDIX D	AVERAGE TIME OF OCCUPANCY	51
APPENDIX E	HOPPING CHANNEL SEPARATION MEASUREMENT	56
APPENDIX F	BANDWIDTH	59
APPENDIX G	OUTPUT POWER	62
APPENDIX H	ANTENNA CONDUCTED SPURIOUS EMISSION	64

REVISION HISTORY

Report No.	Version	Description	Issued Date
BTL-FCCP-6-2103T126	R00	Original Report.	2021/9/17
BTL-FCCP-6-2103T126	R01	Revised Typo.	2021/9/27
BTL-FCCP-6-2103T126	R02	Revised report to address TCB's comments.	2021/10/6
BTL-FCCP-6-2103T126	R03	Revised report to address TCB's comments.	2021/10/14
BTL-FCCP-6-2103T126	R04	Revised report to address TCB's comments.	2021/10/15

1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards.

FCC Part 15, Subpart C (15.247)				
Standard(s) Section	Description	Test Result	Judgement	Remark
15.207	AC Power Line Conducted Emissions	-----	N/A	Note(3)
15.205 15.209 15.247(d)	Radiated Emissions	APPENDIX A APPENDIX B	Pass	-----
15.247 (a)(1)(iii)	Number of Hopping Frequency	APPENDIX C	Pass	-----
15.247 (a)(1)(iii)	Average Time of Occupancy	APPENDIX D	Pass	-----
15.247 (a)(1)	Hopping Channel Separation	APPENDIX E	Pass	-----
15.247 (a)(1)	Bandwidth	APPENDIX F	Pass	-----
15.247 (b)(1)	Output Power	APPENDIX G	Pass	-----
15.247(d)	Antenna conducted Spurious Emission	APPENDIX H	Pass	-----
15.203	Antenna Requirement	-----	Pass	-----

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) The report format version is TP.1.1.1.
- (3) This is a DC input device.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report:

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

The test sites and facilities are covered under FCC RN: 674415 and DN: TW0659.

☐ C05 ☐ CB08 ☐ CB11 ☒ CB15 ☐ CB16
☒ SR05

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately **95 %**. The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{CISPR} requirement.

A. Radiated emissions test :

Test Site	Measurement Frequency Range	U_i (dB)
CB15	0.03 GHz ~ 0.2 GHz	4.17
	0.2 GHz ~ 1 GHz	4.72
	1 GHz ~ 6 GHz	5.21
	6 GHz ~ 18 GHz	5.51
	18 GHz ~ 26 GHz	3.69
	26 GHz ~ 40 GHz	4.23

B. Conducted test :

Test Item	U_i (dB)
Occupied Bandwidth	0.5338
Output power	0.3659
Conducted Spurious emissions	0.5416
Conducted Band edges	0.5348
Dwell time	0.6606
Channel separation	0.6606
Channel numbers	0.6606

NOTE:

Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Environment Condition	Test Voltage	Tested by
Radiated emissions below 1 GHz	23 °C, 54 %	AC 120V	Jay Kao
Radiated emissions above 1 GHz	23 °C, 54 %	AC 120V	Jay Kao
Number of Hopping Frequency	25.9 °C, 34 %	AC 120V	Vincent Lee
Average Time of Occupancy	25.9 °C, 34 %	AC 120V	Vincent Lee
Hopping Channel Separation	25.9 °C, 34 %	AC 120V	Vincent Lee
Bandwidth	25.9 °C, 34 %	AC 120V	Vincent Lee
Output Power	25.9 °C, 34 %	AC 120V	Vincent Lee
Antenna conducted Spurious Emission	25.9 °C, 34 %	AC 120V	Vincent Lee

1.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING


Test Software	Tera Term V4.80			
Modulation Mode	2402 MHz	2441 MHz	2480 MHz	Data Rate
GFSK	10.5	10.5	10.5	1 Mbps
$\pi/4$ -DQPSK	8	8	8	2 Mbps
8DPSK	8	8	8	3 Mbps

1.5 DUTY CYCLE


If duty cycle is $\geq 98\%$, duty factor is not required.

If duty cycle is $< 98\%$, duty factor shall be considered.


Remark	Delta 1			Delta 2		On Time/Period	10 log(1/Duty Cycle)
Mode	ON (ms)	Numbers (ON)	On Time (B) (ms)	Period (ON+OFF) (ms)	Duty Cycle (%)	Duty Factor	Duty Factor (dB)
BT (1 Mbps)	2.900	1	2.900	3.760	77.13%		1.13
BT (2 Mbps)	2.900	1	2.900	3.760	77.13%		1.13
BT (3 Mbps)	2.900	1	2.900	3.760	77.13%		1.13



Date: 29.JUN.2021 16:24:59



Date: 29.JUN.2021 16:27:20



Date: 29.JUN.2021 16:28:49

1.6 OTHER REQUIREMENTS FOR FREQUENCY HOPPING SYSTEM (FHSS) EQUIPMENT UNDER SECTION 15.247

Refer to section 9. c) of FCC KDB 558074 D01 15.247 Meas Guidance v05r02,

The following items must also be addressed in FHSS device filings.

1) Section 15.247(a)(1):

According to 15.247(a)(1): The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

i) Pseudorandom frequency hopping sequence


The EUT generated hopping sequence by below method:

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels.

The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is dividing into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1600 hops/s.


The pseudorandom sequence may be generated in a nine stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

ii) Equal hopping frequency use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

iii) System receiver input bandwidth

The Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

iv) System receiver hopping capability

The Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

2) Section 15.247(g):

According to 15.247(g): Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

3) Section 15.247(h):

According to 15.247(h): The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

The Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

2 GENERAL INFORMATION

2.1 DESCRIPTION OF EUT

Equipment	iTraMS CCU
Model Name	CU-41-3U-CM-PS1
Brand Name	Bosch
Model Difference	N/A
Power Source	DC Voltage supplied from DC Source.
Power Rating	DC 9-32V (12V or 24V)
Products Covered	N/A
Hardware Version/Test Model	AD00 A10 062
Software Version	1277401063
Operation Band	2400 MHz ~ 2483.5 MHz
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	1 Mbps, 2 Mbps, 3Mbps
Output Power Max.	1 Mbps: 6.82 dBm (0.0048 W) 2 Mbps: 3.03 dBm (0.0020 W) 3 Mbps: 3.28 dBm (0.0021 W)
Test Model	CU-41-3U-CM-PS1
Sample Status	Engineering Sample
EUT Modification(s)	N/A

NOTE:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

(2) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

(3) Table for Filed Antenna:

Group I:

Antenna	Manufacture	Part No.	Type	Connector	Frequency (MHz)	Gain (dBi)
External antenna		MA250.A.LBI.001	Dipole	SMA(M)ST	2400-2500	2.72

Group II:

Antenna	Manufacture	Part No.	Type	Connector	Frequency (MHz)	Gain (dBi)
Stubby antenna		TG.08.0723	Dipole	SMA(M)ST	2400-2500	3.29

Group III:

Antenna	Manufacture	Part No.	Type	Connector	Frequency (MHz)	Gain (dBi)
Wi-Fi 2.4GHz antenna		MA240.LBI.001	Dipole	SMA(M)	2400-2500	2.70

NOTE: The EUT includes three groups of antenna, the Stubby antenna is the worst and recorded.

2.2 TEST MODES


Test Items	Test mode	Channel	Note
Transmitter Radiated Emissions (below 1GHz)	1 Mbps	00	-
Transmitter Radiated Emissions (above 1GHz)	1/3 Mbps	00/78	Bandedge
	1/3 Mbps	00/39/78	Harmonic
Number of Hopping Frequency	1/3 Mbps	00~78	-
Average Time of Occupancy	1/3 Mbps	00/39/78	-
Hopping Channel Separation	1/3 Mbps	00/39/78	-
Bandwidth	1/3 Mbps	00/39/78	-
Peak Output Power	1/2/3 Mbps	00/39/78	-
Antenna conducted Spurious Emission	1/3 Mbps	00/39/78	-

NOTE:

- (1) For radiated emission band edge test, both Vertical and Horizontal are evaluated, but only the worst case (Vertical) is recorded.
- (2) All X, Y and Z axes are evaluated, but only the worst case (X axis) is recorded.

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Equipment letters and Cable numbers refer to item numbers described in the tables of clause 2.4.



2.4 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	NB	HP	TPN-I119	N/A	Furnished by test lab.
B	Power Supply	Twintex	TDS-60-15	N/A	Furnished by test lab.
C	Stubby antenna	Taoglas	TG.08.0723	N/A	Supplied by test requester

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	N/A	N/A	2m	Power Cord	Supplied by test requester
2	N/A	N/A	2.1m	RS 232 to USB	Supplied by test requester

3 RADIATED EMISSIONS TEST

3.1 LIMIT

In case the emission fall within the restricted band specified on 15.205, then the 15.209 limit in the table below has to be followed.

LIMITS OF RADIATED EMISSIONS MEASUREMENT (9 kHz to 1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSIONS MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	Radiated Emissions (dBuV/m)		Measurement Distance (meters)
	Peak	Average	
Above 1000	74	54	3

NOTE:

- (1) The limit for radiated test was performed according to FCC Part 15, Subpart C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)

Margin Level = Measurement Value - Limit Value

Calculation example:

Reading Level		Correct Factor		Measurement Value
35.45	+	-11.37	=	24.08

Measurement Value		Limit Value		Margin Level
24.08	-	40	=	-15.92

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average

Spectrum Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector


3.2 TEST PROCEDURE

- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5 m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- For the actual test configuration, please refer to the related Item – EUT TEST PHOTO.


3.3 DEVIATION FROM TEST STANDARD

No deviation.


3.4 TEST SETUP



30 MHz to 1 GHz



Above 1 GHz



3.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULT – BELOW 30 MHZ

There were no emissions found below 30 MHz within 20 dB of the limit.

3.7 TEST RESULT – 30 MHZ TO 1 GHZ

Please refer to the APPENDIX A.

3.8 TEST RESULT – ABOVE 1 GHZ

Please refer to the APPENDIX B.

NOTE:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

4 NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

Please refer to the APPENDIX C.

5 AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

5.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- Measure the maximum time duration of one single pulse.
A Period Time = (channel number) * 0.4

For Non-AFH Mode (79 Channel):

DH1 Time Solt: Reading * (1600/2)/79 * (0.4 * 79)

DH3 Time Solt: Reading * (1600/4)/79 * (0.4 * 79)

DH5 Time Solt: Reading * (1600/6)/79 * (0.4 * 79)

For AFH Mode (20 Channel):

DH1 Time Solt: Reading * (800/2)/20 * (0.4 * 20)

DH3 Time Solt: Reading * (800/4)/20 * (0.4 * 20)

DH5 Time Solt: Reading * (800/6)/20 * (0.4 * 20)

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

Please refer to the APPENDIX D.

6 Hopping Channel Separation Measurement

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


6.2 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels
Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span
Video (or Average) Bandwidth (VBW) $\geq$ RBW
Sweep = Auto
Detector function = Peak
Trace = Max Hold

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 TEST RESULTS

Please refer to the APPENDIX E.

7 BANDWIDTH TEST

7.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

Please refer to the APPENDIX F.

8 OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	0.125Watt or 21dBm	2400-2483.5	PASS


8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 3MHz, VBW= 3MHz, Sweep time = Auto.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

Please refer to the APPENDIX G.

9 ANTENNA CONDUCTED SPURIOUS EMISSION

9.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


9.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.
- Offset=antenna gain+cable loss

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Please refer to the APPENDIX H.

10 LIST OF MEASURING EQUIPMENTS

Radiated Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Preamplifier	EMCI	EMC02325B	980217	2021/4/8	2022/4/7
2	Preamplifier	EMCI	EMC012645B	980267	2021/4/8	2022/4/7
3	Preamplifier	EMCI	EMC001340	980555	2021/4/8	2022/4/7
4	Test Cable	EMCI	EMC-SM-SM-1000	180809	2021/4/8	2022/4/7
5	Test Cable	EMCI	EMC104-SM-SM-3000	151205	2021/4/8	2022/4/7
6	Test Cable	EMCI	EMC-SM-SM-7000	180408	2021/4/8	2022/4/7
7	MXE EMI Receiver	Agilent	N9038A	MY554200087	2021/5/27	2022/5/26
8	Signal Analyzer	Agilent	N9010A	MY56480554	2020/8/25	2021/8/24
9	Loop Ant	Electro-Metrics	EMCI-LPA600	274	2021/6/1	2022/5/31
10	Horn Ant	SCHWARZBECK	BBHA 9120D	9120D-1342	2021/6/2	2022/6/1
11	Horn Ant	Schwarzbeck	BBHA 9170	BBHA 9170340	2021/7/9	2022/7/8
12	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	VULB 9168-352	2021/7/23	2022/7/22
13	5dB Attenuator	EMCI	EMCI-N-6-05	AT-N0625	2021/7/23	2022/7/22
14	Measurement Software	EZ	EZ EMC (Version NB-03A1-01)	N/A	N/A	N/A

Number of Hopping Frequency						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 40	100129	2021/6/8	2022/6/7

Average Time of Occupancy						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 40	100129	2021/6/8	2022/6/7

Hopping Channel Separation						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 40	100129	2021/6/8	2022/6/7

Bandwidth						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 40	100129	2021/6/8	2022/6/7

Output Power						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Power Meter	Anritsu	ML2495A	1128008	2021/5/26	2022/5/25
2	Power Sensor	Anritsu	MA2411B	1126001	2021/5/26	2022/5/25

Antenna conducted Spurious Emission						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 40	100129	2021/6/8	2022/6/7

Remark: "N/A" denotes no model name, no serial no. or no calibration specified.
All calibration period of equipment list is one year.

11 EUT TEST PHOTO


Please refer to document Appendix No.: TP-2103T126-FCCP-3 (APPENDIX-TEST PHOTOS).

12 EUT PHOTOS

Please refer to document Appendix No.: EP-2103T126-1 (APPENDIX-EUT PHOTOS).

APPENDIX A RADIATED EMISSIONS - 30 MHZ TO 1 GHZ

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	157.6843	51.19	-8.34	42.85	43.50	-0.65	QP	
2	!	230.2726	50.65	-10.30	40.35	46.00	-5.65	QP	
3		460.5505	41.48	-3.51	37.97	46.00	-8.03	peak	
4		759.4400	36.06	1.98	38.04	46.00	-7.96	peak	
5	!	833.2893	38.45	3.04	41.49	46.00	-4.51	QP	
6		919.3283	33.24	4.46	37.70	46.00	-8.30	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Horizontal
Temp	23°C	Hum.	54%



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	157.7165	51.23	-8.34	42.89	43.50	-0.61	QP	
2		268.5876	47.01	-8.39	38.62	46.00	-7.38	peak	
3		455.6682	39.69	-3.59	36.10	46.00	-9.90	peak	
4	!	690.8286	39.39	0.66	40.05	46.00	-5.95	QP	
5	!	833.2893	39.10	3.04	42.14	46.00	-3.86	QP	
6		929.9335	34.71	4.64	39.35	46.00	-6.65	peak	


REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

APPENDIX B RADIATED EMISSIONS - ABOVE 1 GHZ

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2387.520	26.50	31.21	57.71	74.00	-16.29	peak	
2		2387.520	12.94	31.21	44.15	54.00	-9.85	AVG	
3	X	2402.000	72.27	31.26	103.53	74.00	29.53	peak	NoLimit
4	*	2402.000	68.16	31.26	99.42	54.00	45.42	AVG	NoLimit
5		2489.173	26.52	31.53	58.05	74.00	-15.95	peak	
6		2489.173	3.19	31.53	34.72	54.00	-19.28	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2480MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2388.547	25.91	31.21	57.12	74.00	-16.88	peak	
2		2388.547	2.95	31.21	34.16	54.00	-19.84	AVG	
3	X	2480.000	70.57	31.51	102.08	74.00	28.08	peak	NoLimit
4	*	2480.000	66.49	31.51	98.00	54.00	44.00	AVG	NoLimit
5		2533.327	27.34	31.67	59.01	74.00	-14.99	peak	
6		2533.327	5.61	31.67	37.28	54.00	-16.72	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2379.973	27.44	31.18	58.62	74.00	-15.38	peak	
2		2379.973	2.76	31.18	33.94	54.00	-20.06	AVG	
3	X	2402.000	66.01	31.26	97.27	74.00	23.27	peak	NoLimit
4	*	2402.000	61.79	31.26	93.05	54.00	39.05	AVG	NoLimit
5		2488.380	27.19	31.53	58.72	74.00	-15.28	peak	
6		2488.380	2.99	31.53	34.52	54.00	-19.48	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2480MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2387.800	25.61	31.21	56.82	74.00	-17.18	peak	
2		2387.800	3.11	31.21	34.32	54.00	-19.68	AVG	
3	X	2480.000	65.28	31.51	96.79	74.00	22.79	peak	NoLimit
4	*	2480.000	61.16	31.51	92.67	54.00	38.67	AVG	NoLimit
5		2540.300	28.41	31.68	60.09	74.00	-13.91	peak	
6		2540.300	3.69	31.68	35.37	54.00	-18.63	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	54.18	-9.84	44.34	74.00	-29.66	peak	
2	*	4804.000	41.42	-9.84	31.58	54.00	-22.42	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Horizontal
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	52.72	-9.84	42.88	74.00	-31.12	peak	
2	*	4804.000	41.22	-9.84	31.38	54.00	-22.62	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2441MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4882.000	55.14	-9.77	45.37	74.00	-28.63	peak	
2	*	4882.000	41.31	-9.77	31.54	54.00	-22.46	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2441MHz	Polarization	Horizontal
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4882.000	53.65	-9.77	43.88	74.00	-30.12	peak	
2	*	4882.000	41.41	-9.77	31.64	54.00	-22.36	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2480MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	53.84	-9.68	44.16	74.00	-29.84	peak	
2	*	4960.000	41.36	-9.68	31.68	54.00	-22.32	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (1Mbps)	Test Date	2021/6/26
Test Frequency	2480MHz	Polarization	Horizontal
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	53.62	-9.68	43.94	74.00	-30.06	peak	
2	*	4960.000	41.52	-9.68	31.84	54.00	-22.16	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	53.70	-9.84	43.86	74.00	-30.14	peak	
2	*	4804.000	41.62	-9.84	31.78	54.00	-22.22	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2402MHz	Polarization	Horizontal
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	53.85	-9.84	44.01	74.00	-29.99	peak	
2	*	4804.000	41.52	-9.84	31.68	54.00	-22.32	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2441MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4882.000	53.24	-9.77	43.47	74.00	-30.53	peak	
2	*	4882.000	41.28	-9.77	31.51	54.00	-22.49	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2441MHz	Polarization	Horizontal
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4882.000	53.67	-9.77	43.90	74.00	-30.10	peak	
2	*	4882.000	41.37	-9.77	31.60	54.00	-22.40	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2480MHz	Polarization	Vertical
Temp	23°C	Hum.	54%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	53.34	-9.68	43.66	74.00	-30.34	peak	
2	*	4960.000	41.59	-9.68	31.91	54.00	-22.09	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BT (3Mbps)	Test Date	2021/6/26
Test Frequency	2480MHz	Polarization	Horizontal
Temp	23°C	Hum.	54%



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	53.60	-9.68	43.92	74.00	-30.08	peak	
2	*	4960.000	41.23	-9.68	31.55	54.00	-22.45	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.


(2) Margin Level = Measurement Value - Limit Value.

APPENDIX C NUMBER OF HOPPING CHANNEL


Test Mode	1/3Mbps
-----------	---------

Test Mode	Number of Hopping Channel	≥ Limit	Test Result
1 Mbps	79	15	Pass
3 Mbps	79	15	Pass

1 Mbps



3 Mbps




Date: 28.JUN.2021 19:04:21

Date: 29.JUN.2021 12:36:00


APPENDIX D AVERAGE TIME OF OCCUPANCY

Test Mode : 1Mbps


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	2.8800	0.3072	0.4000	Pass
DH3	2402	1.6600	0.2656	0.4000	Pass
DH1	2402	0.3850	0.1232	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.6600	0.2656	0.4000	Pass
DH1	2441	0.3850	0.1232	0.4000	Pass
DH5	2480	2.8800	0.3072	0.4000	Pass
DH3	2480	1.6600	0.2656	0.4000	Pass
DH1	2480	0.3850	0.1232	0.4000	Pass




Date: 28_JUN,2021 18:59:51




Date: 28_JUN,2021 18:59:12




Date: 28_JUN,2021 18:59:16




Date: 28_JUN,2021 19:06:26




Date: 29_JUN,2021 12:53:30




Date: 28_JUN,2021 19:08:19



Date: 29_JUN,2021 11:55:19




Date: 29_JUN,2021 11:56:23




Date: 29_JUN,2021 11:55:29

Test Mode : 1Mbps_AFH Mode


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	2.8800	0.1536	0.4000	Pass
DH3	2402	1.6600	0.0885	0.4000	Pass
DH1	2402	0.3850	0.0205	0.4000	Pass
DH5	2441	2.9200	0.1557	0.4000	Pass
DH3	2441	1.6600	0.0885	0.4000	Pass
DH1	2441	0.3850	0.0205	0.4000	Pass
DH5	2480	2.8800	0.1536	0.4000	Pass
DH3	2480	1.6600	0.0885	0.4000	Pass
DH1	2480	0.3850	0.0205	0.4000	Pass




Date: 28 JUN 2021 18:59:51




Date: 28 JUN 2021 18:59:12




Date: 28 JUN 2021 18:59:16




Date: 28 JUN 2021 19:06:26




Date: 29 JUN 2021 12:53:30




Date: 28 JUN 2021 19:08:19



Date: 29 JUN 2021 11:55:19




Date: 29 JUN 2021 11:56:23



Date: 29 JUN 2021 11:55:29


Test Mode : 3Mbps

Data Packet	Frequency (MHz)	Pulse Duration(ms)	Dwell Time(s)	Limits(s)	Test Result
3DH5	2402	2.8800	0.3072	0.4000	Pass
3DH3	2402	1.6400	0.2624	0.4000	Pass
3DH1	2402	0.3900	0.1248	0.4000	Pass
3DH5	2441	2.8800	0.3072	0.4000	Pass
3DH3	2441	1.6400	0.2624	0.4000	Pass
3DH1	2441	0.3800	0.1216	0.4000	Pass
3DH5	2480	2.9200	0.3115	0.4000	Pass
3DH3	2480	1.6400	0.2624	0.4000	Pass
3DH1	2480	0.3900	0.1248	0.4000	Pass



Test Mode : 3Mbps_AFH Mode


Data Packet	Frequency (MHz)	Pulse Duration(ms)	Dwell Time(s)	Limits(s)	Test Result
3DH5	2402	2.8800	0.0389	0.4000	Pass
3DH3	2402	1.6400	0.0221	0.4000	Pass
3DH1	2402	0.3900	0.0053	0.4000	Pass
3DH5	2441	2.8800	0.0389	0.4000	Pass
3DH3	2441	1.6400	0.0221	0.4000	Pass
3DH1	2441	0.3800	0.0051	0.4000	Pass
3DH5	2480	2.9200	0.0394	0.4000	Pass
3DH3	2480	1.6400	0.0221	0.4000	Pass
3DH1	2480	0.3900	0.0053	0.4000	Pass



APPENDIX E HOPPING CHANNEL SEPARATION MEASUREMENT


Test Mode : Hopping on _1Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	0.982	0.639	Pass
2441	1.098	0.640	Pass
2480	1.098	0.641	Pass



Test Mode : Hopping on _3Mbps


Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.002	0.869	Pass
2441	1.005	0.881	Pass
2480	1.006	0.879	Pass



APPENDIX F BANDWIDTH


Test Mode :	1Mbps
-------------	-------

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	0.958	0.876	Pass
2441	0.960	0.884	Pass
2480	0.962	0.868	Pass



Test Mode :	3Mbps
-------------	-------

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.304	1.176	Pass
2441	1.322	1.180	Pass
2480	1.318	1.188	Pass



APPENDIX G OUTPUT POWER

Test Mode :	1Mbps	Tested Date	2021/6/30
-------------	-------	-------------	-----------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	6.52	0.0045	21.00	0.1250	Pass
2441	6.82	0.0048	21.00	0.1250	Pass
2480	6.06	0.0040	21.00	0.1250	Pass

Test Mode :	2Mbps	Tested Date	2021/6/30
-------------	-------	-------------	-----------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	2.95	0.0020	21.00	0.1250	Pass
2441	3.03	0.0020	21.00	0.1250	Pass
2480	3.01	0.0020	21.00	0.1250	Pass

Test Mode :	3Mbps	Tested Date	2021/6/30
-------------	-------	-------------	-----------


Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	3.28	0.0021	21.00	0.1250	Pass
2441	3.25	0.0021	21.00	0.1250	Pass
2480	3.21	0.0021	21.00	0.1250	Pass

APPENDIX H ANTENNA CONDUCTED SPURIOUS EMISSION

Test Mode


1Mbps

2402 MHz_ Lower




Date: 28.JUN.2021 18:52:20

2480 MHz_ Upper




Date: 28.JUN.2021 18:55:46

2402 MHz_ Hopping on mode (Lower)




Date: 28.JUN.2021 19:04:55

2480 MHz_ Hopping on mode (Upper)




Date: 28.JUN.2021 19:05:29


2402 MHz – 10th Harmonics



Date: 28 JUN 2021 18:53:05




Date: 28 JUN 2021 18:53:12




Date: 28 JUN 2021 18:53:16


2441 MHz – 10th Harmonics



Date: 28 JUN 2021 18:54:07




Date: 28 JUN 2021 18:54:14




Date: 28 JUN 2021 18:54:20


2480 MHz – 10th Harmonics



Date: 28 JUN 2021 18:56:30




Date: 28 JUN 2021 18:56:37



Date: 28 JUN 2021 18:56:44


Test Mode 3Mbps

2402 MHz_ Lower




Date: 29.JUN.2021 12:24:38

2480 MHz_ Upper




Date: 29.JUN.2021 12:28:13

2402 MHz_ Hopping on mode (Lower)






Date: 29.JUN.2021 12:36:34

2480 MHz_ Hopping on mode (Upper)






Date: 29.JUN.2021 12:37:25




2402 MHz – 10 Harmonics



2441 MHz – 10 Harmonics



2480 MHz – 10 Harmonics



End of Test Report