

FCC RF Exposure

EUT Description: Tablet PC

Model No.: MD1063B

FCC ID: 2AVWN-MD1063B

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$

Where:

Result = $P/D^* \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
BLE	8.28	7.3±1(8.3)	6.761	5	2.096	3.0	Pass
EDR	7.496	6.6±1(7.6)	5.754	5	1.784	3.0	Pass
2.4GWIFI	7.44	6.5±1(7.5)	5.623	5	1.747	3.0	Pass
5.2GWIFI	7.46	6.5±1(7.5)	5.623	5	2.560	3.0	Pass
5.8GWIFI	7.41	6.5±1(7.5)	5.623	5	2.696	3.0	Pass

Note:

PK Output power = conducted power.

Conducted power see the test report **HK2106031730-1E/2E/3E/4E/5E**,

BT antenna gain=3dBi

2.4GWIFI antenna gain=3dBi

5GWIFI antenna gain=3dBi

Per KDB 447498 D01, when the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 2.696 which is \leq 3, SAR testing is not required.

Note: Exclusion Thresholds Results = $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm

Note: the device could not transmit simultaneously in 2.4G and 5G.