

**FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)****Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

S = PG/4πR<sup>2</sup> = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,j}} \leq 1$$

**Calculated Data:**

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
2.4G Wi-Fi 802.11b	2412~2462	3.0	2.00	17.50	56.23	20	<b>0.0224</b>	1.0
2.4G Wi-Fi 802.11g		3.0	2.00	16.50	44.67	20	0.0178	1.0
2.4G Wi-Fi 802.11 n-HT20		3.0	2.00	16.50	44.67	20	0.0178	1.0
2.4G Wi-Fi 802.11 n-HT40	2422~2452	3.0	2.00	17.50	56.23	20	0.0224	1.0
SRD	2401.6~2477.6	3.0	2.00	17.00	50.12	20	<b>0.0199</b>	1.0

**Note:**

- (1) The Tune-up output power was declared by the Manufacturer.
- (2) Wi-Fi & SRD can transmit simultaneously; the worst condition is as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0224 + 0.0199 = 0.0423 < 1.0$$

**Conclusion:** The device meets MPE at distance 20cm.